MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, (CIRCULAR, ENVIRONMENT RESISTING), RECEPTACLE, (NARROW FLANGE MOUNT, BAYONET COUPLING, PREWIRED SOCKET CONTACT), (SERIES I, CLASSES A, G, AND R (SHELL SIZE 8 FOR INSERTS 8-2, 8-3, AND 8-4 ONLY))

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the connectors described herein shall consist of this document and the latest issue of Specification MIL-C-26482.

INACTIVE. NO SUPERSEDING DOCUMENT.





FIGURE 1

A denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.

FSC 5935



INSERT POSITION

(AS VIEWED FROM ENGAGING END)

FIGURE 2






FIGURE 3


Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.




WITH STRAIGHT BACKSHELL
LESS STRAIN RELIEF




ASSEMBLED TO 90° BACKSHELL
WITH STRAIN RELIEF




ASSEMBLED TO BACKSHELL
WITH STRAIGHT SHRINK STRAIN
RELIEF



ASSEMBLED TO BACKSHELL WITH
90° SHRINK STRAIN RELIEF



ASSEMBLED TO STRAIGHT BACKSHELL
WITH STRAIN RELIEF



MAX PANEL THICKNESS (TYP)

FIGURE 4

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.

NOTES:
1. For alternate polarizing positions, the connector insert is rotated in respect to the shell.
2. In "Normal Position" (Position "N") the insert vertical center line coincides with the center line of the master key of the shell.
3. In "Alternate Positions" (Positions "W", "X", "Y", and "Z") the socket insert is rotated CC degrees clockwise relative to centerline of the master key of the shell.
4. Fully mated coupling indication stripes and polarization stripes shall be color coded blue. Stripes shall have minimum width of .050 on coupling ring and minimum width of .040 on the shell.
5. Four keys (MMC) and insert shall be located within .0035 either side of (TP) relative to master key (MMC) and shell O. D. (MMC).
6. Dimensions in inches. Unless otherwise specified, tolerance shall be .XX ±.010 and .XXX ±.005, angular X° ±1° - 0' and X° X' ±30'.
Ⓐ 7. Contacts in this connector are nonremovable.

REQUIREMENTS:

Dimensions and configuration: See figures.

This connector mates with MIL-C-83723/36 and /48 (USAF).

Ⓐ For insert arrangements see MIL-STD-1669.

Rear hardware must be used per MIL-C-83723/15, /16(USAF).

Contacts and leads shall be furnished in assembled configuration.


Connector assembly must include a backshell to meet moisture sealing requirements.

Ⓐ Shell material: Classes A and R - Aluminum alloy per QQ-A-367.
Class G - Corrosion resistant steel per QQ-S-763.

Ⓐ Circumferential color bands specified in MIL-C-26482 do not apply.

Ⓐ Connector identification marking specified in MIL-C-26482 does not apply. Marking shall be as specified in the part number below.

Part number example:



Custodian:
Air Force - 85

Review activities:
Air Force - 11, 17, 70. 71, 80, 82, 84
DSA - ES

Preparing activity:
Air Force

(Project 5935-F964-18)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-C-83723/39A (USAF) Connectors, Electrical, (Circular, Environment Resisting)

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER FSC 5935

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

C16061

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.

FOLD

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

POSTAGE AND FEES PAID
DEPARTMENT OF THE AIR FORCE
DoD-318

U.S.MAIL

AFLC/MMGE/Stdzn
WPAFB OH 45433

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:19Z
Check the source to verify that this is the current version before use.