[INCH-POUND]
MIL-C-83522/2D
30 December 1988
SUPERSEDING
MIL-C-83522/2C
28 September 1987

MILITARY SPECIFICATION SHEET

CONNECTOR, PLUG, FIBER OPTIC, SINGLE TERMINUS, THREADED, (STRAIGHT NOSE INTERFACE), LENSLESS, EPOXY, FOR 50/125 µm, 62.5/125 µm, AND 100/140 µm

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-C-83522.




FIGURE 1. Dimensions and configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:35Z
Check the source to verify that this is the current version before use.




FIGURE 1. Dimensions and configuration (straight nose optional view) - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:35Z
Check the source to verify that this is the current version before use.

	Min	Max
A	.3858 (9.799)	.3863 (9.812)
C	.080 (2.03)	.100 (2.54)
D	.179 (4.55)	.182 (4.62)
E	.220 (5.59)	.233 (5.92)
F	.485 (12.32)	
G	.183 (4.65)	.224 (5.69)
H		1.50 (38.1)
J	.015 (0.38)	.045 (1.14)
B	Plug must not enter .118 hold gauge	Plug must enter .124 dia. hole gauge

K dimension		
50/125 µm fiber	62.5/125 µm	100/140 µm fiber
132.0 max	132.0 max	147.0 max
127.5 min	127.5 min	142.5 min

Inches	mm
.001	0.03
.002	0.05
.005	0.13
.010	0.25
.015	0.38
.027	0.69
.028	0.71
.030	0.76
.036	0.91
.037	0.94
.039	0.99
.046	1.17
.047	1.19
.060	1.52
.0625	1.588
.065	1.65
.088	2.24
.090	2.29
.123	3.12
.127	3.23
.250	6.35
.309	7.85
.315	8.00

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Millimeters are in parentheses.
4. Dimensions for fiber optic cable shall be in accordance with DOD-C-85045.
5. K dimension is specified in µm. This dimension is critical to fiber alignment. Dimensions for fiber optic fiber shall be in accordance with DOD-F-49291.
6. Dimensions A are obtained after product has beem assembled.
7. Ferrule may be integral part of component.
8. Three holes .016 (0.41 mm) minimum diameter, equally spaced, are required for safety wiring after mating. Location on the coupling nuts optional.
9. O-ring is required. Component shall be machined for either O-ring location A or location B.
10. Dimension of O-ring area.

FIGURE 1. Dimensions and configuration - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:35Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Metals: The plug housing shall be of corrosion resistant steel per QQ-S-763, class 303 or nickel plated brass per QQ-B-626. Other metal components shall be of corrosion resistant steel per QQ-S-763, class 303; nickel plated beryllium copper per QQ-B-530 or nickel plated brass per QQ-B-626.

Epoxies: Use Trabond 230, Eccobond 144B or an equivalent epoxy approved by the qualifying activity.

Dimensions and configuration: See figure 1.

Fiber optic cable requirements:

Cable diameter: In accordance with DOD-C-85045.

Cable configuration: In accordance with DOD-C-85045.

Fiber diameter: 50/125 µm, 62.5/125 µm, and 100/140 µm.

Fiber numerical aperture: In accordance with DOD-F-49291.

Fiber type: Multimode.

Fiber optic termini: In accordance with MIL-F-49291

Method of optical alignment: Precision diameter fit.

Lens configuration: Not applicable.

Coating requirements: Not applicable.

Cleaning procedures: Dampen lens tissue (paper wipes or cotton swab) with a small amount of isopropyl alcohol or water. Gently wipe the face of the connector, removing any debris, particularly around the optical fiber, using clean lens tissue (paper wipes, cotton swab). Carefully dry the contact with a clean, dry tissue.

Optical requirements:

Number of optical termini: One.

Coupling loss (attenuation): 3 dB maximum per mated pair.

Weight: 6 grams maximum.

Polarization: Not applicable.

Safety wire holes: Required.

Force to engage and disengage:

Longitudinal force: 12 pounds maximum.

Torque: 4 inch-pounds maximum.

Coupling proof torque: 5 inch-pounds minimum.

Coupling mechanism retention force: 60 pounds minimum.

Ozone exposure: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:35Z
Check the source to verify that this is the current version before use.

Durability: 200 cycles, 1 dB maximum change.

Low temperature: 1 dB maximum change.

Part or Identifying Number (PIN): See table I.

TABLE I. Part or Identifying Numbers (PIN).

PIN M83522/2-	Safety wire holes	Fiber size
03		50/125
03	Yes	62.5/125
04		100/140

Plug accessories: Each plug shall be supplied with a minimum of one crimp ferrule as needed (see figure 1); one protective cable-end cap; one 1.5 inch length of heat-shrink tubing or one rubber boot; and one set of assembly instructions. The assembly instructions shall include a listing of the epoxies specified in this specification sheet and a cleaning procedure statement as follows:

Cleaning procedures: Dampen lens tissue (paper wipes or cotton swab) with a small amount of isopropyl alcohol or water. Gently wipe the face of the connector, removing any debris, particularly around the optical fiber, using clean lens tissue (paper wipes, cotton swab). Carefully dry the contact with a clean, dry tissue.

NOTE: The plug mates with MIL-C-83522/4 receptacle; MIL-C-83522/5 receptacle; MIL-C-83522/7 receptacle; MIL-C-85322/8 receptacle; or a MIL-C-83522/3 adapter mated with another MIL-C-83522/2 plug. Connection to any other type plug may result in excessive coupling loss.

Revision letters are not used to denote changes due to the extensiveness of the changes.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA

Review activities:
Navy - SH
Air Force - 11, 17, 19, 80, 90, 99
DLA - ES

User activities:
Navy - AS, MC, OS
Air Force - 13, 14

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 6060-0073-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T08:35Z
Check the source to verify that this is the current version before use.