INCH-POUND

MIL-DTL-83723/60E
w/AMENDMENT 2
1 February 2024
SUPERSEDING
MIL-DTL-83723/60E
w/AMENDMENT 1
26 August 2010

DETAIL SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, (CIRCULAR, ENVIRONMENT RESISTING), PROTECTIVE COVERS, RECEPTACLES, (FOR MIL-DTL-26500 AND MIL-DTL-83723, SERIES III, CLASSES A, M, R, T, W AND Z)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-83723.





FIGURE 1. Protective cover, receptacles, threaded coupling M83723/60-1.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.



Shell size	A UNEF-2B coupling thread	C dia max	E dia counterbore min
08	.5625-24	.776 (19.71)	.583 (14.81)
10	.6875-24	.906 (23.01)	.707 (17.96)
12	.8750-20	1.078 (27.38)	.895 (22.73)
14	.9375-20	1.141 (28.98)	.957 (24.31)
16	1.0625-18	1.266 (32.16)	1.084 (27.53)
18	1.1875-18	1.375 (34.93)	1.209 (30.71)
20	1.3125-18	1.510 (38.35)	1.334 (33.88)
22	1.4375-18	1.625 (41.28)	1.459 (37.06)
24	1.5625-18	1.760 (44.70)	1.584 (40.23)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Metric equivalents are in parentheses.
4. Unless otherwise specified, tolerances shall be ± .005 (.13 mm) for three place decimals.
5. The method of attachment is optional. The fastener shall not become loose or be damaged when subjected to a straight axial pull of 5 lb minimum on the chain or rope. The chain or rope shall rotate freely on the fastener.
6. These parts are intended for use as protective covers for MIL-DTL-83723, series III, and MIL-DTL-26500 threaded coupling connector receptacles.

FIGURE 1. Protective cover, receptacles, threaded coupling M83723/60-1 - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.




FIGURE 2. Protective cover, receptacles, bayonet coupling M83723/60-2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.

Shell size	A max outside diameter coupling	B dia min	C dia + .005 - .000	G min	H dia min
08	.776 (19.71)	.632 (16.05)	.540 (13.72)	.079 (2.01)	.079 (2.01)
10	.906 (23.01)	.760 (19.30)	.662 (16.81)	.094 (2.39)	.094 (2.39)
12	1.078 (27.38)	.930 (23.62)	.832 (21.13)	.094 (2.39)	.094 (2.39)
14	1.141 (28.98)	.999 (25.37)	.901 (22.89)	.094 (2.39)	.094 (2.39)
16	1.266 (32.16)	1.126 (28.60)	1.028 (26.11)	.094 (2.39)	.094 (2.39)
18	1.375 (34.93)	1.232 (31.29)	1.134 (28.80)	.094 (2.39)	.094 (2.39)
20	1.510 (38.35)	1.357 (34.47)	1.261 (32.03)	.094 (2.39)	.094 (2.39)
22	1.625 (41.28)	1.482 (37.64)	1.384 (35.15)	.094 (2.39)	.094 (2.39)
24	1.760 (44.70)	1.607 (40.82)	1.511 (38.38)	.094 (2.39)	.094 (2.39)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Metric equivalents are in parentheses.
4. Unless otherwise specified, tolerances shall be ± .005 (.13 mm) for three place decimals.
5. The method of attachment is optional. The fastener shall not become loose or be damaged when subjected to a straight axial pull of 5 lb minimum on the chain or rope. The chain or rope shall rotate freely on the fastener.
6. Coupling assurance indicator shall be provided in accordance with MIL-DTL-83723.
7. These parts are intended for use as protective covers for MIL-DTL-83723, series III, and MIL-DTL-26500 bayonet coupling connector receptacles.

FIGURE 2. Protective cover, receptacles, bayonet coupling M83723/60-2 - Continued.

REQUIREMENTS:

Dimensions and configurations: See figures 1 and 2.

Materials:

Cover – Aluminum alloy.
Gasket – Silicone elastomer.
Sash chain – Stainless steel, passivated, in accordance with RR-C-271, type II, class 3.
Fastener – Stainless steel, passivated.
Rope – Insulated, stainless steel, passivated, braided or stranded. Insulation shall withstand 200°C environment.

Gasket shall be bonded to cover or mechanically retained in cover.

The chain or rope shall rotate freely on the fastener.

Termination style: See table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.

TABLE I. Termination style.

Letter designators	Chain and rope length
C	with a chain length of 5.0 (127.00 mm) + .25 (6.35 mm)
N	without chain
R	with a rope length of 5.0 (127.00 mm) + .25 (6.35 mm)
P	with a chain length of 8.0 (203.20 mm) + .25 (6.35 mm)
T	with a rope length of 8.0 (203.20 mm) + .25 (6.35 mm)

Qualification:

Examination of product.
Coupling torque.
Humidity.
Salt spray (corrosion).

Cover chain or rope and fastener tensile strength:

The protective cover and chain or rope assembly shall be securely held and a tensile static load of 5 lb minimum shall be applied to the end of the chain or rope for 5 minutes in each direction as specified below:

a. Axis of chain or rope at right angles to axis of fastener.
b. Axis of chain or rope in same axis as fastener.

Group A sampling inspection. Sampling for group A inspection shall be as specified in table II.

TABLE II. Group A sampling plan.

Lot size	Sampling size
1 to 13	100 percent
14 to 150	13 units
151 to 280	20 units
281 to 500	29 units
501 to 1,200	34 units
1,201 to 3,200	42 units
3,201 and up	54 units

Marking:

Part or Identifying Number (PIN): M83723/60-X (note: “X” represents the dash number from figure 1 or 2), shell size, and the applicable codes for finish and termination style.

PIN example:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.

M83723/ 60 - 1 08 A C

M83723/	Military designator
60	Specification sheet number
1	Dash number
08	Shell size
A	Finish
C	Termination style (see table I)

Supersession data: See table III.

TABLE III. Supersession data.

Superseding PIN M83723/60-1	Superseded PIN MS27294-
8AR, 08AR	7
10AR	1
12AR	2
14AR	3
16AR	4
18AR	5
20AR	8
22AR	6
24AR	9
Superseding PIN M83723/60-2	Superseded PIN MS27295-
8AR, 08AR	7
10AR	1
12AR	2
14AR	3
16AR	4
18AR	5
20AR	8
22AR	6
24AR	9

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notation.

Referenced documents. In addition to MIL-DTL-83723, this document references the following:

RR-C-271
MIL-DTL-26500

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - AS
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

Review activities:
Army - AR, MI
Navy - EC
Air Force – 19

(Project 5935-2024-069)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:20Z
Check the source to verify that this is the current version before use.