MILITARY SPECIFICATION SHEET

SWITCHES, TOGGLE, MINIATURE, LEVER-LOCK, DOUBLE POLE, UNSEALED

This specification is approved for all Departments and Agencies of the Department of Defense.

The requirements for acquiring the switches described herein shall consist of this specification sheet and the latest issue of MIL-S-83731.




FIGURE 1 Solder lug termination.





FIGURE 2 Printed circuit termination.

© denotes changes

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://apps.dtic.mil - Downloaded: 2026-01-23 09:32
Check the source to verify that this is the current version before use.



Inches	mm	Inches	mm	Inches	mm
001	0 03	.046	1.17	.250	6.35
.002	0.05	.047	1 19	.253	6.43
003	0.08	.060	1.52	.300	7.62
.005	0.13	.065	1 65	.320	8 13
.010	0 25	075	1.91	.400	10 16
.020	0.51	.080	2.03	.410	10 41
.021	0.53	.115	2 92	430	10.92
031	0.79	.155	3.94	.465	11.81
.032	0.81	.185	4 70	.468	11 89
.040	1.02	189	4 80	.510	12.95
		.190	4 83	.577	14.66
		.225	5 72	.685	17.40

NOTES.
1. Dimensions are in inches.
2 Metric equivalents are given for information only.
3. Unless otherwise specified, tolerance are ± .005 (0.13).
4. Direction of internal mechanism movement is opposite to direction of toggle movement.

FIGURE 3 Locking Ring

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:32Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration See figures 1 and 2.

Ⓒ Material and finish: Bushing shall be brass, nickel plated. Toggle lever shall be brass, bright chrome plated Frame shall be stainless steel. The contacts shall be gold plate over nickel over silver over brass.

Ⓒ Mounting hardware. Each switch shall be supplied with two hexagon nuts, one internal-tooth lockwasher in accordance with the appendix of MIL-S-83731, and one locking ring (see figure 3). The locking ring shall be brass with bright nickel finish.

Weight 0.019 pound maximum.

Electrical ratings: See table I.

Strength of terminals: Method 211 of MIL-STD-202, test condition A. The applied force shall be one pound.

Strength of toggle lever, pivot, and lever stop: Test (a) shall use a 10 pound load; test (b) shall use a 8 pound load.

Dielectric withstanding voltage: Test at atmospheric pressure only.

Mechanical endurance: 10,000 cycles at -25°C +0°C, -4°C, and 10,000 cycles at 71°C +4°C, -0°C.

Electrical endurance, electrical overload, intermediate current, logic level life, and temperature rise: Multipole switches are to be tested with a load on each pole and with the same polarity on adjacent poles in accordance with figure 4.




FIGURE 4. Test circuit.

Ⓒ TABLE I. Electrical ratings.

Type of load	High level (current in amperes)			Logic level
	28 V dc	125 V ac, 60 Hz	115 V ac, 400 Hz	5 V dc
Resistive	5	5	5	0.010 ampere
Inductive	2	2	2	---
Lamp	1	1	1	---

Resistive load (dc and ac): Switches shall make and break the rated resistive load for 10,000 operating cycles at room ambient pressure and a temperature of 71°C +4°C -0°C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:32Z
Check the source to verify that this is the current version before use.

Inductive load (dc and ac): Switches shall make and break the rated inductive load for 10,000 operating cycles at room ambient temperature and pressure.

Lamp level load: Switches shall make and break the rated lamp load for 10,000 operating cycles.

© Logic level load: 10,000 cycles at an actuation rate of 10-18 cycles per minute with no 'stick' or 'misses' allowed when tested in accordance with ANSI/EIA RS448, method 17 as follows:

© Each pair of switch contacts shall be tested using a 5.0 ±0.05 V dc, 10 ±1 mA resistive load. During each closure of the contacts, the voltage drop across the switch terminals shall be monitored for a duration of no less than 50 percent of each contact static closure. The switch contacts need not be monitored until 10 ms after the initial contact closure to exclude any contact bounce. During each opening of the contacts, the voltage drop across the switch terminals shall be monitored for a duration of no less than 50 percent of each contact opening.

© A voltage of 2.1 volts or greater across the switch terminals shall constitute a contact 'miss', (failure to properly close the circuit). A voltage drop of less than 90 percent of the open-circuit voltage shall constitute a contact 'stick' (failure to properly open the circuit).

© The monitoring device shall either record the number of contact closures at which 'sticks' or 'misses' occur, or discontinue the test when 'sticks' or 'misses' occur.

© Operating temperature:

a. 50 percent of the test cycle at room ambient conditions.

b. 50 percent of the test cycle at 71 +4°C or -0°C.

Short circuit: Use 100 amperes at 28 V dc.

Flux sealed: The sealing is obtained when the base is sealed to prevent flux from entering the switch case during the wave soldering process.

© Flux seal test: Three switches shall be tested as follows during qualification and group B inspection Measure and record initial contact resistance. Place switches, terminals down, into a shallow pan. Pour flux at 80°F ±5°F, type RMA of MIL-F-14256, specific gravity 0.896, into pan without splashing until level of flux is approximately 1/16 inch above the bottom of the plastic switch case and let switches soak for 10 minutes. Remove switches from flux, clean with flux cleaning solvent and immediately put into oven for drying at 175°F for two hours. After switches have cooled to room temperature, repeat initial measurement. Contact resistance shall not increase by more than 10 milliohms over the initial reading. Disassemble and visually examine the contact area for evidence of flux. Any evidence of flux shall be cause for rejection.

Sand and dust: Not applicable.

Explosion: Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:32Z
Check the source to verify that this is the current version before use.

© Part number: The part number shall consist of the prefix M83731/12 followed in order by the appropriate two-digit number from table II and the number from table III as shown in the following example.

M 83731/12 - 71 1

M — Military designation
83731/12 — Specification sheet number
71 — Number from table II denotes switch has ON-OFF-ON circuit.
1 — Number from table III denotes type of termination 1/ 2/

© TABLE II. Circuit for switching characteristic.

Circuit	Circuit with toggle		
	Toward flat (down position)	Center	Opposite flat (up position)
71	1-2 ON 4-5	OFF	2-3 ON 5-6
73	1-2 ON 4-5	NONE	2-3 ON 5-6
76	1-2 MOM-ON 4-5	NONE	2-3 ON 5-6
77	1-2 MOM-ON 4-5	OFF	2-3 MOM-ON 5-6
81	1-2 MOM-ON 4-5	OFF	2-3 ON 5-6
82	1-2 ON 4-5	2-3 ON 4-5	2-3 ON 5-6

© TABLE III. Number for termination type.

Type of termination	
Solder lug	1
Printed circuit	2

1/ Listed dash numbers, ending with the number 1, are interchangeable with and supersede canceled dash numbers ending with the numbers 3 and 5.
2/ Listed dash numbers, ending with the number 2, are interchangeable with and supersede canceled dash numbers ending with the numbers 4 and 6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:32Z
Check the source to verify that this is the current version before use.

Custodians:
Army - ER
Air Force - 85

Review activities:
Air Force - 99

User activity:
Army - AR

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5930-1344-04)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T09:32Z
Check the source to verify that this is the current version before use.