NOT MEASUREMENT SENSITIVE

MIL-DTL-2/46D
w/Amendment 1
29 September 2006
SUPERSEDING
MIL-DTL-2/46D
25 September 2002

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS: SULFUR HEXAFLUORIDE, OUTLET 590 (PRESSURES THROUGH 3000 psig (20680 kPa) AT 120 ºF (48.9 ºC))

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet, MIL-DTL-2, and QPL-2.

REQUIREMENTS:

TYPE DESIGNATION	CYLINDER SERVICE PRESSURE psig	TYPE PRESSURE RELIEF DEVICE (PRD)
V46-590-2	1800 through 2400	5
V46-590-3	1800	1
V46-590-4	2015	1
V46-590-5	2265	1
V46-590-6	2400	1

TABLE I. Valve requirements.

Style	Class	Composition	Inlet size	Outlet application	Handwheel	PRD
IIB	30	A	6	590	Yes	1 or 5
III	30	A	6	590	Yes	1 or 5

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:41Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS:

1. Mark the valve body: SULFUR HEXAFLUORIDE.
2. When the cylinder service pressure is specified, the appropriate rupture disk PRD (type 1) shall be supplied.
3. When the cylinder service pressure is not specified, a combination PRD (type 5) shall be supplied with a rupture disk with a burst range between 2700 and 3000 psig. This device shall be utilized only for cylinders of 1800 to 2400 psig rating.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. Cylinder service pressure (psig) (unknown).

INTENDED USE: The valves covered by this specification sheet are intended for use with sulfur hexafluoride cylinders.

NOTES:

1. Special requirements will be mandatory for all valve procurements.
2. Optional requirements will be specified for each valve procurement.

AMENDMENT NOTATIONS: The margins of this specification are marked with vertical lines to indicate where modifications from this amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Preparing Activity:
DLA - GS7

(Project 8120-2006-018)

Review Activities:
Army - AV
Navy - AS, MC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST database at http://assist.daps.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:41Z
Check the source to verify that this is the current version before use.