NOT MEASUREMENT SENSITIVE

MIL-DTL-2/50B
25 September 2002
SUPERSEDING
MIL-DTL-2/50A
9 June 1995

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS: METHYL BROMIDE, OUTLET 330
(PRESSURES THROUGH 3000 psig (20680 kPa) AT 120 ºF (48.9 ºC))

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-2 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

REQUIREMENTS:

TYPE DESIGNATION: V50-330-12

TABLE I. Valve requirements.

Style	Class	Composition	Inlet size	Outlet application	Handwheel	PRD[1]
IV	05	A	6	330	Yes	0

[1] Pressure Relief Device

SPECIAL REQUIREMENTS:

1. When specified, valve outlet threads shall be 0.50" NPT.
2. Dip tube shall be in accordance with MIL-DTL-2.
3. Diaphragms shall be made of metal.
4. Mark the valve body: METHYL BROMIDE S.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:42Z
Check the source to verify that this is the current version before use.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. Dip tube assembled to valve (required) (not required).
3. Diameter of cylinder (inches).

INTENDED USE: The valves covered by this specification sheet are intended for use with methyl bromide cylinders.

NOTES:

1. Special requirements will be mandatory for all valve procurements.
2. Optional requirements will be specified for each valve procurement.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Preparing Activity:
DLA - GS3

(Project 8120-1047-50)

Review Activities:
Army - AV
Navy - AS, MC, YD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:42Z
Check the source to verify that this is the current version before use.