NOT MEASUREMENT SENSITIVE

MIL-DTL-2/52
9 June 1995

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS :

HALON FIRE FIGHTING MATERIALS, OUTLET 660

Pressures through 500 PSIG (3,450 KPa) at 120 degrees F (48.9 degrees C)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the valve described herein shall consist of this specification and the latest issue of MIL-DTL-2.

| TYPE DESIGNATION | CYLINDER SERVICE PRESSURE PSI | TYPE SAFETY DEVICE |
|---|---|---|
| V52-660-1-240 | 240 | 7 |
| V52-660-1-300 | 300 | 7 |
| V52-660-1-400 | 400 | 7 |

| Style | Class | Composition | Inlet Size | Outlet Application | Handwheel | Safety Device |
|---|---|---|---|---|---|---|
| I | 30 | A | 6 | 660 | No | 7 |



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:43Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS :

1. Mark the valve body: HALON.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. Disposable outlet cap or plug (required) (not required).
3. Wrench or key for style 1 valve (required) (not required).
4. Diptube assembled to valve (required) (not required).

INTENDED USE:

The valves covered by this specification sheet are intended for use with bromochlorodifluoromethane (1211), dibromodifluoromethane (1202) and bromotrifluoromethane (1301) cylinders.

NOTES:

1. Type designation will include the style valve from the chart above.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Review activities:
Army - AV
Navy - AS, MC, YD1
DLA - GS

Preparing activity:
Air Force - 68

(Project 8120-1025-37)



Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:43Z
Check the source to verify that this is the current version before use.