NOT MEASUREMENT SENSITIVE

MIL-DTL-2/57
9 June 1995

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS :

HELIUM AND NITROGEN, (INERT-OIL TOLERANT) OUTLET 621

Pressures 3001 through 5500 PSIG (20,690 through 37,900 KPa) at 120 degrees F (48.9 degrees C)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the valve described herein shall consist of this specification and the latest issue of MIL-DTL-2.

TYPE DESIGNATION	CYLINDER SERVICE PRESSURE PSI	TYPE SAFETY DEVICE
V57-621-8	3500 through 3600	1
V57-621-10	4000	1
V57-621-11	4500	1

Style	Class	Composition	Inlet Size	Outlet Application	Handwheel	Safety Device
III	55	A	6	621	Required	1

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:44Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS :

1. Mark the valve body: INERT O.T.
2. For type designation V57-621-8, the valve shall only be furnished with a frangible disk with a burst range of 5250 through 5800 psig (36,200 through 39,990 KPa).

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. Cylinder service pressure (psi) (unknown).

INTENDED USE:

The valves covered by this specification sheet are intended for use with helium and nitrogen cylinders in oil tolerant applications.

NOTES:

1. Type designation will include any style valve from the chart above.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Review activities:
Army - AV
Navy - AS, MC, YD1
DLA - GS

Preparing activity:
Air Force - 68

(Project 8120-1025-42)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:44Z
Check the source to verify that this is the current version before use.