NOT MEASUREMENT SENSITIVE

MIL-DTL-2/58
9 June 1995

DETAIL SPECIFICATION SHEET

VALVE, CYLINDER, GAS :

ARGON, HELIUM, NITROGEN, NEON, XENON AND KRYPTON
(INERT-OIL FREE), OUTLET 677

Pressures 5501 through 7500 PSIG (38,000 through 51,700 Kpa) at 120 degrees F (48.9 degrees C)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the valve described herein shall consist of this specification and the latest issue of MIL-DTL-2.

TYPE DESIGNATION: V58-677-9

| Style | Class | Composition | Inlet Size | Outlet Application | Handwheel | Safety Device |
|---|---|---|---|---|---|---|
| III | 75 | A | 8 | 677 | Required | 5 |



DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:44Z
Check the source to verify that this is the current version before use.

SPECIAL REQUIREMENTS :

1. Mark the valve body: INERT O.F.

OPTIONAL REQUIREMENTS:

1. Outlet cap or plug (required) (not required).
2. Cylinder service pressure (psi) (unknown).

INTENDED USE:

The valves covered by this specification sheet are intended for use with argon, helium, nitrogen, neon, xenon and krypton cylinders in oil-free applications.

NOTES:

1. Type designation will include any style valve from the chart above.
2. Special requirements will be mandatory for all valve procurements.
3. Optional requirements will be specified for each valve procurement.

Custodians:
Army - AT
Navy - SH
Air Force - 68

Review activities:
Army - AV
Navy - AS, MC, YD1
DLA - GS

Preparing activity:
Air Force - 68

(Project 8120-1025-43)



Source: https://assist.dla.mil -- Downloaded: 2026-10-15T15:44Z
Check the source to verify that this is the current version before use.