MIL-B-43177B
29 August 1977
SUPERSEDING
MIL-B-43177A
18 April 1968

MILITARY SPECIFICATION

BALING PRESSES

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers hand-operated and electrically-operated baling presses for compact baling of loose pliable material.

* 1.2 Classification. The presses shall be of the following types, sizes, and styles, as specified (see 6.2).

Type I - Downstroke, hand-operated

Size 1 - Bale size: 30 inches (762 mm) long by 16 inches (406 mm) wide by 10 to 30 inches (254 to 762 mm) high
Size 2 - Bale size: 45 inches (1143 mm) long by 24 inches (610 mm) wide by 10 to 38 inches (254 to 965 mm) high

Type II - Downstroke, electrically-operated

Style A - Single chamber - Bale size: 45 inches (1143 mm) long by 24 inches inches (610 mm) wide by 10 to 38 inches (254 to 965 mm)

Type III - Horizontal stroke, Electrically-operated - Bale size: 1/2 to 1-1/2 cubic feet (14 dm^3 to 42 dm^3)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command (GL), Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3540

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

* 2.1 Issues of documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein..

SPECIFICATIONS

FEDERAL

CC-M-1807	-	Motor, Alternating Current, Fractional and Integral Horsepower (500 Horsepower and Smaller)
TT-P-664	-	Primer Coating, Synthetic, Rust-Inhibiting, Lacquer-Resisting
PPP-C-843	-	Cushioning Material, Cellulosic
PPP-T-45	-	Tape: Gummed, Paper, Reinforced and Plain, For Sealing and Securing
PPP-T-60	-	Tape: Packaging, Waterproof

* MILITARY

MIL-C-104	-	Crates, Wood; Lumber and Plywood Sheathed, Nailed and Bolted
MIL-P-116	-	Preservation-Packaging, Methods Of
MIL-B-121	-	Barrier Material, Greaseproofed, Waterproofed, Flexible

STANDARDS

* MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-461	-	Electromagnetic Interference Characteristics Requirements for Equipment
MIL-STD-462	-	Electromagnetic Interference Characteristics Measurement Of

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

NATIONAL BUREAU OF STANDARDS (NBS)

Handbook H28 - Screw Thread Standards for Federal Services

(Application for copies should be addressed to the Superintendent of Documents, US Government Printing Office, Washington, DC 20402.)

UNDERWRITERS LABORATORIES INC. (UL)

Electrical Construction Materials List

(Application for copies should be addressed to the Underwriters Laboratories Inc., 207 East Ohio Street, Chicago, IL 60611; 333 Pfingsten Road, Northbrook, IL 60062; 1285 Walt Whitman Road, Melville, LI, NY 11746; 1655 Scott Boulevard, Santa Clara, CA 95050; or 2602 Tampa East Blvd., Tampa, FL 33619.)

AMERICAN WELDING SOCIETY CODE

Standard Qualification Procedures of the American Welding Society

(Application for copies should be addressed to the American Welding Society, 345 East 47th Street, New York, NY 10017.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Welding Qualification of the American Society of Mechanical Engineers

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

HYDRAULIC INSTITUTE STANDARDS

Hydraulic Standards for Industrial Equipment

(Application for copies of this standard should be addressed to the Standard Hydraulic Institute, 122 East 42nd Street, New York, NY 10012.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to American Trucking Associations, Inc., Traffic Department, 1616 P Street, N.W., Washington, DC 20036.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

* 3.1 First article. When specified (see 6.2), the contractor shall furnish a sample for first article inspection and approval (see 4.3, 6.2 and 6.3).

* 3.2 Standard product. The baling presses shall be new and a standard product of the manufacturer except for any changes necessary to comply with this specification

* 3.3 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer in the fabrication of baling presses provided that the complete baling press complies with all the provisions of this specification.

3.4 Codes and standard. Type II and III baling presses shall comply with the following:

(1) The electrical equipment shall meet the requirements of Underwriters Laboratories (UL) standards, as applicable.

(2) The hydraulic equipment shall comply with requirements of the Hydraulic Institute Standards for Industrial Equipment, as applicable.

* 3.4.1 UL. Prior to approval of the first article if one is submitted, or prior to commencing production, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the electrical materials and components that he proposes to furnish under this specification meet the requirements of UL Standards, as applicable. Acceptable evidence of meeting the requirements of Underwriters Laboratories Inc. shall be the UL label, a listing in the UL "Electrical Construction Materials List" with reexamination, or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the electrical materials and components offered have been tested and conform to UL Standards, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

3.4.2 Hydraulic institute. Prior to the approval of the first article if one is submitted, or prior to commencing production, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative that the hydraulic equipment and components that he proposes to furnish under this specification meets the requirements of the Hydraulic Institute Standards for hydraulic equipment, as applicable. Acceptable evidence of meeting the requirements of the Hydraulic Institute shall be a certificate or a certified test report from a recognized independent testing laboratory, acceptable to the Government, indicating that the hydraulic components offered have been tested and meet the applicable requirements of the Hydraulic Institute.

* 3.5 Design. Baling presses shall be self-contained, floor mounted, and shall have a loading chamber and compression platens of the downstroke or horizontal type (see 1.2). The loading chamber shall be provided with doors for removal of the bale. The presses shall be capable of applying the compressive loads as indicated in table I when tested as specified in 4.6.1. The presses shall be provided with adequate safety means, such as belt or chain guards and tubing for the protection of electrical wires, and shall have lubrication means for bearings and sliding components.

TABLE I. Compression loads

Baling press	Minimum compression loads in pounds (kgs)
Type I (when maximum load of 150 pounds (68 kg) is applied at the handle)	
Size 1	3,400 (1,540)
Size 2	13,200 (5,990)
Type II	
Style A	23,000 (10,430)
Type III	
longitudinal platen	90,000 (40,820)
side platen	154,000 (69,850)
top door	28,000 (12,700)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

3.6 Construction. Presses shall be adequately reinforced to show no visible evidence of bulging, permanent deformation, twisting or fracture of component parts when tested as specified in 4.6.2.1, 4.6.2.2.1, 4.6.2.2.2, and 4.6.2.3, as applicable. Baling press components requiring servicing shall be accessible.

3.6.1 Welders. The welders performing the welding on subassemblies, assemblies, and on the end item shall be certified welders and have passed the qualification test as prescribed by either the Standard Qualification Procedures of the American Welding Society or Welding Qualification of the American Society of Mechanical Engineers' Codes. The contractor shall furnish the Government representative with a list of his welders who are qualified and have passed the test of either referenced code and he shall verify that the welding of this equipment was performed by the welders listed.

3.6.2 Threaded fasteners. Screws, nuts, bolts and other threaded components of the baling presses shall conform to Handbook H28.

3.6.3 Details of components.

* 3.6.3.1 Platens. Platens for type I and II presses shall consist of parallel steel or hardwood cleats spaced at equal distances on a steel plate to allow the bale to be bound. In addition to compression platens, type I and II presses shall have a fixed platen at the bottom of the loading chamber. The platens shall be approximately the same dimensions as the inside of the loading chamber. Type III shall consist of longitudinal and side platens operating horizontally to compress the bale to size, and the plantens shall have replaceable, abrasive resistant, steel plates.

3.6.3.2 Loading chambers. Loading chambers of type I and II presses shall consist of side enclosures and a bottom platen. The side enclosures shall have doors with manually operated, quick-acting, positive locks. The locks shall not bind and show no evidence of permanent deformation or fracture when tested as specified in 4.6.2.1, 4.6.2.2.1, and 4.6.2.2.2, as applicable.

* 3.6.3.2.1 Type I, size 1. Type I, size 1 baling press loading chamber shall have a front and rear door. The minimum dimensions of the chamber shall be 30 inches (762 mm) long by 16 inches (406 mm) wide by 42 inches (1067 mm) high.

* 3.6.3.2.2 Type I, size 2. Type I, size 2 baling press loading chamber shall have an upper, drop type, front hopper door to facilitate loading, and a lower front and rear door to expose three sides of the bale. The minimum inside dimensions of the chamber shall be 45 inches (1143 mm) long by 24 inches (610 mm wide by 55 inches (1397 mm) high.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

* 3.6.3.2.3 Type II, style A. Type II, style A baling press loading chamber shall be provided with a top, drop type, front hopper door and a lower front and rear door that shall open to expose a minimum of two sides of the bale. The minimum inside chamber dimensions shall be 42 inches (1067 mm) long by 24 inches (610 mm) wide by 55 inches (1397 mm) high.

* 3.6.3.2.4 Type III. The type III baling press loading chamber shall be provided with a top compressor door for compressing bailing materials and to obtain a full charge in the loading chamber. The loading chamber capacity shall be at least 13 cubic feet (368 dm^3) and not greater than 30 cubic feet (849 dm^3). The inside loading chamber walls shall have replaceable abrasive resistant, steel plates.

* 3.6.3.3 Electric motor. Electric motors specified for type II and III baling presses shall conform to type II, style A of CC-M-1807. Unless otherwise specified (see 6.2), the motor shall operate on a nominal 230/460 volts alternating current, 3 phase, HZ. All motors shall have an "on" and "off" pushbutton type switch and a thermal overload relay switch. The relay switch shall break the motor circuit when the motor is overloaded and, when the switch is activated, shall restore the circuit for normal operation when tested in 4.6.2.4.

* 3.6.3.4 Hydraulic systems. Hydraulic systems in hydraulically operated type II and III presses shall consist of pumps, fluid reservoir, check and adjustable relief valves, cylinders, and a manually operated directional control valve for each cylinder. The control valve shall be capable of operating the cylinders by holding the ram fast in any position, or by smoothly moving the ram in or out of the cylinder. The hydraulic system shall operate with no external leaks when tested as specified in 4.6.2.2.2 and 4.6.2.3. Adequate venting of the hydraulic system and means for filling and draining the fluid reservoirs shall be provided.

* 3.6.4 Type I. Type I baling presses shall be provided with a hand lever and ratchet. The hand lever and ratchet shall be the means of transmitting the up and down strokes of the compression platen through a pair of chain drives. A stop shall be provided to stop the platen at the end of the upstroke. A quick-return means for the upstroke shall be provided. At the end of the upstroke, the platen shall automatically lift off to the back of the loading chamber to provide more space for loading. Platens and loading chambers shall be as specified in 3.6.3.1 and 3.6.3.2.

3.6.5 Type II. Type II baling presses shall be provided with an electric motor as specified in 3.6.3.3. The motor shall transmit the up and down strokes of the compression platen by means of any one of the drives as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

(a) Chain drive
(b) Screw drive
(c) Rack and pinion drive
(d) Hydraulic drive

Type II press with chain, screw, or rack and pinion drive shall be provided with limit switches and brake. Type II press with hydraulic drive shall have a hydraulic system as specified in 3.6.3.4. Platens and loading chambers for type II presses shall be as specified in 3.6.3.1, 3.6.3.2.3 and 3.6.3.2.4.

3.6.5.1 Limit switches. Limit switches on type II presses shall stop the motor as the compression platen reaches the upstroke position for loading and the compression downstroke position for minimum bale height when tested in 4.6.2.2.1.

3.6.5.2 Brakes. Brakes on type II presses shall automatically engage and hold the compression platen fast as the motor stops, and release as the motor starts and remains in operation when tested in 4.6.2.2.1. In addition, the brakes shall be provided with a manual control for engaging and releasing the brake.

* 3.6.6 Type III. Type III baling press shall consist of an electric motor as specified in 3.6.3.3, a common hydraulic system as specified in 3.6.3.4, and a means for ejection of the bale.

3.7 Finish. Type I, II and III presses shall be finished in accordance with the manufacturer's standard commercial finish.

3.7.1 Plating. Fastener devices such as nuts, bolts, screws, washers and cotter pins shall be commercial quality, cadmium plated. Steel rivets shall be commercial quality, cadmium or zinc plated.

* 3.8 Electromagnetic compatibility. When specified (see 6.2) equipment shall be designed and equipped for electromagnetic compatibility in accordance with class II B of MIL-STD-461 (see 4.6.3).

3.9 Lubrication. At the time of delivery, baling presses shall be completely lubricated with the manufacturer's standard lubricant.

* 3.10 Marking for identification. The presses shall be marked for identification in accordance with the manufacturer's standard practice.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

3.11 Workmanship. The complete press shall be clean, properly assembled, and in alignment. All exposed surfaces shall be free from burrs and sharp edges. Components shall not be loose, bowed, dented or fractured. Surfaces shall show no evidence of rust or corrosion.

3.11.1 Rivets. Rivets shall be tight and heads shall be completely formed and in full contact with the surface of the riveted member.

3.11.2 Fasteners. Fasteners such as screws, nuts and bolts shall be drawn tightly. Fasteners subject to excessive vibration shall be secured with antivibration means such as castelated nuts with cotter pin, lock washer, and self-locking nuts.

3.11.3 Welding. Welding shall be continuous, smooth, adherent, free from pinholes, fractures, slag inclusion and flux deposits.

4. QUALITY ASSURANCE PROVISIONS

* 4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3)
2. Quality conformance inspection (see 4.4)

* 4.3 First article inspection. When a first article is required it shall be examined for defects in table II, dimensions specified, and tested in accordance with 4.4.1, 4.4.2 and 4.4.3, as applicable. The presence of any visual defect, any dimension not within the specified requirements or failure to pass the tests shall be cause for rejection of the first article.

* 4.4 Quality conformance inspection. Except as otherwise specified herein sampling for inspection shall be performed in accordance with MIL-STD-105.

* 4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified, or qualified in this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

* 4.4.2 End item inspection. The lot shall be all baling presses of one type, size and style as applicable, offered for inspection at one time. The sample unit shall be one baling press.

* 4.4.2.1 Visual examination. The completely assembled item shall be examined for defects in table II. The inspection level shall be II and the acceptable quality level (AQL) shall be 2.5 for major and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE II. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Not manufacturer's standard	X	
Design	Any characteristic not in accordance with the specified requirement	X	
Construction and workmanship general (applicable to all components and assemblies)	Evidence of rust or corrosion		X
	Fractured, bowed or dented	X	
	Sharp burr or sharp edges	X	
	Component misplaced, loose or not in proper alignment	X	
	Component that requires abnormal force to operate	X	
	Any adjustable component that cannot be adjusted or is not properly adjusted to perform the functions intended	X	
	Any component not accessible for servicing where required	X	
Welding	Missing or incomplete	X	
	Not adherent	X	
	Burnt holes, slag inclusion or fractured	X	
	Not smooth, or scale not removed		X
Soldering connections (where required)	Missing, loose or broken	X	
	Not clean		X
Rivet connections (where applicable)	Missing or broken	X	
	Loose		X
	Heads not fully formed		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

TABLE II. Classification of defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Bolts, nuts, screws, studs, and other types of threaded fasteners	Missing	X	
	Stripped or fractured	X	
	Loose		X
	Not locking type where required		X
Assembly	Component not properly assembled or secured	X	
	Unit perceptibly out of alignment	X	
Marking for identification	Missing, incomplete, not legible, not permanent or not as specified		X

4.4.2.2 Dimensional examination. Examination shall be made of the end item to determine compliance with dimensional requirements. Any nonconforming dimensions shall be classified as a defect. The inspection level shall be S-4 with an AQL of 6.5, expressed in terms of defects per hundred units.

* 4.4.2.3 Testing of the end item. The baling presses shall be tested in accordance with the applicable tests of 4.6.1 through 4.6.2.4. Any nonconformance shall be considered a defect. The inspection level shall be II with an AQL of 6.5, expressed in terms of defects per hundred units. When applicable, the test as specified in 4.6.3 shall be performed on one representative production unit and failure of the test shall be cause for rejection of the item.

* 4.4.3 Inspection of packaging. An inspection shall be made to determine that preservation-packaging, packing and marking comply with section 5, and an examination shall be made of closure, anchoring, waterproofing and strapping in compliance with the appendix of MIL-C-104. Defects shall be as specified in table III. The lot size shall be all containers offered for inspection at one time. The sample unit shall be one container prepared for delivery. The inspection level shall be S-4 with an AQL of 6.5, expressed in terms of defects per hundred units.

TABLE III. Examination of packaging

Examine	Defect
Markings	Omitted; incorrect; illegible; of improper size, location, sequence or method of application
Materials	Component missing or damaged
Preservation	Preservative improperly applied or missing
Contents	Contents per container is more or less than required

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

* 4.5 Certificate examination. Certificate of compliance, certified test reports, approval labels or listing marks for codes and standards, as applicable, that are submitted as proof of compliance with specification requirements shall be examined and validated.

4.6 Tests.

* 4.6.1 Load test. The force in pounds (kgs) transmitted by the baling press shall be calculated from the motivating force or pressure applied, exclusive of friction losses, to determine compliance with table I requirements.

4.6.2 Operating tests. The baling press loading chamber shall be loaded with baling material as specified herein. The press shall be operated in accordance with the manufacturer's operating instructions to form a complete bale. This test procedure shall be followed to determine compliance with requirements for the respective baling presses specified hereinafter.

4.6.2.1 Type I. Type I baling presses shall be loaded with rags or cotton waste and tested in accordance with 4.6.2 to determine compliance with 3.6 and 3.6.3.2.

4.6.2.2 Type II.

4.6.2.2.1 Chain drive, screw drive, or rack and pinion drive. Type II presses with chain, screw, or rack and pinion drives shall be loaded with rags or cotton waste material and tested in accordance with 4.6.2 to determine compliance with 3.6, 3.6.3.2, 3.6.5.1, and 3.6.5.2.

4.6.2.2.2 Hydraulic drive. Type II presses with hydraulic drives shall be loaded with rags or cotton waste material and tested in accordance with 4.6.2 to determine compliance with 3.6, 3.6.3.2, and 3.6.3.4.

4.6.2.3 Type III. Type III press shall be loaded with scrap steel and tested in accordance with 4.6.2 to determine compliance with 3.6, and 3.6.3.4.

4.6.2.4 Relay switch. The electric motor shaft rotation shall be restrained; the motor shall be energized by the motor "on" and "off" switch and the thermal relay switch shall then be checked to determine compliance with 3.6.3.3.

* 4.6.3 Electromagnetic compatibility. When electromagnetic compatability is required, the first article or initial unit of production as applicable, shall be tested by the contractor in accordance with test methods CE03 and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the contractor or an independent testing agency. The contractor shall furnish the Contracting Officer written certification that the Interference Control Plan, the EMI/EMC Test Plan, the electromagnetic compatability test report and requirements meet MIL-STD-461.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

5. PACKAGING

* 5.1 Preservation-packaging. Preservation-packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. The extent of disassembly shall be determined by the manufacturer. This determination shall be based on the need for protection to fragile or projecting parts and for the reduction of cubage. Parts removed shall be adequately identified or tagged.

5.1.1.2 Preservation. All preservation shall be in accordance with material and method requirements of MIL-P-116 as hereinafter specified.

5.1.1.2.1 Cleaning. All uncoated, unlubricated, exposed ferrous metal surfaces of each press and all interior surfaces of the hydraulic system of each hydraulic drive press shall be cleaned process C-1 and thoroughly dried.

5.1.1.2.2 Noncontacting and contacting surfaces. All noncontacting surfaces (surfaces that do not contact other surfaces in operation), cleaned as specified in 5.1.1.2.1, shall be coated with type P-1 preservative. All contacting surfaces (surfaces that contact with other surfaces in operation), except hydraulic systems and pulleys, cleaned as specified in 5.1.1.2.1, shall be coated with type P-2 or P-6 preservative. All such preserved surfaces that may contact other surfaces or packaging and packing material, except those coated with type P-1 preservative, shall be covered or wrapped with greaseproof barrier material conforming to type I or II, grade A of MIL-B-121. Barrier material shall be secured with twine made of jute, sisal, manila, or cotton, or tape conforming to PPP-T-45 or heat sealed when heat sealable barrier material is used.

5.1.1.2.3 Hydraulic systems. The hydraulic fluid reservoir of each hydraulic system, cleaned as specified in 5.1.1.2.1, shall be flushed with hydraulic fluid designated by the manufacturer. All exposed surfaces of each piston rod shall be coated with type P-2 or P-6 preservative and wrapped with barrier material as specified in 5.1.1.2.2.

* 5.1.1.2.4 Motors. All openings into electrical motors and pumps shall be sealed with tape conforming to class 1, type III or IV color optional of PPP-T-60.

5.1.1.2.5 Brakes. Brake surfaces, cleaned as specified in 5.1.1.2.1, shall be coated with primer conforming to TT-P-664.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

5.1.1.3 Packaging. Disassembled parts shall be packaged, or cushioned and secured in the chamber in such a manner as to prevent movement or damage during transit. Stacking sheets, when furnished, shall be secured in place. All doors shall be locked in the closed position by means provided thereon. Parts of each press that are free to move shall be secured in a fixed position to prevent movement or vibration during transit. Surfaces of hoses subject to damage, and gages shall be protected with cushioning material conforming to type II, class B or PPP-C-843, and the cushioning secured with tape specified in 5.1.1.2.4.

5.1.2 Commercial. Each press shall be cleaned, preserved and packaged to afford adequate protection against deterioration and damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets these requirements.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A packing. Each press, preserved-packaged as specified in 5.1, shall be packed upright in a crate conforming to type I, class 1 or 2, style a of MIL-C-104. Contents shall be anchored in accordance with the appendix of the crate specification.

5.2.2 Level B packing. Each press, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except that waterproofing of the container shall not be required.

* 5.2.3 Commercial packing. Presses, preserved and packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. Container and packing shall comply with the Uniform Freight Classification or National Motor Freight Classification, as applicable.

5.3 Marking. In addition to any special marking required by the contract, unit packages, intermediate packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Type I and II baling presses are intended for the compact baling of material such as clothing, rags, towels, paper, bolt goods, uniforms, feathers, et cetra. Type III baling press or briquetting machine is intended for baling of ferrous or nonferrous scrap metal.

* 6.2 Ordering data. Procurement documents should specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

(a) Title, number and date of this specification.
(b) Type, size, style of baling press (see 1.2).
(c) When a first article is required (see 3.1, 4.3 and 6.3).
(d) Electrical characteristics if other than specified (see 3.6.3.3).
(e) When electromagnetic compatibility is required (see 3.8).
(f) Selection of applicable levels of preservation-packaging and packing (see 5.1 and 5.2).

6.2.1 Contract data requirements. Any data items to be delivered under any contract for items covered by this specification shll be specifically called for in the contract in accordance with the applicable regulations of the procuring activity.

* 6.3 First article. When a first article is required, it should be inspected and approved under the appropriate provisions of ASPR 7-104.55. The first article should consist of one baling press as specified under the article in the ASPR. The contracting officer should include instructions in all procurement instruments regrading arragements for inspection and approval of the first article.

6.4 Changes from previous issue. The margins of this specification have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - SA
Air Force - 99

User activity:

Army - SM

Preparing activity:

Army - GL

Project No. 3540-0122

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRXNM-TD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314

Commander
US Army Natick Research and Development Command
ATTN: DRXNM-TD
Natick, MA 01760

NATICK OP 1 JUL 77
FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-B-43177B - BALING PRESSES

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.