INCH-POUND

MIL-C-43135J
10 September 1993
SUPERSEDING
MIL-C-43135H
30 March 1981

MILITARY SPECIFICATION

CHICKEN AND CHICKEN PRODUCTS, COOKED, DEHYDRATED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers freeze-dehydrated cooked chicken and chicken products for use by the Department of Defense as a component of operational rations.

1.2 Classification. The product shall be of the following types as specified (see 6.1):

Types

I - Chicken, diced
II - Chicken stew

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.1).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5018, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8905

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:46Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

A-A-1898	-	Cushioning Material, Cellulosic, Packaging
L-P-378	-	Plastic Sheet and Strip, Thin Gauge, Polyolefin
QQ-A-1876	-	Aluminum Foil
TT-C-495	-	Coatings, Exterior, for Tinned Food Cans
PPP-B-26	-	Bag, Plastic (General Purpose)
PPP-B-636	-	Boxes, Shipping, Fiberboard
PPP-C-29	-	Canned Subsistence Items, Packaging and Packing of
PPP-C-1752	-	Cushioning Material, Packaging, Unicellular Polyethylene Foam, Flexible
PPP-C-1797	-	Cushioning Material, Resilient, Low Density, Unicellular, Polypropylene Foam
PPP-T-60	-	Tape: Packaging, Waterproof

MILITARY

MIL-L-1497	-	Labeling of Metal Cans for Subsistence Items
MIL-L-35078	-	Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

FEDERAL

FED-STD-595	-	Colors Used in Government Procurement

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

(Copies are available from the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W., Washington, DC 20460.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

Meat and Poultry Inspection Regulations (9 CFR Parts 300-399)

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

U.S. Standards for Grades of Nonfat Dry Milk (Spray Process) (7 CFR Part 58)

(Copies are available from the Dairy Standardization Branch, Dairy Division, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2750, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

U.S. Standards for Grades of Carrots for Processing (7 CFR Part 51)

U.S. Standards for Grades of Fresh Shelled Peas for Canning or Freezing (7 CFR Part 51)

(Copies are available from the Head, Standardization Section, Fresh Products Branch, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2056, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

United States Standards for Condition of Food Containers

(Copies are available from the Chairperson, Condition of Container Committee, Agricultural Marketing Service, U.S. Department of Agriculture, Room 2506, South Building, P.O. Box 96456, Washington, DC 20090-6456.)

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES (HHS), U.S. FOOD AND DRUG ADMINISTRATION (FDA)

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Copies are available from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402-0001.)

2.2 Non-Government publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

AMERICAN DEHYDRATED ONION AND GARLIC ASSOCIATION (ADOGA)

Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products

(Application for copies should be addressed to the American Dehydrated Onion and Garlic Association, One Maritime Plaza, 23rd Floor, San Francisco, CA 94111.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 1238 - Flow Rates of Thermoplastics by Extrusion Plastometer
D 1505 - Density of Plastics by Density Gradient Technique

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

AOAC INTERNATIONAL

Official Methods of Analysis of the AOAC

(Application for copies should be addressed to the AOAC International, 2200 Wilson Boulevard, Suite 400, Arlington, VA 22201-3301.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC., AGENT

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., Traffic Department, 2200 Mill Road, Alexandria, VA 22314.)

THE UNITED STATES PHARMACOPEIAL CONVENTION, INC.

The United States Pharmacopeia (USP) and the National Formulary (NF)

Source: https://assist.dla.mil -- Downloaded: 202640-21T20:46Z
Check the source to verify that this is the currentversion before use.

(Application for copies should be addressed to the United States Pharmaceutical Convention, Inc., 12601 Twinbrook Parkway, Rockville, MD 20852.)

UNIFORM CLASSIFICATION COMMITTEE, AGENT

Uniform Freight Classification

(Application for copies should be addressed to the Uniform Classification Committee, Suite 1120, 222 South Riverside Plaza, Chicago, IL 60606.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.1), a sample shall be subjected to first article inspection (see 6.2) in accordance with 4.4.

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent or insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Chicken. The chicken shall be prepared from chilled or frozen broilers/fryers or roasters that are whole, halved, quartered or cut into parts, which have been processed in accordance with USDA Poultry Product Inspection Regulations. All chicken (raw or cooked) shipped between plants shall be accompanied by a USDA Poultry Product Grading Certificate to certify class and condition of the product and either the initial chilling date or initial freezing (in-storage) date.

3.2.1.1 Chicken, chilled. Raw bone-in or boneless chicken received in the chilled state shall not have been previously frozen and shall have been held at an internal temperature of 28°F to 40°F for a period of time not to exceed six days following initial chilling and prior to preparation and further processing (see 3.3).

3.2.1.2 Chicken, frozen. Raw bone-in or boneless chicken received in the frozen state shall have been held at an internal temperature of 0°F or below for a period of time not to exceed 120 days following initial freezing and prior to preparation and further processing (see 3.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

3.2.1.3 Chicken, cooked, frozen. Frozen cooked chicken shall be prepared from chilled chicken that complies with 3.2.1 and 3.2.1.1. Chicken shall be processed in accordance with 3.3.1. Cooked chicken, in dice form, shall be packaged and vacuum-sealed in water impermeable material having an oxygen permeability rate of not more than 10cc of oxygen per square meter per 24 hours at 73°F and 0 percent relative humidity. The chicken logs or dices shall be frozen to an internal temperature of 0°F or below within 72 hours after packaging. The packaged, frozen, cooked chicken (logs or dices) shall have been held at 0°F or below for a period not to exceed 60 days prior to further processing (see 3.3.2 or 3.3.6). The initial freezing (in-storage) date and processing and packaging requirements shall be certified by a USDA Agricultural Marketing Service (AMS) Poultry Products Agent. Alternatively, chicken dices produced from cooked chicken logs may be packaged in suitable material other than that described above and placed in a freezer immediately after dicing and frozen to 0°F or below within 24 hours after placement in the freezer. Frozen, cooked chicken dices packaged in other than the impermeable material shall be held at an internal temperature of 0°F or below for a period of time not to exceed 30 days. If other than impermeable packaging material is used, the type of material shall be approved by USDA.

3.2.2 Potatoes.

3.2.2.1 Potatoes, fresh. The potatoes shall be fresh, firm, clean, sound, and of a white flesh variety. The specific gravity shall be not less than 1.068 and not greater than 1.081 (total solids not less than 18 percent or greater than 21 percent). The reducing sugar content shall be not more than 2.0 percent on a dry weight basis.

3.2.2.2 Potatoes, diced, water blanched, frozen. The frozen potato dices shall be prepared from fresh potatoes meeting the requirements of 3.2.2.1 and be from the latest seasons crop. The frozen potato dices shall be processed, handled, and packaged in a manner so as to prevent discoloration. Frozen potato dices shall be held at 0°F or below until further processing.

3.2.3 Broth, chicken. Chicken broth shall be either frozen or canned (thermostabilized). The broth shall be clear, essentially fat free with a 3.0 to 3.5 percent solids content. The broth shall have a characteristic mild chicken broth odor and flavor and may contain not more than 1.25 percent salt and/or flavor enhancers approved by the FDA. The chicken broth shall be produced in a USDA inspected plant in accordance with USDA Poultry Products Inspection Regulations. If frozen, it shall have been held at an internal temperature of 0°F or below for a period not to exceed 75 days prior to use in product formulation.

3.2.4 Carrots.

3.2.4.1 Carrots, fresh. The fresh carrots shall be U.S. No. 2 or better of the U.S. Standards for Grades of Carrots for Processing.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:46Z
Check the source to verify that this is the current version before use.

3.2.4.2 Carrots, diced, individually quick frozen (IQF). The IQF diced carrots shall have been prepared from carrots meeting the requirements of 3.2.4.1 and 3.3.3.3. The IQF carrot dices shall be of the latest season's pack.

3.2.5 Peas, green.

3.2.5.1 Peas, green, fresh, shelled. The fresh shelled green peas shall be U.S. No. 2 or better of the U.S. Standards for Grades of Fresh Shelled Peas for Canning or Freezing. The peas shall be of such size as to not pass through a 9/32 inch sieve. Peas shall be slit or perforated to improve rehydration characteristics.

3.2.5.2 Peas, green, shelled, individually quick frozen (IQF). The IQF shelled green peas shall have been prepared from fresh green peas meeting the requirements of 3.2.5.1 and 3.3.3.4. The IQF shelled green peas shall be of the latest season's pack. Peas shall be slit or perforated to improve rehydration characteristics.

3.2.6 Oil, corn. Corn oil shall possess a clean, bland flavor, and shall have a minimum stability of 25 hours (A.O.M.), a free fatty acid value not to exceed 0.05 percent, a moisture/volatile matter content not to exceed 0.06 percent and pass a cold test of 5.5 hours (minimum).

3.2.7 Milk, nonfat, dry, instant. Instant nonfat dry milk shall be U.S. Extra Grade of the U.S. Standards for Grades of Nonfat Dry Milk (Spray Process).

3.2.8 Starch, freeze-thaw stable. Freeze-thaw stable starch shall form a smooth, short textured, heavy bodied, almost clear aqueous solution. The flavor of the cooked solution shall be bland with essentially no cereal or starchy taste.

3.2.9 Onion, chopped, dehydrated. Dehydrated chopped onions shall be Fancy grade of the Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products.

3.2.10 Salt. Salt shall be white, refined sodium chloride with or without anticaking agents and shall comply with the purity standards for sodium chloride of the Food Chemicals Codex.

3.2.11 Poultry seasoning. The poultry seasoning shall be free from lumps, shall have an overall uniform color, and shall not tend to stratify in layers of individual spices. The poultry seasoning shall possess a fragrant, aromatic aroma and shall have a warm pungent taste. The poultry seasoning shall be prepared from ground spices having the characteristics listed below and shall be formulated as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

Ingredient	Percent by weight	Particle size	Minimum volatile oil
Sage	72-78		1.5 mL per 100 g
Thyme	18-22		0.8 mL per 100 g
Pepper, black	4.5-5.5	95% through a U.S. Standard No. 30 sieve	1.5 mL per 100 g

3.2.12 Pepper, black, ground. Ground black pepper shall have been ground from the deep brown to black, deep-set, wrinkled, immature berries of Piper nigrum L. The ground pepper shall have a characteristic, penetrating odor, a hot, biting, pungent flavor and a light gray to speckled black-gray color. The ground pepper shall contain not less than 2.0 mL of volatile oil per 100 grams of ground black pepper and be of such size that 95 percent shall pass through a U.S. Standard No. 16 sieve.

3.2.13 Garlic powder. Garlic powder shall be Fancy grade of the Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products.

3.2.14 Turmeric, ground. Ground turmeric shall be prepared from Curcuma longa L. and shall possess a deep yellow to orange-yellow color with a peppery, aromatic odor. The ground turmeric shall contain not less than 3.5 mL of volatile oil per 100 grams and shall be of such size that not less than 95 percent shall pass through a U.S. Standard No. 40 sieve.

3.2.15 Water. Water used for washing, formulation, blanching, and processing shall conform to the National Primary Drinking Water Regulations.

3.2.16 Nitrogen. Nitrogen shall meet the requirements of the United States Pharmacopeia and shall be water or liquid nitrogen pumped.

3.2.17 Preblended spice and seasoning mix. Preblended spices and seasonings may be used. The spices and seasonings in the mix shall comply with the individual requirements specified in this specification. The containers used for the spice and seasonings mix shall be labeled with each ingredient and the percentage of each ingredient in the mix. The ingredients shall be in the same proportions as specified in the spice and seasoning mix formula (see 3.3.5).

3.3 Preparation and processing. Processing shall be on a continuous basis.

3.3.1 Chicken preparation. The chicken, meeting the requirements of 3.2.1, shall be made boneless and skinless. The wing tips, giblets, neck, feet, and viscera shall be excluded. The boned meat shall be free of pin feathers, skin, blood clots, bruises, blemishes, ligaments, tendons, coarse

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

connective tissue, cartilage, and bone greater than 0.3 inch in any dimension. The boneless chicken meat shall be comprised of at least 50 percent white meat.

3.3.1.1 Chicken log preparation and processing. The chicken logs shall be prepared and processed as follows:

Ingredient	Percent by weight
Chicken meat	99.00
Salt	1.00

a. Fresh chilled chicken meat processed on the day of boning shall be coarse ground within 24 hours following boning. If fresh-chilled (not previously frozen) chicken meat is transported between plants, it shall be maintained at an internal temperature of 28°F to 40°F and coarse ground within six days following initial chilling. Frozen chicken meat shall be maintained at 0°F or lower until further processing and be coarse ground within 120 days after boning. The meat shall be mechanically coarse ground through a grinder plate having openings measuring not less than one inch in diameter.

b. The coarse ground (chunked) chicken meat shall be mechanically mixed with salt. The mixing shall continue until the mixture exhibits a sticky (tacky) consistency. The time from grinding to mixing shall not exceed four hours. The ground chicken meat shall be maintained at an internal temperature of 28°F to 40°F during this time period. Dry ice may be used to control the temperature during mixing.

c. The mixed chicken shall immediately be mechanically tightly stuffed into suitable casings of a size to meet the finished product chicken dimension requirements. The stuffed chicken logs shall be cooked within 24 hours after being stuffed. The internal temperature of the logs shall be maintained at 28°F to 40°F prior to cooking.

d. The chicken logs shall be cooked by any commercially acceptable method until an internal temperature of 165°F to 175°F is reached.

e. Immediately after completion of the cooking process, the cooked chicken logs shall be placed in an ice water bath, or cooled by any other commercially acceptable rapid cooling methods. During cooling, the internal temperature of the chicken log shall not remain between 130°F and 80°F for more than 1.5 hours or between 80°F and 40°F for more than 5 hours. The cooled logs shall be held for not more than 48 hours at an internal temperature of 28°F to 40°F prior to dicing or packaging for frozen storage (see 3.2.1.3).

f. The cooked chicken logs shall be mechanically diced with dicer settings at 1 by 1 by 3/8 inches for the type I product and 1/2 by 1/2 by 1/4 inch for the type II product (± 1/16 inch tolerance is permitted for each

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

dicer setting). The diced chicken shall be held not longer than 4 hours in the temperature range of 28°F to 40°F until preparation of the finished product or, if stored in frozen form, until packaged and vacuum-sealed (see 3.2.1.3). Dices prepared from previously frozen logs, shall not be frozen.

3.3.2 Type I product preparation (chicken, diced). Type I product shall be prepared by freezing and freeze-drying the 1 by 1 by 3/8 inch diced chicken (see 3.4 and 3.5).

3.3.3 Vegetable preparation.

3.3.3.1 Preparation of fresh potatoes. The fresh potatoes shall be thoroughly cleaned to remove dark and extraneous material, peeled, trimmed, and thoroughly washed. The washed potatoes shall be mechanically diced with a dicer setting of 3/8 by 3/8 by 3/8 inch (± 1/16 inch in each dimension). The potato dices shall be cooked sufficiently to assure compliance with finished product requirements. The cooked potatoes shall be immediately cooled with cooling water to the initial temperature of the cooling water and thoroughly drained. The cooled drained potatoes shall be handled in a manner to prevent discoloration and shall be used in product preparation within four hours after cooking.

3.3.3.2 Frozen potato dice preparation. Frozen potato dices shall be cooked and handled as specified in 3.3.3.1 (see 3.3.6).

3.3.3.3 Fresh carrot preparation. The clean, fresh carrots shall be peeled, trimmed, and mechanically diced with dicer settings of 3/8 by 3/8 by 3/8 inch (± 1/16 inch in each dimension). The diced carrots shall be blanched only to the extent necessary to prevent discoloration and to remove excess air. The blanched carrots shall be immediately cooled to the initial temperature of the cooling water and thoroughly drained. The cooled, drained carrots shall be handled in a manner to prevent discoloration and used in product preparation or individually quick frozen within four hours after blanching.

3.3.3.4 Fresh green pea preparation. The fresh green peas shall be blanched only to the extent necessary to prevent discoloration and to remove excess air. The blanched peas shall be immediately cooled to the initial temperature of the cooling water and thoroughly drained. The cooled drained peas shall be handled in a manner to prevent discoloration and used in product preparation or individually quick frozen within four hours after blanching. The peas shall be slit or perforated to improve rehydration characteristics.

3.3.4 Frozen vegetable preparation. Frozen vegetables shall be thawed only to the extent necessary to accommodate product preparation procedures.

3.3.5 Spice and seasoning mix preparation. The spice and seasoning mix shall be a uniform blend of the following ingredients:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

Ingredient	Percent by weight
Onion, chopped, dehydrated	61.8
Salt	31.3
Poultry seasoning	3.2
Pepper, black, ground	1.8
Garlic powder	1.4
Turmeric, ground	0.5

3.3.6 Type II product preparation. The chicken stew shall be formulated and prepared as follows:

Ingredient	Percent by weight
Chicken, cooked, diced	25.0
Potatoes, raw, diced	20.0
Broth, chicken	15.0
Water	12.3
Carrots, raw, diced	10.0
Peas, slit or perforated	10.0
Oil, corn	2.5
Milk, nonfat, dry, instant	1.8
Starch, freeze-thaw stable	1.8
Spice and seasoning mix	1.6

NOTE: The following product preparation procedures were used in the development of this product. Alternative procedures may be used provided finished product requirements are met. (When alternative procedures are used, the time and temperature requirements specified for the prepared product are still applicable.)

a. A slurry shall be made using the starch and a portion of the water.

b. The instant nonfat dry milk shall be reconstituted with the remaining formula water.

c. The seasoning mix and chicken broth shall be added to the slurry and mixed well. The mixture shall then be heated to 180°F with continuous mixing.

d. The chicken dices, peas, carrots and corn oil shall be added and the mixture heated to 160°F to 180°F.

e. The cooked potatoes (see 3.3.3.1) and reconstituted nonfat dry milk shall be added to the mixture and mixed only to the extent necessary to assure a uniform blend of ingredients.

f. The product shall be spread on the dehydrator trays immediately after completion of the cooking process.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

3.4 Freezing. The prepared product shall be spread on dehydrator trays and cooled immediately, placed in the freezer within four hours after cooking, and frozen to 0°F or below within six hours after placing in the freezer. The frozen product shall be maintained at 0°F or lower at all times prior to freeze dehydration and shall be freeze dehydrated within five days after freezing.

3.5 Dehydration. The product shall be freeze dehydrated at an absolute pressure not to exceed 1.5 millimeters of mercury and at a product temperature as indicated by suitable instruments, not to exceed 150°F. If the platen temperature is maintained at 155°F or below with radiant heating, the product temperature may be disregarded. After dehydration is completed, the pressure shall be equalized to atmospheric level with nitrogen and the product shall be packaged as specified in 5.1. In no case shall more than 16 hours elapse between the time the chamber is opened and the time the product is completely packaged. During the interim the product shall be adequately protected from oxygen and moisture by either holding under a nitrogen atmosphere with 2.0 percent or less oxygen, or under a vacuum of at least 27 inches for the entire period. If a vacuum is used, it shall be broken with nitrogen.

3.6 Can or pouch with mixing bag filling and sealing. Each can or pouch with mixing bag shall be filled and sealed with product such as to conform to the finished product requirements and to the requirements specified in 5.1.1.

3.7 Finished product requirements.

3.7.1 Dehydrated product. The dehydrated product shall comply with the following requirements:

a. There shall be no foreign material, such as, but not limited to, dirt, insect parts, hair, wood, glass, or metal.

b. There shall be no foreign odor or flavor, such as, but not limited to, burnt, scorched, stale, sour, rancid, musty or moldy.

c. There shall be no color foreign to the product.

d. The individual net weight shall be not less than 120 grams for the Ration Cold Weather (RCW) pouch and not less than 140 grams for the Long Range Patrol (LRP) pouch.

e. The individual net weight of the canned product shall be not less than 19.2 ounces.

f. The lot average net weight of the canned product shall be not less than 20.0 ounces.

g. There shall be no evidence of incomplete dehydration such as wet or soft spots.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

h. There shall be no evidence of faulty dehydration such as glazed surface areas or burnt areas measuring more than 0.5 inch in any dimension or dark colored cores of any dimension.

i. At least 90 percent (by weight) of the type I product shall be retained on a U.S. Standard No. 3-1/2 sieve and at least 30 percent (by weight) of the type II product shall be retained on a U.S. Standard No. 4 sieve.

j. At least 50 percent by weight of the type I product shall be white meat.

k. The type I product shall not contain more than 23 percent fat.

l. Moisture content of the dehydrated product shall not exceed 2.0 percent.

m. The aerobic plate count shall be not greater than 75,000 per gram in four of five samples, and not greater than 150,000 per gram in any sample.

n. The E. coli count shall be less than 3 per gram (no positives in the standard 3 tube MPN technique) in four of five samples and not greater than 10 per gram in any sample.

3.7.2 Rehydrated product. Rehydration shall be in accordance with the specified instructions in 4.5.6. The rehydrated product shall comply with the following requirements:

a. The rehydrated product shall show complete water penetration. However, gristle and similar materials in the meat do not necessarily rehydrate properly and such materials shall not be considered as evidence of incomplete rehydration.

b. The rehydrated product shall posses the flavor, odor and texture considered normal for cooked, frozen and reheated chicken dices or chicken stew, as applicable.

c. There shall be no feathers or feather parts.

d. Total weight of skin, bone, cartilage, coarse connective tissue, section of tendons or ligaments, and discolored meat, collectively, from a 120 gram aliquot of dehydrated product, shall be not more than ten grams in the type I product after rehydration and not more than two grams in the type II product after rehydration.

3.7.3 Palatability. The finished product shall be equal to or better than the approved preproduction sample (see 6.1) in palatability and overall appearance.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:46Z
Check the source to verify that this is the current version before use.

3.8 Plant qualification. The poultry component and the finished product shall originate and be produced, processed, and stored in plants regularly operating under Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture.

3.9 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this specification. The contractor shall ensure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection and supervision necessary to ensure compliance with the requirements of this specification.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5).

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this specification and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this specification or any appearance or palatability failure shall be cause for rejection of the first article.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material examination. In accordance with 4.1, components and materials shall be examined in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.5.1.1 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, and compliance shall be verified by examination of pertinent labels, markings, U.S. Grade Certificates, certificates of analyses, or other such valid documents acceptable to the inspection agency. If necessary, each

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

ingredient shall be examined organoleptically or inspected according to generally recognized test methods, such as the methods described in the Official Methods of Analysis of the AOAC and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.1.2 Mixing bag, baseboard, and pouch material certification. The material listed below may be accepted on the basis of a contractor's certificate of conformance to the indicated requirements. In addition, compliance to the requirements for inside pouch dimensions and dimensions of manufacturer's seals may be verified by certificate of conformance.

Requirement	Requirement paragraph	Test procedure
Mixing bag material identification	5.1.1.2	Laboratory evaluation
Baseboard (when used)	5.1.1.2.2	Laboratory evaluation
Thickness of films for laminated material	5.1.1.3	As specified in L-P-378, except that a mechanists' micrometer may be used provided that its graduations and accuracy conform to the requirements of L-P-378
Aluminum foil thickness	5.1.1.3	As specified in QQ-A-1876
Laminated material identification and construction	5.1.1.3	Laboratory evaluation
Color of laminated material	5.1.1.3	Visual evaluation

4.5.1.3 Unfilled mixing bag examination. The unfilled mixing bags shall be examined for the defects listed in table I. The lot size shall be expressed in bags. The sample unit shall be one mixing bag. The inspection level shall be S-4 and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 0.65 for major defects.

TABLE I. Unfilled mixing bag defects

Category	Defect
Major	
101	Not formed as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

TABLE I. Unfilled mixing bag defects (cont'd)

Category	Defect
Major	
102	Inside dimensions not as specified
103	Tear, hole, or open seal
104	Bags stick together
105	Not clean
106	Foreign odor

4.5.1.4 Unfilled mixing bag leakage testing. Eight unfilled mixing bags shall be selected at random from the lot regardless of lot size and shall be tested for leakage as follows: Each sample bag shall be filled with eight ounces of boiling water (being careful not to spill any water on the outside) and suspended eight to twelve inches above a sheet of clean paper for 10 minutes. Any moisture on the paper attributable to bag leakage shall be classified as a major defect. The lot size shall be expressed in bags. The sample unit shall be one bag. The finding of any defect shall be cause for rejection of the lot.

4.5.1.5 Unfilled can examination. Conformance of unfilled cans to the requirements specified in 5.1.1.1 shall be determined by examination of certificates of conformance or of other valid documents. Any nonconformance shall be cause for rejection of the can lot or any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, filling, sealing, and packaging requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation, or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Net weight examination.

4.5.3.1 Net weight examination of pouches. The net weight of the filled and sealed pouches shall be determined by weighing each sample unit on a suitable scale tared with a representative empty mixing bag and pouch. Any individual net weight of less than 120 grams for the RCW pouch or less than 140 grams for the LRP pouch shall be classified as a minor defect. Results shall be reported to the nearest gram. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

4.5.3.2 Net weight examination of cans. The net weight of the filled and sealed cans shall be determined by weighing each sample unit on a suitable scale tared with a representative empty can and lid. Any individual net weight less than 19.2 ounces shall be classified as a minor defect. Results shall be reported to the nearest 0.1 ounce. The lot size shall be expressed in cans. The sample unit shall be one filled and sealed can. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 2.5. In addition, the lot shall be rejected if the sample average net weight is less than 20.0 ounces.

4.5.4 Filled and sealed pouch examination. The filled and sealed pouches shall be examined for the defects listed in table II. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.65 for major defects and 4.0 for minor defects.

TABLE II. Filled and sealed pouch defects 1/

Category		Defect
Major	Minor	
101		Tear, cut, hole, or abrasion through one or more layers in the pouch material or leakage through any heat seal 2/
102		Foldover wrinkle extending into the seal such that the effective closure seal is reduced to less than 1/16 inch 3/
103		Presence of entrapped product that reduces the effective closure seal to less than 1/16 inch 3/
104		Presence of delamination 4/
105		Unclean pouch 5/
106		Labeling is missing, incorrect, or illegible
107		Any impression or design on the heat seal surfaces which conceals or impairs visual detection of seal defects 6/
108		Less than 3/16 inch between inside edge of tear notch and inside edge of seal
109		Closure seal width not as specified
110		Closure seal not located as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

TABLE II. Filled and sealed pouch defects 1/ (cont'd)

Category		Defect
Major	Minor	
	201	Tear notch or serrations missing or not located as specified
	202	Depth of tear notch or serrations not as specified
	203	Presence of delamination 4/

1/ Any evidence of rodent or insect infestation shall be cause for rejection of the lot.

2/ Pinholes or breaks inherent to the manufacturing process of the aluminum foil shall not be scored as a defect.

3/ The effective closure seal is defined as any uncontaminated, fusion bonded, continuous path, minimum 1/16 inch wide, from side seal to side seal that produces a hermetically sealed pouch.

4/ Delamination defect classification:

Major - Delamination of the outer ply in the pouch seal area that can be propagated to expose aluminum foil at the food product edge of the pouch after manual flexing of the delaminated area. To flex, the delaminated area shall be held between the thumb and forefinger of each hand with both thumbs and forefingers touching each other. The delaminated area shall then be rapidly flexed 10 times by rotating both hands in alternating clockwise-counterclockwise directions. Care shall be exercised when flexing delaminated areas near the tear notches to avoid tearing the pouch material. After flexing, the separated outer ply shall be grasped between thumb and forefinger and gently lifted toward the food product edge of the seal or if the separated area is too small to be held between the thumb and forefinger, a number two stylus shall be inserted into the delaminated area and a gentle lifting force applied against the outer ply. If separation of the outer ply can be made to extend to the product edge of the seal with no discernible resistance to the gentle lifting, the delamination shall be classified as a major defect. Additionally, spot delamination of the outer ply in the body of the pouch that is able to be propagated beyond its initial borders is also a major defect. To determine if the delaminated area is a defect, use the following procedure: Mark the outside edges of the delaminated area using a bold permanent marking pen. Open the pouch and remove the

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

contents. Cut the pouch transversely not closer than 1/4 inch (± 1/16 inch) from the delaminated area. The pouch shall be flexed in the area in question using the procedure described above. Any propagation of the delaminated area, as evidenced by the delaminated area exceeding the limits of the outlined borders, shall be classified as a major defect.

Minor - Minor delamination of the outer ply in the pouch seal area is acceptable and shall not be classified as a minor defect unless it extends to within 1/16 inch of the food product edge of the seal. All other minor outer ply delamination in the pouch seal area or isolated spots of delamination in the body of the pouch that do not propagate when flexed as described above shall be classified as minor defects.

5/ Outer packaging shall be free from foreign matter which is unwholesome, has the potential to cause pouch damage (for example, glass, metal filings) or generally detracts from the clean appearance of the pouch. The following examples shall not be scored as defects for unclean:

a. Foreign matter which presents no health hazard or potential pouch damage and which can be readily removed by gently shaking the package or by gently brushing the pouch with a clean dry cloth.

b. Dried product which affects less than 1/8 of the total surface area of one pouch face (localized and aggregate).

c. Water spots.

6/ If doubt exists as to whether or not the sealing equipment leaves an impression or design on the closure seal surface that could conceal or impair visual detection of seal defects, samples shall be furnished to the contracting officer for a determination as to acceptability.

4.5.5 Pouch vacuum examination. The filled and vacuum sealed pouches shall be visually examined for conformance to the vacuum requirement in 5.1.1.4 not less than 96 hours after filling and sealing. The sealed pouch shall continue to exhibit tight adherence to the surface contours of the contents when a pulling force is applied at the center of each side seal. This force shall be applied by holding each side seal between thumb and forefinger of each hand, while simultaneously exerting a slight pull with both hands. Any evidence of loss of vacuum shall be classified as a major defect. The lot size shall be expressed in pouches. The sample unit shall be one filled and sealed pouch. The inspection level shall be I and the AQL, expressed in terms of defects per hundred units, shall be 0.65.

4.5.6 Product examination. The finished product, type I and type II, shall be examined for the defects listed in table III. The lot size shall be expressed in pouches or cans. The sample unit shall be the contents of one filled and sealed pouch or can. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 1.5 for major defects and 6.5 for minor defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

TABLE III. Product defects 1/ 2/

Category		Defect
Major	Minor	Applicable to dehydrated product
101		Evidence of incomplete dehydration such as wet or soft spots
102		Presence of glazed surface areas measuring more than 0.5 inch in any dimension
103		Presence of burned areas as indicated by a black spot more than 0.5 inch in any dimension
104		Presence of dark colored cores in any dimension
105		Less than 90 percent of product retained on a U.S. Standard No. 3-1/2 sieve (type I product) 3/
106		Less than 50 percent by weight of the type I product is light meat
	201	Less than 30 percent (by weight) retained on a U.S. Standard No. 4 sieve (type II product) 3/
		Applicable to rehydrated product 4/
107		Incomplete water penetration through all particles 5/
108		Flavor, odor and texture not normal for cooked, frozen and reheated chicken dices or chicken stew, as applicable
109		Presence of feathers or feather parts
110		Total weight of skin, bone, cartilage, coarse connective tissue, section of tendons or ligaments, and discolored meat, collectively from a 120 gram aliquot of dehydrated product, is more than ten grams in the type I product after rehydration or more than two grams in the type II product after rehydration

1/ The presence of foreign material (for example, dirt, insect parts, hair, wood, glass, metal), foreign odor or flavor (for example, burnt, scorched, stale, sour, rancid, musty, moldy), or foreign color shall be cause for rejection of the lot.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

2/ Product not equal to or better than the approved preproduction sample in palatability or overall appearance shall be cause for rejection of the lot (see 3.7.3).

3/ For canned product, 240 grams of dry product shall be mechanically shaken for 2 minutes for sieve testing. For pouched product, randomly select two 120 or two 140 gram pouches, as applicable, and mechanically shake for 2 minutes for sieve testing.

4/ For type I product, rehydrate in accordance with label instruction. For type II product, multiply product weight in grams by 3.3 to get milliliters of hot water for rehydration, then continue with label instructions.

5/ Dry areas attributable to gristle and similar material shall not be considered as defects.

4.5.7 Internal pressure test. Eight filled and sealed pouches shall be selected at random from the lot regardless of lot size and individually tested for internal pressure resistance. The internal pressure resistance shall be determined by pressurizing the pouches while they are restrained between two rigid plates spaced 1/2 ± 1/16 inch apart. If a three-seal tester (one that pressurizes the pouch through an open end) is used, the closure seal shall be cut off for testing the side and bottom seals of the pouch; for testing of the closure seal, the bottom seal shall be cut off. The pouches shall be emptied prior to testing. If a four-seal tester (designed to pressurize filled pouches by use of a hypodermic needle through the pouch wall) is used, all four seals can be tested simultaneously. The distance between rigid restraining plates on the four-seal tester shall be equal to the thickness of the product plus 1/16 inch. Pressure shall be applied at the approximate uniform rate of 1 pound per square inch gage (psig) per second until 14 psig pressure is reached. The 14 psig pressure shall be held constant for 30 seconds and then released. The pouches shall then be examined for separation or yield of the heat seals. Any rupture of the pouch or evidence of seal separation greater than 1/16 inch in the pouch manufacturers seal shall be considered a test failure. Any seal separation that reduces the effective closure seal width to less than 1/16 inch (see table II) shall be considered a test failure. The lot size shall be expressed in pouches. The sample unit shall be one pouch. Any test failure shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.8 Leakage testing of cans. Examination shall be in accordance with the criteria of PPP-C-29.

4.5.9 Oxygen in headspace testing. Eight filled and sealed cans shall be selected at random from the lot regardless of lot size and tested for oxygen content in the headspace. The oxygen content in the headspace gas shall be determined by using an electronic oxygen analyzer which operates on the principle of the difference in partial pressure of oxygen between the oxygen

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

reference and the oxygen content of the sample as detected by a porous ceramic zirconia sensor, such as the Illinois Instruments analyzer or its equivalent; or on the principle of paramagnetic resonance such as the Servomex analyzer, or its equivalent. The oxygen analyzer shall be calibrated to a known standard prior to testing the headspace gas of the product. Product shall be tested within 24 hours of packing. Results shall be reported to the nearest 0.1 percent. The lot size shall be expressed in cans. The sample unit shall be one filled and sealed can. Any nonconformance to the requirement in 5.1.1.1 shall be classified as a major defect and shall be cause for rejection of the lot. The contents of these cans may be used for the product examination in 4.5.6.

4.5.10 Fat content testing. The type I finished product shall be tested for fat content in accordance with the Official Methods of Analysis of the AOAC, method 960.39, 976.21 or 985.15. The results shall be reported to the nearest 0.1 percent. Any result not conforming to the requirement in 3.7 shall be classified as a major defect. The lot size shall be expressed in cans. The sample unit shall be one filled and sealed can. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 1.5.

4.5.11 Moisture content testing. Eight filled and sealed pouches or cans shall be selected at random from the lot regardless of lot size. The contents of the pouches or cans shall be individually blended to uniformity using a blender or a food processor. The blending must be rapid and conducted in such a way that minimum heat is transferred to the product and that the product has minimum exposure to atmospheric moisture. The blended samples shall be tested for moisture content in accordance with the Official Methods of Analysis of the AOAC, method 950.46A for type I product and method 925.45 for type II product, except that the temperature-time cycle shall be modified by using a temperature of 70°C for 16 hours at a pressure of not more than 100 mm of mercury. The results shall be reported to the nearest 0.1 percent. Any result not conforming to the requirement in 3.7 shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.12 Microbiological testing. Five filled and sealed pouches or cans of finished product shall be selected at random from the lot regardless of lot size. The contents of each sample pouch or can shall be tested for aerobic plate count and E. coli in accordance with the Official Methods of Analysis of the AOAC, methods 966.23 and 966.24. The diluent shall be added to each sample of dry product and allowed to stand for 15 minutes before the blending of that sample. Continue as directed by AOAC. Any result not conforming to the microbiological requirements in 3.7 shall be classified as a major defect and shall be cause for rejection of the lot.

4.5.13 Examination of can labeling. Examination shall be in accordance with the criteria of MIL-L-1497.

4.5.14 External examination of cans. External examination of cans shall be performed in accordance with the applicable requirements of the United States Standards for Condition of Food Containers.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

4.5.15 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: Marking missing, incorrect, or illegible
Cushioning material missing or not as specified

Minor: More than 40 pounds packed in shipping container (applicable to pouches)
Bags not packed flat in layers (applicable to pouches)

4.5.16 Unit load examination. Examination of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKAGING

5.1 Preservation. Preservation shall be level A.

5.1.1 Level A. The product shall be unit packed in cans or barrier pouches as specified (see 6.1).

5.1.1.1 Cans. A net weight of 20.0 ounces of product (type I) shall be filled into a size 603 by 700 open top style, round metal can with a soldered or welded side seam and compound lined double seamed ends. A maximum 0.8 ounce tolerance will be allowed in any can provided the lot average net weight of the cans inspected in accordance with 4.5.3.2 is not less than 20.0 ounces. The can shall be made throughout from not less than commercial 0.20 pound per base box electrolytic tin plate and shall be coated overall on the outside with a coating conforming to type I of TT-C-495. The product shall be preserved under an atmosphere of nitrogen equivalent to the holding requirements of 3.5. The filled and sealed can shall not leak when tested in accordance with 4.5.8. The oxygen content of the gases in the filled and sealed cans shall not exceed 2.0 percent when tested in accordance with 4.5.9.

5.1.1.2 Mixing bags. For the type II product, a net weight of 120 grams for the RCW or 140 grams for the LRP shall be filled into mixing bags fabricated from 0.003 inch thick polyethylene made in accordance with type I bags of PPP-B-26, except that the bag shall be made from food grade polyethylene. The bags shall not impart any undesirable odor or flavor to the product and shall be FDA approved for food use. The inside dimensions of the bag shall be 5-1/2 by 3-1/2 by 8 inches (± 1/8 inch in each dimension) with the open end of the bag having the 5-1/2 by 3-1/2 inch dimensions. After filling, the side panels of the bag (corresponding to the 3-1/2 inch dimension) shall be folded in to form gussets, and the bag shall be closed by folding over its open end. Where required by the bulkiness of the product, the bulk of the contents within the bag shall be compressed such that the product thickness is not less than 2-1/4 inches by applying a constant

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

uniform pressure over the entire top surface of the product. The open top of the filled bag shall be folded over to prevent spillage of the product. Alternatively, polyethylene bags conforming to type II of PPP-B-26, with inside dimensions of 9 inches by 8 inches (± 1/8 inch in each dimension) with the open end of the bag having the 9 inch dimension, may be used. The material shall be as specified for type I bags. When type II bags are used, they shall be formed over a baseboard on a mandrel as specified in 5.1.1.2.1 before filling. While the bag is positioned on the mandrel, the two bag ears shall be taped down over a 5-1/2 by 3-1/2 inch baseboard constructed in accordance with 5.1.1.2.2. An eight inch long strip of one inch wide tape complying with type III, class 2 of PPP-T-60, shall be applied across both ears to fasten them securely to the baseboard. Alternatively, both type I and type II mixing bags may be fabricated from unpigmented 0.003 inch (± 0.0006 inch) thick high density 0.941 to 0.965 g/cm^3 food grade, flat polyethylene tubing. The bottom seal of type I and type II mixing bags fabricated from clear polyethylene or the alternate material shall be of adequate strength and integrity to withstand the addition of boiling water when tested in accordance with 4.5.1.4.

5.1.1.2.1 Mandrel. The mandrel face shall be 5-3/8 by 3-3/8 inches and the height shall be not less than 12 inches. All corners and edges of the mandrel shall be rounded and all surfaces finished to prevent damage to the bag material.

5.1.1.2.2 Baseboard. The baseboard shall be constructed from unbleached and uncoated solid sulfate or sulfite paperboard not less than 0.022 inch thick. Alternatively, the baseboard may be constructed from 0.022 inch thick food grade paperboard made from recycled fibers. If paperboard made from recycled fibers is used, it shall be natural color ranging from brown to grey. The baseboard shall be 5-1/2 by 3-1/2 inches (± 1/8 inch in each dimension) and shall have all corners rounded to form a smooth contour.

5.1.1.3 Barrier pouches. The pouch shall be constructed from a multiple ply flexible laminate barrier material consisting of an outer ply of 0.0005 inch thick polyester bonded to an intermediate ply of 0.0007 inch thick aluminum foil with 10 pounds per ream pigmented polyethylene, and bonding the opposite side of the aluminum foil to 0.003 inch thick ionomer (inner ply) or a blend of not less than 50 percent linear low density polyethylene and polyethylene. All tolerances for thickness of pouch materials shall be plus or minus 20 percent. The linear low density polyethylene portion of the blend shall be the copolymer of ethylene and octene-1, having a melt index range of 0.8 to 1.2 g/10 minutes in accordance with ASTM D 1238 and a density range of 0.918 to 0.922 g/cm^3 in accordance with ASTM D 1505. For LRP applications, the complete exterior surface of the pouch shall be uniformly colored in the range of green 34079 through 34087 or 24052 through 24087 or brown 30045 through 30118 (excluding 30109) or 10045 of FED-STD-595. For RCW applications, the complete exterior surface of the pouch shall be colored white overall with a color in the range of 37778 through 37886 of FED-STD-595. The material shall be suitably formulated for food packaging

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

and shall not impart an odor or flavor to the product being packaged. The material shall show no evidence of delamination, degradation, or foreign odor when heat sealed or fabricated into pouches.

5.1.1.3.1 Pouch construction. The pouch shall be a flat style preformed pouch having inside dimensions of 6 inches by 9 inches (± 1/8 inch in each dimension). The first dimension specified shall be the opening of the pouch between the heat sealed sides. The empty pouch shall be made by heat sealing three edges with 3/8 inch (± 1/8 inch) wide seals. A "V", "C", or block "U" tear notch at least 1/32 inch deep located 1 to 1-1/4 inches from the top edge of the pouch, shall be made in one or both side seals. The distance between the inside edge of the tear notch and the inside edge of the seal shall be at least 3/16 inch. One side of the open end of the pouch may be provided with an extended or foldover lip, extended not more than 5/16 inch to facilitate opening and filling. Tear notch location shall be measured from the top of the pouch, excluding the extended or foldover lip. Alternatively, if the pouch has serrated edges, the serrations may be used as tear notches provided that the serrations are sharp (no plastic tailings exists) and the serrations depth and the minimum seal width at the serrated edges are in accordance with the above requirements. The pouch shall be constructed with square or rounded corners at all four corners (radius approximately 3/8-inch).

5.1.1.4 Pouch filling and sealing. The filled mixing bag specified in 5.1.1.2 shall be inserted in a pouch as specified in 5.1.1.3 in such a manner as to avoid puncturing the pouch material or contaminating the heat seal area. The filled pouches shall be sealed under a vacuum level of 23 inches of mercury. The sealed pouch shall show no loss of vacuum when examined as specified in 4.5.5. The filled pouches shall have 3/8 inch (± 1/8 inch) heat seal. If thermal impulse closure seals are used, a seal width of 1/8 to 7/16 inch will be acceptable. When tested as specified in 4.5.7, the filled and sealed pouches shall withstand an internal pressure of 14 psig for 30 seconds without rupture or seal separation greater than 1/16 inch or seal separation that reduces the effective closure seal width to less than 1/16 inch. The closure seal shall not extend below the tear notch on either side of the pouch. The closure seal shall be free of fold over wrinkles that reduce the effective closure seal to less than 1/16 inch.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.1).

5.2.1 Level A packing. Six cans of product, preserved as specified in 5.1, shall be packed three in length and two in width in a snug-fitting fiberboard box constructed and closed in accordance with style RSC, V2s of PPP-B-636. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

5.2.2 Level B packing. Six cans of product, preserved as specified in 5.1, shall be packed three in length and two in width in a snug-fitting fiberboard box constructed and closed in accordance with style RSC, V3c, V3s, or V4s of PPP-B-636. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament reinforced tape in accordance with the appendix of PPP-B-636.

5.2.3 Level C packing.

5.2.3.1 Cans. Six cans of product, preserved as specified in 5.1, shall be packed three in length and two in width in shipping containers conforming to National Motor Freight Classification and Uniform Freight Classification, as applicable, except that the closure of fiberboard boxes shall be in accordance with method II as specified in the appendix of PPP-B-636.

5.2.3.2 Pouches. Not more than 40 pounds of pouched product shall be packed flat in a fiberboard box constructed and closed in accordance with style RSC-L, class domestic, variety SW, grade 200, of PPP-B-636. Cushioning material not less than 1/8 inch thick, conforming to grade II, class B or C of A-A-1898 or cushioning material not less than 1/16 inch thick, conforming to type I of PPP-C-1797 or cushioning material conforming to type VII, class 1 of PPP-C-1752 shall be placed between each of the layers and in the bottom and top of the box to minimize movement of the individual packages.

5.3 Unit loads. When specified (see 6.1), the product packed as specified in 5.2.2 and 5.2.3 shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping.

5.4 Labeling and marking.

5.4.1 Pouches. Each pouch shall be clearly printed or stamped, in a manner that does not damage the pouch, with permanent black ink which is free of carcinogenic elements or ingredients. The information shall be located on the body of the pouch not closer than 1/16 inch to any seal. If a non-contact type printer is used, the information may be located anywhere on the pouch (in one complete print), except the closure seal area. The label shall contain the following information:

CHICKEN STEW, COOKED, DEHYDRATED
(letters not less than 7/32 inch high)
ADD 12-14 OUNCES OF HOT WATER (APPROXIMATELY 1/2 CANTEEN CUP) TO MIXING BAG. STIR, WAIT APPROXIMATELY 5 MINUTES.
(HOT WATER MAY BE ADDED IN STAGES TO KEEP FOOD HOT.)
(letters not less than 1/8 inch high)
Ingredients
(letters not less than 3/32 inch high)
Date 1/
(letters not less than 1/8 inch high)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

Net weight
(letters not less than 1/8 inch high)
Official establishment number (for example, EST-38/USDA stamp)
(letters not less than 1/8 inch high)
Contractor's name and address
(letters not less than 1/8 inch high)

1/ Each pouch shall have the date of pack noted by using a four digit code beginning with the final digit of the current year followed by the three digit Julian day code. For example, March 19, 1991 would read 1079. The Julian day code shall represent the date the product is unit packed into the pouch.

5.4.2 Cans. Cans shall be labeled in accordance with MIL-L-1497 and in addition shall contain the following information:

CHICKEN, DICED, COOKED, DEHYDRATED

DIRECTIONS FOR USE:
ADD 3-3/4 QUARTS OF BOILING WATER TO CONTENTS OF CAN, STIR, COVER, LET STAND 20 MINUTES OR LONGER. DRAIN. USE IN ANY RECIPE REQUIRING COOKED DICED CHICKEN. FOR SALAD, REFRIGERATE AT ONCE IN A SMALL-SIZED COVERED CONTAINER AND USE AT NEXT MEAL. SUBSTITUTE 20 OUNCES (1 CAN) COOKED DEHYDRATED CHICKEN FOR 12-1/2 POUNDS FRESH CHICKEN READY-TO-COOK OR 3-1/3 POUNDS FRESH CHICKEN COOKED AND BONED.
Date
Net weight
Official establishment number (for example, EST-38/USDA stamp)
Contractor's name and address

5.4.3 Shipping containers. Shipping containers shall be marked in accordance with MIL-STD-129.

5.4.4 Unit load marking. Unit loads shall be marked in accordance with MIL-L-35078.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Acquisition requirements. Acquisition document must specify the following:

a. Title, number, and date of this specification.
b. Type of product required (see 1.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
d. When a first article is required (see 3.1, 4.4, and 6.2).
e. Provisions for approved preproduction samples (see 3.6.1 and 6.2).
f. Level of packing required (see 5.2).
g. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).
h. Ration, Cold Weather or Long Range Patrol component.

6.2 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.3 Subject term (key word) listing.

Canned food
Chicken stew
Freeze dried
Long Range Patrol
Pouched food
Ration Cold Weather
Shelf stable foods

6.4 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - SA
Air Force - 50

Preparing activity:

Army - GL

(Project 8905-1107)

Review activities:

Army - MD, QM
Navy - MC
DLA - SS

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-C-43135J	1993 September 10

3. DOCUMENT TITLE

CHICKEN AND CHICKEN PRODUCTS, COOKED, DEHYDRATED

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (*Last, First, Middle Initial*)	b. ORGANIZATION	
c. ADDRESS (*Include Zip Code*) [redacted]	d. TELEPHONE (*Include Area Code*) (1) Commercial [redacted] (2) AUTOVON [redacted] (*If applicable*)	7. DATE SUBMITTED (YYMMDD) [redacted]

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (*Include Area Code*)	
U.S. Army Natick RD&E Center	(1) Commercial 508-651-4501	(2) AUTOVON/DSN 256-4501
c. ADDRESS (*Include Zip Code*) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-WTP Natick, MA 01760-5018	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil — Downloaded: 2026-04-24T20:40Z
Check the source to verify that this is the current version before use.