INCH-POUND

MIL-T-43150C
25 October 1991
SUPERSEDING
MIL-T-43150B
27 April 1984

MILITARY SPECIFICATION

TABLE, PARACHUTE PACKING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirement for a parachute packing table.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard
PPP-T-45 - Tape, Gummed, Paper, Reinforced and Plain for Sealing and Securing

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 7195

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:48Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-C-52950 - Crate, Wood, Open and Covered

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-130 - Identification Marking of U.S. Military Property

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

11-1-3179 - Table, Parachute Packing, Assembly
11-1-3181 - Table Top, Assembly

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-UX, Natick, MA 01760-5017.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:48Z
Check the source to verify that this is the current version before use.

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for related associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials and components. Material and component requirements shall be in accordance with this document and subsidiary documents cited on the applicable drawings. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3 Construction. The construction of the table shall conform in all respects to Drawing 11-1-3179 and all subsidiary drawings and parts lists pertaining thereto, and as specified herein.

3.3.1 Identification marking. The tables shall be marked with the manufacturer's name, tradename, or trademark identifiable with said manufacturer. No advertising names or slogans will be used. Marking shall be applied in accordance with MIL-STD-130.

3.3.2 Rivets. All rivets shall be securely peened and shall have a bucked head not less than 1.6 times the rivet diameter.

3.4 Workmanship. The tables shall be clean and shall be free of scratches, sharp edges and burrs. The finished item shall not show any signs of buckling or damage. Welds shall blend with adjacent surfaces and be free of scale and flux deposits. The end item shall conform to the quality of product established by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:48Z
Check the source to verify that this is the current version before use.

the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect all items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. Any nonconformance shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component and material certification. A certificate of compliance may be acceptable as evidence for three coats of polyurethane applied as specified on drawing 11-1-3181.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:48Z
Check the source to verify that this is the current version before use.

4.4.2 In-process inspection. Inspection of subassemblies shall be made to ascertain that construction details which cannot be examined in the finished product are in accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicated nonconformance.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of tables. The sample unit shall be one completely fabricated table. The inspection level shall be III and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 1.5 for major defects and 2.5 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Finish, cadmium plating	Any area of rust or corrosion	101	
	Any breaks, scratches, or tool marks through plating to metal		201
Construction and workmanship	Any component missing or not assembled or joined as specified	102	
	Any operation omitted or not performed as specified	103	
	Any sharp edges, burrs, slivers, or splinters	104	
	Dirt, oil, grease, smudge, or other foreign matter		202
	Any damaged or malformed component	105	
	Bow in table top greater than 1/8 inch transversely or 3/16 inch longitudinally	106	
Riveting	Rivet not securely or neatly set		203
Marking for identification	Missing, incorrect, illegible or incomplete		204

4.4.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Any dimension not within the specified tolerance shall be classified a defect. The lot size shall be expressed in units of tables. The sample unit shall be one completely fabricated table. The inspection level shall be III and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:48Z
Check the source to verify that this is the current version before use.

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (interior and exterior container)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, defective, or not as specified
Workmanship	Inadequate application of components such as: incomplete sealing or closure of flap, improper taping, loose strapping or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A preservation. Each table shall be folded to its collapsed position. The top and edges of each table top shall be covered with one thickness of highly calendered kraft paper or waxed paper having a minimum basis weight of 30 pounds per ream (24 by 36 - 500), and secured to the underside of the table top with 2 inch minimum width tape conforming to Type III, grade B of PPP-T-45. The table shall then be unit packed in a snug-fitting fiberboard box conforming to style FPF, grade V3c of PPP-B-636, except that the weight and dimensional limitations shall be waived. Each box shall be closed and waterproofed by means of tape in accordance with the appendix of PPP-B-636.

5.1.3 Commercial preservation. The tables shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Two tables, preserved as specified in 5.1, shall be packed top to top in a crate conforming to type II, style A of MIL-C-52950, except that the bottom crossmember shall be nominal 1- by 6-inch lumber with one edge of the top and bottom crossmembers in alignment. Each crate shall be provided with nominal 2- by 4-inch skids laid flat, positioned parallel to the ends, and extending the full exterior width of the crate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:48Z
Check the source to verify that this is the current version before use.

Skids shall be placed one under each end crossmember, flush with the inside edge, and under each intermediate crossmember, flush with its unaligned edge. The ends of the skids shall be beveled one-half the thickness at a 45-degree angle. Skids shall be secured by nailing through the bottom crossmembers and skids, and the nails clinched not less than 1/8 inch. Nails fastening the skids shall be arranged in two rows in a staggered pattern, with spacing between nails in each row to be not more than 6 inches. Each row of nails shall be approximately 1/2 inch in from the edge of the skid. The nailing pattern shall begin and end approximately 1-1/2 inches in from the ends of each skid. Strapping shall be positioned alongside the skids. When level A packaging is specified (see 5.1.1), class weather-resistant boxes shall be used and waterproofed with tape as specified in the appendix of PPP-B-636. Each shipping container shall be closed and strapped in accordance with the appendix of MIL-C-52950.

5.2.2 Level B packing. Two tables, preserved as specified in 5.1, shall be packed top to top in a crate conforming to type II, style B of MIL-C-52950. Each crate shall be provided with skids as specified in 5.2.1. Each crate shall be closed and strapped in accordance with the appendix of MIL-C-52950.

5.2.3 Commercial packing. Tables, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special marking required by the contract or purchase order, unit packs and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The parachute packing table is intended for use in packing parachutes. The design provides for the tables to be used in multiples to accommodate length requirements.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:48Z
Check the source to verify that this is the current version before use.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Aid, assembly

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:

Army - GL
Navy - AS
Air Force - 99

Preparing activity:

Army - GL

(Project 7195-0099)

Review activities:

Navy - MC
Air Force - 84
DLA-GS

User activity:

Army - ME

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:48Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-T-43150C	1991 October 25

3. DOCUMENT TITLE
TABLE, PARACHUTE PACKING

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4531	256-4531
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-UXT Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2024-05-12 04:48Z
Check the source to verify that this is the current version before use.