INCH-POUND

MIL-DTL-43150D
26 November 2024
SUPERSEDING
MIL-T-43150C
25 October 1991

MILITARY SPECIFICATION

TABLE, PARACHUTE PACKING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirement for a parachute packing table.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation or contract.

DRAWINGS

US ARMY NATICK SOLDIER SYSTEMS CENTER (NSSC)

11-1-3179	- Table, Parachute Packing, Assembly
11-1-3181	- Table Top, Assembly

(Copies of drawings are available from US Army Natick Soldier Systems Center, https://www.army.mil/natick.)

Comments, suggestions, or questions on this document should be addressed to DLA Troop Support – Construction and Equipment (C&E) (ATTN: Code FCSB), 700 Robbins Avenue, Philadelphia, PA 19111-5096 or email CE_Standardization@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil .

AMSC N/A FSC 7195

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:48Z
Check the source to verify that this is the current version before use.

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

AMERICAN SOCIETY FOR QUALITY (ASQ)

ASQ-Z1.4 -Sampling Procedures and Tables for Inspection by Attributes

(Copies of this documents are available online at http://www.asq.org or the American Society for Quality, 600 North Plankinton Avenue, Milwaukee, WI 53203.)

2.4 Order of Precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this specification takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.2.

3.2 Materials and components. Material and components requirements shall be in accordance with this document and subsidiary documents cited on the applicable drawings (see 4.3.1). Recycled, recovered, environmentally preferable, or biobased materials should be used to the maximum extent possible, provided that the material meets or exceeds the operational and maintenance requirements, and promotes economically advantageous life cycle costs.

3.3 Construction. The construction of the table shall conform in all respects to Drawing 11-1-3179 and all subsidiary drawings and parts lists pertaining thereto, and as specified herein (see 4.3.3).

3.3.1 Identification marking. Identification marking shall conform to drawing 11-1-3179 and subsidiary drawings (see 4.3.3).

3.3.2 Rivets. All rivets shall be securely peened and shall have a bucked head not less than 1. 6 times the rivet diameter (see 4.3.3).

3.4 Workmanship. The tables shall be clean and shall be free of scratches, sharp edges and burrs. The finished item shall not show any signs of buckling or damage. Welds shall blend with adjacent surfaces and be free of scale and flux deposits (see 4.3.3).

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.2).
b. Conformance inspection (see 4.3).

4.2 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.3.3 and 4.3.4. Any nonconformance shall be cause for rejection of the first article.

4.3 Conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with ASQ-Z1.4.

4.3.1 Component and material inspection. In accordance with 3.2, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:48Z
Check the source to verify that this is the current version before use.

4.3.1.1 Component and material certification. A certificate of compliance may be acceptable as evidence for three coats of polyurethane applied as specified on drawing 11-1-3181.

4.3.2 In-process inspection. Inspection of subassemblies shall be made to ascertain that construction details which cannot be examined in the finished product are in accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance, any material or service for which in-process inspection has indicated nonconformance.

4.3.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of tables. The sample unit shall be one completely fabricated table. The inspection level shall be III.

TABLE I. End Item visual defects.

Examine	Defect	Classification Major	Minor
Finish, cadmium plating	Any area of rust or corrosion	101	
	Any breaks, scratches or tool marks Through plating to metal		201
Construction and workmanship	Any component missing or not assembled or joined as specified	102	
	Any operation omitted or not performed as specified	103	
	Any sharp edges, burrs, slivers, or splinters	104	
	Dirt, oil, grease, smudge, or other foreign matter		202
	Any damaged or malformed component	105	
	Bow in tabletop greater than 1/8 inch transversely or 3/16 inch longitudinally	106	
Riveting	Rivet not securely or neatly set		203
Marking for Identification	Missing, incorrect, illegible or incomplete		204

4.3.4 End item dimensional examination. The end items shall be examined for conformance to the dimensions specified on the drawings. Any dimension not within the specified tolerance shall be classified a defect. The lot size shall be expressed in units of tables. The sample unit shall be one completely fabricated table. The inspection level shall be III.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of material is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Services or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:48Z
Check the source to verify that this is the current version before use.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The parachute packing table is intended for use in packing parachutes. The design provides for the tables to be used in multiples to accommodate length requirements.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title number and date of this specification.
b. When the first article is required (see 3.1, 4.2 and 6.3).
c. Packaging requirements (see 5.1).

6.3 First article. When a first article is required, it should be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection. Inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Aid, assembly

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:
Army - GL
Navy - AS
Air Force - 84
DLA - CQ

Review activities:
Army - CR4
Navy - MC

Preparing activity:
DLA - CQ

(Project 7195-2024-001)

NOTE: The activities listed above were interested in this document as of the date of document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:48Z
Check the source to verify that this is the current version before use.