MIL-S-43176C
7 October 1987
SUPERSEDING
MIL-S-43176B
30 June 1971

MILITARY SPECIFICATION

SCREEN, LATRINE, FIRE, WATER, WEATHER, AND MILDEW RESISTANT TREATED, O.D.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers a latrine screen made of olive drab cotton duck, fire, water, weather, and mildew resistant treated. A cover is provided to protect the screen during storage and transportation.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issue of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

A-A-203 - Paper, Kraft, Untreated
T-T-871 - Twine, Cotton, Wrapping

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

T-T-911 - Twine, Jute
V-T-285 - Thread, Polyester
CCC-C-429 - Cloth, Osnaburg, Cotton
CCC-C-467 - Cloth, Burlap, Jute (or Kenaf)
DDD-L-20 - Label: For Clothing, Equipage, and Tentage, (General Use)
PPP-B-601 - Boxes, Wood, Cleated-Plywood
PPP-B-636 - Boxes, Fiberboard, Shipping

MILITARY

MIL-P-549 - Poles, Tent, Upright and Ridge
MIL-L-1709 - Lines, Tent
MIL-S-1734 - Slips, Tent Line
MIL-P-2383 - Pins, Tent, Wood
MIL-C-2399 - Cement, Liquid, Tent Patching
MIL-G-16491 - Grommet, Metallic
MIL-T-40625 - Tubing, Bias Sewn (Burlap or Osnaburg) Cloth
MIL-C-43627 - Cloth, Duck, Cotton, Plied Yarns, Fire, Water, Weather and Mildew Resistant Treated, Lightdry Finish

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

5-4-821 - Screen, Latrine, FWWMRT, O.D.; Illustration and Details
5-4-822 - Cover
5-4-823 - Erection Instructions

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents. The following other Government documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

Department of the Army Field Manual FM 10-16
- General Repair of Tents, Canvas and Webbing

2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

3.2 Materials and components. Materials and components shall be as specified herein and on applicable drawings (see 6.5).

3.2.1 Cloth, duck, cotton. Cloth shall conform to Olive Drab 7 of MIL-C-43627 (see 6.5).

3.2.2 Thread, polyester. The thread shall conform to type I, class 1, subclass A or B, shade S-1 (CA 66022) of V-T-285. The dyed thread shall show colorfastness to weathering equal to or better than the standard shade sample (see 6.3). If no standard shade sample is available, the thread shall show good colorfastness to weathering. Thread sizes shall be as follows:

For all stitching except stitching indicated by "Z" on drawings	Size F for needle and bobbin
For stitching indicated by "Z" on drawings	Size F for needle and size E for looper

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

3.2.3 Lines, tent. The tent lines shall conform to types VI, XV, XVIII, and XXI of MIL-L-1709.

3.2.4 Grommets, metallic. The grommets shall conform to type III, class 3, size No. 4 of MIL-G-16491.

3.2.5 Slips, tent line. The tent line slips shall conform to type II of MIL-S-1734.

3.2.6 Pins, tent, wood. When required (see 6.2), the tent pins shall be size 1, conform to MIL-P-2383.

3.2.7 Poles, tent, upright and ridge. When required (see 6.2), the tent poles shall conform to MIL-P-549.

3.3 Construction. The construction of the latrine screen shall conform to the drawings listed in section 2 and shall be as specified herein.

3.3.1 Stitching, machine. All stitching shall conform to FED-STD-751 as follows:

For all stitching except stitching indicated by "Z" on drawings	Type 301, 5 to 7 stitches per inch
For stitching indicated by "Z" on drawings	Type 401, 5 to 7 stitches per inch. The chain portion of stitching shall not appear on outside of screen or cover.

3.3.1.1 Stitching ends. Stitching ends shall be overstitched not less than 1 inch on stitch type 301, except where ends are turned under in a hem, where ends are held down by other stitching, or where stitching is performed automatically. When stitch patterns such as box, box with cross-stitch, "W" stitching, or straight line tacking are performed automatically, at least three or more tying, overlapping, or back stitches shall be used to secure the ends of stitching.

3.3.1.2 Thread breaks. Thread breaks in stitching shall be overstitched not less than 1 inch at each break on stitch type 301 and not less than 1-1/2 inches at each break on stitch type 401. Thread breaks noted during inspection shall be repaired by overstitching the existing stitching and the defective area for not less than 1 inch on type 301 stitching and 1-1/2 inches on type 401 stitching on each side of the break. The ends of repair stitchings are not required to be backstitched. Thread breaks in type 401 stitching may be overstitched with stitch type 301.

3.3.1.3 Thread ends. All thread ends that are visible on the finished item shall be trimmed to a length of not more than 1/4 inch.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:51Z
Check the source to verify that this is the currentversion before use.

3.3.1.4 Lubrication of thread. There shall be no lubrication of the thread by any means prior to or during sewing (see 4.4.2).

3.3.1.5 Stitching ends. Stitching at the ends shall be overstitched not less than 1 inch on stitch type 301, except where ends are turned under in a hem, where ends are held down by other stitching, or where stitching is performed automatically. When stitch patterns such as box, box with cross-stitch, "W" stitching, or straight line tacking are performed automatically, at least three or more tying, overlapping, or backstitches shall be used to secure the ends of stitching.

3.3.1.6 Skipped stitches. Two or more consecutively skipped stitches occurring in type 301 stitching shall be overstitched not less than 1 inch on each side of skips. Any skipped stitch in type 401 stitching shall be overstitched not less than 1-1/2 inches on each side of skip. Skipped stitches in type 401 stitching may be overstitched with type 301 stitching.

3.3.1.7 Automatic stitching. Automatic stitching machines may be used to perform any of the required stitch patterns provided the requirements of the stitch pattern, stitches per inch, size and type of thread are met, and at least three or more tying, overlapping or backstitches are used to secure the ends of the stitching.

3.4 Repairs. All necessary repairs shall be effected in accordance with Department of the Army Field Manual FM 10-16, except that hand-sewn patches, or cemented patches other than as specified herein will not be acceptable. Cemented patches on holes, cuts, or tears not more than 1 inch in diameter or length, using cement specified in MIL-C-2399, will be permitted. A maximum of two cemented patches per section will be allowable without prior contracting officer authorization. All other repairs shall require authorization by the contracting officer.

3.5 Location marks. Marks for showing location of component parts may be done with marking ink or by the use of drill holes. Ink marks or drill holes shall be located such that the marks or holes are completely and permanently covered by the component part.

3.6 Replacement of defective components. During the spreading, cutting, and manufacturing process, components of the latrine screens having material defects or damages that are classified as defects in 4.4.3 shall be removed from production and replaced with non-defective and properly matched components.

3.7 Marking. All labels and markings shall conform to DDD-L-20.

3.7.1 Identification marking. The letters "US" on the screen and cover and the nomenclature on the cover shall conform to type IV, class 9, in the size charac-ters and the locations shown on the drawings. Class 9 markings shall be clearly legible after exposure to accelerated weathering.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:51Z
Check the source to verify that this is the currentversion before use.

3.7.2 Identification label. Identification labels shall conform to type VI class 6 and shall be 3-1/2 inches by 5-1/2 inches minimum with a blank space at least 1-1/4 inches provided on the bottom of the label for the Department of Defense inspector's stamp. Identification labels shall be stitched to the screen and cover in the locations shown on the drawings.

3.7.3 Erection instructions label. Erection instructions labels shall conform to type VI, class 7 and shall be stitched to the screen and cover in the loca-tions shown on the drawings. The label shall be a proportionate copy of Drawing 5-4-823 as reproduced from a glossy print of this drawing furnished by the contracting officer. The size of the label shall be, borderline to borderline, 15 inches plus or minus 1/4 inch in the longer dimension with a minimum 1/2 inch margin outside of the borderline on all sides.

3.8 Workmanship. The latrine screen shall conform to the quality of product established by this document and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the rig to perform any of the inspections set forth in this document where such inspec-tions are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:51Z
Check the source to verify that this is the currentversion before use.

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in tables I and II. The presence of any defect shall be cause for rejec-tion of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.2 In-process examination. Inspection shall be made to determine that there is no lubrication of the polyester thread prior to or during the sewing operations as specified in 3.3.1.4.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of latrine screens or covers. The sample unit shall be one latrine or screen cover. The inspection level shall be I and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be as follows:

For screen:
6.5 major
15.0 major and minor A combined
40.0 major, minor A, and minor B combined

For cover:
10.0 major
25.0 major and minor A combined
100.0 major, minor A, and minor B combined

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor A	Minor B
Fabric	Cut or tear longer than 1/8 inch; hole (including exposed drill hole) larger than 1/8 inch diameter:			
	- on screen		X	
	- on cover			X
	Exposed drill hole (1/8 inch or less) i.e., not covered by attached parts:			

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Fabric (cont'd)	- more than one but not more than four			X
	- more than four		X	
	Broken or missing yarn; multiple floats clearly visible at normal inspection distance (approximately 3 feet)		X	
Rope components	Any cut; any break			
	- on guy line		X	
	- on tie line			X
	Eye splice omitted		X	
	Eye splice not as specified			X
	Free ends not finished as specified			X
Hardware	Broken	X		
	Malformed:			
	- fails to perform intended function	X		
	- but will perform intended function		X	
	Corroded area			X
	Burr or sharp edge which may cause injury in handling or damage to fabric	X		
Poles and pins	Any pole or pin not as specified or omitted	X		
Grommets	Improperly set, two or more teeth exposed			X
	Clinched loosely, allowing grommet to rotate around hole			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Grommets (cont'd)	Clinched excessively tight, cutting fabric	X		
	Insecurely clinched; i.e., grommets or washers become disengaged	X		
Seams and stitching	Open seam on stitch type 301:			
	- for more than 1/4 inch but not more than 1 inch			X
	- for more than 1 inch		X	
	Open seam on stitch type 401:			
	- one row of stitching open for 1 inch or less			X
	- one row of stitching open for more than 1 inch		X	
	- both rows of stitching open (not necessarily at same location)	X		
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken, or when one or more skipped or run-off stitches occur. On double stitched seams, a seam shall be classified as open when either one or both sides of a seam are open.			
	Raw edges caught in stitching:			
	- more than 1 inch but not more than 3 inches			X
	- more than 3 inches		X	
	Thread breaks:			
	- overstitched less than 1-1/2 inches on stitch type 401			X
	- overstitched less than 1 inch on stitch type 301		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Seams and stitching (cont'd)				
	NOTE: Thread breaks not overstitched shall be classified as open seams.			
	Skipped stitches overstitched less than:			
	- 1-1/2 inches on stitch type 401		X	
	- 1 inch on stitch type 301		X	
	NOTE: Skipped stitches not overstitched shall be classified as open seams.			
	Needle chews resulting in cut or tear larger than 1/8 inch in length, or hole larger than 1/8 inch in diameter:			
	- on screen		X	
	- on cover			X
	One or more required rows of stitching omitted	X		
Stitching ends	Overstitched less than 1 inch on stitch type 301 (except where ends are held down by other stitching or turned under in a hem)		X	
Seams	Seams pleated			X
Seam type	Wrong seam type	X		
Stitch type	Wrong stitch type	X		
Stitch tension	Loose, resulting in an exposed bobbin or top thread for more than 6 inches		X	
	Tight, as evidenced by puckering on fabric for more than 6 inches		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

that plate center hole fails

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Seams and stitching (cont'd)				
Stitches per inch	Less than minimum specified:			
	- one stitch			X
	- two or more stitches		X	
	More than maximum specified:			
	- one stitch			X
	- two or more stitches		X	
	NOTE: Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy seams or in turning corners, shall be classified as follows:			
	a. Within the minor "B" defect classification - no defect			
	b. Within the minor "A" defect classification - Minor B defect			
Stitching gage	Not as specified		X	
	NOTE: Applicable when double needle machine is used. When two rows of stitching are applied with a single needle machine, tolerances for stitching margin shall apply.			
Stitching margin	Larger than specified by more than 3/16 inch:			
	- for more than 2 inches but less than 4 inches in length			X
	- for 4 inches or more in length		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Seams and stitching (cont'd)				
Stitching indicated by "Z" on drawings	Chain portion of stitching shows on outside of screen or cover		X	
Mends, darns, or patches	Repairs not in accordance with Department of the Army Field Manual FM 10-16 or not authorized by the contracting officer	X		
Components and assembly	Any component not fabricated of applicable referenced material	X		
Hems	Constructed with partial turnunder when double turnunder is required			X
	Twisted or pleated			X
Reinforcements	Improperly applied, causing excessive fullness on reinforcement or reinforced parts			X
Labels	Omitted, incorrect, illegible or misplaced:			
	- erection instructions		X	
	- identification			X
Markings, "US" and nomenclature	Omitted, incorrect, illegible or misplaced			X
Cleanness	Grease or oil stains			X
	Thread ends not trimmed to 1/4 inch or less			X
Packaging	One or more bags/bundles omitted	115		

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

4.4.4 End item dimensional examination. The end item shall be examined for the defects listed in table II. The lot size shall be expressed in units of latrine screens or covers. The sample unit shall be one latrine screen or cover. The inspection level shall be S-3 and the AQL expressed in terms of defects per hundred units, shall be as follows:

For screen:
2.5 major
6.5 major and minor A
10.0 major, minor A, and minor B

For cover:
4.0 major
10.0 major and minor A
25.0 major, minor A, and minor B

TABLE II. End item dimensional defects

Examine	Defect	Classification Major	Minor A	Minor B
Overall dimensions	Smaller than specified dimensions less applicable minus tolerance indicated on drawings:			
	- on screen	X		
	- on cover		X	
	Larger than specified dimensions and applicable plus tolerance indicated on drawings:			
	- on screen			X
	- on cover			X
Hems and seams	Hems or seams required to finish:			
	- 1/2 inch or more but less than 1-1/2 inches in width, less than specified by more than 1/8 inch		X	
	- 1-1/2 inches or more but less than 2-3/4 inches in width, less than specified by more than 1/4 inch			X
	- 2-3/4 inches or more in width, more or less than specified by 1/2 inch			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

TABLE II. End item dimensional defects

Examine	Defect	Classification Major	Minor A	Minor B
Rope components (cont'd)	Guy line less than specified length:			
	- by not more than 4 inches			X
	- by more than 4 inches but not more than 12 inches		X	
	- by more than 12 inches	X		
	Tie line less than specified finished length:			
	- by not more than 2 inches			X
	- by more than 2 inches but not more than 6 inches		X	
	- by more than 6 inches	X		
Grommets	Set beyond specified location by more than 1/2 inch (unless otherwise specified)			X

4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling. Bulged or distorted container.
Content	Number per container is more or less than required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each screen shall be folded in a compact bundle to fit the screen cover, with the end bearing the erection instructions on the outside of the bundle. All lines and tent slips shall be placed inside the folds. The completely folded screen shall be placed within the screen cover and the cover secured with the tie lines.

5.1.2 Commercial. Screens shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A or Commercial as specified (see 6.2).

5.2.1 Level A packing. Screens, preserved as specified in 5.1, shall be packed in quantities of ten or more in a close fitting cleated-plywood box conforming to overseas type of PPP-B-601. Box and skids shall be fabricated in accordance with load type and gross weight requirements of PPP-B-601. Each shipping container shall be closed and reinforced with flat steel strapping in accordance with PPP-B-601.

5.2.1.1 Screen with cover, pins, and poles. Screen with cover, pins, and poles, when procured together (see 6.2), shall be packed in a snug-fitting wood-cleated plywood shipping container conforming to overseas type, style A or J of PPP-B-601. Each container shall be provided with skids fabricated as specified in the container specification. The inside dimensions of the shipping container shall be 108 inches in length, 19-1/2 inches in width, and 5-1/2 inches in depth. Pins and poles, as specified, shall be placed flat in the bottom of the shipping container. The screen shall be folded to form a bundle 63 inches in length, 19 inches in width, and 2-1/2 inches in depth. The cover shall be folded to form a bundle 22 inches in length, 15 inches in width, and 2-1/2 inches in depth. The screen and cover shall be wrapped in 60-pound basis weight kraft paper and placed flat, next to each other on top of the pins and poles. The contents of the shipping container shall be cushioned and immobilized, as applicable, to afford protection against abrasion during shipment and storage. Each shipping container shall be closed and reinforced with flat strapping in accordance with the appendix of PPP-B-601.

5.2.2 Level B packing. One screen, preserved as specified in 5.1, shall be packed in a close fitting fiberboard shipping container conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each box shall be fitted with box liner conforming to type CF (variety SW), class domestic, grade 275 of PPP-B-636. Each container shall have the contents completely covered on the top and bottom with a sheet of 30-pound minimum basis weight kraft paper conforming to A-A-203. Each container shall be closed in accordance with method II as specified in the appendix of the container specification. Alternatively, screens may be wrapped and sewn in

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

cotton osnaburg cloth conforming to class 2 of CCC-C-429; or burlap cloth conforming to class 3 of CCC-C-467. The cloth wrapping shall be securely hand sewn with type I or II, 16-ply, cotton twine conforming to T-T-871, or type . size no. 2 jute twine conforming to T-T-911, with approximately one stitch to the inch and every third stitch overhand knotted. Alternatively, the bottom and side may be machine-sewn. A minimum of 5 inches of wrapping material shall be gathered together on each of the four corners and securely hand-sewn into ears for handles. In lieu of the sewn wrapping indicated above, bias-sewn tubing (or bag presewn one end) conforming to MIL-T-40625 may be used. One end of the tubing may be machine-sewn. The formation of handles shall be effected by hand sewing in conformance with method as described above. Wherever machine sewing is used, the thread type, stitch type, and number of stitches per inch shall conform to the requirements specified in MIL-T-40625. However, the polyester thread used in manufacturing the end item may be used for effecting the machine sewn closure of the wrapping or tubing.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with method III as specified in the appendix of PPP-B-636.

5.2.2.2 Screen with cover, pins and poles. Screen with cover, pins, and poles, when procured together (see 6.2), shall be packed as specified in 5.2.1.1, except that the container shall conform to domestic type of PPP-B-601.

5.2.3 Commercial packing. Screens, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special marking required by the contract or order, shipments shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.3.1 Additional marking. The following shall be stencilled or imprinted on each cloth covered bundle in characters not less than 3/4-inch high:

"SEE ERECTION INSTRUCTIONS SEWED TO INSIDE OF SCREEN COVER"

6. NOTES

6.1 Intended use. The latrine screen is intended for issue to units in the field for use at an outdoor latrine.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.3, and 6.4).
c. Selection of applicable levels of preservation and packing (see 5.1 and 5.2).
d. When screen with cover, pins, and poles are procured together (see 5.2.1.1 and 5.2.2.2).
e. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

6.3 Standard shades. For access to a standard shade sample of thread, address the contracting activity issuing the invitation for bids.

6.4 First article. When a first article sample is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.5 Components. The following components, to be issued in the field, are required for the erection of the latrine screen.

Part	Quantity	Document
Pole, tent, upright, 7-foot	7	MIL-P-549
Pole, tent, ridge, 9-foot	2	MIL-P-549
Pole, tent, ridge, 7-foot	1	MIL-P-549
Pin, tent, wood, 16-inch	16	MIL-P-2383

6.6 Subject term (key word) listing.

Latrine
Screen

6.7 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army - GL
Air Force - 82

Review activity:

Army - MD

Preparing activity:

Army - GL

Project No. 8340-0495

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS. In a continuing effort to make our standardization documents better, the DOD provides this form for use i submitting comments and suggestions for improvements. All users of military standardization documents are invited to provid suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, an mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, w too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

NO POSTAG
NECESSAR
IF MAILED
IN THE
UNITED STAT

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-S-43176C	Screen, Latrine, Fire, Water, Weather, and Mildew Resistant Treated, O.D.

3. NAME OF SUBMITTING ORGANIZATION

4. TYPE OF ORGANIZATION (Mark one)

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER (Specify): _____

5. ADDRESS (Street, City, State, ZIP Code)

6. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

7. REMARKS

8a. NAME OF SUBMITTER (Last, First, MI) – Optional	b. WORK TELEPHONE NUMBER (Include Area Code) – Optional
c. MAILING ADDRESS (Street, City, State, ZIP Code) – Optional	9. DATE OF SUBMISSION (YYMMDD)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.