MIL-D-43164C
27 September 1978
SUPERSEDING
MIL-D-43164B
10 October 1969

MILITARY SPECIFICATION

DRY CLEANING UNITS, SINGLE BATH, COLD TYPE, FULLY AUTOMATIC, FOR SYNTHETIC SOLVENT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers synthetic solvent (perchlorethylene) dry cleaning units consisting of a washer-extractor, filter, and a combination sludge cooker and still.

1.2 Classification. The dry cleaning units shall be of the following minimum sizes, as specified (see 6.2):

Size 35 - 35 pounds (13.6 kg) dry-weight load capacity
Size 100 - 100 pounds (45.4 kg) dry-weight load capacity

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Natick Research and Development Command, Natick, MA 01760, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 3510

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:50Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

CC-M-1807	-	Motor, Alternating Current, Fractional and Integral (500 Horsepower and Smaller)
QQ-N-281	-	Nickel-Copper Alloy Bar, Plate, Rod, Sheet, Strip, Wire Forgings, and Structural and Special Shaped Sections
QQ-N-288	-	Nickel-Copper Alloy and Nickel-Copper-Silicon Alloy Castings

MILITARY

MIL-L-3153	-	Laundry and Dry Cleaning Machinery and Equipment (For Fixed Installations) Preparation for Delivery Of

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-461	-	Electromagnetic Interference Characteristics, Requirements for Equipment
MIL-STD-462	-	Electromagnetic Interference Characteristics, Measurement of
MIL-STD-1474	-	Noise Limits for Army Material

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

LAWS AND REGULATIONS

29 CFR 1910.1000 - Air Contaminants

HEW Publication No. (NIOSH) 75-159 - Statistical Methods for the Determination of Noncompliance with Occupational Health Standards

(The Code of Federal Regulations (CFR) and the Federal Register (FR) are for sale on a subscription basis by the Superintendent of Documents, US Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the Federal agency responsible for issuance thereof.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:50Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

FACTORY MUTUAL RESEARCH CORPORATION

Approval Standard - Classes II, III and IV Commercial Dry Cleaning

(Application for copies should be addressed to Factory Mutual Testing Laboratories, 1151 Providence Highway, Norwood, MA 02062.)

NATIONAL ELECTRICAL MANUFACTURERS' ASSOCIATION (NEMA)

Publication ICS - Industrial Controls and Systems

(Application for copies should be addressed to the National Electrical Manufacturers' Association, 155 East 44th Street, New York, NY 10017.)

UNDERWRITERS LABORATORIES INC. (UL)

UL 664 - Commercial Dry-Cleaning Machines (Class IV)

(Application for copies should be addressed to the Underwriters Laboratories Inc., 207 East Ohio Street, Chicago, IL 60611; 333 Pfingsten Road, Northbrook, IL 60062; 1285 Walt Whitman Road, Melville, Long Island, NY 11746; 1655 Scott Boulevard, Santa Clara, CA 95050; or 2602 Tampa East Boulevard, Tampa, FL 33619.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

Standard No. 32 - Drycleaning Plants (Class IV)

Standard No. 70 - National Electrical Code

(Application for copies should be addressed to the National Fire Protection Association, 470 Atlantic Avenue, Boston, MA 02210.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS CODE (ASME)

Welding Qualifications of the American Society of Mechanical Engineers

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:50Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

A 167	-	Stainless and Heat-Resisting Chromium-Nickel Steel Plate, Sheet and Strip
A 176	-	Stainless and Heat-Resisting Chromium Steel Plate, Sheet, and Strip

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Standard product. The units furnished under this specification shall be the manufacturer's current standard product except for changes necessary to comply with the requirements of this specification.

3.2 Codes and standards.

3.2.1 NFPA. The units shall conform to NFPA Standard No. 32. The electrical wiring and conduit shall conform to NFPA Standard No. 70.

3.2.2 UL or FM. The units shall comply with Underwriters Laboratory Standard UL 664 or Factory Mutual Approval Standard - Classes II, III and IV Commercial Dry Cleaning.

3.2.3 NEMA. Motor controllers, switches, relays, and time delays shall conform to performance requirements of NEMA Publication ICS.

3.2.4 Certification. Prior to approval of the first shipment, the contractor shall submit satisfactory evidence to the contracting officer or his authorized representative, that the units meet the requirements specified in 3.2.1, 3.2.2, and 3.2.3, as applicable.

3.2.4.1 NFPA. Acceptable evidence of meeting the requirements of 3.2.1 shall be the manufacturer's certified statement that the units conform to NFPA Standard No. 32 and are wired to conform to NFPA Standard No. 70.

3.2.4.2 UL or FM. Acceptable evidence of meeting the requirements of 3.2.2 shall be the UL label or FM approval mark in the finished unit, or certification from an independent testing laboratory acceptable to the contracting officer or his authorized representative that the wiring, fittings and conduit conforms to applicable UL Standards.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:50Z
Check the source to verify that this is the current version before use.

3.2.4.3 NEMA. Acceptable evidence of meeting the requirements of 3.2.3 shall be the manufacturer's certified statement that the motor controllers, switches, relays and time delays, conform to NEMA Publication ICS. A tag or label attached to these items stating these components conform to this standard is acceptable evidence.

3.3 Materials. Materials not definitely specified shall be of the quality normally used by the manufacturer for the specified equipment, provided the completed item complies with all provisions of this specification (see 6.3).

3.3.1 Corrosion-resistant metal. Corrosion-resistant metal used in the fabrication of the dry cleaning units shall be corrosion-resisting steel conforming to the requirements of ASTM A 167 or A 176, as applicable, or nickel-copper alloy conforming to QQ-N-281 or QQ-N-288.

3.3.2 Materials for fasteners. Rivets, bolts, screws, nuts, and washers shall be of carbon or alloy steel. Where brass or corrosion-resistant metal is to be fastened the fasteners shall be brass or corrosion-resistant metal respectively. Where dissimilar metals are to be fastened the fasteners shall be corrosion-resistant metal.

3.3.3 Pipe, tube, fittings, and valves. Pipe, tube, valves, and fittings used for solvent, water, air, and steam lines shall comply with the manufacturer's commercial practice.

3.3.4 Conduit, fittings, and electric wire. Electrical conduit shall be rigid electrical, metallic tubing or flexible conduit in accordance with standard commercial practice. All electrical wire shall be stranded copper heat-resistant grade, thermoplastic insulated. Solid nonstranded wire shall not be used. All conduit fittings and electric wire shall be UL listed or labeled.

3.3.5 Motors. Motors shall be drip proof or splash proof or totally inclosed for operation in a 40°C ambient temperature. Motors shall conform to the applicable requirements of CC-M-1807 and to the following:

(a) All motors shall have windings impregnated to resist moisture.

(b) Motors shall be equipped with ball bearings, except that motors of 1/2 horsepower (373 W) or less when used for horizontal applications may have sleeve bearings.

(c) Motor bearings shall be of the permanently lubricated type or shall have adequate and accessible means for lubrication.

(d) Each motor of 1/8 hp (93 W) or larger shall be provided with manually reset thermal-overload protection incorporated as a part of the motor or installed in the controller.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:50Z
Check the source to verify that this is the current version before use.

3.4 Design and construction. Assemblies of coils, cylinders and chambers, fittings and pipes using steam, water, or solvent shall have no visible leakage when tested as specified in 4.3.1. The assembled units when tested as specified in 4.3.2 shall conform to the following requirements:

(a) Starting and stopping devices operate.
(b) No leakage.
(c) No structural failures.
(d) Moving parts and bearings shall not overheat.

3.4.1 Electrical system. The electrical components of the equipment shall operate on the voltage, frequency, and number of phases as specified (see 6.2). Wiring shall be provided between motors, controllers, timers, pushbuttons and switches installed on the equipment. Flexible conduit shall be furnished where movement of a motor is required for belt adjustment. Installation of the components shall conform to the requirements of NFPA Standard No. 70. All wiring shall terminate in connection boxes with provisions for connections beyond the machine. Each conductor shall be identified by different colors. Wiring and connection diagram shall be furnished with each unit, where applicable. All motors of 1 horsepower (746 W) or greater shall have a controller of the magnetic across-the-line-type having a separate pole for each ungrounded conductor and conform to NEMA Standard ICS, as applicable.

3.4.2 Safety guards. All belts, chains, shafts, pulleys, gears and other moving parts shall be fully inclosed or guarded. Guards shall be cast iron, sheet metal, or wire mesh. All parts of the guards, shall be rigid and suitably secured and shall be removable without disassembling pipes or fittings on the machine. Provisions to permit easy access shall be made in guards fitted over parts requiring frequent adjustment with accesses fitted with covers.

3.4.3 Gearing. All gears shall have machined teeth. Spiral, hypoid, bevel, and worm gears, if used, shall operate in lubricant. When run in an oil bath, the pinion shall be of ferrous metal and the gear shall be of ferrous metal or bronze. Gears not run in an oil bath shall be of a phenolic formaldehyde resin or other noise-reducing material. When gears are of a composition material, either the motor pinion or gear with which it meshes shall be not less than 1/4 inch (6 mm) wider than the other. When thrust bearings are used on the armature shaft the gear and pinion may be of the same width.

3.4.4 Belts and pulleys. Drives for equipment shall be through V-belts or chain. V-belts shall be of the grades commercially known as multiple-drive or variable speed types, except that where a single belt is furnished with a

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:50Z
Check the source to verify that this is the current version before use.

fractional-horsepower motor, a V-belt, commercially known as a fractional-horsepower belt may be supplied in lieu of the multiple-drive or variable speed types. Pulleys for V-belts shall be suitably grooved. Chain drives shall be of the silent or roller-chain type. Means shall be provided for adjusting belts and chain tension.

3.4.5 Washer-extractor. The size 35 unit shall have not less than 35 pounds (13.6 kg) dry weight load capacity and shall be end loading open pocket type. The size 100 unit shall have not less than 100 pounds (45.4 kg) dry weight load capacity and shall be end loading open pocket, or two or three compartment type. The units shall be capable of extracting solvent from woolen garments or blankets at no greater than 25 percent of their dry weight (see 4.3.3). The shell shall be solvent tight and provided with a door mounted on rigid hinges. A latching means shall be provided so that the door is solvent tight when closed. The shell door shall be interlocked so that when the door is opened the interlock operates to stop the cylinder (see 4.3.4). Inlets and outlets for the solvent shall be such that during filling the clean solvent is pumped into the shell above the normal solvent high level and during drainage the dirty solvent shall be drawn from the lowest point in the bottom of the shell. The cylinder construction shall prevent distortion or failure due to stresses created during the extraction cycle (see 4.3.4). Washer-extractor cylinders without partitions shall contain three or more lifting ribs. The lifting ribs shall be of the same material as the cylinder. Inching or positioning of the cylinder doors for loading and unloading shall be provided for cylinders with two or more compartments (see 4.3.4). Operation of the cylinder shall require the operator to use both hands on pushbuttons. Each washer-extractor shall have replaceable bearings and when two cylinder trunnion bearings are used, they shall be of the self-aligning, anti-friction type. A brake system shall stop and hold the cylinder at rest for loading and unloading (except for the open pocket type), prior to loading the washer-extractor and operating at extracting speed (see 4.3.4). A brake interlock shall be provided and prevent operation of the cylinder when the brake is applied except for inching or positioning.

3.4.6 Filter, solvent. The solvent filter shall be of the pressure tubular type. The filter shall be provided with either an air or motor operated bumping mechanism for removing filter cake. The bumping mechanism shall be designed for both manual and automatic operation. Used solvent shall be filtered at not less than 1500 gallons per hour (5680 l/hr.) for size 35 unit and not less than 5000 gallons per hour (18930 l/hr.) for the size 100 unit (see 4.3.4). Filters shall be furnished with a combination sludge/muck cooker. Each filter shall be furnished with a water type solvent cooler. The filter pump capacity shall be equivalent to the filter for normal operation.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:50Z
Check the source to verify that this is the current version before use.

3.4.7 Still. The still shall be of the batch type. The still for the size 35 units shall be not less than 25 gallons per hour (95 l/hr.). The still for the size 100 units shall be not less than 65 gallons per hour (246 l/hr.). The still shall have a steam heating evaporating unit with sludge space below the unit.

3.4.8 Automatic controls. Each unit assembly shall be equipped with automatic controls for a complete cleaning cycle. A timer shall be provided for setting the washing time from 0 to at least 20 minutes and will cause the machine to wash, drain, extract, apply the brake, and signal the operator that the cleaning cycle is completed. Extraction cycle length should be set to meet the extraction requirements specified in 3.4.5 (see 4.3.4).

3.4.9 Seals. Means shall be provided to prevent the lubricant from entering parts of the machines where clothes are handled. Means shall be provided to prevent cleaning solvent from entering the bearings (see 4.3.4).

3.4.10 Lubrication. Forced lubrication fittings shall be provided and accessibly located for lubricating bearings. Where lubricant reservoirs are required for chain or gear drives, they shall be provided with a threaded cap at the top and a drain plug at the bottom (see 4.3.4).

3.4.11 Marking for identification. Marking for identification shall be in accordance with the manufacturer's commercial practice.

3.4.12 Finish and color. The unit shall be finished in accordance with the manufacturer's standard practice. Emergency stop control push buttons shall be red in color.

3.4.13 Noise limits. The units shall meet the noise limits specified in MIL-STD-1474 and where practicable, shall not exceed 85 decibels A-weighted at the normal operating position (see 4.3.5).

3.4.14 Electromagnetic compatability. When specified (see 6.2), equipment procured shall be designed and equipped to conform to class IIB of MIL-STD-461 (see 4.3.6).

3.4.15 Air exhaust. Air exhaust volume into all openings, including the washer-extractor cylinder door, shall be sufficient to maintain airborne solvent concentrations in the breathing zone of the worker during loading and unloading below current occupational health standards as specified in Title 29, Code of Federal Regulations (CFR) 1910.1000 Air Contaminants and amendments thereto. The exhaust fan should be interlocked with the cylinder door so that the fan is operating when the door is open (see 4.3.4).

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:50Z
Check the source to verify that this is the currentversion before use.

3.5 Contract data requirements. The contract data requirements shall be as specified (see 6.2 and 6.4).

3.6 Workmanship. The units, including inside surfaces of the cylinder shall be free from defects such as fractures, splits, punctures, tears, dents, creases, deteriorations, or malfunction. There shall be no sharp edges, slivers, burrs or projections. The finish applied to the units shall be continuous, smooth, adherent, have no imbedded foreign matter and contain no sags, runs, drips, creeps, laps, bubbles or streaks. No rust or tool marks shall show through the coating. Threaded fasteners shall not be broken, stripped, fractured or loose. Rivets shall completely fill the holes, with full size heads neatly finished and in full contact with the surface of the riveted members and shall not be loose. Wiring shall not be cut, abraded, or have insulation stripped, and shall be joined at terminals. Wiring shall have adequate slack to provide strain relief.

3.6.1 Welders. The welders performing the welding on subassemblies, assemblies, and on the units shall be certified welders and have passed the qualification test as prescribed by the American Society of Mechanical Engineers Code. The contractor shall furnish the Government with a list of names of his welders who are certified and have passed the test. The contractor shall certify that the welding of the units was performed by welders on the list.

3.6.2 Welding. The surface of parts to be welded shall be free from oxide, scale, paint, grease, and other foreign matter. Welds shall be sound, smooth, and free from porosity, cracks, incomplete fusion, and deformation of material. All scale and flux deposits shall be free from the finished welds. Soldering shall be complete and adherent with all flux and residue removed and shall contain no pinholes.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Certificate of compliance. When certificates of compliance are submitted, the Government reserves the right to check test such items to determine the validity of the certification.

Source: https://assist.dla.mil -- Downloaded: 202640-21T20:50Z
Check the source to verify that this is the currentversion before use.

4.2 Quality conformance inspection. Except as otherwise specified herein, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.2.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced specifications and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase document.

4.2.2 End item inspection. A lot shall be all dry cleaning units of one size as applicable, offered for inspection at one time. The sample unit shall be one completely fabricated unit.

4.2.2.1 Visual examination. The completely assembled item shall be examined for defects in table I. The inspection level shall be level II and the acceptable quality level (AQL) 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

TABLE I. Classification of defects

Examine	Defect	Classification Major	Minor
Finish	Not finished where required	X	
	Finish and color not as specified	X	
	Not continuous, smooth, adherent, foreign matter imbedded and sags, runs, drips, creeps, laps, bubbles or streaks		X
	Rust or tool marks		X
Design, construction and workmanship general (applicable to all components and assemblies)	Any part missing or not specified type	X	
	Split, punctured, torn, dented, creased, deteriorated or malformed	X	
	Shell heads not constructed to permit removal of cylinder, shell door not hinged as specified	X	
	Sharp burr, sliver, or sharp edge	X	
	Not lubricated where required		X
	Excessive lubrication		X
Marking	Not manufacturer's commercial practice		X

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:50Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Design, construction and workmanship general (applicable to all components and assemblies) (cont'd)			
Welding and brazing (where required)	Missing, incomplete, burn holes, fractured, or not fused	X	
	Slag inclusion, undercut, not smooth and uniform, or deposit of scale and flux not removed	X	
Soldering (when applicable)	Missing, incomplete or not adherent	X	
	Not clean (flux or residue not removed) or contains pinholes		X
Bolts, nuts, screws, studs and other threaded fasteners	Missing, broken, stripped or fractured	X	
	Threaded fasteners loose		X
Rivets (where applicable)	Missing, broken, not peened or not peened sufficiently	X	
	Rivets loose		X
Electrical apparatus wiring	Wiring cut, abraded, insulation stripped, not properly joined or loose at terminal	X	
	Not inclosed in specified conduit where required	X	
	Adequate slack not provided for wiring to relieve strain or excessive insulation stripped from wiring		X
Marking for identification	Missing, incomplete, not legible		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:50Z
Check the source to verify that this is the current version before use.

4.2.2.2 Dimenisonal examination. Inspection shall be made of the end item for compliance with dimensions specified. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units. Any nonconformance shall be classified a defect.

4.2.2.3 Testing of the end item. The first produced end item shall be tested as specified in 4.3.1 through 4.3.5 and when applicable 4.3.6. Remaining units of the same lot shall be tested as specified in 4.3.1 and 4.3.2. Failure to pass the tests shall be cause to reject the effected end item.

4.2.3 Inspection of preparation for delivery. Preservation-packaging, packing and marking shall be inspected in accordance with the quality assurance provision in MIL-L-3153.

4.3 Tests.

4.3.1 Hydrostatic pressure tests. Assemblies of coils, cylinders, and chambers, fittings and pipes shall be tested with 150 pounds per square inch (1034 kPa) hydrostatic pressure. Nonconformance to leakage requirements of 3.4 shall constitute failure of the test.

4.3.2 Operational testing. Each assembly of the dry cleaning units shall be filled with solvent and operated without load. Nonconformance to the operational requirements of 3.4 shall constitute faulure of this test.

4.3.3 Washer extractor testing. The machine shall be filled with the dry weight capacity of woolens or blankets for the applicable size of machine and operated through one complete rinse cycle and then extracted for not more than 5 minutes. The load shall be removed and weighed. Nonconformance with the extracting requirements of 3.4.5 shall constitute failure of this test.

4.3.4 Functional testing. Assemblies of the dry cleaning units shall be filled with solvent under full load requirements (woolens or blankets). Procedures for the determination of airborne concentrations of solvent will be performed utilizing the most current methodology approved by the National Institute for Occupational Safety and Health (NIOSH). The results of such determinations will be tested for noncompliance utilizing the procedures set forth in U.S. Department of Health, Education and Welfare (HEW) publication number (NIOSH) 75-159-Statistical Methods for Determination of Noncompliance with Occupational Health Standards. The following shall be checked and nonconformance shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:50Z
Check the source to verify that this is the current version before use.

(a) Washer-extractor interlocking shell door for compliance with 3.4.5.
(b) Cylinder distortion during the extraction cycle (see 3.4.5).
(c) Inching or positioning of cylinder doors for two or more compartments (see 3.4.5).
(d) Brake system for compliance with 3.4.5.
(e) Filter capacity for compliance with 3.4.6.
(f) Still capacity for compliance with 3.4.7.
(g) Automatic controls for compliance with 3.4.8.
(h) Lubricant seals and cleaning solvent for compliance with 3.4.9.
(i) Means of lubrication for compliance with 3.4.10.
(j) Airborne solvent concentrations for compliance with 3.4.15.

4.3.5 Noise test. The units shall be tested for conformance with the noise limits of 3.4.13 in accordance with MIL-STD-1474.

4.3.6 Electromagnetic compatibility test. When electromagnetic compatibility test is required, the initial unit of production shall be tested by the contractor in accordance with test methods CE03 and RE02 of MIL-STD-462. The Government reserves the right to witness tests performed by the contractor or an independent testing agency. The contractor shall furnish the contracting officer written certification that the Interference Control Plan, the EMI/EMC Test Plan, the electromagnetic Test Report and the requirements meet MIL-STD-461 (see 3.4.14).

5. PACKAGING

5.1 Preservation-packaging, packing and marking. Preservation-packaging, packing and marking for level A, B, or C shall be in accordance with MIL-L-3153 (see 6.2).

6. NOTES

6.1 Intended use. The washer-extractor, filter, sludge/muck cooker and still units covered by this specification are intended for use with a tumbler to form a complete closed or transfer system for using synthetic solvent, nonflammable at ordinary temperatures.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Size required (see 1.2).
(c) Electrical characteristics (see 3.4.1).
(d) When electromagnetic compatability is required (see 3.4.14).
(e) When moisture and fungus-resistant treatment is required (see 3.4.15).
(f) Contract data requirements (see 3.5 and 6.4).
(g) Applicable levels of preservation-packaging and packing (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:50Z
Check the source to verify that this is the current version before use.

6.3 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

6.4 Contract data requirements. Any data items to be delivered under any contract for items covered by this specification shall be specifically called for in the contract in accordance with the applicable regulations of the procuring agency (see 3.5 and 6.2).

6.5 Metric equivalent. Metric equivalents indicated in parentheses throughout this document, are based on practices, conversion factors, and symbols specified in ASTM E 380 Standard for Metric Practice, and are for information only. In each instance, the value stated in customary units shall be controlling.

6.6 Supersession data. The 40 and 50 pound (18 and 23 kg) capacity tumblers in MIL-D-43164B are replaced by the 35 and 50 pound (13.6 and 23 kg) capacity tumblerss in MIL-D-43970, respectively. The size 70 dry cleaning unit assembly in MIL-D-43164B is no longer required.

6.7 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD
Air Force - 45
DLA - GS

User activity:

Army - CE

Preparing activity:

Army - GL

Project No. 3510-0275

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:50Z
Check the source to verify that this is the currentversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-D-43164C Dry Cleaning Units, Single Bath, Cold Type, Fully Automatic, For Synthetic Solvent

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:50Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
US ARMY NATICK RESEARCH and DEVELOPMENT COMMAND
NATICK, MASSACHUSETTS 01760
OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRDNA-ES

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD-314



Commander
US Army Natick Research and Development Command
ATTN: DRDNA-ES
Natick, MA 01760

NATICK OP 1 AUG 78
FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:50Z
Check the source to verify that this is the current version before use.