MIL-H-43174C
9 November 1983
SUPERSEDING
MIL-H-43174B
12 December 1975

MILITARY SPECIFICATION

*HELMET, PARACHUTISTS': FREE FALL

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers the requirements for the free fall parachutists' helmet.

1.2 Classification. The helmet shall be two types in the following sizes:

Type I - Without communication equipment
Type II - With communication equipment

Sizes:

Small
Medium
Large

2. APPLICABLE DOCUMENTS

* 2.1 Government documents. Unless otherwise specified, the following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein:

SPECIFICATION

FEDERAL

PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research and Development Center, Natick, MA 01760 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 8415

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Table for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage

* DRAWINGS

U.S. ARMY NATICK RESEARCH AND DEVELOPMENT CENTER

11-1-397 - Helmet, Parachutist's, Small, Medium and Large; Type I Without Communication Equipment; Assembly
11-1-398 - Helmet, Parachutist's, Small, Medium and Large; Inner Shell and Outer Shell; Types I and II; Assembly
11-1-399 - Helmet, Parachutist's, Small, Medium and Large; Outer Shell; Types I and II; Assembly and Sections
11-1-400 - Helmet, Parachutist's, Small, Medium and Large; Inner Shell; Types I and II; Assembly and Sections
11-1-401 - Helmet, Parachutist's; Types I and II; Patterns, Size Small
11-1-402 - Helmet, Parachutist's; Types I and II; Patterns, Size Medium
11-1-403 - Helmet, Parachutist's; Types I and II; Patterns, Size Large
11-1-404 - Helmet, Parachutist's, Types I and II; Miscellaneous Patterns for Small and Medium Sizes
11-1-951 - Helmet, Parachutist's, Small, Medium and Large; Type II with Communication Equipment; Assembly
11-1-952 - Bracket, Microphone MT-1627/AIC Assembly
11-1-2968 - Helmet, Parachutist's, Small, Medium and Large; Types I and II; Chin Strap Details

U.S. AIR FORCE

55C13289 - Bracket, Microphone, MT-1627/AIC, Assembly of
56E12858 - Cushion, Earphone, MX-2088/U; Assembly of
57C12630 - Bracket, Earphone Cushion, Electrical Headset
60C4459 - Receiver, Oxygen Mask; Assembly of

(Copies of documents required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

2.2 Other publications. Unless otherwise specified, the following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this document to the extent specified herein.

AMERICAN SOCIETY FOR TESTING AND MATEIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence.

3. REQUIREMENTS

3.1 Samples.

3.1.1 Guide samples. Samples, when furnished are solely for guidance and information to the contractor (see 6.3). Variation from the document may appear in the samples, in which case the document shall govern.

3.1.2 Standard color samples. Unless otherwise specified, standard samples for color shall apply (see 6.3).

3.1.3 First article. When specified, a sample shall be subjected to first article inspection (see 4.3, 6.2 and 6.5).

3.2 Materials and components. Materials and components shall be as specified on the applicable drawings and as specified herein. For materials or components for which it is stated "or equal", if the contractor proposes to use an item considered to be equal to the material or component specified, prior to its use the contractor shall furnish a sample of the material or component, with supporting data to the contracting officer for subsequent evaluation by the responsible military agency.

3.2.1 Instructions for use. An instructions for use sheet, of white paper, approximately 8-1/2 inches by 11 inches, shall be furnished with each helmet (see 5.1.1). The contents of the instruction sheet shall be as shown on figure 1.

3.3 Construction. The construction shall conform in all respects to the drawings listed in 2.1 and as specified herein.

3.3.1 Stitching. All stitching shall be as specified on the applicable drawings and as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

3.3.2 Thread tension. Thread tension shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread, or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

3.3.3 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When a thread break or bobbin run-out occurs during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch back of the end of the stitching. 1/

b. Any thread break, two or more consecutive skipped stitches or runoff stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area, continue over the defective area and continue a minimum of 1 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs the ends of the stitching are not required to be backstitched.

3.3.4 Automatic stitching. Automatic machines may be used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch, size and type of thread are met, and at least three or more tying, overlapping or back stitches are used to secure the ends of the stitching.

3.3.5 Thread ends. All thread ends shall be trimmed to a length of not more than 1/4 inch.

3.3.6 Setting of snap fasteners. A hole shall be prepunched to receive the button and eyelet components of the snap fasteners. The hole shall be smaller than the outside diameter of the button and eyelet barrels so that the barrel must be forced through the hole. The hole shall not be punched in the setting operation with the button or eyelet barrel. The fasteners shall be securely clinched without cutting the adjacent materials.

3.3.7 Repairs. Except as otherwise specified herein, repairs are not allowed to be made to the helmet.

3.3.8 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in 4.4.3 shall be removed from production and replaced with non-defective and properly matched components.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

3.3.9 Patterns. Standard patterns for the helmet components are shown full size on drawings and shall be used as a guide for cutting working patterns. The standard patterns shall not be altered in any way and the working patterns shall conform exactly to the standard patterns.

3.3.10 Cutting of components. Components covered by a pattern shall be cut within +1/16 - 1/32 inch of the applicable pattern.

3.4 Communications equipment operation. After installation in the helmet, the communication equipment (headset microphone assembly) in the type II helmet, shall function satisfactorily when tested as specified in 4.4.5.

* 3.5 Fit. The assembled helmet shall fit snugly upon a standard head form when tested as specified in 4.4.5. Head forms that may be owned by a contractor and had been used for previous contracts, shall be approved by the contracting officer prior to use (see 6.2).

3.6 Workmanship. The helmet assembly shall conform to the quality of product established by this document and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all requirements of referenced documents unless otherwise excluded, amended, modified or qualified in this document or applicable purchase document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

4.4.2 In-process inspection. Inspection of the helmet components during the manufacturing operations shall be made to ascertain that construction details which can not be examined on the finished product are in accordance with specified requirements. The in-process inspection shall include inspection of the working patterns to assure that they conform to the standard patterns, inspection of the cut parts covered by patterns to ascertain that the parts are cut properly with respect to size and material directional requirements and that the diameter of the holes for the snap fasteners is smaller than the outside diameter of the button and eyelet barrels. Whenever non-conformance is noted, corrections shall be made to the components affected and lot in-process. Parts which cannot be corrected shall be removed from production.

* 4.4.3 End item visual examination. The end item shall be examined for the defects listed below. The lot size shall be expressed in units of one helmet assembly. The sample unit shall be one helmet assembly. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 10.0 for total (major and minor combined) defects.

Examine	Defect	Classification Major	Minor
Leather	Color not uniform		X
	Any hole, cut, tear, or rip	X	
	Any needle chews	X	
	Any abraded area		X
	Grain surface not on outside	X	
	Not soft or pliable	X	
	Finish omitted, flaky, cracked or tacky		X
	Flanky, spongy, or boardy		X
	Any mend, darn, or patch		X
Cloth	Any hole, cut, or tear	X	
	Any mend, darn, or patch		X
Webbing	Any hole, cut, or tear	X	
	Edges not seared		X
Hardware,			
general	Broken or malformed, corroded area, burr, or sharp edge	X	
	Finish omitted or not as specified, where required	X	
	Any required component improperly installed causing failure to serve intended purpose	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Snap fastener	Clinched excessively tight, cutting adjacent materials	X	
	Clinched loosely, permitting any component to rotate freely but not to the degree that any component can be expected to become detached during use		X
	Clinched loosely to the degree that components can be expected to become detached during use	X	
	Incorrect style	X	
	Orientation of button and socket components on chin strap not as specified	X	
	Any fastener not functioning properly, i.e., fails to be snapped closed, provide a secure closure or to open freely	X	
	NOTE: The fasteners shall be snapped and unsnapped twice to determine whether parts of fastener separate freely and also effect a secure closure.		
D-Ring	Not type, style, or size specified	X	
Receiver, oxygen mask	Attaching screw(s) not securely tightened		X
	One or more screws omitted	X	
	Short screw used where long screw is required or vice versa		X
Ear cushion(s)	Any hole, cut, tear or abraded area	X	
	Not hand tacked to helmet as specified		X
	Two or more screws omitted	X	
	Two screws loose		X
	Three or more screws loose	X	
Pressure pads	Any omitted, cut or torn	X	
Reinforcements (outer shell)	Any reinforcement omitted (check by feel)	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Communication equipment (type II helmet):			
General	Any wire cut, cracked, or abraded	X	
	Any hardware component:		
	- Corroded	X	
	- Omitted	X	
	- Not attached as specified	X	
	Any component omitted	X	
Earphone(s)	Dirt or any foreign matter in earphone baffle holes	X	
Connecting cord, earphone	Not routed as specified	X	
	Any stitching passing through cord	X	
Microphone	Cracked	X	
	Not adjustable by hand	X	
Microphone boom	Broken or deformed	X	
	Will not adjust or swing when locking screw is loosened, or cannot be locked in set position	X	
Plug, earphone connecting cord	Not secured to helmet as specified		X
Seams and stitching:			
Open seams	Any on leather component	X	
	On materials other than leather:		
	- One-half inch or less		X
	- More than 1/2 inch	X	
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or runoff stitches occur.		
Seams and stitch type	Incorrect seam or stitch type	X	
	Any seam not flat and smooth		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Stitch tension	Loose, resulting in loose top or bobbin thread		X
	Excessively tight, resulting in puckering of material		X
Stitches per inch	One to two stitches less than minimum specified		X
	Three or more stitches less than minimum specified	X	
	Two or more stitches in excess of maximum specified		X
	NOTE: Variation in the number of stitches caused by the operator's speeding up the machine and pulling the material in order to sew over heavy seams, heavy places or in turning corners shall be classified as follows: a. Within the Major defect classification - Minor defect b. Within the Minor defect classification - No defect		
Thread breaks, skipped stitches, or runoffs	Overstitched less than 1 inch in each direction beyond defective stitching area		X
	NOTE: Thread breaks or two or more consecutive skipped or runoff stitches not overstitched shall be classified as open seams.		
Stitching ends	Not secured as specified		X
Rows of stitching	Any row missing except on box-x stitching	X	
	On box-x stitching:		
	- One row omitted		X
	- Two or more rows omitted	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

Examine	Defect	Classification Major	Minor
Components and assembly	Any required component or operation omitted (unless otherwise classified herein)	X	
	Any component misplaced or not assembled as specified (unless otherwise classified herein)	X	
	Color of any component not as specified		X
	Any unauthorized repair	X	
	Rivet omitted on chin pull tab		X
Identification label and instruction sheet	Omitted, incorrect, or illegible		X
Cleanness	Any greese, oil or stain clearly noticeable		X
	Thread ends not trimmed as specified		X

4.4.4 End item dimensional examination. The end item shall be examined for conformance to all dimensions shown on drawings, including stitch margins and gage which can be examined on the end item. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of complete helmets of one size only. The sample unit shall be one complete helmet assembly. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 4.0.

4.4.5 End item testing of the complete helmet assembly. The complete helmet assembly shall be tested for the characteristics listed in table I. The lot shall be expressed in terms of individual helmets of one type and size only. The sample unit shall be one helmet.

4.4.5.1 Fit testing. For testing of the helmet for fit, the inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 0.40.

4.4.5.2 Communication equipment operation testing (type II only). One hundred percent of the helmet assemblies in the lot shall be tested for operation of the communication equipment. Any helmet failing to pass the test shall be rejected.

Source: https://assist.dla.mil. Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

TABLE I. End item tests

Characteristics	Specification reference		No. deter. per unit	Results reported as pass or fail
	Requirement	Test method		
Fit	3.5	4.5.1	1	X
Communications equipment operation	3.4	4.5.2	2	X

4.4.6 Packaging inspection. An examination shall be made to determine that preservation, packing and marking comply with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packaged except that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (interior and exterior	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Components missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as: Open and non-continuous heat sealed seams and closure of polyethylene bag. Alternative polyethylene bag not provided with mechanical tie specified. Incorrectly fabricated bag. Improper cushioning. Fiberboard insert not fabricated correctly. Helmet not securely seated. Incomplete closure of container flap, improper taping, inadequate stapling, or loose strapping. Bulged or distorted container.
Content	Number of unit packs per shipping container is more or less than required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection.

* 4.5.1 Fit test. For this test the contractor shall fabricate head forms which conform in all respects to the standard head forms to be furnished by the Government (see 3.5 and 6.4). The helmet shall be inserted upon the test form of it's indicated size using normal force. The helmet shall be rejected if the helmet does not fit easily into a snug position on the form.

4.5.2 Communications equipment test (talk-listen test). Each type II helmet assembly shall be tested by connecting the headset-microphone assembly to a suitable test system. The presence of sidetone in the headset, when the microphone unit is spoken into, constitutes the test. Failure to hear sidetone in either earphone of the headset shall be evidence of failure of the communications equipment to properly perform and shall be cause for rejection of the helmet tested.

* 5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each helmet, with an instructions-for-use sheet (see 3.2.1) placed inside the crown, shall be inserted in a close-fitting clear polyethylene film bag of 0.0015-inch thickness (± 20 percent tolerance). The polyethylene bag shall be formed with heat sealed seams that are straight, continuous, and parallel to each other and the formed edges of the bag. The bag may be fabricated from polyethylene film tubing or sheeting. The opening of the plastic bag shall be heat sealed or secured with a mechanical tie (paper or plastic covered soft wire, aluminum band, etc.). Prior to or during the closure operation, excess air within the bag shall be expelled. Type II helmets before bagging shall have the microphone boom extended with the microphone in a horizontal position in the open area between the ear cushions. The microphone shall be completely inclosed in minimum 1/4-inch thickness of paperback cellulosic cushioning material and secured in place with pressure-sensitive tape. All helmets shall have the chinstrap snapped in place.

5.1.1.1 Unit pack. One helmet, prepared as specified in 5.1.1, shall be unit packed in a fiberboard box that is provided with a one-piece die-cut fiberboard insert. The fiberboard box shall conform to style CSSC, grade W6c of PPP-B-636. Inside dimensions of the box shall measure 12-3/4-inches in length, 12-inches in width, and 10-1/2-inches in depth. The fiberboard insert shall be fabricated from sheet stock of the same material as the box. The insert shall be scored and corner cut, and shall have a disc cut-out to securely seal the helmet. The disc cut-out shall be positioned so as to provide a 1-3/4-inch clearance on each side of the insert length and 1-inch clearance on each side of the insert width. The dimensions of the set-up insert shall be 12-5/8-inches in length, 11-7/8-inches in width, and 4-inches in depth. Each fiberboard box shall be closed and waterproofed with tape in accordance with method IV as specified in the appendix of PPP-B-636.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

5.1.2 Commercial. The helmets shall be preserved in accordance with MIL-STD-1188.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Six helmets of one type and size only, packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style FOL, grade V2s of PPP-B-636. Level A unit packs shall be packed flat three in length, two in width, and one in depth within a shipping container. Inside dimensions of the shipping container shall approximate 37-1/4 inches in length, 26-1/2 inches in width and 11-inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.6. Towards the end of the contract, or when there are less than the required amount per container of the same size, mixed sizes of one type only may be packed within the same container.

5.2.2 Level B packing. Six helmets of one type and size only, packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to style OSC (minimum 3-inch overlap), type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. Level A unit packs shall be packed flat, three in length, two in width, and one in depth within a shipping container. Inside dimensions of the shipping container shall approximate 37-1/4 inches in length, 26-1/2 inches in width and 11-inches in depth. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method II as specified in the appendix of PPP-B-636, except that the inspection shall be in accordance with 4.4.6. Towards the end of the contract, or when there are less than the required amount per container of the same size, mixed sizes of one type only may be packed within the same container.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the shipping container shall be a grade V3c, V3s or V4s fiberboard box fabricated in accordance with method III as specified in the appendix of the box specification, except that the inspection shall be in accordance with 4.4.6.

5.2.3 Commercial packing. Helmets, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Marking. In addition to any special marking required by the contract or purchase order, unit packs and shipping containers shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.3.1 Special marking. Arrows or prominent marks shall be placed on two sides of each unit pack and the shipping container to indicate the position in which the container shall be handled in transit or storage. The word "UP" shall be placed at the point of the arrows. The letters and arrows shall be at least 2-inches in height. The side panels of each unit pack and shipping container shall be plainly marked as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

UP HANDLE WITH CARE UP

The top panel shall be plainly marked as follows:

HANDLE WITH CARE

TOP

THIS SIDE UP

5.3.2 Labels, mixed sizes. Each shipping container packed with mixed sizes, of one type only, shall have securely attached to the end and side, directly under the printing or stenciling, a white paper label 5 by 4 inches, with the words "MIXED NSN's" plainly printed or stamped thereon, and under these words shall be legibly printed the correct quantity and NSN's contained therein.

* 6. NOTES

6.1 Intended use. The helmet is intended for use as protective head gear for parachutists conducting free fall jumps.

6.2 Ordering data. Acquisition documents should specify the following:

(a) Title, number, and date of this document.
(b) Type and size helmet required.
(c) When a first article sample is required (see 3.1.3. 4.3 and 6.5).
(d) Approval of headforms (see 3.5).
(e) Selection of the applicable level of preservation and packing (see 5.1 and 5.2).
(f) When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).

6.3 Samples. For access to samples address the contracting activity issuing the invitation for bid.

6.4 Head forms. Standard head forms, for use by the contractor to fabricate duplicate forms for use in production, will be furnished by the contracting activity issuing the invitation for bid.

6.5 First article. First article samples shall be inspected and approved under the appropriate provisions of DAR 7-104.55. The first article should be a preproduction sample consisting of one completed helmet assembly. The contracting officer should include specific instructions in all acquisition documents, regarding arrangements for inspection and approval of the first article samples.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

6.6 Changes from previous issue. The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Preparing activity:

Army - GL

Project No. 8415-0344

Review activities:

Army - MD
Navy - MC
Air Force - 82
DLA - CT

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

*HELMET PARACHUTISTS': FREE FALL

INSTRUCTIONS FOR USE

1. The parachutist's helmet is provided in sizes small, medium, and large. The type I helmet is used by regular parachutists and the type II helmet with communication equipment is used by the jump master. Selection of the proper helmet size should be made only with regard to the actual head circumference measurement. The following table may be used for determining helmet size:

Head Circumference (inches)	Helmet Size
Up to 21.9	Small
22 - 22.5	Medium
22.6 - 23.7	Large

2. The maximum circumference shall be measured with a tape placed just above the bony ridges on the forehead, just above both ears and across the most prominent point at the back of the head. Semiflexible construction of the helmet allows for variations in head configuration. The helmet should fit snugly but not uncomfortably tight when new.

3. Correct positioning of the ear cushion assemblies may be accomplished by restitching through the helmet at the desired new location. The pressure of the ear cushions can be regulated by addition or removal of foam rubber pads located between the inner shell and the ear cushion mounting bracket.

4. The helmet should be stored in a warm place when not in use. At cold temperatures, the padding material will stiffen, making the helmet difficult to don.

5. The helmet and lining may be cleaned with mild soap suds.

6. ALWAYS FASTEN CHIN STRAP WHEN WEARING THE HELMET.

7. CAUTION - THIS HELMET IS NOT A RECOGNIZED HEARING PROTECTION DEVICE. USE APPROVED EARPLUGS IN AIRCRAFT SUSPECTED OF BEING NOISE HAZARDOUS.

FIGURE 1

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS. In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY
US Army Natick Research and Development Center
Natick, Massachusetts 01760

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300
DRDNA-ES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research and Development Center
ATTN: DRDNA-ES
Natick, MA 01760

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2 DOCUMENT TITLE
MIL-H-43174C	Helmet, Parachutists': Free Fall

3a. NAME OF SUBMITTING ORGANIZATION	4 TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)* _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5 PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording

c. Reason/Rationale for Recommendation

6 REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

NATICK OP, 1 APR 83

Source: https://assist.dla.mil - Downloaded: 2026-10-21T20:51Z
Check the source to verify that this is the current version before use.