INCH-POUND

MIL-P-43134C
22 February 1993
SUPERSEDING
MIL-P-43134B
30 May 1973

MILITARY SPECIFICATION

This Specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one size of parachute packing tension plate.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks forma part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and Supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

MMM-A-130 - Adhesive, Contact
PPP-B-636 - Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5017 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 1670

AMSC N/A

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:45Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 – Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-147 - Palletized Unit Loads

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, AND ENGINEERING AND CENTER

11-1-99 - Plate, Tension, Parachute Packing Assembly
11-1-6889 - Plate, Tension Base Assembly

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineer ing Center, ATTN: SATNC-UX, Natick, MA 01760-5017.)

2.2 Non–Government Publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:45Z
Check the source to verify that this is the current version before use.

2.3 Order of Precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Materials and components. Materials and components shal conform to the requirements on the applicable drawings, to subsidiary specifications and standards applicable thereto and as specified herein. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3 Construction. The construction shall conform in all respects to Drawing 11-1-99 and all subsidiary drawings and parts lists pertaining thereto, and as specified herein.

3.3.1 Type 301. Ends of all type 301 stitching shall be backstitched or overstitched not less than 1/2 inch in accordance with the required stitch pattern. Thread tension shall be maintained so that there will be no loose stitching resulting in puckering of the materials sewn.

3.3.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1 inch (1/2 inch for W-W stitching) from the end of the stitching.

b. Thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch back from the defective area, (1/2 inch for W-W stitching), continue over the defective area, and continue a minimum of 1 inch (1/2 inch for W-W stitching) beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the end of the stitching are not required to be backstitched.

3.3.2 Marking for identification. Each tension plate shall be marked in accordance with the requirements specified on Drawing 11-1-99.

3.3.3 Workmanship. The plates shall be clean and free of scratches, sharp edges and burrs. The webbing strap assembly shall he free of dirt, oil or

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:45Z
Check the source to verify that this is the current version before use.

other foreigh rotter. The end item shall conform to the quality of product establish by this specification and the occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where Such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the spcification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspections. The inspection requirments specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1) and 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:45Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component and material certification. A certificate of compliance may be acceptable as evidence that the felt is bonded to the plate as specified in drawing 11-1-6889 using MMM-A-130 cement.

4.4.2 In-process inspection. Inspection of subassemblies shall be made to ascertain that construction details which cannot be examined in the finished product are in accordance with specified requirements. The Government reserves the right to exclude from consideration for acceptance any material or service for which in-process inspection has indicated nonconformance.

4.4.3 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of tension plates. The sample unit shall be one tension plate. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Materials	Not as specified	101	
Construction	Any component missing, cracked, visually malformed, misaligned or not assembled as specified	102	
	Felt not securely bonded to plate (i.e., more than one opening in cement line to plate, or any opening more than one inch long)	103	
Hardware	Component fractured or malformed, protective finish emitted; corroded areas; burrs or sharp edges	104	
Protective finish	Any area of rust or corrosion	105	
	Coating is blistered, peeling, flaking or otherwise not adherent	106	
	Dirt, smudge, oil, grease, or other foreign matter		201

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:45Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Protective finish (cont'd)	Any breaks, scratches or tool marks through coating to metal		202
Stitches and stitching	Wrong stitch type	107	
	One stitch per inch under or over minimum or maximum specified		203
	Two or more stitches per inch under or over minimum or maximum specified	108	
	Thread breaks, runoffs, or two or more consecutive skips in stitching not overstitched or restitched as specified		204
	NOTE: Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling fabric to sew over heavy places: (a) Within the major defect classification - minor defect (b) Within the minor defect classification - no defect		
	Improper tension resulting in loose top or bobbin threads		205
	Any row of stitching missing	109	
	Needle chews	110	
	Stitching pattern not as specified	111	
	Stitch margin or gage not as specified		206
	Ends of stitching not secured as specified		207
Workmanship	Any sharp edge, burrs, or metal sliver	112	
	Any component loose or not securely retained	113	
	Dirt, grease, oil, or other foreign matter embedded in webbing		208
	Thread ends not trimmed as specified		209
	Exposed ends of webbing not seared as specified		210

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:45Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Identification marking	Missing, not legible, incomplete, improper location, or not applied as specified		211

4.4.4 End item dimensional examination. The end item shall be examined for conformance to the dimensions specified on the drawings. Only those dimensions that can be evaluated without damaging or disassembling the end items shall be examined. Any dimension not within the specified tolerance shall be classified as a defect. The lot size shall be expressed in units of tension plates. The sample unit shall be one tension plate. The inspection level shall be S-3 and the AQL, expressed in term of defects per hundred units, shall be 4.0.

4.4.5 Packaging examination. The fully packaged end item shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of flap, improper taping, loose strapping, or inadequate stapling Bulged or distorted container
Content	Number per container is more or less than required

4.4.6 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in term of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirement

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:45Z
Check the source to verify that this is the current version before use.

Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or commercial, as specified (see 6.2).

5.1.1 Level A preservation. The screws shall be placed in a plastic bag and the bag closure heat sealed. Each ear shall be wrapped in kraft paper. The plate, ears, and screws shall be packaged in a box conforming to RSC, grade 200 of PPP-B-636. The inside dimensions of the box shall be approximately 13-1/4 inches in length, 9-3/4 inches in width and 2-1/4 inches in depth. The box shall be fitted with a bottom pad.

5.1.2 Commercial preservation. Plates and components shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

5.2.1 Level A packing. Six plates, preserved as specified in 5.1, shall be packed in a shipping container conforming to style RSC, grade V2s of PPP-B-636. Inside dimensions of the box shall be approximately 20 inches in length, 14 inches in width and 8 inches in depth. Each box shall be closed, waterproofed, and reinforced in accordance with the appendix of PPP–B-636.

5.2.2 Level B packing. Six plates, preserved as specified in 5.1, shall be packed in a shipping container conforming to style RSC, grade V3S of PPP-B-636. Inside dimensions of the box shall be approximately 20 inches in length, 14 inches in width and 8 inches in depth. Each box shall be closed, waterproofed, and reinforced in accordance with the appendix of PPP–B-636.

5.2.3 Commercial packing. Plates, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), plates preserved as specified in 5.2, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Each prepared load shall be bonded with straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be number 95 in accordance with the appendix of MIL-STD-147.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:45Z
Check the source to verify that this is the current version before use.

5.4 Marking. Marking of unit packs, shipping containers, and unit loads shall be in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The tension plate is a parachute packing aid intended for use by parachute riggers.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.1, 4.3, and 6.3).
d. Selection of applicable levels of packaging and packing (see 5.1 and 5.2).
e. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of Federal Acquisition Regulation (FAR) 52.209-4. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

6.4 Subject term (key word) listing.

Packing aid

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:

Army-GL
Navy-AS
Air Force - 99

Preparing activity:

Army - GL

(Project 1670-0800)

Review activities:

Army-TR
Air Force - 82

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T20:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-P-43134C	1993 February 22

3. DOCUMENT TITLE

PLATE, TENSION, PARACHUTE PACKING

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4531	256-4531
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: SATNC-UXT Natick, MA 01760-5017	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil - Downloaded: 2026-10-21T20:45Z
Check the source to verify that this is the current version before use.