MILITARY SPECIFICATION

PRINTING PLANT, SPECIAL WARFARE,

TRANSPORTABLE, (LIGHTWEIGHT) MODEL 800

This amendment forms a part of Military Specification MIL-P-43155F(GL), dated 30 March 1984, and is approved for use within the Natick Research and Development Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense,

PAGE 8

TABLE I, Item No. 2: Delete and substitute

2	1	Extinguisher, Fire, 5 pound, Pressurized, Halon 1211, with bracket, Fire Type A20 355T FSCM CODE (54905).”

TABLE II, Item No. 4: Delete and substitute

4	1	Camera, process, vertical, 14 by 18 inches image size, diaphragm control, fixed copyboard 16 by 20 inches, electronic exposure control with eight memory channels, four 420 watt quartz iodine lamps, 220 volts 60 hertz, alternating current with vacuum pump and grid chart FSCM Code 25631, model WE-1418 FSCM Code 93791."

PAGE 9

Table II, Item No. 11, line 3: Delete “81494061” and substitute “8 149 4061”.

Item No. 12, line 3: Delete “58 149 7395” and substitute “58 149 7395”.

Item No. 13, line 3: Delete “471494368" and substitute “47 149 4368”.

Item No. 14, line 3: Delete “251494178” and substitute “25 149 7072”.

FSC 3610

DISTRIBUTION STATEMENT A. Approved for public releases distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:49Z
Check the source to verify that this is the current version before use.

PAGE 10

TABLE II, Item No. 25: Delete and substitute

"	25	1	Phototypesetter, direct entry, language Model Comp/ Edit 5810, Image Previewer option 20-2745-0, telecommunication option 20-6118-0, dry process option 20-1349-0, extended memory option 20-2629-0, RAM mult-format/language option 20-2831-0, language option 20-1483-0, AM International FSCM CODE (62812). Processor, Dry X for 12 inch paper, table top mounted, Model 712 AM International FSCM CODE (62812)."

PAGE 12

TABLE II, add:

"	47	1	Rod, ground, copper weld surface treatment, male thread " bottom, female thread top and coupling, 3 sections, conical point, 108.00 inches overall length, 0.625 inches in diameter, seperate ground wire clamp, conductor wire stranded, terminal lug with hole, wire termination, driving stud, W-R-550 (Code 81348) type 111, class B, 9 feet long, Barber-Greene Co. (FSCM Code 05643) No. 20P41, Chemetron Fire Systems (FSCM Code 07464> No. (346742, Volcanic Heater Inc., (FSCM Code 82370), NO. A104.
	48	1	Slide hammer, ground rod emplacement."

Custodian:

Army - GL

Review activity:

Army - MD

Preparing activity:

Army - GL

project NO. 3610-A340

Source: https://assist.dla.mil -- Downloaded: 202610-21T20:49Z
Check the source to verify that this is the current version before use.