MILITARY SPECIFICATION

COLLECTIVE PROTECTION EQUIPMENT, CBR,

NIKE-HERCULES, CONUS, M12

1. SCOPE

1.1 This specification covers one type of CBR collective protection equipment.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-S-781	-	Steel, Strapping, Flat.
TT-W-00572	-	Wood-Preservative; Water-Repellent.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.

MILITARY

MIL-P-116	-	Preservation, Methods of.
MIL-B-2427	-	Boxes, Ammunition Packing; Wood Nailed.
MIL-C-50007	-	Chute, Contaminated Clothing, M1.
MIL-V-0050010	-	Valve, Antiback Draft, Protective Shelter, M2.
MIL-F-51318	-	Filter Unit, Gas-Particulate, EMD, 300 CFM, M6A2.
MIL-M-51328	-	Manometer Assemblies, M159, M160, M161, M162, and M1.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-1186	-	Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; with Appropriate Test Methods.

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

DL5-19-5383 - Collective Protection Equipment, CBR, Nike-Hercules, CONUS, M12.

PUBLICATIONS

EDGEWOOD ARSENAL PURCHASE DESCRIPTION

197-54-981 - Door, Permeable Membrane, Protective Shelter, M2.
197-54-1066 - Filter Unit, Gas-Particulate, EMD, 600 CFM, M46.
EA-M-1045 - Measuring Devices, Air, Collective Protection Equipment.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies of these ratings, rules, and regulations should be addressed to Uniform Classification Committee, 202 Union Station, 516 West Jackson Boulevard, Chicago, Illinois 60606.)

AMERICAN TRUCKING ASSOCIATIONS, INC.

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., 1616 P Street, N. W., Washington, D. C. 20036.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL5-19-5383 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

3.1.2 Components. All components of the collective protection equipment shall conform to the specifications and drawings listed on Drawing DL5-19-5383.

3.2 Workmanship. The packaged components of the M12 collective protection equipment shall be free from damage (cuts, tears, rips, or punctures) and contamination (dirt, grease, or oil).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Quality conformance inspection.

4.2.1 Lotting. A lot shall consist of the M12 collective protection equipment offered for acceptance at one time.

4.2.2 Sampling for examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.2.3 Inspection procedures.

4.2.3.1 For examination. Sample M12 collective protection equipment and the level A preparation for delivery shall be examined in accordance with the classification of defects and MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

4.2.3.2 Classification of defects.

(a) Preparation for delivery (section 5).

Categories	Defects
Critical:	None defined
Major:	AQL 2.5 percent defective
101	Components not preserved and packaged as specified
102	Component packing boxes not numbered as specified
103	Component missing
104	Packing method for components not as specified
105	Outer container not as specified
106	Internal cushioning and bracing missing or not as specified
107	Boxes not coated with wood preservative, when applicable
108	Marking missing, incorrect or illegible

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Gas-particulate filter unit, EMD, 300 CFM, M6A2. The filter unit shall be preserved and packaged as specified in the level A requirements of MIL-F-51318.

5.1.1.2 Gas-particulate filter unit, EMD, 600 CFM, M46. The filter unit shall be preserved and packaged as specified in the level A requirements of Purchase Description 197-54-1066.

5.1.1.3 Contaminated clothing chute, M1. The chute shall be preserved and packaged as specified in the level A requirements of MIL-C-50007.

5.1.1.4 Protective shelter antiback draft valve, M2. The valve shall be preserved and packaged as specified in the level A requirements of MIL-V-0050010.

5.1.1.5 Protective shelter permeable membrane door, M2. The door shall be packaged as specified in the level B packing requirements of Purchase Description 197-54-981.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

5.1.1.6 Manometer assemblies, M159, M160, M161, M162, and M1. The manometer assemblies shall be individually packaged as specified in the level B packing requirements of MIL-M-51328.

5.1.1.7 Shelter wall air flow measuring device. The magnehelic gage and pitot tube for the shelter wall air flow measuring device shall be packaged as specified in the level A requirements of Purchase Description EA-M-1045.

5.1.1.8 Technical publications and drawings. The technical publications and drawings shall be packaged in accordance with method IC-3 of MIL-P-116.

5.1.2 evel C. The components of the M12 Collective Protection Equipment shall be packaged as specified in the level C requirements of their respective specification or purchase description.

5.2 Packing. Packing shall be level A or C as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Gas-particulate filter unit, EMD, 300 CFM, M6A2. The filter unit shall be packed as specified in the level A requirements of MIL-F-51318. Three of these filter units are required. The boxes shall be marked 1 of 31, 2 of 31, and 3 of 31.

5.2.1.2 Gas-particulate filter unit, EMD, 600 CFM, M46. The filter unit shall be packed as specified in the level A requirements of Purchase Description 197-54-1066. Three of these filter units are required. The boxes shall be marked 4 of 31 thru 18 of 31.

5.2.1.3 Contaminated clothing chute, M1. The chute shall be packed as specified in the level A requirements of MIL-C-50007. Two of these clothing chutes are required. The boxes shall be marked 19 of 31 and 20 of 31.

5.2.1.4 Protective shelter antiback draft valve, M2. The valve shall be packed as specified in the level A requirements of MIL-V-0050010. Six of these valves are required. The boxes shall be marked 21 of 31 thru 26 of 31.

5.2.1.5 Protective shelter permeable membrane door, M2. Two doors, individually packaged as specified in 5.1.1.5, shall be packed in a wooden box conforming to class 2, overseas, style 4 of PPP-B-621, having approximate inside dimensions of 84-3/4 by 36-1/2 by 4 inches length, width, and depth respectively. The wooden box shall be closed and strapped in accordance with the appendix thereto. Strapping conforming to type I, class B of QQ-S-781 shall be used. The wood box, or the finished wood parts thereof, shall be preserved by completely immersing for a minimum of three minutes in a water repellent wood preservative conforming to composition A of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

TT-W-00572 and then dried. Prior to packing the items in the box, the treated wooden box shall meet the dryness of preservative requirement specified in MIL-B-2427. The box shall be marked 27 of 31.

5.2.1.6 Manometer assemblies, M159, M160, M161, M162, and M1. Two manometers M159, one manometer M160, three manometers M161, two manometers M162, and three manometers M1, packaged as specified in 5.1.1.6, shall be packed in a nailed wood box conforming to class 2, overseas, style 2 or 2-1/2 of PPP-B-621. The container shall be provided with skids. Internal cushioning, blocking, and bracing shall be accomplished in accordance with MIL-STD-1186, to prevent movement within the shipping container. The wooden box shall be closed and strapped in accordance with the appendix thereto. Strapping conforming to type I, class B of QQ-S-781 shall be used. The wood box, or the finished wood parts thereof, shall be preserved by completely immersing for a minimum of three minutes in a water repellent wood preservative conforming to composition A of TT-W-00572 and then dried. Prior to packing the items in the box, the treated wooden box shall meet the dryness of preservative requirement specified in MIL-B-2427. The box shall be marked 28 of 31.

5.2.1.7 Shelter wall air flow measuring device. The shelter wall air flow measuring device shall be packed as specified in the level A requirements of Purchase Description EA-M-1045. One of these measuring devices is required. The box shall be marked 29 of 31.

5.2.1.8 Air resistance flow measuring device. The air resistance flow measuring device shall be packed as specified in the level A requirements of Purchase Description EA-M-1045. One of these measuring devices is required. The box shall be marked 30 of 31.

5.2.1.9 Technical publications and drawings. The technical publications and drawings, packaged as specified in 5.1.1.8 shall be packed in a wooden box conforming to class 2, overseas, style 4 of PPP-B-621. The wooden box shall be closed and strapped in accordance with the appendix thereto. Strapping conforming to type I, class B of QQ-S-781 shall be used. The wood box, or the finished wood parts thereof, shall be preserved by completely immersing for a minimum of three minutes in a water repellent wood preservative conforming to composition A of TT-W-00572 and then dried. Prior to packing the items in the box, the treated wooden box shall meet the dryness of preservative requirement specified in MIL-B-2427. The box shall be marked 31 of 31.

5.2.2 Level C. The components of the M12 Collective Protection Equipment, packaged as specified in 5.1.2, shall be packed as specified in the level C requirements of their respective specification or purchase description. When any component items are to be combined and over packed, it shall be in such a manner as to insure carrier acceptance and safe delivery to the first domestic destination. Containers shall be in accordance with Uniform Freight Classification rules or National Motor

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.

Freight Classification rules. All shipping containers exceeding the gross weight of 250 pounds shall be provided with skids to facilitate the ease of handling. The boxes shall be numbered as provided for in the level A packing requirements herein.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with MIL-STD-129. All markings on the shipping containers shall be clear, legible, and permanent after the application of the wood preservative specified in 5.2.1.5, 5.2.1.6, and 5.2.1.9.

6. NOTES

6.1 Intended use. The equipment covered by this specification provides protection against CBR agents for the M12 Nike-Hercules CONUS installation.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Level of packaging and packing required (see 5.1 and 5.2).

6.3 Component specifications. Component specifications for the M12 NiKe-Hercules CONUS collective protection equipment are:

Title	Number
Chute, Contaminated Clothing, M1	MIL-C-50007
Door, Permeable Membrane, Protective Shelter, M2	197-54-981
Filter Unit, Gas-Particulate, EMD, 300 CFM, M6A2	MIL-F-51318
Filter Unit, Gas-Particulate, EMD, 600 CFM, M46	197-54-1066
Manometer Assemblies, M159, M160, M161, M162, and M1	MIL-M-51328
Measuring Devices, Air, Collective Protection Equipment	EA-M-1045
Valve, Antiback Draft, Protective Shelter, M2	MIL-V-0050010

Custodian:

Army - MU

Preparing activity:

Army - MU(EA)

Project No. 4240-A396

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:57Z
Check the source to verify that this is the current version before use.