MIL-I-60526(MU)
15 August 1967
SUPERSEDING
FA-PD-MI-2561
7 September 1962

MILITARY SPECIFICATION
INITIATOR, CARTRIDGE ACTUATED, DELAY, XM64
METAL PARTS ASSEMBLY

1. SCOPE

1.1 This specification covers Initiator, Cartridge Actuated, Delay, XM64, Metal Parts Assembly. The assembly will ultimately be loaded and used in conjunction with other propellant actuated devices in the recovery system of training bombs, or in aircrew emergency escape systems.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-A-2550	- Ammunition and Special Weapons, General Specification for

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-413	- Visual Inspection Guide for Rubber O-Rings
MIL-STD-639	- Surface Roughness Values Preferred for Army Ordnance Materiel
MIL-STD-1167	- Ammunition Data Card

DRAWINGS

Munitions Command

D10522500	- Initiator, Cartridge Actuated, Delay, XM64, Metal Parts Assembly
C8846785	- Container, Ammunition, Fiber, M459 for Initiators, Delay, Cartridge Actuated

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

2.1 (Cont'd)

DRAWINGS (Cont'd)

Munitions Command

C8846786 - Box, Packing, Ammunition for Initiators, Delay, Cartridge Actuated in Fiber Container M459

IEL 10522500 - Inspection Equipment List for Initiator, Cartridge Actuated, Delay, XM64, Metal Parts Assemblies

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall comply with the requirements specified in the applicable drawings and referenced specifications.

3.2 Physical and mechanical properties.- Physical or mechanical properties required by the drawing shall be uniform throughout each part within specified tolerances. Mechanical properties for all alloy steel parts shall be achieved by quenching and tempering.

3.3 Hydrostatic pressure.- The initiator chamber and cap shall withstand a hydrostatic pressure of 14,000 to 15,000 pounds per square inch (psi) for 15 seconds, minimum without deformation or mechanical failure (See 6.1).

3.4 Firing pin release.- The firing pin of the metal parts assembly, less safety pin, shall release from the cocked position when the application of an axial load of 15 to 30 pounds has withdrawn the initiator pin .370 inches, minimum and .425 inches, maximum.

3.5 Initiator pin security.- Application of an axial load of 200 to 220 pounds to the initiator pin of the metal parts assembly shall not withdraw the initiator pin past the safety pin. Load application shall cause no permanent deformation of the safety pin.

3.6 Protective finish.- Protective finish shall be in accordance with the applicable specifications and drawings and shall apply to all surfaces of the component regardless of configuration.

3.7 Residual magnetism.- The metal parts assembly shall not deflect the indicator of the compass more than 3 degrees in either direction when passed in front of the compass at a distance of six inches.

3.8 Workmanship.- The requirements for workmanship are as specified on the applicable drawing, referenced specifications and the following.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

3.8.1 Metal defects.- The part shall be free from cracks, splits, cold shuts, inclusions, porosity or other metal defects.

3.8.2 Burr.- The part shall not have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.8.3 Foreign matter.- The part or assembly shall not contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550.

4.2 First article sample.

4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 5 assemblies, 50 units of each component for hardness tests, and 10 sets of unassembled components for visual and dimensional examination and shall be tested as indicated in Table I.

TABLE I

Paragraph Requirement	Test	Type of Test	Sample Size	Dest.	Non-Dest.
3.2	4.4.1	Hardness	50 (Unplated)	-	X
3.3	4.4.2	Hydrostatic Pressure	Each	-	X
3.4	4.4.3	Firing Pin Release	Each	-	X
3.5	4.4.4	Initiator Pin Security	Each	-	X
3.6	4.4.5	Protective Finish	As specified in referenced spec.	X	-
3.7	4.4.6	Residual Magnetism	Each	-	X

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.2.1 (Cont'd)

The sample shall be manufactured using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and test.- After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility as specified in the contract.

4.2.1.2 Initial production sample failure.- Failure of the sample to comply with the requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

4.3.1 Lot

4.3.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Size of lot.- Unless otherwise specified by the procuring agency, a lot shall consist of 1200 metal parts assemblies, maximum, exclusive of test samples.

4.3.2 Examination.- One hundred percent examination shall be performed for all critical defects. Examination for major or minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plan and associated criteria in Tables II and III. For an individual defect (single characteristic), the criteria in Table II shall be used. For total defects within a major or minor group, the criteria in Table III shall be used. All non-conforming material shall be rejected. Inspection for rubber O-rings shall be in accordance with MIL-STD-413. The Ordnance Standard Finish Blocks prescribed in MIL-STD-639 shall be used as a basis of comparison for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

TABLE II

Lot Size	Sample Size	Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% Examination	-	-	-	-
301 - 1300	110	1	2	2	3
1301 - 3200	150	2	3	3	4
3201 - 8000	225	3	4	4	5
8001 - 22000	300	4	5	5	6

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2 (Cont'd)

TABLE III

Sample Size for Major Defects Number of Defects in Class	Total Allowable defects Per Sample Size 110	150	225	300
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 - 19	3	4	5	7
20 - 43	4	5	8	10
Over 43	6	8	11	14

Sample Size for Minor Defects Number of Defects in Class	Total Allowable defects Per Sample Size 110	150	225	300
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
Over 48	8	11	17	20

4.3.2.1 Chamber, Initiator, Drawing C8597928, covering a detail of Drawing D10522500

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Pitch diameter of large external thread, min.	Gage
102. Major diameter of large external thread, min.	Gage
103. Pitch diameter of small external thread, min.	Gage
104. Major diameter of small external thread, min.	Gage
105. Pitch diameter of internal thread, max.	Gage
106. Minor diameter of internal thread, max.	Gage
107. Concentricity of datum location with pitch diameter of small external thread	Gage
108. Concentricity of pitch diameter of large thread with cavity	Gage
109. Concentricity of large external thread pilot with large external thread	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.1 (Cont'd)

	Defect	Method of Inspection
MAJOR (Cont'd)		
110.	Concentricity of counterbore with cavity, including perpendicularity with base of counterbore	Gage
111.	Diameter of counterbore	Gage
112.	Diameter of large thread pilot	Gage
113.	Depth of cavity	Gage
114.	Length to datum location	Gage
115.	Thickness of wall, min.	Gage
116.	Metal defective	Visual
117.	Protective finish inadequate or defective	Visual
118.	Surface finish of cavity and angle of gas port improper	Visual
119.	Burr or sharp corner	Visual
120.	Foreign matter	Visual
MINOR		
201.	Pitch diameter of large external thread, max.	Gage
202.	Pitch diameter of small external thread, max.	Gage
203.	Pitch diameter of internal thread, min.	Gage
204.	Diameter of small external thread relief	Gage
205.	Diameter of small external thread pilot	Gage
206.	Diameter of hole in gas port	Gage
207.	Diameter of cavity	Gage
208.	Depth of counterbore	Gage
209.	Length of gas port	Gage
210.	Length of small thread relief	Gage
211.	Length from face of gas port to small thread	Gage
212.	Length of external thread pilot	Gage
213.	Thickness of wall, max.	Gage
214.	Depth of threaded hole	Measure
215.	Diameter of chamfer at internal thread	Measure
216.	Total length	Measure
217.	Length of large external thread	Measure
218.	Marking missing, incorrect or illegible	Visual
219.	Radius or chamfer missing or incorrect	Visual
220.	Surface finish improper, except as otherwise classified	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.2 Housing, Firing Pin. Drawing C10520410, covering a detail of Drawing D10522500

	Defect	Method of Inspection
CRITICAL		
1.	Diameter of striker hole, min.	Gage
MAJOR		
101.	Pitch diameter of thread, min.	Gage
102.	Major diameter of thread, min.	Gage
103.	Concentricity of striker hole with cavity	Gage
104.	Concentricity of cavity with body	Gage
105.	Concentricity of pitch diameter of thread with body	Gage
106.	Perpendicularity of face with body	Gage
107.	Diameter of body, min.	Gage
108.	Diameter of cavity	Gage
109.	Diameter of flange, min.	Gage
110.	Diameter of boss	Gage
111.	Diameter of undercut, min.	Gage
112.	Total length, max.	Gage
113.	Width of undercut	Gage
114.	Thickness at striker hole	Gage
115.	Location of thread	Gage
116.	Chamfer at striker hole	Gage
117.	Height of boss	Gage
118.	Metal defective	Visual
119.	Protective finish inadequate or defective	Visual
120.	Surface finish of cavity improper	Visual
121.	Burr	Visual
122.	Foreign matter	Visual
MINOR		
201.	Pitch diameter of thread, max.	Gage
202.	Diameter of body, max.	Gage
203.	Diameter of striker hole, max.	Gage
204.	Diameter of flange, max.	Gage
205.	Diameter of wrench hole	Gage
206.	Depth of wrench hole	Gage
207.	Total length, min.	Gage
208.	Length of body to flange	Gage
209.	Location of wrench holes	Gage
210.	Marking missing, incorrect or illegible	Visual
211.	Radius or chamfer missing or incorrect, except as otherwise classified	Visual
212.	Surface finish improper, except as otherwise classified	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.3 Pin, Firing, Drawing C10520411, covering a detail of Drawing D10522500

	Defect	Method of Inspection
CRITICAL		
	None defined	
MAJOR		
101.	Concentricity of large cavity with body	Gage
102.	Concentricity of striker with body	Gage
103.	Concentricity of cavity with body	Gage
104.	Symmetry of pin relief hole with small cavity	Gage
105.	Symmetry of ball hole counterbore with ball holes	Gage
106.	Diameter of striker	Gage
107.	Diameter of body	Gage
108.	Diameter of ball hole, max.	Gage
109.	Diameter of ball hole counterbore	Gage
110.	Diameter of pin relief holes, min.	Gage
111.	Depth of ball counterbore, min.	Gage
112.	Length of striker, min.	Gage
113.	Location of ball hole counterbore	Gage
114.	Metal defective	Visual
115.	Protective finish inadequate or defective	Visual
116.	Surface finish of body improper	Visual
117.	Burr or sharp corner	Visual
118.	Foreign matter	Visual
MINOR		
201.	Diameter of large cavity	Gage
202.	Diameter of small cavity	Gage
203.	Diameter of ball hole, min.	Gage
204.	Diameter of pin relief holes, max.	Gage
205.	Depth of large cavity	Gage
206.	Depth to bottom of small cavity	Gage
207.	Depth of ball hole counterbore, max.	Gage
208.	Length of striker, max.	Gage
209.	Total length	Gage
210.	Location of pin relief holes	Gage
211.	Marking missing, incorrect or illegible	Visual
212.	Radius or chamfer missing or incorrect	Visual
213.	Surface finish improper, except as otherwise classified	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.4 Spring, Initiator, Drawing B10520412, covering a detail of Drawing D10522500

	Defect	Method of Inspection
CRITICAL		
	None defined	
MAJOR		
101.	Load at specified height	Gage
102.	Closed length, max.	Gage
103.	Ends incorrect	Visual
104.	Protective finish inadequate or defective	Visual
105.	Burr	Visual
106.	Foreign matter	Visual
MINOR		
201.	Diameter, outside	Gage
202.	Free length	Gage

4.3.2.5 Pin, Safety, Drawing B10522817, covering a detail of Drawing D10522500

	Defect	Method of Inspection
CRITICAL		
	None defined	
MAJOR		
101.	Diameter of wire	Gage
102.	Profile incorrect	Visual
103.	Metal defective	Visual
104.	Protective finish inadequate or defective	Visual
105.	Burr	Visual
106.	Foreign matter	Visual
MINOR		
201.	Diameter of head, outside	Measure
202.	Length between high and low ends	Measure
203.	Total length	Measure
204.	Location of center loop	Measure
205.	Radius of center loop incorrect	Measure

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.6 Filter, Drawing C10520414, covering a detail of Drawing D10522500

	Defect	Method of Inspection
CRITICAL		
	None defined	
MAJOR		
101.	Pitch diameter of thread, min.	Gage
102.	Major diameter of thread, min.	Gage
103.	Concentricity of thread with center hole and outside diameter	Gage
104.	Symmetry of holes with outside diameter	Gage
105.	Diameter of center hole	Gage
106.	Diameter of holes	Gage
107.	Depth of center hole	Gage
108.	Depth of slot, max.	Gage
109.	Location of holes	Gage
110.	Angular location of holes	Gage
111.	Nylon patch not properly located or fused	Manual and Visual
112.	Number of holes incorrect	Visual
113.	Metal defective	Visual
114.	Protective finish inadequate or defective	Visual
115.	Burr	Visual
116.	Foreign matter	Visual
MINOR		
201.	Pitch diameter of thread, max.	Gage
202.	Diameter of undercut	Gage
203.	Diameter of body	Gage
204.	Depth of slot, min.	Gage
205.	Total length	Gage
206.	Length of body	Gage
207.	Width of undercut, max.	Gage
208.	Width of slot	Gage
209.	Location of slot	Gage
210.	Marking missing, incorrect or illegible	Visual
211.	Chamfer missing or incorrect	Visual
212.	Surface finish improper	Visual

4.3.2.7 Seal, Drawing B10520415, covering a detail of Drawing D10522500

CRITICAL

None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.7 (Cont'd)

Defect	Method of Inspection
MAJOR	
101. Diameter, outside, min.	Gage
102. Width, min.	Gage
103. Thickness, min.	Gage
104. Cut, cracked or split	Visual
105. Flash	Visual
106. Foreign matter	Visual
MINOR	
201. Diameter, outside, max.	Gage
202. Width, max.	Gage
203. Thickness, max.	Gage

4.3.2.8 Cap, Initiator, Drawing D10522501, covering a detail of Drawing D10522500

CRITICAL	
None defined	
MAJOR	
101. Pitch diameter of external thread, min.	Gage
102. Major diameter of external thread, min.	Gage
103. Pitch diameter of small internal thread, max.	Gage
104. Minor diameter of small internal thread, max.	Gage
105. Pitch diameter of large internal thread, max.	Gage
106. Minor diameter of large internal thread, max.	Gage
107. Concentricity of pitch diameter of large internal thread with midsection cavity, including perpendicularity with base of counterbore of large cavity	Gage
108. Concentricity of large cavity behind undercut with pitch diameter of large internal thread	Gage
109. Concentricity of pitch diameter of small internal thread with midsection cavity	Gage
110. Concentricity of hole between small cavity and boss cavity with midsection cavity	Gage
111. Concentricity of undercut in large cavity with large internal thread	Gage
112. Concentricity of small cavity with hole between small cavity and boss cavity	Gage
113. Concentricity of boss cavity with midsection cavity	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.8 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
114. Symmetry of width across flats with pitch diameter of external thread	Gage
115. Diameter of large cavity rear of undercut	Gage
116. Diameter of small cavity	Gage
117. Diameter of boss cavity, max.	Gage
118. Diameter of hole between small cavity and boss cavity, max.	Gage
119. Diameter of undercut at large internal thread	Gage
120. Diameter of safety pin hole, max.	Gage
121. Diameter over top of pellet	Gage
122. Length of effective exterior thread, min.	Gage
123. Length of effective small interior thread, min.	Gage
124. Length of exterior thread, max.	Gage
125. Length of small interior thread, max.	Gage
126. Width of undercut behind large interior thread	Gage
127. Location of safety pin hole	Gage
128. Height of boss	Gage
129. Pellet missing, loose or improperly inserted	Visual
130. Angular location of pellet	Visual
131. Metal defective	Visual
132. Protective finish inadequate or defective	Visual
133. Surface finish of undercut behind large interior thread improper	Visual
134. Burr or sharp corner	Visual
135. Foreign matter	Visual
MINOR	
201. Pitch diameter of set screw thread	Gage
202. Minor diameter of set screw thread, max.	Gage
203. Pitch diameter of external thread, max.	Gage
204. Pitch diameter of small internal thread, min.	Gage
205. Pitch diameter of large internal thread, min.	Gage
206. Diameter of body, small end	Gage
207. Diameter of body, large end	Gage
208. Diameter of groove, small end	Gage
209. Diameter of groove on internal boss	Gage
210. Diameter of chamfer, large internal thread	Gage
211. Diameter of chamfer, small internal thread	Gage
212. Diameter of midsection cavity	Gage
213. Diameter of boss cavity, min.	Gage
214. Diameter of hole between small cavity and boss cavity, min.	Gage
215. Diameter of safety pin hole, min.	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.8 (Cont'd)

Defect	Method of Inspection
MINOR (Cont'd)	
216. Depth from base of large cavity rear of undercut to base of midsection cavity	Gage
217. Depth from base of large cavity rear of undercut to face of internal boss	Gage
218. Depth to bottom of large cavity rear of undercut	Gage
219. Depth of large cavity, rear of undercut	Gage
220. Depth from base of large cavity, rear of undercut to face of internal boss	Gage
221. Total length	Gage
222. Length of body, large end	Gage
223. Length of body, large end, including shoulder	Gage
224. Length of flat	Gage
225. Width of groove, small end	Gage
226. Width across flat	Gage
227. Location of set screw hole	Gage
228. Location of pellet	Gage
229. Location of groove, small end	Gage
230. Safety pin hole obstructed	Visual
231. Pellet radius incorrect	Visual
232. Marking missing, incorrect or illegible	Visual
233. Radius or chamfer missing or incorrect, except as otherwise classified	Visual
234. Surface finish improper, except as otherwise classified	Visual

4.3.2.9 Pin, Initiator, Drawing C10520553, covering a detail of Drawing D10522500

CRITICAL

None defined

MAJOR

101.	Concentricity of head with body	Gage
102.	Concentricity of flange with body	Gage
103.	Concentricity safety pin groove with body	Gage
104.	Concentricity of end of body with body	Gage
105.	Symmetry of pull hole with body	Gage
106.	Symmetry of flat of head with body	Gage
107.	Diameter of recess at end of body	Gage
108.	Diameter of flat at end of body	Gage
109.	Metal defective	Visual
110.	Protective finish inadequate or defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.9 (Cont'd)

Defect	Method of Inspection
MAJOR (Cont'd)	
111. Surface finish of recess at end of body, body and face of flange improper	Visual
112. Burr	Visual
113. Foreign matter	Visual
MINOR	
201. Diameter of flange	Gage
202. Diameter of safety pin groove	Gage
203. Diameter of body, min (if applicable) (Alt.)	Gage
204. Diameter of body	Gage
205. Diameter of flange	Gage
206. Diameter of safety pin groove	Gage
207. Diameter of pull hole	Gage
208. Length of body to step	Gage
209. Total length	Gage
210. Width of flat	Gage
211. Width of safety pin groove	Gage
212. Width of head	Gage
213. Thickness of flange	Gage
214. Thickness of head	Gage
215. Location of recess at end of body	Gage
216. Location of pull hole	Gage
217. Cut out behind flange (if applicable) (Alt.)	Gage
218. Surface finish improper, except as otherwise classified	Visual

4.3.2.10 Assembly, Drawing D10522500, less all drawings, except C10520410, C10520411 and MS19060-3

CRITICAL	
1. Firing pin protrusion	Gage
2. Steel ball missing	Gage
MAJOR	
101. Burr	Visual
102. Foreign matter	Visual
MINOR	
None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.11 Assembly, Drawing D10522500

Defect	Method of Inspection
CRITICAL	
None defined	
MAJOR	
101. Firing pin not cocked	Manual
102. Initiator pin not free to rotate	Manual
103. Any part missing, except as otherwise classified	Visual
104. Improper assembly	Visual
105. Safety pin improperly inserted	Visual
106. O-ring not lubricated	Visual
107. Marking missing, incorrect or illegible	Visual
MINOR	
201. Shipping cap missing	Visual
202. Protective finish inadequate or defective	Visual

4.3.2.12 Fiber Container, Drawing C8846785

CRITICAL	
None defined	
MAJOR	
None defined	
MINOR	
201. Contents loose	Manual
202. Metal ends loose or distorted	Manual
203. Gap between body and cover, max.	Visual
204. Cut or damaged through all impregnated layers	Visual

4.3.2.13 Packing, Box, Drawing C8846786

CRITICAL	
None defined	
MAJOR	
None defined	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.2.13 (Cont'd)

Defect	Method of Inspection
MINOR	
201. Contents loose	Manual
202. Hardware missing, loose, broken or improperly engaged	Manual and Visual
203. Strapping missing, loose, broken or improperly assembled	Manual and Visual
204. Contents of box exposed	Visual
205. Box damaged	Visual
206. Marking missing, incorrect or illegible	Visual
207. Number of units incorrect	Visual

4.3.3 Inspection testing.- The following tests shall be performed in accordance with the provisions of 4.4:

4.3.3.1 Hardness.- Fifty units from each heat-treated lot of components shall be tested for compliance with the requirements specified on the applicable drawing. Failure of any unit to comply with 3.2 shall be cause for rejection of the lot.

4.3.3.2 Hydrostatic pressure.- Each chamber and cap subassembly shall be subjected to the hydrostatic pressure test. Failure of any subassembly to comply with the requirement of 3.3 shall be cause for rejection of the subassembly.

4.3.3.3 Firing pin release.- The initiator pin of each subassembly consisting of all parts, except the safety pin and chamber, shall be subjected to the firing pin release test. Failure of any subassembly to comply with the requirement of 3.4 shall be cause for rejection of the subassembly.

4.3.3.4 Initiator pin security.- The initiator pin of each subassembly consisting of all parts, except the chamber, shall be subjected to the initiator pin security test. Failure of any subassembly to comply with the requirements of 3.5 shall be cause for rejection of the subassembly.

4.3.3.5 Protective finish.- The number of specimens and acceptance criteria for protective finish tests shall be in accordance with the applicable Military Standard referenced on the drawing. Failure of any component to comply with the requirements of 3.6 shall be cause for rejection of the lot.

4.3.3.6 Residual magnetism.- Each assembly shall be subjected to the test for excessive residual magnetism. Failure of any assembly to comply with the requirements of 3.7 shall be cause for rejection of the assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

4.3.4 Inspection equipment.- The examination and test shall be made using equipment listed on IEL-10522500.

4.4 Test methods and procedures.

4.4.1 Hardness.- A hardness testing machine shall be used for determining the hardness values specified on the applicable drawing.

4.4.2 Hydrostatic pressure.- Prior to the application of protective finish, the chamber and cap subassembly shall be mounted in the device, using the fixtures for properly sealing all openings and subjected to the hydrostatic pressure to determine compliance with 3.3.

4.4.3 Firing pin release.- The subassembly shall be secured in the fixture. A pull shall be applied to the initiator pin in the longitudinal direction in conjunction with the fixture which registers the amount of pull.

4.4.4 Initiator pin security.- The subassembly shall be secured in the fixture with the safety pin in place. A pull shall be applied to the initiator pin in the longitudinal direction in conjunction with the fixture which registers the amount of pull. The test shall be performed with the safety pin in both positions.

4.4.5 Protective finish.- Test procedures for protective finish shall be in accordance with the applicable Military Standard referenced on the drawing.

4.4.6 Residual magnetism.- The assembly shall be tested for excessive residual magnetism in an area free of local magnetic effects by placing the assembly 6 inches from and at the same height as the compass, in a north-south horizontal position (cap end at south) with the compass set in an east-west heading. The assembly shall be slowly moved past the compass for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the assembly.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking.- Packing and marking shall be in accordance with Drawings C8846785 and C8846786.

5.2 Data cards.- Data card information shall be as specified in MIL-STD-1167.

6. NOTES

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

6.1 A mechanical failure is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

CUSTODIAN:

Army - MU

PREPARING ACTIVITY:

Army - MU

Project No. 1377-A034

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

Frankford Arsenal
Philadelphia, Pa. 19137

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-N1100
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:41Z
Check the source to verify that this is the current version before use.