# MILITARY SPECIFICATION

## TIEDOWN, WEB, SPECIAL PURPOSE

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

## 1. SCOPE

1.1 Scope. This military specification covers one type of special purpose web tiedown used to secure weapon containers during transportation modes.

## 2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specification and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issues of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

FEDERAL

FED-STD-751 - Stitches, Seams and Stitchings

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to. Commander, U.S. Army ARDEC, ATTN. SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC - 5340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:07Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings and publications. The following other Government document forms a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT DRAWINGS

9392419 Tiedown, Web, Special Purpose

PACKAGING DATA DRAWINGS

P9392419 Packaging Data Sheet

(Copies of drawings, and publications required by manufacturers in connection with specific acquisition functions, should be obtained from the contracting activity or as directed by the contracting officer).

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials and components. Materials shall conform to applicable specifications and drawings. Each component shall conform to all dimensions and tests specified on the component drawing. The contractor shall have available verifiable proof (i.e., objective evidence (see 6.4.)) that materials and components were fabricated, inspected, and tested under controllable conditions as set forth in the contractor's quality control or inspection procedures.

3.2 Assembly. The tiedown shall comply with all requirements specified on drawing (dwg.) 9392419, with all requirements specified herein, and with the requirements of applicable specifications to the extent specified on the drawings and herein.

3.3 First article. When specified in the contract or purchase order (see 6.2), a sample shall be subjected to first article inspection in accordance with the technical provisions herein (see 4.3).



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

3.4 Function requirement.

3.4.1 Tensioning mechanism test. The ratchet handle shall be capable of exerting a minimum tension of 150 pounds to the tiedown, and the handle force required to apply this tension shall not exceed 50 pounds. During this test, there shall be no slippage of the ratchet spool. Testing shall be as specified in 4.5.1.1.

3.4.2 Locking latch engaging test. The ratchet handle shall be capable of being closed when the tiedown assembly is manually tensioned to get the locking latch engaged to the next tooth on the sprockets. The closed position is when the ears of the locking latch are seated behind the respective left and right ratchet gear tooth, and the locking ears of the handle are in place behind the respective ears of the locking latch. Test as specified in 4.5.1.2.

3.4.3 Release mechanism test. The ratchet handle shall be capable of operating the release mechanism when the tiedown is stressed to a minimum tension of 750 pounds. The handle force required to operate the release mechanism shall not exceed 50 pounds. Testing shall be as specified in 4.5.1.3.

3.4.4 Proof load test. The tiedown shall withstand a minimum load of 5,000 pounds, for a minimum period of 30 seconds, without evidence of deterioration or damage that may impair its intended operation. In addition, swivel hooks shall rotate freely, hook keepers must function properly, and webbing must slip freely through the ratchet buckle. Testing shall be as specified in 4.5.1.4.

3.4.5 Ultimate load test. The tiedown shall withstand a minimum load of 7,000 pounds, for a minimum period of 30 seconds, without evidence of slippage of the webbing or rupture of the stitches and metal parts. The following damage criteria shall not be cause for rejection:

a. Broken stitches without complete separation.

b. Split, torn or frayed webbing without complete rupture.

c. Permanent deformation but not rupture of the hardware.

Testing shall be as specified in 4.5.1.5.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

3.4.6 Ratchet load test. The tiedown, when load tested to failure, shall withstand a minimum load of 8,000 pounds before failure occurs. The following damage criteria shall not be cause for rejection:

a. Broken stitches without complete separation.

b. Split, torn or frayed without complete rupture.

c. Permanent deformation but not rupture of the hardware.

Testing shall be as specified in 4.5.1.6.

3.4.7 Stitching pattern load test. A test length of tiedown webbing, having the same stitching pattern at both ends, shall be load tested to failure (complete separation of the webbing), and shall withstand a minimum load of 8,700 pounds before failure occurs. Testing shall be as specified in 4.5.1.7.

3.4.8 Ratchet handle load test. The ratchet handle shall withstand a minimum load of 300 pounds, for a minimum period of 30 seconds, without evidence of deterioration or damage that may impair its intended operation. In addition, the ratchet handle when load tested to failure shall withstand a minimum load of 800 pounds before failure (rupture of any metal part) occurs. Permanent deformation of the ratchet shall not be cause for rejection. Testing shall be as specified in 4.5.1.8.

3.4.9 Stitching. All stitching of the tiedown shall be in accordance with FED-STD-751, Type 301, 5 - 8 stitches per inch. Stitching shall be backstitched one-quarter inch at the ends, except where ends are turned under in a hem or held down by other stitching. Thread tension shall be maintained so that there will be no loose stitches and that the stitch lock will be embedded in the webbing material. All thread ends shall be trimmed. Testing shall be as specified in 4.4.2.1.

3.5 Serialization. Not applicable.

3.6 Workmanship. All parts and accessories shall be constructed, assembled, and finished in a thoroughly workmanlike manner. Particular attention shall be given to neatness, marking, cleaning, and freedom of the parts from burrs and sharp edges which may affect performance or result in injury during handling. All parts shall be free of chips, dirt, grease, rust, and other foreign material. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agents.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3.2)

b. Quality conformance inspection (see 4.4)

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the assemblies, components and test specimens listed below in the quantities indicated.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

4.3.2 Inspections to be performed. As determined by the Government, the first article assemblies, components and test specimens may be subjected to any or all of the examinations and tests specified in Table I and be inspected for compliance with any or all requirements of the applicable drawings.

4.3.3 Rejection. If any assembly, component or test specimen fails to comply with any of the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate inspection upon any failure of an assembly, component or test specimen to comply with any of the requirements.

TABLE I. First article tests

| Test | Requirement paragraph | Sample Number to be tested |
|---|---|---|
| a. Tensioning mechanism | 3.4.1 | 1,2,3,4 |
| b. Locking latch engaging | 3.4.2 | 1,2,3,4 |
| c. Release mechanism | 3.4.3 | 1,2,3,4 |
| d. Proof load | 3.4.4 | 1,2,3,4 |
| e. Ultimate load | 3.4.5 | 1,2,3,4 |
| f. Ratchet load | 3.4.6 | 5,6,7 |
| g. Stitching pattern load | 3.4.7 | 8,9,10 * |
| h. Ratchet handle load | 3.4.8 | 8,9,10 * |

*Sample number 8,9, and 10 shall be disassembled for these tests. The three short webbings shall be used for test g, and three ratchets shall be used for test h.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. The term "inspection lot" is defined as a homogeneous collection of units or product from which a representative sample is drawn or which is inspected 100 percent to determine conformance with applicable requirements. Units of product selected for inspection shall represent only the inspection lot from which they are drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods, in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of inspection procedure which is being applied to determine conformance with requirements.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

4.4.2 Examinations and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program of detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified. When cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

b. Alternative quality conformance provisions. Alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by the contractor when they provide, as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted tothe Government for evaluation (see 6.6). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equal to or better than the specified quality assurance provision(s) herein. In cases of dispute as to whether the contractor's proposed alternative(s) provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system, as applicable.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

TABLE II. Attributes sampling inspection

| Lot Size | Inspection Levels | | | | | |
|---|---|---|---|---|---|---|
| | I | II | III | IV | V | VI |
| 2 to 8 | * | * | * | * | 5 | 3 |
| 9 to 15 | * | * | * | 13 | 5 | 3 |
| 16 to 25 | * | * | * | 13 | 5 | 3 |
| 26 to 50 | * | * | 32 | 13 | 5 | 3 |
| 51 to 90 | * | * | 32 | 13 | 13 | 5 |
| 91 to 150 | * | 125 | 32 | 13 | 13 | 5 |
| 151 to 280 | * | 125 | 32 | 32 | 20 | 8 |
| 281 to 500 | * | 125 | 32 | 32 | 20 | 8 |
| 501 to 1200 | * | 125 | 80 | 50 | 20 | 13 |
| 1201 to 3200 | 1250 | 125 | 80 | 50 | 32 | 13 |
| 3201 to 10000 | 1250 | 125 | 125 | 50 | 32 | 13 |
| 10001 to 35000 | 1250 | 315 | 125 | 80 | 50 | 13 |
| 35001 to 150000 | 1250 | 315 | 125 | 80 | 50 | 13 |
| 150001 to 500000 | 1250 | 500 | 200 | 125 | 50 | 13 |
| 500001 and over | 1250 | 500 | 200 | 125 | 50 | 13 |

Numbers under inspection levels indicate sample size; asterisks (*) indicate one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept zero and reject on one or more for all inspection levels.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION
CLASSIFICATION OF CHARACTERISTICS

| PARAGRAPH | TITLE | SHEET 1 OF 2 | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.1 | Tiedown, Web, Special (static) | | 9392419 |
| | | | NEXT HIGHER ASSEMBLY |

| CLASSIFICATION | EXAMINATION OR TEST | CONFORMANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD REFERENCE |
|---|---|---|---|---|
| Critical | None defined | | | |
| Major | | | | |
| 101. | Length, extended, min. | Level III | 3.2 | Gage |
| 102. | Length of handle, min. | Level III | 3.2 | Gage |
| 103. | Inability to open closed ratchet while wearing arctic mittens | Level III | 3.2 | Manual |
| 104. | Stitching improper | Level III | 3.4.9 | Visual |
| 105. | Spool segment cracked or damaged (2 segments/spool) | Level III | 3.2 | Visual |
| 106. | Any component missing, damaged, or improperly assembled (including swivel hooks (2), ratchet, identification tag, and protector sleeves (2)) | Level III | 3.2 | Visual |
| 107. | Verify each web segment per tiedown is from common supplier | Level III | 3.2 | Visual |
| Minor | | | | |
| 201. | Marking missing, improper, or illegible | Level IV | 3.2 | Visual |
| 202. | Evidence of poor workmanship | Level IV | 3.6 | Visual |
| 203. | Objective evidence that web elongation at 9,000 pounds between 12 to 16 percent | Level IV | 3.1 | Visual |

NOTES



Source: https://assist.dla.mil -- Downloaded: 2026-02-23T03:07Z
Check the source to verify that this is the current version before use.

# QUALITY CONFORMANCE INSPECTION
# CLASSIFICATION OF CHARACTERISTICS

| PARAGRAPH | TITLE | SHEET 2 OF 2 | DRAWING NUMBER |
|---|---|---|---|
| 4.4.2.1 | Tiedown, Web, Special Purpose (Functional) | | 9392419 |
| | | | NEXT HIGHER ASSEMBLY |

| CLASSIFICATION | EXAMINATION OR TEST | CONFORMANCE CRITERIA | REQUIREMENT PARAGRAPH | INSPECTION METHOD REFERENCE |
|---|---|---|---|---|
| Critical | None defined | | | |
| Major | | | | |
| 101. | Tensioning mechanisms | 1/ | 3.4.1 | 4.5.1.1 |
| 102. | Locking latch engaging | 1/ | 3.4.2 | 4.5.1.2 |
| 103. | Release mechanism | 1/ | 3.4.3 | 4.5.1.3 |
| 104. | Proof load | 1/ | 3.4.4 | 4.5.1.4 |
| 105. | Ultimate load | 1/ | 3.4.5 | 4.5.1.5 |
| 106. | Ratchet load | 2/ | 3.4.6 | 4.5.1.6 |
| 107. | Stitching pattern load | 3/ | 3.4.7 | 4.5.1.7 |
| 108. | Ratchet handle load | 3/ | 3.4.8 | 4.5.1.8 |
| Minor | None defined | | | |
| | Sample size: 10 from each lot of 1,000 tiedowns or portion thereof. If any tiedown fails to comply, the lot shall be rejected. | | | |

NOTES:
1/ Four tiedowns subjected to test in sequence listed.
2/ Three tiedowns subjected to this test only.
3/ Three tiedowns disassembled, test fixed end (short) webbings per 107 and test ratchets per 108.



Source: https://assist.dla.mil -- Downloaded: 20260-23T03:07Z
Check the source to verify that this is the current version before use.

4.4.3 Inspection equipment. The inspection equipment required to perform the inspections specified herein is identified in the "Inspection Method Reference" column of the Classification of Characteristics listings starting with 4.4.2.1. Contractor inspection equipment designs shall be submitted for Government approval as specified in the contract. Designs which provide variable measurements instead of attributes data are preferred in order to facilitate the use of statistical process control. (See MIL-A-48078 and 6.4)

4.5 Methods of inspection. The tolerances specified in this specification are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerance less the accuracy tolerances of the test equipment used. Unless otherwise specified, the tests shall be conducted at room temperature (77° ± 10°F).

4.5.1 Function tests.

4.5.1.1 Tensioning mechanism test. The tiedown shall be securely attached, by means of the two swivel hooks, to a Government-approved test fixture, with a minimum of 1 1/2 wraps of double-thickness webbing around the ratchet spool. The tiedown may be any convenient length for the performance of this test. Manually operate the ratchet handle until a minimum load of 150 pounds is obtained. Measure the force, perpendicular to the ratchet handle, required to obtain the 150 pound load. The tensioning mechanism shall comply with the requirements of 3.4.1 during this test.

4.5.1.2 Locking latch engaging test. The tiedown shall be securely attached, by means of the two swivel hooks, to a Government approved fixture, with a minimum of 1 1/2 wraps of double thickness webbing around the ratchet spool, and a minimum hook to hook length of 36 inches. Gradually apply tension to the strap, at any convenient rate, until a minimum load of 100 pounds is obtained. Manually operate the ratchet handle to get the locking latch engaged to the next tooth of the sprockets. The ratchet handle locking latch function shall comply with the requirements of 3.4.2.

4.5.1.3 Release mechanism test. The tiedown shall be securely attached, by means of the two swivel hooks, to a Government-approved test fixture, with a minimum of 1 1/2 wraps of double-thickness webbing around the ratchet spool. The tiedown may be any convenient length for this test. Completely open the ratchet handle, and gradually apply tension to the tiedown, at any convenient rate, until a minimum load of 750 pounds is obtained. Release the handle lock, and slowly move the handle toward its full-open position until the release mechanism is disengaged. The tiedown shall comply with the requirements of 3.4.3 during this test.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

4.5.1.4 Proof load test. The tiedown shall be securely attached, by means of the two swivel hooks, to a Government-approved test fixture with the ratchet spool slots perpendicular to the direction of the applied load and with a minimum of 1 1/2 wraps of webbing around the ratchet spool. Adjust the tiedown and the test fixture so that the hook-to-hook distance is a minimum of 36 inches. Place the ratchet handle in the closed position and gradually apply tension to the tiedown, at a rate not exceeding 1.5 inches/minute, until a minimum load of 5,000 pounds is obtained. Hold this load for a minimum period of 30 seconds. Release the load, rotate the ratchet spool 180°, and repeat the load test. The tiedown shall comply with the requirements of 3.4.4 during this test.

4.5.1.5 Ultimate load test. The tiedown shall be securely attached, by means of the two swivel hooks, to a Government-approved test fixture with the ratchet spool slots perpendicular to the direction of the applied load and with a minimum of 1 1/2 wraps of webbing around the ratchet spool. Adjust the tiedown and the test fixtures so that the hook-to-hook distance is a minimum of 36 inches. Place the ratchet handle in the closed position and gradually apply tension to the tiedown, at a rate not exceeding 1.5 inches/minute, until a minimum load of 7,000 pounds is obtained. Hold this load for a minimum period of 30 seconds. The tiedown shall comply with the requirements of 3.4.5 during this test.

4.5.1.6 Ratchet load test. The two swivel hooks shall be removed from the strap assembly. The tiedown shall be securely attached to a Government-approved test fixture by means of the loops in the webbing where the swivel hooks were removed. The ratchet spool slots shall be perpendicular to the applied load. The tiedown may be any convenient length for the performance of this test. Place the ratchet handle in the closed position and gradually apply tension to the tiedown, at a rate not exceeding 1.5 inches/minute, until failure occurs. The tiedown shall comply with the requirements of 3.4.6 during this test.

4.5.1.7 Stitching pattern load test. The fixed-end (short) webbing shall be removed from a tiedown by removing the structural pins/bolts from the ratchet and from the hook. This test webbing shall be securely attached to a Government-approved test fixture by means of the loops in the webbing. Gradually apply tension to the test strap, at a rate not exceeding 1.5 inches/minute, until failure occurs. The test length of webbing shall comply with the requirements of 3.4.7 during this test.



Source: https://assist.dla.mil -- Downloaded: 202610-23T03:07Z
Check the source to verify that this is the current version before use.

4.5.1.8 Ratchet handle load test. The ratchet, removed from a tiedown for the stitching pattern load test (see 4.5.1.7), shall be used for this test. The ratchet, in the closed position, shall be securely attached to a Government-approved test fixture with the handle in the upper position. The load shall be applied perpendicular to the handle and to the round structural pin/bolt (in the lower part of the ratchet). A steel plate shall be inserted into the ratchet spool slot so that it will jam against the lower part of the ratchet and prevent the spool from turning. Gradually apply tension to the structural pin/bolt and the handle, at a rate not exceeding 1.5 inches/minute, until a minimum load of 300 pounds is obtained. Hold this load for a minimum period of 30 seconds. Release the load and inspect the handle as specified in 3.4.8. Return the ratchet to the test fixture and reapply the load, at the previous rate, until failure occurs. The ratchet shall comply with the requirements of 3.4.8 during this test.

## 5. PACKAGING

5.1 Preservation, packaging, packing, and marking. The box assembly shall be preserved, packaged, packed, and marked in accordance with P9392419 or as specified in the contract or purchase order.

## 6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The tiedown covered by this specification are intended for use in securing weapon containers during transportation modes.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Type of tiedown being procured, part number and nomenclature.

c. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1).

d. Requirements for submission of first article sample (see 3.3).

e. National stock number: 5340-01-204-3009.



Source: https://assist.dla.mil -- Downloaded: 202610-23T03:07Z
Check the source to verify that this is the current version before use.

6.3 Objective evidence.

6.3.1 General. Contractors inspection records and documents verifying compliance with applicable dwg. and specification requirements.

6.3.2 Materials. A statement (certification), supported by test data, that all materials produced or purchased by the contractor meets all requirements when such material is controlled by Government or commercial specification referenced in contractual documents.

6.4 Acceptance inspection equipment. The contractor shall obtain approval of equipment designs, operating instructions, and calibration procedures from Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: SMCAR-QAN-I, Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract.

6.5 Subject term (key word) listing.

| | |
|---|---|
| Load test | Stitching pattern |
| Ratchet | Locking latch |

6.6 Submission of alternative quality conformance provisions. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor for evaluation by the technical activity responsible for the preparation of this specification.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 5340-A051)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.

# STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1 The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given

2 The submitter of this form must complete blocks 4, 5, 6, and 7.

3 The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

| I RECOMMEND A CHANGE: | 1 DOCUMENT NUMBER<br>MIL-T-63960 (AR) | 2 DOCUMENT DATE (YYMMDD)<br>24 April 1992 |
|---|---|---|

3 DOCUMENT TITLE

TIEDOWN, WEB, SPECIAL PURPOSE

4 NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible Attach extra sheets if needed )

5 REASON FOR RECOMMENDATION

6 SUBMITTER

| a NAME (Last First Middle Initial) | b ORGANIZATION | |
|---|---|---|
| c ADDRESS (Include Zip Code) | d TELEPHONE (Include Area Code)<br>(1) Commercial<br>(2) AUTOVON (If applicable) | 7 DATE SUBMITTED (YYMMDD) |

8 PREPARING ACTIVITY

| a NAME<br>US ARMY ARDEC<br>STANDARDIZATION OFFICE | b TELEPHONE (Include Area Code)<br>(1) Commercial: (201) 724-6662<br>(2) AUTOVON: 880-6662 |
|---|---|
| ADDRESS (Include Zip Code)<br>ATTN: SMCAR-BAC-S<br>PICATINNY ARSENAL,NJ 07806-5000 | IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT<br>Defense Quality and Standardization Office<br>5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466<br>Telephone (703) 756-2340 AUTOVON 289-2340 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:07Z
Check the source to verify that this is the current version before use.