INCH-POUND

MIL-T- 87995 (84)
12 February 1990

MILITARY SPECIFICATION

TRAILER, RAPID RUNWAY REPAIR

This specification is approved for use within WR-ALC
Department of the Air Force, and is available
for use by all Departments and Agencies of the
Department of Defense.

1. SCOPE.

1.1 Scope. This specification covers a 10,000 pound capacity trailer van used to carry tools and equipment which would support a Rapid Runway Repair (RRR) team. The trailer shall be equipped with a dual axle suspension system and a parking brake. Trailers procured under this specification are commercial items which shall be warranted by the manufacturer as specified in procurement documents.

2. APPLICABLE DOCUMENTS.

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

Federal

ZZ-T-381	Tires, Pneumatic, Vehicular (Highway)

Military

MIL-P-23377	Primer Coating, Epoxy-Polyamide, Chemical and Solvent Resistant
MIL-C-46168	Coating, Aliphatic Polyurethane, Chemical Agent Resistant
MIL-C-53039	Coating, Aliphatic Polyurethane Single Component, Chemical Agent Resistant

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: WR-ALC/MMVRS, Robins AFB, GA 31098-5609 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 2330

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

STANDARDS

Federal

FED-STD-297D	Rustproofing of Commercial Vehicles
FED-STD-595	Colors

Military

MIL-STD-130	Identification Marking of US Military Property
MIL-STD-808	Finishes, Materials and Processes for Corrosion Prevention and Control in Support Equipment
MIL-STD-889	Dissimilar Metals
MIL-STD-1223	Nontactical Wheeled Vehicles Treatment, Painting, Identification Marking and Data Standards
MIL-STD-1595	Qualification of Aircraft, Missile and Aerospace Fusion Welders
MS 51336	Lunette - Coupler, Drawbar Ring
MS 52125	Composite light, tail
USAF 8838302	Fastener Quality Assurance Requirements for WR-ALC/MMV Vehicle and Support Equipment

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099).

2.2 Non-Government publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

American Society of Mechanical Engineers (ASME)

Welding Qualifications

(Application for copies should be addressed to American Society of Mechanical Engineers, United Engineering Center, 345 East 47th Street, New York NY 10017)

American Welding Society (AWS)

Standard D1.1	Standard Qualification Procedure of the American Welding
Standard B2.1	Standard for Welding Procedure and Performance Qualifications

(Application for copies should be addressed to American Welding Society, 2501 NW 7th Street, Miami FL 33125.)

Department of Transportation (DOT)

Federal Motor Carrier Safety Regulations (FMCSR)
Federal Motor Vehicle Safety Standards (FMVSS)

(Application for copies should be addressed to the Department of Transportation, Federal Highway Administration, Washington DC 20591.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

Society of Automotive Engineers, Incorporated (SAE)

J534	Lubrication Fittings
J560	Seven Conductor Electrical Connector for Truck Trailer Combinations
J588	Turn Signal Lamps
J695	Turning Ability and Off Tracking
J702	Brake and Electrical Connections – Truck/Trailer
J1292	Automobile, Truck, Truck-Tractor, Trailer Wiring

(Application for copies should be addressed to Society of Automotive Engineers, Incorporated, 400 Commonwealth Drive, Warrendale PA 15096.)

Tire and Rim Association

Yearbook

(Application for copies should be addressed to Tire and Rim Association, Incorporated, 3200 West Market Street, Akron OH 44313.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informal services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the release cited herein, the text of this specification shall take precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS.

3.1 Standard vehicle and accessories. Except as specified herein, vehicles, components, assemblies and accessories to be delivered under the contract shall be the manufacturer's standard or optional items which meet or exceed the requirements of this specification. All vehicle items shall be as represented and rated in the vehicle and equipment manufacturer's technical data. Technical data shall be limited to specifications and technical material, identical to that furnished to the authorized company representatives for selection of vehicle models and components and shall be on file in the engineering offices of the procuring activity prior to delivery of the items. Vehicles and furnished accessories shall comply with all Federal Motor Vehicles Safety Standards in effect on the date of manufacture.

3.1.1 Special requirements. In addition to the standard trailer specified in 3.1, the vehicle shall be furnished with special equipment as specified herein.

3.1.1.1 Finish and protective treatment.

3.1.1.1.1 Cleaning, painting, plating, anodic films and chemical treatment. Cleaning, painting, plating, anodic films and chemical treatment shall be in accordance with MIL-STD-808. Unless otherwise approved by the procuring activity, primer shall be in accordance with MIL-P-23377.

3.1.1.1.2 Forest Green. Unless otherwise specified (see 6.2), the exterior and interior surfaces of the vehicle shall be painted with polyurethane paint in accordance with MIL-C-46168 and MIL-C-53039, Forest Green, Color Number 24052 of FED-STD-595. All exterior trim items (such as wheels, wheel covers, running boards, door handles and drip rails) shall be the same color as the exterior finish of the vehicle.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

3.1.1.1.3 Desert Sand. When specified (see 6.2), the outer surface of the vehicle and the interior surfaces of compartments shall be painted with polyurethane paint in accordance with MIL-C-46168 or MIL-C-53039, Desert Sand, Color Number 30313 of FED-STD-595. All exterior trim items (such as wheels, wheel covers, drip rails, bumpers, door handles, and light trim rings) shall be painted with the same paint as the exterior of the vehicle.

3.1.1.1.4 Marking. Unless otherwise specified, marking for vehicles painted Forest Green, shall be applied with black paint, Color Number 37038 of FED-STD-595 and markings for vehicles painted Desert Sand shall be applied with white paint, Color Number 37875 of FED-STD-595.

3.1.1.2 Identification. An identification plate, permanently marked in accordance with MIL-STD-130, shall be securely attached to the vehicle in a readily accessible location. The identification plate shall contain the following information:

NOMENCLATURE

MANUFACTURER'S MODEL NUMBER

MANUFACTURER'S SERIAL NUMBER

MANUFACTURER'S NAME

MANUFACTURER'S ADDRESS

MANUFACTURER'S SERVICE PHONE NUMBER

DATE OF MANUFACTURE

CONTRACT NUMBER

NATIONAL STOCK NUMBER

3.1.1.3 Wood treatment. Wood shall be treated in accordance with MIL-STD-1223.

3.1.1.4 Protective treatment. When materials that are subject to deterioration when exposed to climatic and environmental conditions likely to occur during service usage are used, they shall be protected against such deterioration in a manner that shall in no way prevent compliance with the performance requirements of this specification. Protective coatings that will chip, crack or scale with age or extremes of climatic conditions shall not be used.

3.1.1.5 Rustproofing. When specified (see 6.2), the vehicle shall be rustproofed in accordance with FED-STD-297. When specified (see 6.2), tropical rustproofing in accordance with FED-STD-297 shall be furnished.

3.1.1.6 Dissimilar metals. Unless protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-STD-889.

3.2 Design and construction.

3.2.1 Materials. Materials shall be as specified herein. Materials not specifically covered by this specification or referenced specifications shall be suitable in every respect for this type of equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

3.2.2 Recycled materials. All materials, equipment and articles incorporated in the work covered by this specification shall be new and fabricated using materials produced from recovered materials to the maximum extent possible without jeopardizing the intended use. The term "recovered materials" means materials which have been collected or recovered from solid waste and reprocessed to become a source of raw materials, as opposed to virgin raw materials. None of the above shall be interpreted to mean that the use of used or rebuilt products is allowed under this specification.

3.2.3 Construction. The vehicle shall be constructed so that parts shall not work loose in service and shall withstand the loads, shocks, vibrations and other conditions incident to operation, shipping and storage with minimum loss of time for maintenance, repair and servicing. The design of the vehicle shall ensure safe, efficient and economical operation. All assemblies, controls and installed equipment shall be located so there will be no adverse interference with each other or with operations and shall be readily accessible for maintenance, operation, removal and replacement.

3.2.4 Design. The structure, including drawbar, chassis, decking, axles and tires, shall be designed to provide, on yield strength, a static safety factor of three to one or dynamic safety factor of two to one, whichever is greater, while accomplishing any of the performance requirements described herein.

3.2.5 Stress analysis. Stress analysis for the trailer, loaded as specified in 3.3.2 shall be furnished. The stress analysis shall include shear and moment diagrams and deflection calculations. The weight of the floor, crossmembers and outside frame members imposed on the main frame shall be included in the total load.

3.2.6 Waterproofness. The vehicle shall be leakproof to preclude entrance of water when exposed to a spray of 25 pounds per square inch (psi) located two feet from the vehicle for at least 15 minutes. The spray shall be projected on all sides of the vehicle.

3.2.7 Maintainability. The vehicle shall be designed and constructed to provide the following:

a. A minimum number of parts consistent with the performance required herein.
b. Parts and components that are located or positioned for ease of inspection and recognition of excessive wear or potential failure.
c. Ease of adjusting, servicing and replacing parts and components.
d. Use of readily available standard tools and equipment for maintenance.
e. Maintenance with a minimum number of tools.

3.2.8 Fastening devices. All screws, bolts, nuts, pins and other fastening devices shall be properly designed, manufactured and installed with adequate means of preventing loss of torque or adjustment. Cotter pins or lock washers shall not be used on the frame assembly. All threaded steel fasteners of at least Grade 5 as well as any special threaded steel fasteners of a unique contractor design shall be verified as conforming to Air Force drawing 8838302.

3.2.9 Servicing provisions. Drains, grease fittings, lines and check points for all components shall be located so they are readily accessible and do not require special tools for proper servicing.

3.2.10 Lubrication. All parts normally requiring grease for lubrication shall be provided with lubrication fittings conforming to SAE J534. Where the use of high lubricating pressures may damage grease seals, a pressure relief device shall be provided. Extended fittings shall be provided to lubricate parts or assemblies which are not readily accessible for direct lubrication or which are likely to be overlooked because of inaccessibility.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

3.2.11 Protective features. All space in which work is performed during operation, service and maintenance of the unit shall be free of hazardous protrusions, sharp edges or other features which may cause injury to personnel. All parts subject to high operational temperatures or to being electrically energized, that are of such nature or so located as to be hazardous to operating personnel, shall be guarded or insulated to the extent necessary to eliminate the hazard.

3.2.12 Component protection. All electrical lines shall be securely clipped to the frame or the body structure and except where a through frame connector is necessary, shall be furnished with metal protective looms or grommets at each point where they pass through a panel or structural member.

3.3 Weights and dimensions.

3.3.1 Net weight. The net weight of the fully equipped trailer shall be the minimum practicable for the service intended.

3.3.2 Rated payload capacity. The rated payload capacity shall be not less than 10,000 pounds.

3.3.3 Weight distribution. The weight distribution of the unloaded unit shall not be unbalanced or improperly distributed. The weight difference between the right and left wheels shall not be greater than 2.5 percent of the total weight on the axle.

3.3.4 Dimensions and clearances. The trailer, uncoupled from the towing vehicle, shall conform to the dimensions specified in Table I.

TABLE I
DIMENSIONS AND CLEARANCES (INCHES)

DIMENSIONS	INCHES
Overall Length	197
Overall Width	96
Overall Height (Ground to Top)	124
Deck Height	36
Ground Clearance	14

Length dimension excludes the towbar. All tolerances shall be plus or minus one inch.

3.4 Performance.

3.4.1 Operation. The vehicle shall be capable of transporting a rated payload of 10,000 pounds of cargo over improved roads at sustained speeds at 45 miles per hour (MPH) and unimproved roads at sustained speeds of up to 25 MPH while being towed by a commercial type truck or military designed vehicle.

3.4.2 Trailing ability. When coupled to the towing vehicle operating in its minimum turning circle, the trailer shall follow without cramping. Tracking ability shall be in accordance with FMCSR 393.52(A).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

3.4.3 Turning ability. Trailers shall be capable of performing the following operations:

a. The inside turning angle in both left and right directions shall be no less than 40 degrees. Means shall be provided to prevent turning force from damaging the steering mechanism after the maximum turning angle has been reached.
b. With the trailer undercarriage (tow hitch) in line with the remainder of the trailer, the trailer shall be capable of moving through an angle of not less than 55° with the coupled towing vehicle without upsetting and without interference between the trailer and the towing vehicle. This angle shall be measured at the lunette and shall be the angle between the longitudinal axis of the trailer and the longitudinal axis of the towing vehicle. The ability of the trailer to meet the requirement shall be demonstrated actually or graphically with a 96 inch wide towing vehicle having the center of its pintle located at the extreme rear of the towing vehicle.

3.4.4 Parking brakes. The hand parking (mechanical) brakes shall hold the fully loaded trailer (see 3.3.2) on a dry hard surfaced road on a grade of not less than 20 percent, with the trailer uncoupled from the towing vehicle and headed both up and down the incline. Mounting of the parking brake shall be at an easily accessible location on the front of the trailer.

3.4.5 Ratings. Vehicle ratings shall be the manufacturer's published ratings. Component and vehicular ratings shall not be raised to meet the requirements of this specification. When published ratings are not available, verification of ratings must be submitted to the engineering office of the procuring activity.

3.5 Design requirements.

3.5.1 Chassis components. The vehicle shall be a four wheel, van style, full trailer. The trailer shall be furnished with all accessories, components, parts and assemblies to provide a complete vehicle.

3.5.2 Towing hitch. The trailer shall be equipped with Ackerman steering as defined in SAE J695. The steering motion will be activated by the motion of the tow pintle as it follows the path of the towing vehicle. The trailer chassis shall be equipped with a towbar designed for towing by vehicles having a pintle height of 22 inches to 40 inches. The towbar shall be equipped with a lunette conforming to MS51336. The towbar shall be hinged and provided with a convenient and positive hold in the up (vertical) position that works at all turning angles of the front wheels. The towbar shall be capable of being removed for shipment.

3.5.3 Underbody. The underbody load carrying longitudinal members shall be one piece, without splices. The trailer shall be mounted on a double axle chassis. The location of the axles shall be such to provide stability for stand alone operations without the need for external attachments such as landing gear or leveling jacks. All trailer chassis components, including frame, axles, springs and bearings shall be designed and constructed to withstand the forces imposed on the fully loaded vehicle operating under conditions in an on/off road environment at speed specified by paragraph 3.4.1.

3.5.4 Flooring. A full length single level floor shall be provided. The floor support members shall be primed (see 3.1.1.6) and painted to preclude galvanic or electrolytic action. The hardwood flooring, treated in accordance MIL-STD-1223, shall be not less than 1 1/4 inch thick and lengths of not less than six feet. Flooring shall be secured with zinc plated screws or bolts. Not less than two securing screws or bolts shall be installed at each cross sill and not less than two on each side of each butt joint. Countersunk screws on bolt leads shall be not less than 1/8 inch and not greater than 1/4 inch below the top of the wood surface. Butt joints shall be centered on crossmembers and staggered. Rails for attaching loading ramps will be provided at the bottom rear of the platform. The rails or pockets will be used to stow the loading ramp while not in use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

3.5.5 Body construction. Body construction shall be of a trussed or monocoque type design. The longitudinal upper rails at the roof level shall be continuous, without splices, extending the full length between the front and rear walls of the vehicle and designed for attachment of full width roof bows, located on not more than 12 inch centers. All vertical structural members shall be one piece without splice. The corner posts shall be such as to present nominal square, rounded or chamfered corners on the vehicle. The contact face on noncompatible metals shall be protected from corrosion (see 3.1.1.6). Doors, body, roof and panel joints shall be watertight and leakproof. All doors, windows and other cutouts shall be reinforced.

3.5.6 Trussed body. Trussed body framing structure shall include at least the following:

a. Vertical members, consisting of corner and intermediate posts, shall be inserted between the roof structure and the chassis frame and employed to combine the roof structure to the chassis frame.
b. The corner and intermediate posts shall be continuous without splice between the roof structure and chassis frame except at door opening areas and shall be spaced on not more than 12 inch centers, except different intervals shall be permitted at door opening regions.
c. The vertical posts may be used to add to the rigidity of the truss.

3.5.7 Monocoque or semi-monocoque body. The stressed skin monocoque or semi-monocoque body unitized structure shall be constructed to preclude buckling of the skin sheets when the vehicle is operating under the intended service.

3.5.8 Body attachments. Body attachments shall be fastened together in a manner which shall preclude loosening of bolts, screws and rivets, as well as cracking of welded joints when the vehicle is properly maintained and operated under the intended service conditions. Fasteners shall be compatible to the metal being secured. Self tapping screws shall not be used in areas subjected to stress, and wood shall not be utilized for structural framing.

3.5.9 Body roof panels. Body roof panels shall be stretcher leveled and secured to the roof bows to preclude panel vibration. The roof shall be capable of withstanding a static load of 30 pounds per square foot. The roof shall be crowned to permit drainage and shall be provided with drip molding or rain gutters over the doors.

3.5.10 Double rear doors. Double rear doors shall provide full interior width opening for access into the body rear compartment. Interior door opening height shall be not less than 72 inches. The doors shall be hung between box posts with not less than three heavy duty strap hinges on each door. Doors shall be hung to permit folding back against body sides. Means shall be provided to retain doors in a fully opened position. The door clearance shall not exceed 3/8 inch. A center door post shall not be acceptable.

3.5.11 Rear door hardware. Each door shall lock independently of each other in the closed position. The curbside rear door shall be designed to open from inside or outside the vehicle. Each door shall be provided with cam type locks with top and bottom vertical drawbolts. The curbside rear door shall be provided with interior and exterior handles enabling the closing and opening of the doors from inside and outside the vehicle with arctic gloves and shall be operable in a -50° F ambient air temperature. Rear service doors shall be capable of being locked from the exterior with a key. Locking mechanism shall have an internal safety release handle to enable doors to be unlocked from the inside of the van when locked from the outside.

3.5.12 Door gaskets. Doors shall be provided with weatherproof, nonabsorbent, light tight, rubber sealing gaskets. Gaskets shall be fitted around the door openings and between the doors. Gaskets shall have appropriate flexural and compressibility characteristics and shall not absorb moisture. When doors are closed, light, wind or rain shall not penetrate. Gaskets shall withstand an ambient air temperature range of -50°F to +160°F.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

3.5.13 Loading ramp. The trailer shall be equipped two loading ramps. The ramps shall slide under the deck when not in use. The ramps shall be 36 inches wide and 108 inches long, and they shall be capable of supporting a 500 pound load without any evidence of deformation. The ramps shall be capable of being attached to the rear of the trailer, side by side, to form a 72 inch unobstructed loading ramp, or one ramp may be placed in the center of the rear opening to provide a 36 inch loading ramp. Ramps shall be of all steel or aluminum construction and shall be provided with a means of being locked in position when in use, or when in storage under the trailer. Tolerances shall not be greater than 1/8 inch joining the trailer and loading ramp while in use.

3.5.14 Safety chains. Safety chains shall be provided. Two chains with eyes shall be furnished. Chains shall conform to Federal Motor Carrier Safety Regulation 393.70(d).

3.5.15 Axles and suspension. The axle and suspension system shall be of rated capacity at least equal to the load imposed at the ground when the trailer is loaded with rated payload (see 3.3.2). The axles shall be sturdy construction and capable of sustaining the gross load without evidence of overloading.

3.5.16 Wheels, rims, tires and tubes.

3.5.16.1 Wheels and rims. The vehicle shall be equipped with dual wheels on the front and rear of the trailer. Except as specified herein, rims and tire ratings shall conform to Tire and Rim Association recommendations for the type and size of tires furnished. Tire size and load range (ply rating) shall be the same for all tires on each vehicle. Wheels shall be interchangeable without the use of an adapter. When specified (see 6.2), disc type wheels shall be furnished.

3.5.16.2 Tires. Tires shall be tube or tubeless type with highway tread. Tires shall be the steel belted radial or, when specified (see 6.2), bias ply. Tires shall be of rated capacity at least equal to the load imposed on each tire, measured at the wheel at the ground, with the vehicle loaded to specified GVW. Tires shall conform to Tire and Rim Association recommendations or to ZZ-T-381 with a size designation system the same as the Tire and Rim Association.

3.5.16.3 Inner tubes. When tube type tires are furnished, inner tubes shall be heavy duty type and shall be of proper size for tires furnished. Tire flaps shall be provided for tube type tires in accordance with Tire and Rim Association recommendations.

3.5.16.4 Carrier for spare tire assembly. Unless otherwise specified (see 6.2), a carrier for a rim and tire assembly shall be installed in a readily accessible location. Threaded fasteners, when used to secure the spare tire in the carrier, shall be constructed of, or plated with, corrosion resistant material. The spare tire shall be mounted at the front exterior wall of the trailer. It shall be centered so no interference exists between the tire and folded "A" frame hitch.

3.5.16.5 Parking brakes. Manually applied parking brakes shall be furnished and shall conform to FMCSR 393.41. Parking brakes shall be of the internal expanding type. Parking brake lever shall have sufficient moment arm to require not more than 30 pounds of effort for application and release. Provisions shall be made for slack adjustment.

3.6 Electrical system.

3.6.1 Lighting. All lights and reflectors shall be protected from operational hazards by mounting in recessed or otherwise guarded locations. Lights and reflectors shall not be mounted on vertical surfaces of the rub rail (unless recessed and fully protected) or on the semitrailer bumper. Turn signal lamps shall conform to SAE J588. All electrical wiring shall conform to SAE J1292. Clearance and identification lamps shall be constructed for easy removal and replacement of lamps and lenses without the use of hand tools. When specified (see 6.2), the trailer shall be equipped with two composite blackout lights as specified in MS52125-1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

3.6.2 Twelve volt direct current (DC) system. A 12 volt DC lighting system conforming to 3.6.1 and 3.6.3 shall be provided. The 12 volt DC lighting system shall conform to FMCSR 393.14, 393.20, 393.22, 393.23, 393.25 through 393.29, 393.32, and 393.33.

3.6.3 Receptacle for 12 volt DC system. The front of the trailer shall be equipped with a seven contact receptacle conforming to SAE J560 with the connectors connected and color coded as specified therein. The receptacle shall be provided with a spring loaded cover. The receptacle shall be located in accordance with SAE J702. The plugs shall be of sufficient length to connect the trailer to the towing vehicle and to allow adequate clearance for turning. Provisions shall be made to secure the cable when not in use to the drawbar or trailer body.

3.6.4 One hundred twenty volt alternating current (AC) lighting system. A 120 volt, 60 cycle, AC lighting system shall be provided. The lighting system shall be sufficient to provide full illumination for personnel working inside the trailer. The lighting system shall be powered by an external source. The lighting system shall be equipped with an equipment base receptacle, NSN 5935-00-660-5207, located at the rear exterior of the trailer. The receptacle shall be recessed and shall be provided with a spring loaded cover. A circuit breaker shall be provided at the rear of the left interior wall.

3.6.5 Reflectors. Trailers shall be provided with reflectors in accordance with FMCSR 393.14 and 393.26. Reflectors shall not be mounted on the vehicle bumper.

3.7 Servicing and adjusting. Prior to acceptance of the trailer by the Government inspector, the contractor shall service and adjust the trailer for immediate operational use. The servicing and adjusting shall include, but not be limited to, the following:

a. Inflation of all tires.
b. Adjustment of brakes.
c. Proper functioning of all lighting.
d. Complete lubrication with grades of lubricants recommended for ambient temperature at the delivery point. The trailer shall be conspicuously tagged to identify the lubricants and their temperature range.

3.8 Bolted and riveted connections. Bolt and rivet holes shall be accurately punched or drilled and shall have the burrs removed. Washers shall be provided in accordance with good commercial practice, and all bolts, nuts and screws shall be tight. Rivet heads shall be full, neatly made, concentric with the rivet holes and in full contact with the surface of the member.

3.9 Welding. Welding shall conform to procedures prescribed by the American Welding Society. The surface of parts to be welded shall be free from rust, scale, paint, grease, or foreign matter. Welding rods shall be compatible with the metal being welded. Spot, tack, or intermittent welds shall not be used where structural strength is required. Weld penetration shall provide transference of maximum design when necessary to reduce stress concentrations.

3.10 Welders. Before assigning any welder to manual welding work covered by this specification, the contractor shall obtain certification that the welder has passed qualification tests as prescribed in accordance with MIL-STD-1595A or prescribed by either AWS D1.1 and AWS B2.1, or ASME Welding Qualifications. Certification shall be made available for review by the contracting officer or designated representative. Contractors who make only horizontal welds need not qualify welders for "all position welding". The contractor shall be responsible for determining that automatic welding equipment operators are capable of producing quality welds in accordance with AWS and ASME codes.

3.11 First Article. A first article sample shall be subjected to first article inspection (see 6.4) in accordance with 4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

3.12 Workmanship. Defective components or parts and assemblies which have been repaired or modified to overcome deficiencies shall not be furnished. Welded, bolted, and riveted construction utilized shall be in accordance with the best commercial practice.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract, or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Government verification. Quality assurance operations performed by the contractor will be subject to Government verification at unscheduled intervals. Verification will consist of observation of the operations to determine that practices, methods and procedures of the contractor's inspection are being properly applied. Failure of the contractor to promptly correct product deficiencies within 60 days discovered shall be cause for suspension of acceptance until correction has been made or until conformance of product to specification criteria has been demonstrated.

4.3 First article test sample. The first article test sample shall be identical to the items procured under the terms of the contract. Approval of the first article test report shall not constitute a waiver by the government of its rights under the provisions of the contract.

4.3.1 Test Report. The following shall be incorporated as a part of the test report:

a. All data collected, failures, maintenance performed, and other events recorded shall be identified by accumulated operation time, miles, cycles, or position in the test procedure, as appropriate. Test conditions at the time of failures or irregular operations identified shall be recorded.
b. Summary of the engineering reasoning and of any tests conducted to determine assignable causes for all failures and irregular operations identified.
c. Summary of the engineering reasoning behind any corrections made, to be made or proposed to be made and the predicted effectiveness of those corrections.
d. Test activity and/or contractor comments on the item features or requirements that , if modified, should improve the item.
e. Test activity and/or contractor comments on field conditions or operating procedures to be avoided or cultivated to increase the reliability and useful life of the item.
f. List of all cleaning and finishing procedures to be used in accordance with MIL-STD-808.
g. List of methods to be used to protect against electrolytic corrosion of dissimilar metals in intimate contact in accordance with MIL-STD-889.
h. List of special tools and diagnostic equipment necessary to perform field level maintenance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

4.3.2 Test rejection criteria. Throughout all tests specified herein, the vehicle shall be closely observed for the following conditions, which shall be cause for rejection:

a. Failure to conform to design or performance requirements specified herein.
b. Spillage or leakage of any fluid, including lubricant, or hydraulic fluid, under any operating condition.
c. Structural failure of any component, including permanent deformation, or evidence of impending failure.
d. Interference between vehicle components or between the vehicle, the ground, and all required obstacles, with the exception of normal contact by the tires.
e. Misalignment of components.
f. Evidence of undesirable roadability characteristics, including instability in handling during cornering, braking, and while traversing rough terrain.
g. Conditions which present a safety hazard to personnel during operation, service, or maintenance.

4.3.3 First article tests. The first article tests shall consist of all tests listed under 4.4.

4.4 Examination of product. The vehicle shall be inspected to determine compliance with the requirements specified herein. Particular attention shall be given to materials, workmanship, dimensions, surface finishes, protective coatings and their application, welding and riveting, and markings. This examination shall be accomplished by use of a checklist which lists each requirement not validated by a test and the results of the examination.

4.4.1 Weight and payload capacity. The first article vehicle shall be weighed to determine the curb weight and distribution of the curb weight on the axles. The weight distribution shall be computed using the curb weight and payload as specified. Calculated imposed loads on the axle shall be utilized to ascertain that the tires, suspension and axle are of adequate capacity to meet contractual requirements.

4.4.2 Road test. The first article vehicle shall be examined and road tested less payload by the contractor to assure that the vehicle shall operate in accordance with contractual requirements. The road test shall be conducted by the contractor, at the contractor's site and under the direction and surveillance of Government representatives. The vehicle shall be towed for a minimum distance of 250 miles. The speed and distance shall consist of 100 miles on dry level smooth prepared hard surfaced roads at sustained speeds up to 50 MPH, 100 miles on gravel roads with sharp turns at speed up to 25 MPH, and 50 miles off road at speeds up to 15 MPH. The course shall be arranged so as to return the vehicle to the manufacturer's plant at the completion of each day of road testing for reinspection and servicing. All mileage accumulated and all service or maintenance performed during the road test shall be recorded and copies shall be furnished to the Government representatives. Upon completion of the road test, all equipment shall be thoroughly examined and inspected. The equipment shall show no evidence of damage. During the road test, tracking ability shall be verified as specified by 3.4.2.

4.4.3 Water spray test. The first article vehicle shall be water spray tested after the road test. All production trailers shall also be subjected to a water spray test and shall be free of leakage after exposure to a 100 percent water spray for not less than 15 minutes. Test may be conducted in sections. The spray shall be delivered by nozzles operating at not less than 25 psi water pressure, sufficient in number and so placed (approximately two feet from body) to afford full coverage of the sides, roof, front, rear and undercarriage of the body. During test, doors shall be closed as in normal travel position.

4.4.4 Brake test. The first article shall be tested to establish its conformance with paragraph 3.4.4.

4.4.5 Turning ability test. The first article shall be tested to verify its turning ability is in conformance with paragraph 3.4.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

4.4.6 Wood treatment certification. Manufacturer's records, acceptable to the Government, shall be furnished to verify that all wood requiring treatment in accordance with MIL-STD-1223 has been treated.

4.4.7 First article sample. Upon acceptance of the first article sample it shall be restored to a like new condition. It shall remain at the manufacturing facility as a production sample and be the last vehicle shipped on the contract.

4.5 Inspection of production trailer. The contractor's inspection system shall as a minimum assure that the trailer conforms to the physical and dimensional requirements and is capable of meeting the performance requirements contained herein.

4.6 Inspection of the preparation for delivery. Vehicle preparation for delivery shall be inspected to verify conformance to requirements specified in 5.1.

5. PACKAGING

5.1 Vehicle processing. Semitrailer shall be processed for shipment from the manufacturer's plant to initial receiving activity in accordance with the manufacturer's standard commercial practice.

6. NOTES

(This section contains information of a general or Explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The vehicle covered by this specification is intended for use by the Government for transporting equipment for Rapid Runway Repair teams.

6.2 Ordering data. Procurement documents shall specify the following:

a. Title, number and date of this specification.
b. Rustproofing required (see 3.1.1.5).
c. Disc type wheel (see 3.5.16.1).
d. Tire type specified (see 3.5.16.2).
e. Tire carrier required (see 3.5.16.4).
f. Blackout lights required (see 3.6.1).
g. Finish color required, if not Forest Green, Color Number 24052 of FED-STD-595 (see 3.1.1.1.2).

6.3 Data requirements. The following Data Item Descriptions (DID's) must be listed, as applicable, on the Contract Data Requirements List (DD Form 1423) when this specification is applied on a contract, in order to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference Paragraph	DID Number	DID Title	Suggested Tailoring
4.3.1	DI-T-4902	First Article Inspection Report	See DD Form 1423

The above DID's were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Form 1423.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

6.4 First Article. The first article test sample shall be identical to the items procured under the terms of the contract. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results and disposition of first articles. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract.

6.5 Subject term (key word) listing.

Ackerman steering
Axles
Lunette

Custodians:
Air Force - 99

Preparing activity:
Air Force - 84

Project No: 2330-F978

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 Alexandria, VA

POSTAGE WILL BE PAID BY

WR-ALC/MMEDTB
Robins AFB, GA 31098-5609

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-87995 (84)	Distributor, Bituminous Material, Tank-Type ~~Truck Mounted~~

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 1426 82 MAR PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T12:29Z
Check the source to verify that this is the current version before use.