R-29-27

FF-I-00535A(GSA-FSS)
AMENDMENT-4
October 12, 1972
SUPERSEDING
AMENDMENT-3
June 15, 1972

AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

INCINERATOR, STATIONARY, CLASSIFIED WASTE (SECURITY)

This amendment was developed by General Services Administration Federal Supply Service, Standardization Division, Washington, DC 20406, based upon currently available technical information. The General Services Administration has authorized this amendment as part of Interim Federal Specification FF-I-00535A(GSA-FSS), dated June 15, 1966.

PAGE 1

Paragraph 1.1: Delete text in its entirety and substitute the following:

"This specification covers emergency use type incinerators which are designed to conform to the standards for security equipment as set forth in the 'National Security Council Directive Governing The Classification, Downgrading, Declassification And Safeguarding Of National Security Information.' The incinerators are intended for use in critical situations where it is essential that classified papers be immediately destroyed. The incinerators are not designed to burn wood, wood products, or refuse. They are not designed for routine, day to day burning operations; such use will result in damage to the incinerators."

Paragraph 2.1: Insert new reference as follows:

Government Specification Drawings:

Drawing Set #354A - Incinerators, Size 1.
Drawing Set #362A - Incinerators, Size 2.

(Copies of specification drawings are available for examination, or will be furnished at a cost of $38.00 per set upon request to the General Services Administration Business Service Center, Region 3, Washington, DC 20407.)

PAGE 2

Paragraph 3.2, line 2: Delete reference "(see 6.2)".

PAGE 3

Paragraph 3.3.1, line 2: Delete reference "(see 6.2)".

Paragraph 3.3.2, line 3: Delete "(see specification drawing No. 254)".

Paragraph 3.3.2, after subparagraph (m): Insert new subparagraph:

"(n) As inner liner support bolts and fly ash basket are drawn-up inner liner should not be raised off of the inner liner base cone assembly."

PAGE 4

Paragraph 3.3.2, line 1: Delete "(see specification drawing No. 362)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

PAGE 5

Paragraph 3.3.2, after subparagraph (r): Insert new subparagraph:

"(s) As inner liner support bolts and fly ash basket are drawn up, inner liner should not be raised off of the bottom plate assembly."

PAGE 6

Paragraph 3.5.2: Delete in its entirety without substitution.

PAGES 7 AND 8

Paragraph 3.12, spare parts list for size 1 and 2 incinerators: Delete and insert new lists:

"For the size 1:

Description	Drawing Number	Required
"V" Band Assembly	354A-110	1
Basket Assembly	517	1
Clamp Band Assembly	217	2
Beveled Basket Mounting Washer	521	8
Door Gasket	347	2
Door Gasket	348	2
Cotter Pin	350	4
Screw	357	24
Flange Gasket	396	45 ft.
Cap Screw	397	24
Sight Glass	398	1
Gasket	399	2
Nut	403	24
Lock Washer	404	24
Flexible Duct	434	1
Duct Flange Gasket	438	1
Nut	447	24
Lockwasher	448	24
Thermocouple Assembly	454	1
Nut	540	16
Basket Installation Tool Kit	520	1

The spare part kit shall also contain one 3-ounce tube of sealing compound conforming to MIL-S-45180 for use in cementing the door gasket to the door assembly."

"For the size 2:

Description	Drawing Number	Required
Basket Assembly	362A-105	1
"V" Band Clamp Assembly	208	1
Basket Support Washer	516	4
Door Gasket	359	2
Door Gasket	360	2
Sight Glass	370	1
Gasket	372	4
Item # 130	000	4
143	000	8
144	000	4
145	000	8
146	000	12 ft.
148	000	4
Thermocouple Assembly	378 & 380	1

The spare part ket shall also contain one, 3-ounce tube of sealing compound conforming to MIL-S-45180, and one, 3-ounce tube of adhesive conforming to MIL-A-1154."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

PAGE 9

Paragraph 4.5.2.1.1: Delete in its entirety and substitute the following:

"4.5.2.1.1 Plenum chamber pressure test. This test shall be made with the incinerator empty. The completely assembled incinerator shall be connected to an appropriate electrical source. The manometer shall be filled with water (with or without dye) and connected by the rubber tubing to the pressuer tap fitting attached to the bottom assembly outer shell. The blower shall be turned on and the damper set to the "Operating" position on the control plate. Under these conditions, the internal air pressure, as indicated on the manometer, shall be between 6.0 and 7.0 inches of water. Any errors or defects stemming from the manufacture and assembly of the incinerator that contribute to internal pressure outside the range of 6.0 to 7.0 inches shall be corrected by the manufacturer. The measurement of plenum chamber pressure shall then be rerun before proceeding with the paper burning test in 4.5.2.1.2."

PAGE 10

Paragraph 4.5.2.2.1: Delete in its entirety and substitute the following:

"4.5.2.2.1 Plenum chamber pressure test. This test shall be made with the incinerator empty. The completely assembled incinerator shall be connected to an appropriate electrical source. A manometer and a length of tubing and a brass fitting shall be provided for measurement of the plenum chamber pressure. The blower shall be turned on and the damper set to the "Operating" position (Number 11 notch is used for 50 cycle operation and Number 5 notch for 60 cycle operation. Under these conditions, the internal air pressure, as indicated by the manometer, shall be between 2.7 and 3.6 inches of water. Any errors or defects stemming from the manufacture and assembly of the incinerator that contribute to internal pressure outside the range of 2.7 and 3.6 inches shall be corrected by the manufacturer. The measurement of the plenum chamber pressure shall then be rerun before proceeding with the paper burning test in 4.5.2.2.2."

PAGES 12 THROUGH 19

Paragraph 6.2: Delete in its entirety without substitution.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.