FF-O-605B
February 16, 1973
SUPERSEDING
Int. Fed. Spec. FF-O-00605A(GSA-FSS)
September 14, 1970

FEDERAL SPECIFICATION

OPENER, CAN, HAND (DISPOSALBLE, COMBINATION OPENER AND PUNCH)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 This specification covers one type of disposable opener, one end of which is used to puncture a hole in a can and the other end to remove bottle caps.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, from a part of this specification to the extent specified herein:

Federal Specifications:

PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Box, Fiberboard.
PPP-B-665 - Boxes, Paperboard, Metal Stayed (Including Stay Material).
PPP-B-676 - Boxes, Setup.

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications and Standards from established distribution points in their agencies.)

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking For Shipment and Storage.

(Copies of Military Specifications and Standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

American Society for Testing and Materials (ASTM) Standard:

E18 - Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials, Test for.

(Application for copies should be addressed to the American Society for Testing and Materials 1916 Race St., Philadelphia, PA 19103.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chiacgo, IL 60606.)

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Association, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Material. Openers shall be manufactured from 1025 carbon steel.

3.2 Design. Openers shall be of the punch type design capable of punching a Vee-shaped opening 3/4 inch plus or minus 1/16 inch on all legs in the tops of steel and aluminum cans. On the opposite end there shall be a bottle opener, capable of opening a compression type bottle cap.

3.2.1 Hanging purposes. The end having the bottle opener shall have a 1/4 inch hole plus or minus 1/16 inch for hanging purposes.

3.2.2 Dimensions. Openers shall have a projected length of 4-1/4 inches plus or minus 1/4 inch; the width shall be 3/4 inch plus or minus 1/32 inch; and the thickness shall be 0.060 inch plus or minus 0.005 inch.

3.3 Hardness. When tested in accordance with 4.4.1, openers shall have a rockwell hardness of C40 to C48.

3.4 Coating. Openers shall have a bright nickel plated finish.

3.5 Workmanship. Openers shall be free of burrs, projections, fins, and except for the punch opener end they shall be free of sharp edges. Surfaces shall be free of loose or flaked plating or any other defect which would impair its serviceability for the purposes intended.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Sampling.

4.2.1 Lot. Unless otherwise specified (see 6.2), a lot shall consist of all openers submitted for inspection at the same time.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

4.2.3 Sampling for test. Samples for test shall be as follows:

Sample Size	Level or Number
Up to 250	2
251-500	S-3
501-1000	S-4

4.3 Inspection.

4.3.1 End item. Openers shall be examined for defects listed in table I. The Acceptable Quanlity Levels (AQL's) for defects listed in table I shall be 2.5 percent defective for major defects and 4.0 percent defective for minor defects.

TABLE I. Classification of defects, end item

Defects	Major	Minor
Dimensions (length, width, thickness not as specified); see 3.2.2.	X	
Bent bodies.	X	
Hole for hanging purposes missing (see 3.2.1).	X	
Hole diameter not correct.		X
Sharp edges, fins, projections, burrs (see 3.5).	X	
Not plated (see 3.4).	X	
Plating flaked (see 3.5).	X	
Damage or defects not affecting function or serviceability.		X

4.3.2 Inspection of preparation for delivery requirements. An inspection shall be made to insure that packaging, packing and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with Table II. For examination of contents the sample unit shall be one shipping container fully prepared for delivery selected just prior to the closing operations. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 4.0 defects per hundred units.

TABLE II. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; or improper size, location, sequence, or method of application.
Materials	Any component missing, or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Bulging or distortion of container.

4.4 Tests.

4.4.1 Hardness. Samples selected in accordance with 4.2.3 shall be tested in accordance with ASTM E18, Part A, and shall conform to hardness requirements of 3.3.

4.4.2 Punching and opening test. Openers selected in accordance with 4.2.3 shall be tested to open steel cans and to remove bottle caps to determine conformance to 3.2.

5. PREPARATION FOR DELIVERY

5.1 Packaging Packaging shall be level A or C, as specified (see 6.2).

5.1.1 Level A. Fifty nested openers shall be packaged in a box conforming to PPP-B-566, PPP-B-665, or PPP-B-676. The box shall be closed in accordance with the applicable box specification or appendix thereto.

5.1.2 Level C. The openers shall be packaged to insure protection during shipment and safe delivery to destination.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. The openers packaged as specified in 5.1 shall be packed in quantities as specified (see 6.2) in a close-fitting box conforming to PPP-B-636, class weather-resistant. The box shall be closed in accordance with the appendix to PPP-B-636.

5.2.2 Level B. Ten unit packages of openers shall be packed in a close fitting box conforming to PPP-B-636, class domestic. The box shall be closed in accordance with the appendix to PPP-B-636.

5.2.3 Level C. The openers packaged as specified in 5.1, shall be packed in containers to assure carrier acceptance and safe arrival at destination in compliance with National Motor Freight Classification or Uniform Freight Classification.

5.3 Marking. In addition to any special marking required by the contract or purchase order, all marking shall be in accordance with 5.3.1 or 5.3.2, as specified (see 6.2).

5.3.1 Civil agencies. All marking shall be in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. All marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Openers are intended to be used as a punch type opener for cans to allow the dispensing of their contents. Openers are also intended to remove bottle caps.

6.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents:

(a) Title, number and date of this specification.
(b) Size of lot, if different from 4.2.1.
(c) Level of packaging and packing required (5.1 and 5.2).
(d) Marking required (5.3).

Preparing activity:

GSA-FSS

Civil Agency Coordinating Activity:

GSA-FSS

Orders for this publication are to be placed with the General Services Administration, acting as an agent for the Superintendent of Documents. See section 2 of this specification to obtain extra copies and other documents referenced herein. Price 10 cents each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.