FF-P-00416F(GSA-FSS)
AMENDMENT-1
June 13, 1984

AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

PIN, SAFETY

This amendment was developed by General Services Administration, Office of Federal Supply and Services, Washington, DC 20406, based upon currently available technical information. The General Services Administration has authorized this amendment as a part of FF-P-00416F(GSA-FSS), dated November 15, 1971.

Page 1

Paragraph 1.2, delete the first two lines and substitute the following:

"1.2 Classification. The safety pins shall be of one type and the following classes, sizes (lengths), and finishes, as specified (see 6.2):"

Paragraph 1.2, under "Size 6", add the following:

"Finish 1 - Standard, as plated or polished metal surface.
Finish 2 - Black, in accordance with MIL-STD-171."

Paragraph 2.1, under "Federal Standards:", delete: "Int. Fed. Test Method Std. No. 00304 - Metals, Chemical Test Methods (For Identification)."

Page 2

Paragraph 2.1, under "Military Standards:", add: "MIL-STD-171 - Finishing of Metal and Wood Surfaces."

Page 3

Paragraphs 3.3 and 3.3.1, delete in their entirety and substitute the following:

"3.3 Finish.

3.3.1 Finish 1 - Standard. Unless another finish is specified, this finish shall be used. All surfaces of the copper zinc alloy safety pins shall be uniformly plated with nickel of a thickness used in standard commercial practices. Corrosion resisting steel pins shall have a No. 2D bright finish, or a No. 4 general purpose polished finish.

3.3.2 Finish 2 - Black. Copper zinc alloy safety pins shall conform to finish 1.4.4 or finish 3.2 of MIL-STD-171. Nickel plated copper zinc alloy pins shall conform to finish 1.4.4 of MIL-STD-171. Corrosion resisting steel pins shall conform to finish 3.3.4 of MIL-STD-171.

FSC 8315

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

3.3.3 Resistance to corrosion (copper zinc alloy pins only). When tested for resistance to corrosion as specified in 4.4.1.2, the total surface of any pins showing corrosion shall not exceed 2 percent."

Add new paragraph 3.7, as follows, at the end of Section 3.

"3.7 Certificates of compliance. A certificate of compliance is required for each shipment to verify that all safety pins are manufactured from nickel-plated copper zinc alloy, or all safety pins are manufactured from corrosion resisting steel. Where certificates of compliance or reports of analysis are submitted, the Government reserves the right to check test such items to determine the validity of the certificate or analysis. Where Government inspection results indicate a certificate is not valid, the Government may refuse to accept any more such certificates, and require a contractor to submit actual inspection (including test) results."

Page 4

Paragraph 4.4.1.2, at the end of the paragraph, delete "(see 3.3.1)" and substitute "(see 3.3.3)."

Paragraphs 4.4.1.3 and 4.4.1.4, delete in their entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.