FF-S-001169 (GSA-FSS)
July 5, 1971

INTERIM FEDERAL SPECIFICATION

SHREDDING MACHINE, OFFICE TYPE, CLASSIFIED WASTEPAPER, SECURITY

This Interim Federal Specification was developed by Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use this document in procurement and forward any recommendations for changes to the preparing activity at the address shown above.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers paper shredding machine which are designed to meet the document destruction criteria for classified information set forth in Executive Order 10501, as amended, "Safeguarding Official Information in the Interest of the Defense of the United States". The machines are intended for use as specified in 6.1.

1.2 Classification. The paper shredding machines under this specification shall be of the following classes and models, as specified (see 6.2).

Class 1 - Cross cut shreds (see 3.5).
Class 2 - Non cross cut shreds (see 3.5).

Model A - Desk type.
Model B - Cabinet type.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issues in effect on the date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

Federal Specifications:

CC-M-636 - Motor, Alternating Current (Fractional Horsepower).
CC-M-641 - Motor, Alternating Current (Integral Horsepower, 200 Hp. and Smaller).
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Nailed and Lock-Corner.
PPP-B-636 - Boxes, Fiberboard.
PPP-B-640 - Boxes, Fiberboard, Corrugated, Triple Wall.
PPP-T- 42- Tape, Pressure-Sensitive Adhesive, (General Packaging Application).

Federal Standard:

Fed. Std. No. 123 - Marking for Domestic Shipment (Civil Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications and Standards and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington, D. C. 20402.

(Single copies of this specification and other Federal Specifications required by activities outside the Federal Government for bidding purposes are available without charge from Business Service Centers at the General Services Administration Regional Offices in Boston, New York, Washington, DC, Atlanta, Chicago, Kansas City, MO, Fort Worth, Denver, San Francisco, Los Angeles, and Seattle, WA. ngton.

(Federal Government activities may obtain copies of Federal Specifications, Standards and Handbooks and the Index of Federal Specifications and Standards from the established distribution points in their agencies.)

Military Specifications:

MIL-P-116 - Preservation, Methods.
MIL-B-121 - Barrier Materials, Greaseproofed, Waterproofed, Flexible.
MIL-P-16298- Preservation, Packaging, Packing and Marking of Electric Machines having Rotating Parts and Asscociate Repair Parts.

FSC 3615

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

Military Standards:

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specification procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Motor Freight Traffic Association, Incorporated, Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the National Motor Freight Traffic Association, Inc., Agent, 1616 P Street, N.W., Washington, D. C. 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Tariff Publishing Officer, Room 202 Union Station, 516 W. Jackson Blvd., Chicago, Illinois 60606.)

3. REQUIREMENTS

3.1 Preproduction sample. Before production is commenced, a sample of the finished commodity shall be submitted or made ready for approval of the contracting officer or his authorized representative for inspection and tests at the manufacturer's plant to determine compliance with this specification. The contractor shall notify the designated Regional Quality Control Division set forth in the notice of award of the availability of the sample. The approval of the preproduction sample authorizes the commencement of production, but does not relieve the contractor of responsibility for compliance with all requirements of this specification. Production units shall not vary from the approved preproduction sample in design or construction without written approval of the contracting officer.

3.2 Materials and components. All materials and components for the shredding machine (hereinafter called "machine") shall be new and of the manufacturer's latest design current at the time of delivery, except for such modification as may be necessary to conform with the requirements of this specification. The machine shall be complete with all accessories for satsifactory operation.

3.2.1 Protective coating. Parts shall be corrosion resistant or shall have a protective coating which will not scale, crack, or chip with age or extremes of climate and environmental conditions.

3.3 Construction and design. The machine's construction, design, and the materials used therein shall provide a product able to withstand heavy continuous operation over extended periods of time. The cutters or knives and cutter shafts shall be of a core to surface hardened steel and the cutter mechanism shall operate on precision ball bearings. It shall be unnecessary to remove ordinary office type, metal, paper fastening staples from papers prior to the shredding process and the machine shall accept these objects without causing damage to any part of the machine or causing the machine to render shreds in dimensions larger than specified in 3.5. The machine's design shall afford protection to the user against personal injury. A pilot light shall be provided which shall be activated when the machine is in the "on" condition The feed tray for the machine shall be as specified in 3.3.1. The housing for the machine shall be of metal or other tough, dent and abrasion resistant material, or combination thereof, to provide a structurally strong and neat piece of office furniture. The machine shall run quietly and smoothly without objectionable vibration, and shall not create dust during the shredding operation. The sound level of the machine in operation shall not exceed 60 dB when tested as specified in 4.6. The machine shall shred the paper material at the rate specified in 4.6.

3.3.1 Feed tray. The feed tray shall be a slanted, gravity feed type which will easily accept and channel legal and letter size sheets of paper into the cutting chamber. The tray shall prevent the sheets of paper from running to the outside of the cutter where no shredding action occurs. The tray shall have a guard or the machine shall be of a design that makes it impossible for any part of the user's hand to come into contact with any part of the machine which might cause personal injury.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

3.3.2 Construction practices. All screws, bolts, pins, nuts, and similar hardware shall be installed with an adequate means for preventing loss of proper adjustment and tightness. Hardware subject to removal or adjustment shall not be peened, swaged, or otherwise permanently deformed. All casting and forgings shall be uniform and of good quality and free from defects which might affect the structural strength of the parts involved.

3.4 Models.

3.4.1 Model A (desk type). The desk type model shall be portable and of a size and weight that it may be easily moved from one location to another within an office complex. The machine shall be capable of readily and automatically discharging the shred material into an external waste bin or plastic bag. The base of the machine shall have feet of soft rubber or other non-abrasive material to protect desk and table surfaces. The feet shall be securely attached to the base and be removable.

3.4.3 Model B (cabinet type). The cabinet type model shall be housed or mounted in a cabinet of suitable design. The cabinet may be of metal or wood or a combination thereof to provide a strong, sturdy and neat piece of office furniture. A large, removable waste bin or plastic bag shall be provided within the cabinet to readily and automatically accept the processed paper. There shall be no spillage in the transfer of shreds from the machine to the waste receptacle. The cabinet shall be securely mounted on removable non-marring casters to roll the machine quickly and easily where wanted. The casters shall have a lock feature that holds the assemblage motionless in operation.

3.5 Dimension of shreds. The dimensions of the processed paper (shreds) from the machines shall be as specified hereunder. A plus tolerance of 1/64-inch shall be allowed in the width of shreds for both the class I and the class II machines.

Class I (cross cut) - Width of shreds not more than 1/32-inch in length, plus tolerance, and not more 1/2-inch in length.
Class II (non cross cut) - Width of shreds not more than 1/32-inch, plus tolerance.

3.6 Motor. Unless otherwise specified by the procuring activity (see 6.2), the motor for the machine shall be a 60 cycle, 110 volts, single phase, A.C. reversal type with precision ball bearings. The motor shall be capable of developing sufficient power to maintain continuous full load output without excessive temperature rise. Motors shall be in accordance with the standards of the National Electrical Manufacturers' Association. Fractional horsepower motors shall conform to CC-M-636; one horsepower and larger motors shall conform to CC-M-641. The motor shall be equipped with an electric power cable not less than 8 feet in length. The motor shall have a thermal cut off switch that stops the motor in the event it becomes overheated or jammed. Protection against electrical shock shall be provided.

3.7 Color and finish. The color and finish shall be the supplier's commercial standard and of good quality and application.

3.7 Identification label. A metallic type label shall be securely affixed to an external surface of the machine readily visible to the operator. The label shall show the model and serial number, the contract number, the class (I or II), year of manufacturer, and the manufacturer's name or trademark.

3.9 Parts interchangeability. Parts subject to replacement because of wear or damage shall be manufactured to definite standards, tolerances, and clearances so that parts may be replaced or adjusted without modification. To the extent possible all parts shall be legibly marked with the manufacturer's part number.

3.10 Workmanship. The machine, including all parts and accessories shall be fabricated and finished in accordance with good workmanship standards and the machine shall be free from any defect which affects operation or serviceability or which might cause personal injury.

3.11 Instruction manual. An instruction manual shall be furnished with each machine supplied by the manufacturer. The manual shall contain complete instructions necessary for operation, maintenance, and minor repair of the machine. The manual shall contain a section clearly identifying all parts by description and part number.

4. QUALITY ASSURANCE PROVISIONS

4.1 Inspection responsibility. Except as otherwise specified, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facility or service acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to the prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

4.1.1 Component and material inspection. In accordance with 4.1, the supplier is responsible for insuring that components and materials used are manufactured, tested, and inspected in accordance with the requirements of referenced subsidary specifications and standards to the extent specified or, if none, in accordance with this specification.

4.2 Preproduction inspections and test. The preproduction sample in the class or classes the manufacturer proposes to furnish shall be visually inspected as specified in 4.5 and tested as specified in 4.6. Any visual defect or test failure shall be considered as failure to meet specification requirements and the sample shall be rejected.

4.3 Inspection and test for acceptance.

4.3.1 Inspection. Each machine offered for acceptance shall be visually inspected for compliance with 4.5. Any visual defect shall provide reason to reject the machine.

4.3.2 Test. Samples shall be taken by the Government inspector from each lot of the same class offered for acceptance and tested as specified in 4.6. The number of samples from each lot shall be as specified hereunder.

One sample from lots containing less than 7 machines.
Two samples from lots containing more than 6 but less than 19 machines.
Three samples from lots containing more than 18 but not exceeding 30 machines.
No lot shall contain more than 30 machines.

Failure of a sample to meet the test shall provide reason to reject the entire lot represented by the sample.

4.4 Inspection of preparation for delivery. An inspection shall be made to determine that preservation, packaging, packing, and marking comply with the requirements in section 5. Defects shall be scored in accordance with table I. For examination of interior packaging the sample unit shall be one shipping container fully prepared for delivery, selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 6.5 defects per hundred units.

TABLE I. Classification of preparation for delivery defects

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible, improper size, location, sequence, or method of application.
Materials	Any component missing, or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate stapling. Distortion of container.

4.5 Visual inspection. The visual inspection shall consist of an examination of the completely assembled and working machine for compliance with this specification's requirements for material, protective coating and finish, construction practices, identification labels, and workmanship. Failure to comply with any of these requirements shall provide reason to reject the shredding machine.

4.6 Test. The machine under test shall be operated a total of 20 hours. The test cycle shall consist of one hour of operation with paper fed into the machine followed by not less than one hour of non-operation with the power to the machine cut off. This test cycle shall be repeated until the machine has been operated 20 hours. During the periods of operation, 8-inch by 10-1/2-inch, sixteen pound bond paper shall be fed into the machine (2 sheets at a time for the class I machine and 4 sheets at a time for the class II machine). The rate of feed shall be that which can normally be accomplished by an average adult. During the periods of operation, paper jamming in the cutting chamber shall not occur more than once every 25 minutes of operation. Periodically, samples of the shredded material shall be taken from the machine and measured for compliance with the requirements for terminal destruction in 3.5. The machine shall operate throughout the test period without exceeding the sound level specified in 3.3 and without creating dust. Failure to meet all provisions of 4.6 shall provide reason to reject the shredding machine.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A, B, or C as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

5.1.1 Level A.

5.1.1.1 Disassembly. When design of machine permits, disassembly of the machine shall be the minimum to safeguard parts that can be removed and reinstalled without special tools.

5.1.1.2 Cleaning and drying. The machine shall be cleaned and dried as specified in MIL-P-116. The method of cleaning shall be C-1 and the drying shall be method D-1.

5.1.1.3 Preservation application. All surfaces of the machine shall be preserved as specified in MIL-P-116. The interior surfaces of the machine subject to corrosion shall be coated with a type P-10 preservative and all exterior surfaces of the machine subject to corrosion shall be coated with type P-1 preservative.

5.1.1.4 Unit packaging. All openings of the machine shall be covered or wrapped with material conforming to MIL-B-121, type II, grade A, class 2 and sealed with tape conforming to PPP-T-42.

5.1.1.5 Spare parts. The spare parts shall be preserved and packaged in accordance with MIL-P-116. A close-fitting box conforming to PPP-B-636, class weather-resistant shall be utilized as the container. Necessary cushioning, blocking and bracing shall be provided within the box to prevent damage to the contents during shipping and storage. The box shall be closed in accordance with the appendix to PPP-B-636.

5.1.1.6 Motor. The motor shall be preserved in accordance with MIL-P-16298.

5.1.1.7 Technical publications. The technical publications shall be preserved in accordance with method 1C-1 of MIL-P-116.

5.1.2 Level B. The machine shall be preserved and packaged as specified in 5.1.1, except that the fiberboard box shall conform to PPP-B-636, class-domestic.

5.1.3 Level C. The machine shall be preserved and packaged in accordance with the manufacturers standard practice, providing that this insures protection for the machine during shipment and provides for safe delivery to its destination.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Each complete machine shall be packed in a close-fitting box conforming to PPP-B-601, overseas type; PPP-B-621, class 2 or PPP-B-640, class 2, grade A. Blocking and bracing shall be utilized as required to prevent movement within the shipping container. The box shall be closed and strapped in accordance with the appendix to the applicable box specification.

5.2.2 Level B. Each machine shall be packed as specified in 5.2.1 except that the boxes shall conform to PPP-B-601, domestic type, PPP-B-621, class 1 or PPP-B-640, class 1, grade B.

5.2.3 Level C. Machines packaged as specified in 5.1.2 shall be packed in containers that will assure carrier acceptance and safe arrival at destination in compliance with the Uniform Freight Classification or the National Motor Freight Classification.

5.3 Marking. Marking shall be in accordance with 5.3.1 or 5.3.2 as specified (see 6.2).

5.3.1 Civil agencies. In addition to any special markings required by the contract or order, all interior packages and shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.3.2 Military agencies. In addition to any special markings required by the contract or order, all interior packages and shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The shredding machines under this specification are intended for use as prescribed by the using agency.

6.2 Ordering data. Purchasers should exercise any desired options offered herein, and procurement documents should specify the following:

(a) Title, symbol, and date of this specification.
(b) Class, and model required, (see 1.2).
(c) Motor electrical characteristics required, if other than specified (see 3.6).
(d) Packaging, packing, and marking required (see 5.1, 5.2, and 5.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.

6.3 Recommended security precautions by the users. Security precautions exercised during the use of the machine should include the following:

(a) Periodic examination of the shredded paper to assure its proper destruction.
(b) Examination of the cutting chamber for unshredded paper.
(c) Use of the feed tray at all times, otherwise large shreds may result by paper running to the outside edges of the machine where no shredding action occurs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:47Z
Check the source to verify that this is the current version before use.