INCH-POUND

MIL-DTL-3943/265
25 February 2000

DETAIL SPECIFICATION SHEET

DECORATION, MERITORIOUS PUBLIC SERVICE AWARD, NAVY

Inactive for new design after 25 February 2000.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

OBVERSE



REVERSE

Dash No.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match The Institute of Heraldry (TIOH) Metal Finish Chip number 4.

DIMENSIONS:

HEIGHT (including lug):
-1: 1-5/8 inch (REF)
-2: 23/32 inch (REF)
DIAMETER:
-1: 1-3/8 inch (REF)
-2: 5/8 inch (REF)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:49Z
Check the source to verify that this is the current version before use.

THICKNESS (overall):
-1: 0.085 inch ± 0.010 inch
-2: 0.080 ± 0.010 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The lug shall have a 1/32 inch minimum thickness. The hole through the lug shall be 1/8 inch ± 1/64 inch in diameter.

3. Decoration set shall consist of a regular size medal, a miniature size medal, a service ribbon, and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type VIII, Style 6 with a Class 1, 1A or 3 pad.

4. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/523.

5. The lapel button shall conform to MIL-DTL-11484/262.

6. The use of any type of plastic packaging material is prohibited.

Custodians:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-1008)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:49Z
Check the source to verify that this is the current version before use.