INCH-POUND

MIL-DTL-3943/266
18 February 2000

DETAIL SPECIFICATION SHEET

DECORATION, DISTINGUISHED CIVILIAN SERVICE AWARD, INSPECTOR GENERAL, DEPARTMENT OF DEFENSE

Inactive for new design after 18 February 2000.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

OBVERSE

REVERSE

MATERIAL: Red Brass

FINISH: Gold Plated, Light Rose Gold Plated, Polished Highlights.

DIMENSIONS:

HEIGHT (including lug): 1-19/32 inches (REF)
DIAMETER (without lug): 1-3/8 inches (REF)
THICKNESS (at thickest point): 0.135 inch ± 0.010 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:49Z
Check the source to verify that this is the current version before use.

2. The lug shall have a 1/32 inch minimum thickness. The hole through the lug shall be 1/8 inch ± 1/64 inch in diameter

3. Decoration set shall consist of a regular size medal, a service ribbon, and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type VIII, Style 6 with a Class 1, 1A, or 3 pad.

4. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/527 .

5. The lapel button shall conform to MIL-DTL-11484/263.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-1008)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:49Z
Check the source to verify that this is the current version before use.