INCH-POUND


MIL-DTL-3943/270A
09 October 2012
SUPERSEDING
MIL-DTL-3943/270
16 August 2000

DETAIL SPECIFICATION SHEET

DECORATION, JOINT CIVILIAN SERVICE COMMENDATION AWARD, CHAIRMAN OF THE JOINT CHIEFS OF STAFF

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:50Z
Check the source to verify that this is the current version before use.

DIMENSIONS:
HEIGHT (Without lug): 1-3/8 inches (REF)
WIDTH: 1-3/8 inches (REF)
THICKNESS (At thickest point): 0.140 inch ± 0.010 inch

DECORATION SET AND CASE: Decoration set shall consist of a regular size medal and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Type VIII, Style 6 with a Class 1, 1A, or 3 pad.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon for the pendant drape is MIL-DTL-11589/530.

3. The specification slash sheet for the lapel button is MIL-DTL-11484/267.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

(Project No. 8455-2012-143)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:50Z
Check the source to verify that this is the current version before use.