INCH-POUND

MIL-DTL-3943/281B
13 November 2017
SUPERSEDING
MIL-DTL-3943/281A
8 January 2013

DETAIL SPECIFICATION SHEET

DECORATION, COMMISSIONER'S EXCELLENCE IN GROUP ACHIEVEMENT AWARD, U.S. BORDER PATROL

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Brass, Oxidized, Buffed Relieved and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 4.

DIMENSIONS:
HEIGHT (Including lug)
-1: 1-5/8 inches (REF)
-2: 13/16 inch (REF)

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:53Z
Check the source to verify that this is the current version before use.

DIAMETER:
-1: 1-3/8 inches (REF)
-2: 11/16 inch (REF)
THICKNESS (At word "BORDER")
-1: 0.130 ± 0.010 inch
-2: 0.100 ± 0.010 inch

DECORATION SET AND CASE: Decoration set shall consist of a regular size medal, a miniature size medal, and a service ribbon all packaged in a presentation case conforming to MIL-C-14633, Type VIII, with a Class 2a or 4 pad.

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon for the pendant drape is MIL-DTL-11589/548.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2018-027)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:53Z
Check the source to verify that this is the current version before use.