INCH-POUND

MIL-B-14036E
15 July 1992
SUPERSEDING
MIL-B-14036D
24 April 1985

MILITARY SPECIFICATION

BRACKET, OUTBOARD MOTOR: BOW ATTACHMENT; 12-TON, PNEUMATIC HALF FLOAT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a bracket for mounting outboard motors on the bow of a 12-ton pneumatic half float.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5420

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-18T02:46Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

PPP-B-621	- Boxes, Wood, Nailed and Lock-Corner.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-T-704	- Treatment and Painting of Materiel.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking, and Waterproofing; with Appropriate Test Methods.

(Unless otherwise indicated, copies of federal and military specifications and standards are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.1.2 Other Government drawings. The following other Government drawings form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those cited in the solicitation.

DRAWINGS

ME

TA13214E9400	- Bracket, Outboard Motor: Bow Attachment, 12-Ton Pneumatic Half Float.

(Copies of drawings required by contractors in connection with specific acquisition functions should be obtained from the USA Belvoir Research, Development, and Engineering Center. ATTN: STRBE-JBS, Fort Belvoir, VA 22060-5606.)

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DoDISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS are the issues of the documents cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:46Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX, Qualification Standard for Welding and Brazing Procedures, Welders, Brazers, and Welding and Brazing Operators.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3953 - Strapping, Flat Steel and Seals.
D 4675 - Selection and Use of Flat Strapping Material.

(Applications for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

AMERICAN WELDING SOCIETY (AWS)

D1.1 - Structural Welding Code - Steel.

(Application for copies should be addressed to the American Welding Society, 550 N.W. LeJeune Rd, P.O. Box 351040, Miami, FL 33135.)

UNIFORM CLASSIFICATION COMMITTEE AGENT

Uniform Freight Classification Rules.

(Application for copies should be addressed to the Uniform Classification Committee, ATTN: Tariff Publishing Officer, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION, INC. AGENT

National Motor Freight Classification Rules.

(Application for copies should be addressed to the American Trucking Association, Inc., ATTN: Traffic Order Section, 2200 Mill Road, Alexandria, VA 22314.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:46Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description. The outboard motor bracket (hereafter referred to as "bracket") shall consist of a frame, transom, puller, and platform and shall be in accordance with TA13214E9400 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviations from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to ensure correct fit, assembly and operation of the bracket. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or the designated representative.

3.2 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.3 Materials. Materials shall be as specified herein and on the drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3.1 Material deterioration prevention and control. The bracket shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the bracket may be exposed.

3.3.1.1 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.3.2 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the bracket may be newly fabricated from recovered materials to the maximum extent practicable, provided the bracket produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the bracket.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:46Z
Check the source to verify that this is the current version before use.

3.4 Puller assembly. The puller assembly shall include a brake, clutch, and a ratchet with pawl. The puller shall be capable of moving a cable load of 600 pounds without damage, permanent deformation, or failure of any part. The puller shall withstand a load of 2,000 pounds without permanent deformation, failure of any component, or release of the winch mechanism. Directions for lifting and lowering shall be permanently marked on the puller and shall be visible.

3.5 Identification marking. The bracket shall be identified in accordance with MIL-STD-130 and as shown on the drawings.

3.6 Treatment and painting. The bracket shall be cleaned, treated, and painted in accordance with MIL-T-704, type B.

3.6.1 Cleaning. All ferrous metal surfaces requiring painting shall be cleaned to the bare metal by sandblasting to remove all oil, grease, mill scale, products of erosion, dirt, welding slag or spatter, and other foreign substances that may be detrimental to the coating system.

3.7 Workmanship. All parts, components, and assemblies of the bracket including welded parts shall be clean and free from sand, dirt, fins, pits, sprues, scale, flux, and other harmful, extraneous material. External surfaces shall be free from burns, sharp edges, and corners except when sharp edges and corners are required.

3.7.1 Steel fabrication. Steel used in the fabrication of the equipment shall provide original quality surface finish and be free from kinks and sharp bends. Steel having an eroded surface is not acceptable. The forming of material shall be done by methods that will not cause damage to the metal. Shearing and chipping shall be done neatly and accurately. Corners shall be square and true. Burned surfaces of flame-cut material shall be free of slag. Precautions shall be taken to avoid overheating, and heated metals should be allowed to cool slowly except where heat treatment is required. All bends of a major character shall be made with metal dies or jigs to insure uniformity of size and shape.

3.7.2 Plywood fabrication. Plywood shall be drilled and cut square and true using cutting blades, speeds, and feeds that will not split or splinter the corners and outside veneers. Sharp edges that are exposed in the assembled bracket shall be rounded and sanded smooth. Wood screws shall not be hammer-driven. Pilot holes for wood screws shall be centered and shall not exceed 90 percent of the length of the screw. Diameter of the lead holes shall not exceed 70 percent of the root diameter of the screw.

3.7.3 Welders and welding operators. Before assigning any welder or welding operator to welding work covered by this specification, the contractor shall obtain certification that the welder or welding operator has passed qualification tests as prescribed by either of the following listed codes for

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:46Z
Check the source to verify that this is the current version before use.

the type of welding operations to be performed and that such qualification is effective as defined by the particular code: ASME Boiler and Pressure Vessel Code, Section IX, and AWS D1.1 - Structural Welding Code - Steel.

Certification (see 6.4) shall be made available for inspection by the contracting officer or designated representative. Contractors who make only horizontal welds need not qualify welders for "all position welding". In the event of evidence of poor welds, the Government reserves the right to require recertification of any welder or welding operator. The test results shall be made available for review by the contracting officer or the contracting officer's representative.

3.7.3.1 Welding. The quality of welds shall be in compliance with 8.15.1 of AWS D1.1.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements; however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Component and material inspection. The contractor is responsible for ensuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards as applicable.

4.1.3 Parts and components. Parts and components detailed on the drawings shall be inspected in accordance with the quality assurance provisions (QAP) shown on the drawings. The drawings specify the characteristics requiring QAP inspection, the sampling plan, and the basis for acceptance and rejection (see 6.4 and 6.5).

Source: https://assist.dla.mil -- Downloaded: 202610-18T02:46Z
Check the source to verify that this is the currentversion before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article bracket shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article bracket shall be tested as specified in 4.5.2. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Examination. Each bracket shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4.2 Tests.

4.4.2.1 Individual. Each bracket shall be tested as specified in 4.5.2. Failure of this test shall be cause for rejection.

4.5 Inspection procedure.

4.5.1 Examination. The brackets shall be examined as specified herein for the following defects:

Major

101. Materials not as specified (see 3.3).
102. Materials are not resistant to corrosion and deterioration or treated to be resistant to corrosion and deterioration for the applicable and operation environments (see 3.3.1).
103. Dissimilar metals are defined in MIL-STD-889 are not effectively insulated from each other(see 3.3.1.1).
104. Contractor does not have documentation available for identification of material, material finishes or treatment (see 3.3.1.2).
105. Used, rebuilt or remanufactured components, pieces, or parts incorporated in the bracket (see 3.3.2).
106. Bracket not true to dimensions and lines, contains twists, bends, or other imperfections.
107. Assembly incorrect.
108. Components missing or not as specified.
109. Chains not as specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:46Z
Check the source to verify that this is the current version before use.

110. Any parts or components not in accordance with the QAP requirements as shown on the drawings.
111. Marking illegible, incorrect, incomplete, or missing (see 3.5).
112. Treatment and painting not as specified (see 3.6).
113. Improper finishing of hardware.
114. Workmanship not as specified (see 3.7).
115. Steel fabrication not as specified (see 3.7.1).
116. Plywood fabrication not as specified (see 3.7.2).
117. Welder or welding operator certification not available for review (see 3.7.3).
118. Welding and weldments not in accordance with requirements (see AWS D1.1).

4.5.2 Tests.

4.5.2.1 Test procedure. The bracket shall be mounted on a test stand in a manner duplicating the mounting on 13214E1400-1. A load of 600 pounds shall be placed on the operator's platform. The transom board assembly shall be winched the full length of its travel in both directions not less than five times. The brake shall be engaged during the raising and lowering operation. The platform shall be centered in its travel, and the transom board loaded with an additional load of 1400 pounds. Failure to conform with 3.4 shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and table Ia. A lot shall be accepted when zero defects are found and rejected when one or more defects are found.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. Presence of one or more defects shall be cause for rejection.

119. Disassembly not as specified for level A (see 5.1.1.1).
120. Unprotected metal surfaces not coated with preservative for level A (see 5.1.1.2).
121. The components comprising a complete bracket not packed in a shipping container as specified for level A or B.
122. Blocking and bracing not in accordance with referenced document (see 5.2.1).
123. Strapping not as specified for level A or B (see 5.2.1 or 5.2.2).
124. Marking missing, illegible, incorrect, or incomplete for level A, level B, or level C (see 5.3).

Source: https://assist.dla.mil -- Downloaded: 202610-18T02:46Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or level C as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly. The bracket shall be disassembled to the maximum practical extent consistent with effecting a reduction in cube while providing ease of packing and preventing damage during shipment.

5.1.1.2 Unprotected surfaces. Unpainted or otherwise unprotected metal surfaces requiring a contact preservative in accordance with the criteria of MIL-P-116 shall be coated with P-1 preservative as specified in MIL-P-116.

5.1.2 Level C. The bracket shall be preserved in a manner to afford protection against deterioration and damage during shipment from the contractor to the initial destination.

5.2 Packing. Packing shall be level A, level B, or level C as specified (see 6.2).

5.2.1 Level A. The components comprising a complete bracket shall be packed in a close fitting box conforming to PPP-B-621, class 2. Blocking and bracing necessary to prevent movement and damage shall be in accordance with MIL-STD-1186. Strapping shall be in accordance with ASTM D 3953. Type 1 or 2, zinc-coated, size as applicable and ASTM D 4675.

5.2.2 Level B. The components comprising a complete bracket shall be packed as specified in 5.2.1 except the box shall be class 1 and strapping may be zinc-coated.

5.2.3 Level C. Each bracket shall be packed to assure carrier acceptance and safe delivery to destination of lowest ratings in compliance with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.3 Marking. Bundles shall be marked in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The bracket is intended for use on the bow of 12-ton pneumatic half floats, for mounting one or two 25 horsepower outboard motors.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:46Z
Check the source to verify that this is the current version before use.

b. Issue of DoDISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required for inspection and approval, and the number of units required (see 3.2 and 6.3).
d. Level of preservation and packing required (see 5.1 and 5.2).

6.3 First article. When a first article inspection is required, the item(s) should be a production model. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of the first article test results and disposition of the first articles. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Consideration of data requirements. The following data requirements should be considered when this document is applied on a contract. The applicable Data Item Description (DIDs) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/ provided and that the DIDs are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of the data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 27.475-1 exempts the requirement for a DD Form 1423.

Reference Paragraph	DID Number	DID Title
a. 3.7.3	DI-MISC-80875	Welding Procedures.
b. 3.7.3	DI-MISC-80876	Welding Procedure Qualification Test Report.

The above DIDs were those cleared as of the date of this specification. The current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DIDs are cited on the DD Form 1423.

6.5 Quality assurance provisions (QAP). The contracting officer should require the supplier to maintain record of all QAP inspections. A suggested paragraph is as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:46Z
Check the source to verify that this is the current version before use.

"The contractor shall maintain complete records of all examinations and tests performed to verify the requirements of classified QAP characteristics. The records shall include, as a minimum, lot size, sample size, drawing requirements, actual measurements, number and type of deficiencies found, quantity approved, quantity rejected, corrected action taken when applicable."

6.6 Definitions.

6.6.1 Quality assurance provisions (QAP). A QAP is a contractual requirement that supplements section 4 of the specification. QAP indicates the minimum requirements which must be inspected on the product drawings to verify the design objectives of the product and assure interchangeability of repair parts.

6.7 Subject term (key word) listing.

12-ton half float
Frame
Puller
Transom

6.8 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - ME

Review activity:
Navy - MC

Preparing activity:
Army - ME

Project 5420-0173

Source: https://assist.dla.mil -- Downloaded: 202640-18T02:46Z
Check the source to verify that this is the currentversion before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-B-14036E	2. DOCUMENT DATE (YYMMDD) 920715

3. DOCUMENT TITLE
Bracket, Outboard Motor: Bow Attachment; 12-Ton, Pneumatic Half Float

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (if applicable) (2) AUTOVON	7. DATE SUBMITTED

8. PREPARING ACTIVITY

a. NAME Geraldine F. Harlow	b. TELEPHONE (Include Area Code) (1) Commercial (703) 704-3468	(2) AUTOVON 654-3468
c. ADDRESS (Include Zip Code Army Belvoir RDE Center ATN: STRBE-TSE Fort Belvoir, VA 22060-5606	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:46Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:46Z
Check the source to verify that this is the current version before use.