MIL-C-0014003B(AS)
24 November 1972

USED IN LIEU OF
MIL-C-14003A
2 November 1955

MILITARY SPECIFICATION

CAPS, BLASTING, SPECIAL

This limited coordination Military Specification has been prepared by the Naval Air Systems Command based upon currently available technical information, but it has not been approved for promulgation as a coordinated revision of Military Specification MIL-C-14003A. It is subject to modification. However, pending its promulgation as a coordinated Military Specification, it may be used in procurement.

1. SCOPE

1.1 Scope. This specification covers special blasting caps for use in detonating various types of explosives (see 6.1).

1.2 Classification. The special blasting caps shall be of the following types, as specified (see 6.2):

Type I - Nonelectric, J-1
Type II - Electric, J-2
Type III - Electric, Shielded, J-3

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

W-B-411	Blasting-Apparatus (Machines, Blasting; Galvanometers and Rheostats for Testing Blasting Circuits and Machines)
QQ-A-250/8	Aluminum Alloy 5052; Plate and Sheet
QQ-L-201	Lead, Sheet
PPP-B-621	Box, Wood, Nailed and Lock Corner
PPP-B-636	Box, Fiberboard
PPP-B-1055	Barrier Material, Waterproofed, Flexible

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:45Z
Check the source to verify that this is the current version before use.

Military

MIL-P-387	Pentaerythrite Tetranitrate (PETN)
MIL-R-398	RDX
MIL-G-2550	General Specification for Ammunition Except Small Arms Ammunition
MIL-L-3055	Lead Azide

STANDARDS

Military

MIL-STD-129	Marking For Shipment and Storage

PUBLICATIONS

Department of Defense

4145.26M	DoD Contractors' Safety Manual for Ammunition, Explosives and Dangerous Related Materials

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 171-178	Hazardous Materials Regulations, Department of Transportation

(Copies are available from the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:45Z
Check the source to verify that this is the current version before use.

that are used in estimating the relationship between A$_o$ and mission effectiveness

3. REQUIREMENTS

3.1 Material. The materials used in the manufacture of the blasting caps shall be as specified herein. All materials not definitely specified shall be of the best quality normally used for the purpose in good commercial practice. The materials shall be free of all defects and imperfections that might affect the serviceability of the finished product.

3.1.1 Lead azide. The lead azide shall comply with the requirements of MIL-L-3055.

3.1.1.1 Moisture content of the lead azide. The moisture content of the lead azide at the loading station, at the time of loading the blasting caps, shall not exceed 0.50 percent, when tested as specified in 4.5.1.

3.1.2 Pentaerythrite tetranitrate (PETN). Pentaerythrite tetranitrate (PETN) shall comply with the requirements of MIL-P-387, class D, except that it shall not be required to pass a vacuum stability test.

3.1.3 RDX. RDX shall comply with the requirements of MIL-R-398, type A or B, class A or B.

3.2 Construction. Each blasting cap shall consist of a shell and a charge.

3.2.1 Shell.

3.2.1.1 Material. The shell shall be made of aluminum alloy in accordance with QQ-A-250/8.

3.2.1.2 Dimensions. The shell shall be closed at one end and shall be of the dimensions specified in table I, when measured (except for length) at a point one-half inch below the open end disregarding any corrugations near the top of the blasting cap.

Table I

DIMENSIONAL REQUIREMENTS

Type of cap	Overall length (inches)	External diameter (inches)	Internal diameter (inches)	Wall thickness (inches)
I	2.344 ± 0.030	0.232 to 0.242	0.217 to 0.225	0.007 ± 0.002
*II and III	3.000 ± 0.030	0.271 to 0.279	0.256 to 0.262	0.007 ± 0.002

*NOTE: Maximum diameter of bead of Type II and Type III Blasting Caps shall be 0.0315 inch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:45Z
Check the source to verify that this is the current version before use.

3.2.2 Charge. The charge shall consist of a base charge of not less than 13-1/2 grains of PETN (see 3.1.2), or of RDX (see 3.1.3), and a priming charge consisting of sufficient lead azide (see 3.1.1) to insure complete detonation of the base charge as required by the performance tests. When necessary, suitable ignition charge shall be used in addition to the priming charge.

3.3 Details of assembly.

3.3.1 Type I caps. The charge shall be compressed into the shell so that not less than 0.75 inch above the charge shall be left empty for insertion of a suitable safety fuse.

3.3.2 Type II caps. The base charge shall be compressed into the shell. A primer charge, or a primer charge and ignition charge, shall be placed in the shell. The caps shall be provided with a pair of copper lead wires of Number 22 B-and-S gage, 12 feet in length, with a suitable bridge wire attached to the lead wire terminals and sealed into the cap to make a waterproof assembly. The electric wires shall be enameled copper, double-cotton covered, or copper wire with an insulation of equivalent dielectric value. If cotton coverings are used, they shall be waterproofed with a suitable wax. The color of the wires shall be either yellow or white. The bare ends of the lead wires shall be coated for a distance of not less than 1-3/4 inches from the end with tin or other metal or alloy acceptable to the contracting officer. As a means of protection against stray currents, the bare ends of the electric wires shall be effectively short-circuited by means of an easily removable device. The device shall be of such shape as to identify the manufacturer and shall be approved by the contracting officer. The outside of the shells shall be colored to identify the manufacturer, as approved by the contracting officer.

3.3.3 Type III caps. The base charge shall be compressed into the shell. A primer charge, or a primer and ignition charge, shall be placed in the shell. The caps shall be provided with a pair of copper lead wires of Number 22 B-and-S gage, sealed into the cap to make a waterproof assembly. The electric wires shall be enameled copper, double-cotton-covered, or copper wire with an insulation of equivalent dielectric value. If cotton coverings are used, they shall be waterproofed with a suitable wax. The color of the wires shall be either yellow or white. The lead wires shall be twisted a minimum of 10 turns to the inch, 24 feet in length after being twisted, and jacketed with a closely-woven metal braided shielding. The shielding shall be soldered or brazed to the cap and to a female connector throughout their respective entire peripheries to form a continuous shield without electrical discontinuities or gaps. The pins on the inner conductors of the connector shall be female and recessed into the insulator to

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:45Z
Check the source to verify that this is the current version before use.

prevent unintentional contact by fingers or tools. In addition, the tips of the female pins shall be recessed well below the lip of the surrounding shield to provide additional shielding. The shielded lead wires shall be covered with a heat shrinkable, flexible, insulation sleeving of appropriate quality. A metal-cased male plug, designed to completely mate with the outer shell (shield) surface before any of its inner shorted conductors make contact with the recessed pins of the female connector, shall be installed in the female connector. The plug connector, when being unmated, shall completely open-circuit the female conductor pins before the shell (shield) contact surface has broken contact. The female connector and plug shall be approved by the contracting officer. The outside of the blasting cap shell shall be color coded to identify the manufacturer, as approved by the contracting officer. One male plug with 36 inch leads compatible to female connector, shall be provided with each package of 10 blasting caps for detonation use.

3.4 Impact resistance (applicable to type I caps only). The cap shall not crack or break, and the cap charge shall not loosen or drop out upon impact, when tested as specified in 4.5.2.

3.5 Functioning (applicable to types II and III caps only).

3.5.1 Electrical resistance. The resistance of the complete cap assembly, including its leads, shall not differ more than 0.25 ohm from the average standard resistance of the cap assemblies specified in the purchase order (see 6.2), when tested as specified in 4.5.3.

3.5.2 Waterproofness. The caps shall withstand submersion in water for a period of 4 hours at a temperature of 70° Fahrenheit (F) $\pm$ 5° and a pressure of 50 pounds per square inch (psi) as specified in 4.5.3.2. Following the test the caps shall function satisfactorily, as evidenced by the perforation of the lead discs when the caps are tested as specified in 4.5.3.2 and 4.5.4.1, and shall either:

(a) Function upon application of an electric current of 1.5 amperes for a period not exceeding 50 milliseconds, as specified in 4.5.3.2, or

(b) Function through a total resistance of 32 ohms when fired with a blasting machine, as specified in 4.5.3.2.

3.6 Static functioning (applicable to type I caps only).

3.6.1 After impact test. The caps shall detonate completely, as evidenced by the perforation of the lead discs, when tested as specified in 4.5.4.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:45Z
Check the source to verify that this is the current version before use.

3.6.2 Low temperature phase (-58°F). The caps shall detonate completely, as evidenced by the perforation of the lead discs, when tested as specified in 4.5.4.1.2.

3.6.3 High temperature phase (120°F). The caps shall detonate completely, as evidenced by the perforation of the lead discs, when tested as specified in 4.5.4.1.3.

3.7 Current requirements (applicable to types II and III caps only).

3.7.1 Functioning. The electric caps shall fire without failure when an electric current of 0.45 ampere is applied as specified in 4.5.5.1.

3.7.2 Nonfunctioning. The electric caps shall not fire when an electric current of 0.2 ampere is applied for 5 seconds, as specified in 4.5.5.2.

3.8 Safety. The supplier shall observe the safe practices and standards set forth in DoD 4145.26M.

3.9 Workmanship. All parts shall be free of chips, dirt, grease, rust, and other foreign material. The cleaning method used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents used.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Lot. A lot shall consist of blasting caps produced by one manufacturer under one contract in one unchanged process and in accordance with the same specification and same specification revision. Each lot shall contain:

(a) Blasting caps of one type only.

(b) Aluminum shell of new manufacture made by one manufacturer in accordance with the same specification and same specification revision

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:45Z
Check the source to verify that this is the current version before use.

(c) Lead azide of one manufacturer from the same interfix lot number

(d) Pentaerythrite tetranitrate (PETN) (where applicable) of one manufacturer from the same interfix lot number

(e) RDX (where applicable) of one manufacturer from the same interfix lot number

(f) Suitable ignition charge (where applicable) consisting of batches blended by the same process, each ingredient being from one lot only

(g) Parts or inert parts made by one manufacturer in accordance with the same specification and same specification revision

4.2.1 Grouping for shipment. When specified in the contract or order, groups for shipment shall be formed of the blasting caps in each lot. The number of units in a group, and the corresponding marking, shall be as specified in the contract or order (see 6.2).

4.3 Sampling.

4.3.1 Type I caps. One hundred forty-five caps shall be taken at random by the inspector from the lot for use in the inspection and in the applicable tests specified herein.

4.3.2 Types II and III caps. Three hundred twenty caps shall be taken by the inspector from the lot for use in the inspection and in the applicable tests specified herein.

4.3.3 Component materials. The component materials shall be sampled as required for the applicable tests (see 4.5.1).

4.4 Inspection. Inspection shall be as specified in MIL-G-2550.

4.4.1 Dimension inspection. One hundred empty shells shall be taken from each lot and inspected for compliance with the dimensional requirements.

4.5 Test procedures.

4.5.1 Determination of moisture content of lead azide. A tared, dried aluminum dish, 2 inches in diameter, shall be covered with a sheet of polytetrafluoroethylene (see 6.3), 2-1/2 inches square, and sufficiently flat to form a tight cover. An accurately weighed portion of approximately 2 grams of the lead azide shall be transferred to the moisture dish while both the cover and dish are on the balance pan. The uncovered dish and its contents shall be placed in an oven and dried at 95° centigrade (C) ± 2° for 2 hours. The dish cover shall be placed in a desiccator containing

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:45Z
Check the source to verify that this is the current version before use.

anhydrous calcium sulfate, with indicator, during the drying period. After drying, the dish shall be quickly transferred to the desiccator and allowed to cool to room temperature. The polytetrafluoroethylene cover shall be placed on the dish and the assembly weighed. The loss in weight shall be calculated to percentage of moisture, as follows:

$$\text{Percentage of moisture} = \frac{(A - B)}{A} \times 100$$

where:

A = weight of the sample before drying, in grams

B = weight of the sample after drying, in grams.

4.5.2 Impact test (applicable to type I caps only).

4.5.2.1 Apparatus. The apparatus shall consist of a 7-foot length of 1-9/16 inch ID galvanized iron pipe, erected in a vertical position 3-1/2 inches above a steel anvil. Two holes shall be drilled above a steel anvil. Two holes shall be drilled through the pipe, diametrically opposite each other, at a point 48 inches above the anvil. A pulley shall be installed approximately 3 feet above the upper end of the pipe. A rope, attached to a cylindrical steel weight, shall pass through the pulley. The weight shall weigh approximately 5.3 pounds and shall measure 14 inches long by 1-3/8 inches in diameter approximately. The weight may thus be lowered into the pipe by means of the rope. A hole shall be drilled either in the bottom or in the top of the weight, corresponding in length and diameter to the size of the cap to be tested. If the hole is drilled in the bottom of the weight, a slot, corresponding in length to the depth of the hole, shall be cut through the weight alongside the hole. (This slot will make it easier to remove the cap after the test.) A steel pin, of appropriate size for inserting into the holes drilled in the pipe, shall be attached to a rope which extends behind a barricade. The bottom of the apparatus around the anvil shall be shielded from above and on three sides.

4.5.2.2 Procedure. Twenty-five sample blasting caps shall be tested for impact resistance in the following manner: The cap shall be inserted in an inverted position into the hole in the top or bottom of a steel weight. If a weight with hole in the bottom is used, a short length of split rubber tubing may be placed around the cap so that it will stay up in the hole. The steel pin attached to the rope shall be inserted into the pair of holes in the pipe, 48 inches above the anvil. The weight shall then be raised by means of the rope that passes through the overhead pulley and lowered into the pipe until it rests upon the steel pin. The operator shall then retire behind the barricade. The rope attached to the steel pin shall then be pulled, allowing the weight to fall to the anvil below. This procedure shall be repeated until two drops have been made for each of the 25 caps. Observation shall be made for evidence of cracking or breaking of the cap and for loosening

Source: https://assist.dla.mil -- Downloaded: 202610-18T02:45Z
Check the source to verify that this is the currentversion before use.

interconnections to the detonating systems shall be shown.

or dropping out of the cap charge. The cap shall then be removed from the weight and subjected to the static functioning test specified in 4.5.4.1.

4.5.2.3 Acceptance. The lot shall be considered acceptable provided the sample caps comply with the impact-test requirements. The lot shall be rejected if the limits for eligibility for retest are exceeded.

4.5.2.4 Retest. A retest, as provided for in 4.5.2.3, may be made, if requested by the contractor, using double the number of samples specified in the original test. The lot shall be considered acceptable on retest provided that each of the 50 sample caps comply with the impact-test requirements.

4.5.3 Functioning (applicable to types II and III caps only).

4.5.3.1 Electrical resistance. One hundred sample caps shall be tested. The electrical resistance of each sample cap, including its leads, shall be measured by the Wheatstone bridge method. The average resistance of the caps shall be calculated, and the resistance of each individual cap compared with the average to determine compliance with the requirements.

4.5.3.2 Waterproofness. Upon completion of the electrical resistance test specified in 4.5.3.1, the 100 caps shall be completely immersed in water for 4 hours at a temperature of 70°F ± 5°, and a pressure of 50 psi. Immediately upon removal from the water, 20 of the sample caps shall be subjected to the static functioning test specified in 4.5.4.1. The remaining 80 caps shall be either connected in series and an electric current of 1.5 amperes, maximum, applied to the circuit for a period not exceeding 50 milliseconds; or else the 80 caps shall be connected in series, in groups of 10 each, and fired with a 10-cap capacity blasting machine complying with W-B-411, type I, class A, through a total resistance of 32 ohms. Observations shall be made for evidence of complete detonation of the caps to determine compliance with the functioning requirements.

4.5.3.3 Acceptance. The lot of types II and III caps shall be considered acceptable in this phase of testing (electrical resistance and functioning following waterproofness) provided that all the tested caps comply with the applicable functioning requirements. The lot shall be considered eligible for retest under the provisions of 4.5.3.4 provided that 99 of the 100 sample caps comply with the applicable requirements. The lot shall be rejected if the limits for eligibility for retest are exceeded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:45Z
Check the source to verify that this is the current version before use.

4.5.3.4 Retest. A retest, as provided for in 4.5.4.3, may be made if requested by the contractor, using the same number of sample caps specified in the original test. The lot shall be considered acceptable on retest provided that each of the 100 sample caps tested complies with the applicable functioning requirements.

4.5.4 Static functioning test.

4.5.4.1 Procedure. The lead discs used in this test shall be made of 8-pound sheet lead complying with QQ-L-201, grade B, and shall be 0.1345 inch in thickness and 1.22 -0.01 inches in diameter. The disc shall be centered over a 15/16-inch-diameter hole in a metal support. The cap shall be suitably fixed in an upright position so that the base of the cap is in contact with the lead disc. The cap shall be fired in an upright position, with its bottom resting on the unsupported section of the lead disc. Observation shall be made for complete detonation of the cap as evidenced by the perforation of the lead disc.

4.5.4.1.1 Functioning (applicable to type I caps only). Twenty-five caps which have been subjected to the impact test specified in 4.5.2 shall be subjected to the static functioning test specified in 4.5.4. Observation shall be made for perforation of the lead disc to determine compliance with the requirements.

4.5.4.1.2 Low temperature phase (-58°F). Ten sample caps shall be stored at a temperature of -58°F, or colder, for a period of 2 hours, minimum. The caps shall then be immediately subjected to the static functioning test specified in 4.5.4. Observation shall be made for perforation of the lead discs to determine compliance with the requirements.

4.5.4.1.3 High temperature phase (120°F). Ten sample caps shall be stored at a temperature of 120°F for 5 days. The caps shall then be subjected to the static functioning test specified in 4.5.4. Observation shall be made for perforation of the lead disc to determine compliance with the requirements.

4.5.4.2 Acceptance. The lot shall be considered acceptable provided that, in the phase being tested (that is, static functioning following impact testing; low temperature phase (-58°F), or high temperature phase (120°F), the caps fire and comply with the applicable static functioning requirements. The lot shall be considered eligible for retest under the provisions of 4.5.4.3 provided that:

(a) Not more than one cap fails to function satisfactorily in the functioning phase following impact testing; or

(b) Not more than one cap fails to function satisfactorily in the -58°F phase; or

Source: https://assist.dla.mil -- Downloaded: 202610-18T02:45Z
Check the source to verify that this is the currentversion before use.

(c) Not more than one cap fails to function satisfactorily in the 120°F phase.

The lot shall be rejected if in the phase being tested the applicable limits for eligibility for retest listed above are exceeded.

4.5.4.3 Retest. A retest, as provided for in 4.5.4.2, may be made if requested by the contractor, using double the number of samples used in the original test. The lot shall be considered acceptable provided that in the phase being retested no failures occur.

4.5.5 Electric current test (applicable to types II and III caps only).

4.5.5.1 Functioning. Fifty sample caps shall be subjected to this test. An electric current of 0.45 ampere shall be applied singly to each cap. Observation shall be made for detonation of the cap to determine compliance with the requirements.

4.5.5.2 Nonfunctioning. Fifty sample caps shall be subjected to this test. An electric current of 0.20 ampere shall be applied singly to each cap for a period of 5 seconds. Observation shall be made for nonfunctioning of the cap to determine compliance with the requirements.

4.5.5.3 Acceptance. The lot of blasting caps shall be considered acceptable provided that in the phase being tested (functioning or nonfunctioning) the caps comply with the applicable requirements. The lot shall be considered eligible for retest under the provision of 4.5.5.4 provided that:

(a) Not more than one cap fails to fire in the functioning phase; or

(b) Not more than one cap fires in the nonfunctioning phase.

The lot shall be rejected if the limits for eligibility for retest are exceeded.

4.5.5.4 Retest. A retest, as provided for in 4.5.5.3, may be made if requested by the contractor, using double the number of samples used in the original test for the phase or phases being retested. The lot shall be considered acceptable provided that in the phase being retested 99 of the 100 caps comply with the applicable requirements.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Unit packages.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:45Z
Check the source to verify that this is the current version before use.

5.1.1.1 Type I caps. Type I blasting caps shall be unit-packaged in metal cans (see 5.1.1.3) in quantities of 50 caps to a can.

5.1.1.2 Types II and III caps. Types II and III caps shall have the lead wires laid in folds in such a manner that the folds will open readily without tangling the wires and shall be placed in individual packages 5 inches or more in length, constructed of chipboard having a thickness of not less than 0.010 inch.

5.1.1.3 Metal cans. The metal can used in packaging type I blasting caps shall be a round container having a diameter of 2-1/8 inches and a body height of 2-11/16 inches (inside height 2-7/16 inches). The body and bottom shall be of 90-pound tin plate, and the cover shall be of 95-pound tin plate. The can shall have the side seam grooved and soldered outside and the compound-lined bottom double seamed to the body. The top of the body shall be curled inward and beaded and shall have a continuous thread between the bead and the top of the body. The cover shall have a continuous thread and shall be knurled and curled and fitted with a waterproof rubber gasket, or equal, 2-1/16 inches in diameter by 3/32 inch in thickness. As an alternative to the continuous thread specified for both the body and cover, an interrupted thread may be used for both the body and cover. The can shall be fitted with a bottom pad, 1-31/32 inches in diameter by 1/32 inch in thickness. At the option of the contractor the can shall also be fitted with a liner, 6-5/16 inches by 2-1/4 inches by 0.016 inch, and a top felt 1-29/32 inches in diameter by 1/16 inch in thickness.

5.1.1.3.1 Finish. The outside of the cans shall be finished in olive drab, except for a plain tin solder margin, and plain tin above the head. The entire inside of the container and cover shall be plain tin.

5.1.1.3.2 Marking for identification. Each metal can shall have the following marking lithographed in yellow print:

Top:

KEEP LID ON TIGHT
U.S. ARMY SPECIAL
(MANUFACTURER'S TRADEMARK)
(MANUFACTURER'S NAME AND ADDRESS)

Front:

50
ORDNANCE CORPS
U.S. ARMY SPECIAL
TYPE I BLASTING CAPS
(NONELECTRIC)
WILL DETONATE COMPOSITION C-3
AND COMPOSITION C-4

Source: https://assist.dla.mil -- Downloaded: 20261O-18T02:45Z
Check the source to verify that this is the current version before use.

Back:

DANGEROUS
HANDLE CAREFULLY
KEEP DRY
KEEP FIRE AWAY

5.1.2 Intermediate packages.

5.1.2.1 Type I caps. Type I unit packages shall be packaged in fiberboard boxes in quantities of 20 unit packages each.

5.1.2.2 Types II and III caps. Type II unit packages shall be packaged in fiberboard boxes in quantities of 50 unit packages each and Type III unit packages shall be packaged in fiberboard boxes in quantities of 10 unit packages each.

5.1.2.3 Boxes. The boxes shall be snug fitting, W-board, interior fiberboard boxes complying with the requirements of PPP-B-636, type SF, class weather-resistant, grade W6s, style FOL, for type 2 load, and closed in accordance with requirements of the appendix thereto.

5.1.2.4 Liners. The unit packages shall be separated with water-resistant fiberboard complying with the requirements of PPP-B-636, grade W6s. Liners shall be used at the sides, ends, top, and bottom of the box, using the same material as specified above, to make a snug fit, if necessary.

5.1.2.5 Marking for identification. Each intermediate box shall be marked or labeled to indicate the item and quantity contained therein as follows:

(QUANTITY)
ORDNANCE CORPS
U.S. ARMY SPECIAL
TYPE II (OR TYPE III) BLASTING CAPS,
ELECTRIC (OR ELECTRIC-SHIELDED)
WILL DETONATE COMPOSITION C-3
AND COMPOSITION C-4

No commercial number designation for the cap shall appear on the box.

5.2 Packing.

5.2.1 Type I caps. Type I intermediate packages shall be packed in lined nailed wood boxes in quantities of 5 packages each.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:45Z
Check the source to verify that this is the current version before use.

5.2.2 Types II and III. Type II intermediate packages shall be packed in lined nailed wood boxes in quantities of 10 packages each, and Type III intermediate packages shall be packed in lined nailed wood boxes in quantities of 1 package each.

5.2.3 Boxes. Nailed wood boxes shall comply with the requirements of PPP-B-621, class 2, style 2, for type 3 load.

5.2.3.1 Liner. Each shipping container shall contain a barrier material complying with the applicable requirements of PPP-B-1055, classes C1, C2(a), E1, E2, H1, H2, H3(a), H4, H5, L2(b), and M1. The liner shall completely inclose the contents of the box. The dimensions of the liner shall be one-fourth inch greater than the interior length and width of the container to avoid tensional strain when the box is tightly packed. The liner shall be securely sealed at all joints, seams, and folds with a water-resistant adhesive. All flaps shall be folded over, and a rectangular piece of similar liner material equal in size to the width and length of the box, shall be coated with a similar adhesive and securely bonded to the top of the sealed case liner for additional protection.

5.2.3.2 Cushioning. The intermediate packages shall be cushioned with dry excelsior, sawdust, or equivalent material. The cushioning material shall be spread over the bottom of the lined box to a depth of at least 1 inch, and at least 1 inch of the cushioning material shall be packed tightly between the interior containers and the sides and ends of the lined box. In addition all voids shall be filled tightly and the box filled to the level of the top with at least 1 inch of cushioning material to provide a tight pack when the box is closed.

5.2.3.3 Closure and strapping. The wood boxes shall be closed and strapped in accordance with the requirements of PPP-B-621 and the appendix thereto. The straps shall be tensioned and sealed but not stapled.

5.3 Marking. Each wood box shall be marked or labeled to indicate the item and quantity contained therein. The exterior shipping containers shall be marked as required by the Code of Federal Regulations 49 CFR 171-178 and DoD 4145.26M to insure safe handling. In addition marking shall be as specified in MIL-STD-129, except as may be modified by the contracting officer.

6. NOTES

6.1 Intended use. The blasting caps covered by this specification are intended for detonating compressed TNT, compressed nitrostarch, Composition C-3, and Composition C-4 explosives.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:45Z
Check the source to verify that this is the current version before use.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification

(b) Type required (see 1.2)

(c) Connector and shorting plug (see 3.3.3)

(d) Standard resistance of the types II and III cap assembly (see 3.5.1)

(e) Grouping for shipment, group size, and corresponding marking, when required (see 4.2.1)

6.3 "Teflon," a product of E. I. du Pont de Nemours and Company, Wilmington, Delaware, has been found satisfactory for making the dish covers used in the moisture content determination of the lead azide (see 4.5.1).

Preparing activity:
Navy - AS
(Project No. 1375-N109)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R355

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE
MIL-C-0014003B(AS) CAPS, BLASTING, SPECIAL

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?
☐ YES ☐ NO (If "Yes", in what way?)

4. REMARKS

SUBMITTED BY (Printed or typed name and address - Optional)

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-18T02:45Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
Naval Air Engineering Center
Philadelphia, PA 19112

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
DEPARTMENT OF THE NAVY
DOD 316

U.S. MAIL

Engineering Specifications and Standards Department (Code X)
Naval Air Engineering Center
Philadelphia, PA 19112

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:45Z
Check the source to verify that this is the current version before use.