MIL-C-14041B(MU)
28 February 1964
SUPERSEDING
MIL-C-14041A(CmlC)
7 October 1957

MILITARY SPECIFICATION

CARRIER, HOSPITAL PROTECTOR HEADPIECE, M12

1. SCOPE

1.1 This specification covers a vinyl plastic bag.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

FEDERAL

FED-STD-406 - Plastics: Methods of Testing .

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage .

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:47Z
Check the source to verify that this is the current version before use.

DRAWINGS

EDGEWOOD ARSENAL

DL5-4-1002 - Carrier, Hospital Protector Headpiece, M12.
(All drawings referenced herein are listed on Drawing DL5-4-1OO2.)

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein , Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Rules

(Application for copies of these freight classification rules should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago 6, Illinois.)

3. REQUIREMENTS

3.1 Materials and components.

3. 1.1 Materials. All materials cited on Drawing DL5-4-1OO2 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings .

3. 1.2 Components. All components of the headpiece carrier shall conform to the specifications and drawings listed on Drawing DL5-4-1002 and subsidiary drawings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:47Z
Check the source to verify that this is the current version before use.

3.2 Manufacture and assembly. The carrier shall be manufactured and assembled in accordance with Drawing D5-4-1002.

3.3 Seam strength. The seams shall withstand a minimum pull of 4.0 pounds when tested as specified in 4.6 at a steady pull rate of 2 riches per minute,

3.4 Workmanship. The headpiece carrier shall have neat, uniform and continuous seams and shall be free from wrinkles, punctures and tears and foreign matter (dirt, oily and viscous material).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection . Supplier's responsibility will be as specified in the contract or order.

4.2 Special provisions.

4.2.1 Alternative inspection. The supplier may utilize any alternative inspection procedures which will provide equal or better assurance of quality by submitting a written proposal with justification and obtaining written approval from the Government prior to instituting the procedure . In case of dispute, the procedures of this specification will govern .

4. 2.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.3 Lotting. A lot shall consist of the carriers produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions. However, no more than one lot of vinyl material shall be represented in any one lot of finished carriers.

4.4 Sampling .

4,4.1 For examination. Sampling shall be conducted in accordance with Standard MIL-STD-l05.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:47Z
Check the source to verify that this is the current version before use.

4.4.2 Destructive tests. Sampling shall be conducted in accordance with Level S-3 of Standard MIL-STD-105.

4.5 Inspection provisions.

4.5.1 For examination. Sample carriers shall be examined in accordance with the classification of defects and Standard MIL-STD-l05.

4.5.2 For destructive tests. Sample carriers shall be tested in accordance with 4.6 and Standard MIL-STD-105 using an AQL of 4.0 percent defective for acceptance.

4.5.3 Classification of defects.

4.5.3.1 Carrier, hospital protector headpiece, Ml2 (Dwg D5-4-1002).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Component missing or incorrectly assembled or location incorrect
102	Size incorrect
103	Marking incorrect
104	Workmanship (see 3 .4)
Minor:	AQL 2.5 percent defective
201	Marking illegible

4.6 Seam strength test. The carrier shall be tested for seam strength in accordance with Method 1011 of Standard FED-STD-406, using one type II specimen (figure 1011A) from each sample carrier . The full width of the seam shall be within the constricted portion of the specimen and the long dimension of the specimen shall be approximately perpendicular to the seam.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:47Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY (For repair parts packaging see 6.3)

5.1 Packaging, level C. Carriers shall be suitably packaged in accordance with the manufacturer's commercial practice for shipment from the supply source to the first receiving activity for immediate use.

5.2 Packing, level C. Carriers packaged as specified in 5.1 shall be packed in a manner to insure carrier acceptance and safe delivery at first domestic destination. Containers shall be in accordance with Uniform Freight Classification Rules or regulations of other carriers applicable to the mode of transportation.

5.3 Marking. In addition to any special marking required by the contract or order, unit and intermediate packages and shipping containers shall be marked in accordance with Standard MIL-STD-l29.

6. NOTES

6.1 intended use. The Ml 2 carrier is intended for use with the M13 and Ml3A1 Hospital Headpieces.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Applicable end item marking.

6.3 Repair parts packaging. When repair parts packaging is required for items authorized for stocking as repair parts, the repair parts packaging data sheets covering the carrier shall be used. (Copies of repair parts packaging data sheets may be obtained from the Director of Engineering and Industrial Services, ATTN: Chief, Design Branch, US Army Edgewood Arsenal , Edgewood Arsenal, Maryland - 21010.)

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 4240-A170Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:47Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:47Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

PECIFICATION

RGANIZATION *(Of submitter)* | CITY AND STATE

ONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT
$

ATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

BMITTED BY *(Printed or typed name and activity)* | DATE

FORM 1426
APR 63

REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE

C-8278

Source: https://assist.dla.mil -- Downloaded: 20260-18T02:47Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:47Z
Check the source to verify that this is the current version before use.