INCH-POUND

MIL-T-14056G
21 November 1988
SUPERSEDING
MIL-T-14056F
30 May 1972

MILITARY SPECIFICATION

TENT LINER, GENERAL PURPOSE, LARGE, FIRE, WATER AND MILDEW RESISTANT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

* 1.1 Scope. This document covers one type of tent liner with cover for use with the large general purpose tent. Permanently attached screen side walls are provided with the tent liner (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8340

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

L-P-378	-	Plastic Sheet and Strip, Thin Gauge, Polyolefin
L-S-125	-	Screening, Insect, Nonmetallic
T-T-871	-	Twine, Cotton, Wrapping
T-T-911	-	Twine, Fibrous, Jute
V-T-285	-	Thread, Polyester
CCC-C-429	-	Cloth, Osnaburg, Cotton
CCC-C-467	-	Cloth, Burlap, Jute (or Kenaf)
DDD-L-20	-	Label; For Clothing, Equipage, and Tentage, (General Use)
PPP-B-601	-	Boxes, Wood, Cleated-Plywood

MILITARY

MIL-W-530	-	Webbing, Textile, Cotton, General Purpose, Natural or in Colors
MIL-L-1709	-	Lines, Tent
MIL-C-2399	-	Cement, Liquid, Tent Patching
MIL-R-3390	-	Rings, Dee
MIL-C-10859	-	Cloth, Oxford, Cotton (Permeable)
MIL-G-16491	-	Grommet, Metallic
MIL-T-43566	-	Tape, Textile, Cotton or Polyester, General Purpose, Natural or in Colors
MIL-W-43638	-	Webbing, Textile, Woven, for Tent Framing
* MIL-W-44049	-	Webbing, Textile and Tape, Textile, Polypropylene, General Purpose, Natural or in Colors

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage

* (Copies of specifications, standards, and handbooks required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of solicitation.

* Department of the Army Field Manual FM 10-16 -
General Repair of Tents, Canvas and Webbing

(Copies may be obtained from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402.)

DRAWINGS

* U. S. ARMY NATICK RESEARCH, DEVELOPMENT & ENGINEERING CENTER

Size		
* D	54-3359	- Tent Cover, for General Purpose Use
D	54-515	- Tent Liner, General Purpose, Large, FWWMR; Illustrations, Views and Sections
D	54-516	- Inside View at Corner and Sections
D	54-517	- Body Assembly
D	54-518	- Body Views and Sections
D	54-519	- End Assembly, Views and Sections
D	54-520	- Side Wall Screen Assembly
D	54-521	- Miscellaneous Details
F	54-523	- Erection Instructions
D	54-524	- Care and Maintenance Instructions
B	54-525	- Packaging Procedure

* (Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of solicitation.

* AMERICAN SOCIETY FOR TESTING AND MATERIALS

D 3951 - Standard Practice for Commercial Packaging

(Copies may be obtained from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

* (Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

* 3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2 and 6.4).

* 3.2 Materials and components. Materials and components shall be as specified herein and on the applicable drawings (see 6.5).

3.2.1 Cloth, oxford, cotton. The cloth for the tent liner shall conform to type I, class 2 of MIL-C-10859.

* 3.2.2 Tape, textile, cotton. The cotton tape shall conform to type I, class 1b, 3/4 inch width of MIL-T-43566. Alternatively the tape shall be polypropylene conforming to type I, class 3 of MIL-W-44049.

* 3.2.3 Webbing, cotton. The cotton webbing shall conform to type II, class 1b, 1-1/2 inch width of MIL-W-530. Alternatively the webbing shall be polypropylene conforming to type II, class 3 of MIL-W-44049.

3.2.4 Webbing, low elongation. The low elongation webbing shall conform to type I, 1 inch width of MIL-W-43638.

* 3.2.5 Thread polyester.

* 3.2.5.1 Liner. The thread for the liner shall be natural and conform to class 1 (sub class A) of V-T-285.

* 3.2.5.2 Cover. The thread for the cover shall conform to type I, class 1, (sub class B) shade S-1, Cable No. 66022 of V-T-285. The dyed thread shall show fastness to weathering equal to or better than the standard shade sample (see 6.3). When no standard shade sample is available the dyed thread shall show good fastness to weathering.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

* 3.2.5.3 Sizes. Thread sizes shall be as follows:

For all stitching on tent liner except stitching indicated by "Z" on drawings and bartacking	Size E for needle and B for bobbin
For all stitching on tent liner indicated by "Z" on drawings	Size E for needle and B for looper
Bartacking	Size E
For all stitching on cover except stitching indicated by "Z" on drawings	Size F for needle and E for bobbin
For all stitching on cover indicated by "Z" on drawings	Size F for needle and E for looper

3.2.6 Screening, nonmetallic. The screening shall conform to type III, class 1 or 2, size 18 x 18, of L-S-125 and the color shall be green.

3.2.7 Film, plastic. The plastic film shall conform to the requirements for 0.0060-inch material, type I, class 1, grade A, B, or C, finish 1 of L-P-378, except that the thickness shall be 0.020 ± 0.004 inch. The requirements for water-vapor permeability, slip, impact resistance, ink adhesion, and heat-seal strength shall not be applicable.

3.2.8 Lines, tent. The tent lines shall conform to MIL-L-1709 in the following types:

Type I	-	for footstop
Type L	-	for eave, lantern and ridge suspension lines (except finished length of line shall be 34 inches)
Type XXI	-	for guy line

3.2.9 Grommet, metallic. The metallic grommets shall conform to type III, class 3, size No. 4 of MIL-G-16491.

3.2.10 Rings, dee. The dee rings shall conform to symbol K, size 1 x 3/4, class 1 or 2, of MIL-R-3390.

3.3 Construction. The construction shall conform to the drawings listed in Section 2 and shall be as specified herein.

Source: https://assist.dla.mil -- Downloaded: 202610-18T02:48Z
Check the source to verify that this is the currentversion before use.

3.3.1 Stitches, machine.

* 3.3.1.1 Types of stitching. All stitching, except bartacking, shall conform to FED-STD-751 as follows:

For all stitching on liner, except stitching indicated by "Z" on drawings	Type 301 - 6 to 8 stitches per inch on liner
For all stitching on liner indicated by "Z" on drawings	Type 401 - 6 to 8 stitches per inch. The chain portion of the stitching shall not appear on the outside of the liner
* Bartacking	Bartack - 5/8 ± 1/16 inch long with 1/8 ± 1/32 inch bight and shall contain 28 stitches
For all stitching on cover, except stitching indicated by "Z" on drawings and bartack	Type 301 - 5 to 7 stitches per inch
For all stitching on cover indicated by "Z" on drawings	Type 401 - 5 to 7 stitches per inch. The chain portion of the stitching shall not appear on the outside of cover

* 3.3.1.2 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched 1/2 inch minimum except when caught in other stitching or turned under in a hem. Thread tension shall be maintained so that there will be no loose stitching resulting in puckering of material sewn. The lock shall be embedded in the material sewn.

* 3.3.1.2.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of one inch behind the end of the stitching. 1/

b. Thread breaks, two or more consecutive skipped stitches or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of one inch before the defective area (1/2 inch on Box, Box and Cross and W-W stitching) and continue a minimum of one inch beyond the defective area onto the existing

Source: https://assist.dla.mil -- Downloaded: 20260-18T02:48Z
Check the source to verify that this is the current version before use.

stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching, without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

* 3.3.1.3 Type 401 stitching. Thread tension shall be maintained so that there will be no loose stitching. Both ends of all seams or stitching produced with a 401 stitch type, when not turned under in a hem or held down by other stitching, shall have a 1/2 to 3/4 inch chain extending beyond each end. The looper (under thread) shall always be on the inside of the tent or cover. All repairs shall be made in accordance with 3.3.1.2.1a or 3.3.1.2.1b. Repairs may be made using a 301 stitch type.

* 3.3.1.4 Automatic stitching. Automatic stitching machines may be used to perform any of the required stitch patterns provided the requirements of the stitch pattern, stitches per inch, size and type of thread are met, and at least three tying, overlapping or backstitches are used to secure the ends of the stitching.

* 3.3.1.5 Thread ends. All thread ends that are visible on the finished item shall be trimmed to a length of not more than 1/4 inch.

* 3.3.1.6 Lubrication of thread. The addition of any lubricant to the polyester sewing thread prior to or during the sewing operation is prohibited.

3.3.1.7 Stitching margins. Unless otherwise specified, all stitch margins shall be 1/8 $\pm$ 1/16 - 0 inch.

3.3.1.8 Bartacking. Bartacking shall be free of thread breaks or loose stitching.

3.3.2 Setting of grommets. Holes punched to receive the grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. The grommets shall be securely clinched without cutting the materials.

* 3.3.3 Splicing of cloth. One splice per roof panel will be allowed and, if performed, shall conform to section B-B of Drawing 5-4-517. Splicing of reinforcement, if performed, shall conform to the following requirements:

a. Eight feet or less - one splice permitted.
More than eight feet, but not not more than 12 feet in length - two splices permitted.
More than 12 feet in length - three splices permitted.

b. The shortest length of any splice shall not be less than 2 feet.

c. Pieces shall be joined as shown on Drawing 5-4-516, Section J-J.

Source: https://assist.dla.mil -- Downloaded: 202640-18T02:48Z
Check the source to verify that this is the currenversion before use.

* 3.3.4 Splicing of webbing. Splicing of webbing will be allowed in the liner roof and other areas, and, if performed, shall conform to Drawing 5-4-520. There shall be a minimum of 5 feet between splices.

* 3.3.5 Fusing of ends of synthetic webbing and tape. All ends of synthetic webbing and tape shall be fused. The apparatus used to fuse the ends shall be capable of providing sufficient heat to provide a smooth edge and with the cut ends of the yarns all fused together. Fusing of the ends shall be accomplished prior to being assembled for stitching.

* 3.3.6 Replacement of defective components. During the spreading, cutting and manufacturing process, components of the tent having material defects or damages that are classified as defects in 4.4.3 or 4.4.4 shall be removed from production and replaced with non-defective and properly matched components.

* 3.3.7 Wicking of sewing thread (cup test). There shall be no dripping of water through the cover stitching when the cover is tested as specified in 4.5.1. The cup test is intended to insure that non-wicking thread has been utilized and that no lubrication has been added to the polyester thread prior to or during the sewing operation.

* 3.3.8 Repairs. Any necessary repairs shall be effected in accordance with Department of the Army Field Manual FM 10-16, except that handsewn patches, or cemented patches other than as specified herein, will not be acceptable. Cemented patches on holes, cuts or tears not more than 1 inch in diameter or length, using the cement specified in MIL-C-2399, shall be permitted. A patch shall be large enough to overlap the damaged area with a margin of at least 3/4 inch on all sides. Cemented patches shall not be applied over seams or hardware area. A maximum of three cemented patches per liner shall be allowed, without prior authorization for the contracting officer. All other repairs shall require contracting officer authorization.

3.4 Marking. All marking and labels shall conform to DDD-L-20.

* 3.4.1 Identification label. Identification labels shall conform to type VI, class 6, and shall be 3-1/2 inches by 5-1/2 inches minimum with a blank space of at least 1-1/4 inches provided on the bottom of the label for the Department of Defense inspector's stamp. Identification labels shall be stitched to the tent liner and cover in the locations shown on the drawings.

* 3.4.2 Erection and care and maintenance instruction labels. Labels of erection instructions and care and maintenance instructions shall conform to type VI, class 7, and shall be stitched to the tent liner and cover in the locations shown on the drawings. The labels shall be proportionate copies of Drawings 5-4-523 and 5-4-524 as reproduced from a glossy print of the applicable drawing furnished by the contracting officer. The size of the labels shall be, borderline to borderline, 15 $\pm$ 1/4 inches in the longer dimension with a minimum 1/2 inch margin outside of the borderline on all sides.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

3.4.3 Special marking. The letters "US" on the tent liner and cover, and the special markings on the cover shall conform to type IV, class 9, in the size characters and in the locations shown on the drawings. Class 9 markings shall be clearly legible after subjection to accelerated weathering.

* 3.5 Workmanship. The liner shall conform to the quality of product established by this document and the occurrence of defects shall not exceed the applicable acceptable quality levels. Cloth components shall be clean and free of holes, cuts, tears, or cloth defects such as multiple floats or broken or missing yarn. Thread tension shall be maintained so that there will be no loose stitching, and seam allowances shall be maintained with seams properly sewed so that no runnoffs, twists, pleats or open seams shall result. Care shall be taken to see that no needle chews occur. Webbing and tape shall not have frayed or scalloped edges. Rope components shall be free of cuts or breaks. Metal components shall be free of burrs, sharp edges or corroded areas and shall not be broken or malformed.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

* 4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-18T02:48Z
Check the source to verify that this is the current version before use.

* 4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

* 4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3 and 4.4.4. The presence of any defect shall be cause for rejection of the first article.

* 4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

* 4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

* 4.4.2 In-process inspection. Inspection shall be made of the following operations or assemblies to establish conformance to specified requirements. Whenever nonconformance is noted, correction shall be made to the items affected and to the operation. Items which cannot be corrected shall be removed from production.

a. There shall be no lubrication of polyester thread prior to or during sewing operations in compliance with 3.3.1.6.

b. Holes punched to receive grommets are in compliance with 3.3.2.

* 4.4.3 End item visual examination.

* 4.4.3.1 Tent liner with cover. The end item shall be in an erected position so that both the inside and outside of the liner can be examined, along with its cover, for defects listed in table I. The lot size shall be expressed in units of liners with covers. The sample unit shall be one tent liner with cover. The inspection level shall be I, and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 25 for major defects, 65 for major and minor A combined defects and 150 for total (major, minor A and minor B combined) defects.

* 4.4.3.2 Cover only. The end item shall be in position so that both the inside and outside of the cover can be examined for defects listed in table I. The lot size shall be expressed in units of covers. The sample unit shall be one cover. The inspection level shall be I, and the AQL, expressed in terms of defects per hundred units, shall be 10 for major defects, 15 for major and minor A combined defects and 40 for total (major, minor A and minor B combined) defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor A	Minor B
Fabric	Cut, tear or hole:			
	- greater than 1/4 inch in length or diameter	X		
	- greater than 1/8 inch but not greater than 1/4 inch in length or diameter		X	
	- more than 5 holes 1/8 inch or less in length or diamter			X
	Broken or missing yarns, multiple floats clearly visible at normal inspection distance (approximately 3 feet)		X	
	NOTE: Any open place larger than 1/8 inch shall be classified under cut, tear or hole.			
* Screening	Mesh openings larger than specified	X		
	Cut or tear:			
	- more than 2 inches in length	X		
	- more than 1/4 but less than 2 inches in length		X	
	- less than 1/4 inch in length			X
Tape and webbing	Edge frayed or scalloped			X
Rope components	Any cut, any break		X	
	Eye splice omitted		X	
	Eye splice not as specified		X	
	Line not spliced through eave chape, pole opening loop or ridge suspension line		X	
	Free end not finished as specified			X
Hardware	Broken	X		
	Malformed:			
	- fails to perform intended function	X		
	- but will perform intended function		X	
	Corroded area			X
	Burr or sharp edge which may cause injury in handling or damage to fabric	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Grommets	Improperly set; two or more teeth exposed (except where grommet is set as specified but is in an area of uneven thickness which prevents uniform clinching)			X
	Clinched loosely, allowing grommet to rotate in hole			X
	Clinched excessively tight, cutting fabric:			
	- on liner	X		
	- on cover		X	
	Insecurely clinched, i.e., grommet or washer becomes disengaged:			
	- on liner	X		
	- on cover		X	
	Ridge grommet set with rim extending beyond edges of grommet reinforcement webbing		X	
Seams and stitching	Open seam on stitch type 301:			
	- for more than 1/4 inch but not more than 1 inch		X	
	- for more than 1 inch	X		
	Open seam on stitch type 401:			
	- one row of stitching open for 1 inch or less			X
	- one row of stitching open for more than 1 inch	X		
	- both rows of stitching open (not necessarily at the same location)	X		
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken, or when two or more skipped or run-off stitches occur. On double stitched seams, a seam shall be classified as open when either one or both sides of a seam are open.			

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Seams and stitching (cont'd)	Raw edges caught in stitching:			
	- more than 1 inch but not more than 3 inches			X
	- more than 3 inches		X	
	Pleated seams			X
*	Thread breaks:			
	- overstitched less than 1 inch on stitch type 401 or 301			X
	NOTE: Thread breaks not overstitched shall be classified as open seams.			
*	Skipped stitches:			
	- overstitched less than 1 inch on stitch type 401 or 301 (when 2 or more skipped stitches occur consecutively)			X
	NOTE: Skipped stitches not overstitched shall be classified as open seams.			
	Needle chews resulting in cut, tear or hole (see cut, tear or hole under Fabric examination).			
	One or more required rows of stitching omitted (except on boxstitching)	X		
Boxstitching	Incomplete:			
	- one row of stitching omitted		X	
	- two or more rows of stitching omitted	X		
Bartacking	Less than specified length by more than 1/8 inch		X	
Seam type	Wrong seam type	X		
Stitch type	Wrong stitch type	X		

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Stitch tension	Loose, resulting in an exposed bobbin or top thread for more than 6 inches		X	
	Tight, as evidenced by puckering of seam for more than 6 inches		X	
Stitch per inch	Less than minimum specified (except on panel joining seams):			
	- one stitch			X
	- two or more stitches		X	
	Less than minimum specified on panel joining seams		X	
	More than maximum specified:			
	- one stitch			X
	- two or more stitches		X	
	NOTE: Variation in the number of stitches per inch, caused by the operator speeding up the machine in order to sew over heavy places or heavy seams or in turning corners, shall be classified as follows:			
	a. Within the minor "A" defect classification - minor "B" defect			
	b. Within the minor "B" defect classification - no defect			
Stitching gage	Not as specified		X	
Stitching margin	Larger than specified:			
	- for less than 4 inches in length			X
	- for 4 inches or more in length		X	
	Less than specified:			
	- for more than 2 inches but not more than 4 inches in length			X
	- for more than 4 inches in length		X	

Source: https://assist.dla.mil -- Downloaded: 20261O-18T02:48Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
* Stitching ends	Overstitched less than 1/2 inch on stitch type 301 (except where ends are held down by other stitching, turned under in a hem, or where stitching is performed automatically)			X
	Secured with less than 3 tying, overlapping or backstitches when automatic stitching is performed			X
Stitching indicated by "Z" on drawings	Chain portion of stitching shows on outside of liner or cover		X	
Mends, darns or patches	Repairs not in accordance with Department of the Army Field Manual FM 10-16 and not authorized by contracting officer (see 3.3.8)	X		
Components and assembly	Any component not fabricated of applicable referenced material	X		
	Any component or operation omitted, unless otherwise specified herein	X		
Construction details:				
Hems	Constructed with partial turnunder when double turnunder is required		X	
	Twisted or pleated			X
Reinforcements	Improperly applied, causing excessive fullness on reinforcement or reinforced parts			X
Binding	Improperly or loosely applied			X
	Ends not finished as specified			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Construction details: (cont'd)				
* Cloth splicing	More than one splice per roof panel	X		
	Number of splices per reinforcement more than specified		X	
	Spliced pieces not joined as shown on Drawing 5-4-517		X	
	Length of spliced pieces less than specified		X	
* Splicing of webbing	Splicing (when necessary) not made as indicated on Drawing 5-4-520		X	
	Distance between splices less than specified		X	
Screen wall	Ends of sod cloth caught in stitching attaching screen sidewall to end wall			X
	Top edge of screen or top end of screen reinforcement webbing not caught in both rows of stitching attaching eave reinforcement webbing to body eave		X	
	Webbing reinforcements set on inside of wall in lieu of outside		X	
	Sod cloth set on outside	X		
Corner lugs	Top or bottom ends of lugs stitched together, failing to provide clearance for side walls		X	
	Any part of lugs single ply construction in lieu of double ply		X	
Window panes	Film not securely caught in stitching attaching reinforcement webbing to opening:			
	- for more than 1 inch, but not more than 3 inches			X
	- for more than 3 inches		X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Construction details: (cont'd)				
Roof and ridge, inside	End of ridge reinforcement webbing not looped at pole opening		X	
	Folded edge of end roof reinforcement not looped at ridge and pole opening		X	
	End of side roof reinforcement webbing not caught in binding around pole opening or in eave reinforcement		X	
Tie tapes	One missing per body or end section		X	
	Two or more missing per body or end section	X		
General	Any other construction detail not performed as specified		X	
Labels	Omitted, incorrect, illegible or misplaced:			
	- erection or maintenance instructions		X	
	- identification			X
Marking: U.S. and nomenclature	Omitted, incorrect, illegible or misplaced			X
Cleanness	Grease or oil stains			X
	Thread ends not trimmed throughout to 1/4 inch or less			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

* 4.4.4 End item dimensional examination.

* 4.4.4.1 Liner with cover. The end item shall be in an erected position so that both the inside and outside of the tent liner can be examined, along with its cover, for defects listed in table II. The lot size shall be one expressed in units of tent liners with covers. The sample unit shall be one tent liner with cover. The inspection level shall be S-4, and the AQL, expressed in terms of defects per hundred units, shall be 6.5 for major defects, 15 for major and minor A combined defects and 40 for total (major, minor A and minor B combined) defects.

* 4.4.4.2 Cover only. The end item shall be in position so that both the inside and outside of the cover can be examined for defects listed in table II. The lot size shall be expressed in units of covers. The sample unit shall be one cover. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects, 6.5 for major and minor A combined defects and 25 for total (major, minor A and minor B combined) defects.

TABLE II. End item dimensional defects

Examine	Defect	Classification Major	Minor A	Minor B
Overall dimensions of liner	Smaller than specified dimensions less applicable minus tolerance indicated on drawings	X		
	Larger than specified dimensions and applicable plus tolerance indicated on drawings			X
Dimensions of cover, location and component dimensions (unless otherwise specified)	Smaller than specified dimensions less applicable minus tolerance indicated on drawing, but not smaller than specified dimensions less twice the applicable minus tolerance			X
	Smaller than the specified dimensions less twice the applicable minus tolerance indicated on drawing		X	
	Larger than specified dimensions and applicable plus tolerance indicated on drawing (except cover)			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

TABLE II. End item dimensional defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Pole openings	Larger or smaller than specified dimensions by more than 1/2 inch			X
Hems	Hems required to finish less than 3/4 inch in width: - less than specified			X
	Hems required to finish 3/4 inch or more in width: - less than specified by more than 1/4 inch			X
Webbing, tie tapes, and wall ties	Finished length less than specified by more than 1 inch			X
	Turn under at ends of ridge webbing forming loops at pole opening less than specified: - by more than 1/2 inch but not more than 1-1/2 inches			X
	- by more than 1-1/2 inches		X	
Rope components	Eye less than specified by more than 1/2 inch		X	
	Finished length less than specified by more than 2 inches		X	
Reinforcements	Finished dimensions of reinforcements less than specified by more than 1/2 inch			X
	Ridge grommet reinforcement off center of roof section (between pole cut outs) by more than 2 inches			X
Reinforcement webbing	Edges of doorway, ventilator, window or or stovepipe opening webbing misplaced by more than 1/8 inch			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

TABLE II. End item dimensional defects (cont'd)

Examine	Defect	Classification Major	Minor A	Minor B
Sod cloth	Finished width of sod cloth less than specified by 1 inch or more			X
Screen wall	Center line of vertical webbing out of alignment with eave grommets by more than 1/2 inch		X	
Window openings	Vertical centerline of window openings out of alignment with roof reinforcement webbing by more than 1/2 inch		X	
Stovepipe opening	Any stovepipe openings less than 15-1/2 by 15-1/2 inches or more than 17 inches by 17 inches		X	
Grommets	Grommets on bottom of screen wall at location of vertical reinforcement webbing set off center of reinforcement webbing by more than 1/2 inch		X	
	Intermediate grommets on bottom of screen wall unequally spaced by more than 2 inches			X
	End grommet on screen wall set with rim extending beyond folded edge of sod cloth by 1/4 inch or more			X
	Any eave grommet set out of alignment with roof webbing reinforcement by more than 1/2 inch		X	
	Ridge grommet set less than 3/4 inch or more than 1-3/4 inches from ridge line		X	
	Cover grommet set less than 1 inch from corners or off center of hem by more than 1/2 inch			X

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

* 4.4.5 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified.
Workmanship	Inadequate application of components, such as incomplete closure of cloth wrapping and loose stitching
Content	Number per container is more or less than required.

* 4.5 Methods of inspection.

* 4.5.1 Wicking of sewing thread (cup test). The cover shall be tested at the panel seams as follows: Suspend the seamed section of the test fabric in the center of a 6 + 1/8 inch diameter hoop and form a depression with the seamed fabric in the hoop to a depth of 1 ± 1/4 inch. Slowly pour 500 mL of water at 77°F ± 4°F into the cupped area (depression) and observe the under surface of the fabric for water penetration. Any wicking of water along the sewing thread, identified by a discoloration or darkening of the thread within five minutes after water is poured, shall constitute a failure. Water leakage through the needle holes or between the plies of the lapped seamed fabric shall not be considered a failure.

* 5. PACKAGING

* 5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Tent liner with cover. Each tent liner shall be folded and packaged within the cover provided in accordance with Drawing 5-4-525.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

5.1.1.2 Tent liner covers. Each tent liner cover shall be compactly folded so that the identification markings are clearly visible. The folded cover shall measure approximately 18 x 24 inches. All tie lines shall be placed within the folds. Five folded covers shall be stacked and cross-tied with cotton tape or twine.

* 5.1.2 Commercial. Each tent liner with a cover or five folded and tied covers only shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B or Commercial as specified (see 6.2).

* 5.2.1 Level A packing.

5.2.1.1 Tent liners with covers. Tent liners, preserved as specified in 5.1, shall be packed in a snug-fitting wood-cleated plywood shipping container conforming to overseas type, style A or PPP-B-601. Each container shall be provided with skids in accordance with gross weight requirements as specified in the container specification. Each shipping container shall be closed and reinforced with flat strapping in accordance with the appendix of the container specification.

5.2.1.2 Tent liner covers. Tent liner covers preserved as specified in 5.1 shall be packaged in a snug-fitting cleated plywood shipping container as specified in 5.2.1.1.

* 5.2.2 Level B packing. One tent liner with cover or ten tent liner covers only, preserved as specified in 5.1, shall be wrapped in cotton osnaburg cloth conforming to class 2 of CCC-C-429; or burlap cloth conforming to class 3 of CCC-C-467. The wrapping shall be securely hand sewn with type I or II, 16-ply cotton twine conforming to T-T-871, or type I, size No. 2 jute twine conforming to T-T-911, with approximately one stitch to the inch and every third stitch knotted. Alternatively, the seams of the wrap may be machine-sewn. A minimum of five inches of wrapping material, or tubing, shall be gathered together on each of the four corners and securely sewn into ears for handles. The polyester thread used to manufacture the end items may be used for effecting the machine sewn closure of the wrapping or tubing.

* 5.2.3 Commercial packing. Tent liners with covers or tent liner covers only, preserved as specified in 5.1 shall be packed in accordance with ASTM D 3951.

* 5.3 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and cloth covered bundles shall be marked in accordance with MIL-STD-129 or ASTM D 3951 as applicable.

5.3.1 Additional marking. The following shall be stenciled or printed on each shipping container or cloth covered bundle in characters not less than 3/4 inch high:

"SEE ERECTION INSTRUCTIONS SEWED TO INSIDE OF TENT COVER"

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The tent liner covered by this document is designed to be used with Tent, General Purpose, Large, to provide insulation. In hot weather, the tent and tent liner side walls can be rolled up, exposing the attached screen side of the liner, thus providing increased ventilation of the tent.

* 6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this document.
b. When a first article is required (see 3.1, 4.3 and 6.4).
c. Selection of the applicable levels of preservation and packing (see 5.1 and 5.2).

* 6.3 Samples. For access to samples, address the contracting activity issuing the invitation for bids.

* 6.4 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.5 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of this document (see 3.2).

* 6.6 International standardization agreements. Certain provisions of this document are the subject of international standardization agreement as cited in NATO, STANAG No. 2882, relative to camouflage requirements for tents, shelters and subsidiary components. When amendment, revision, or cancellation of this document is proposed which will affect or violate the international agreement concerned, the contracting activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

* 6.7 Subject term (key word) listing.

Liner
Tent, GP, Large

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

* 6.8 Changes from previous issue. The margins of this document are marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content, irrespective of the marginal notations and relationship to the previous issue.

Custodians:

Army - GL
* Navy - NU
* Air Force - 99

Review activities:

Army - MD
* Air Force - 82
* DLA - CT

User activities:

Navy - YD
* Air Force - 45

Preparing activity:

Army - GL

Project No. 8340-0516

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-14056G	Tent Liner, General Purpose, Large, Fire, Water and Mildew Resistant

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T02:48Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use i submitting comments and suggestions for improvements. All users of military standardization documents are in:ited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 202640-18T02:48Z
Check the source to verify that this is the currentversion before use.