MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6CG7

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Twin triode, miniature, medium Mu

Outline --- 6-3 (EIA)

Base --- E9-1

Envelope --- T6-1/2

Cathode --- Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7	8	9
Element	---	2p	2g	2k	h	h	1p	1g	1k	internal shield

ABSOLUTE RATINGS:

Parameter:	Ef	Eb	Ec	Pp/p	Pp (total)	Rgl	Ehk	Ib/b	Alt
Unit:	V	Vdc	Vdc	W	W	Meg	v	mAdc	ft
Maximum:	6.9	300	---	3.85	5.5	1.1	100	22.0	(see note 5)
Minimum:	5.7	---	---	----	---	---	---	0.5	
TEST CONDITIONS:	6.3	250	-8	----	---	---	0	----	---

GENERAL

Qualification - Required

(B) Denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:08Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS		UNIT
						Min	Max	
	Quality conformance inspection, part 1							
1266	Total grid current	See notes 1 and 4	0.65	II	Ic	0	-2.0	µAdc
1231	Emission	Eb = Ec = 30 Vdc See note 2	0.65	II	Is	50	---	mAdc
1306	Transconductance (1)	See notes 2 and 4	0.65	II	Sm	2,075	3,125	µmhos
1246	Audio frequency noise	Esig = 70 mVac; Rp = 10,000 ohms See notes 1 and 3	0.65	II	---	---	---	---
1201	Short and discontinuity detection		0.4	II	---	---	---	---
	Quality conformance inspection, part 2							
1211	Insulation of electrodes	See note 2	4.0	L6	R	100	---	Meg
1301	Heater current		6.5	L6	If	550	650	mA
2126	Glass strain		4.0	I	---	---	---	---
1121	Base strain		---	---	---	---	---	---
1336	Heater-cathode leakage	See note 2	6.5	L6	Ihk	---	10	µAdc
1256	Electrode current (1) (anode)	See note 2	6.5	L6	Ib	5.5	12.5	mAdc
1256	Electrode current (2) (anode)	Ec = -27 Vdc See note 2	6.5	L6	Ib	---	20	µAdc
1306	Transconductance (2)	Eb = 90 Vdc; Ec = 0 See note 2	6.5	L6	Sm	2,400	3,600	µmhos
1316	Amplification factor	See note 2	6.5	L6	Mu	18	23	---
1031	Low-frequency vibration	Rp = 3,000 ohms See note 1	2.5	I	Rp	---	200	mVac
(R)	Quality conformance inspection, part 3							
1501	Intermittent life	Group A; Ehk = 100 V	---	---	---	---	---	---
	Life-test end points: (intermittent) (500 hours)							
1306	Transconductance (1)		---	---	Sm	1,550	---	µmhos
1266	Total grid current		---	---	Ic	0	-6.0	µAdc

Source: https://assist.dla.mil -- Downloaded: 202610-15T14:08Z
Check the source to verify that this is the current version before use.

NOTES:

1. Tie 1k to 2k; 1g to 2g; 1p to 2p.
2. Test each unit separately.
3. The rejection level shall be set at the VU meter reading obtained during calibration.
4. This test to be performed at the conclusion of the holding period.
5. See "Reduced pressure (altitude)" and "Altitude, maximum peak voltage."

Custodian:
Army - EL
Navy - EC
Air Force - 85

Preparing activity:
Air Force - 85

(Project No. 5960-3125)

Review activities:
Army - EL
Navy - EC
Air Force - 99
DSA - ES

User activities:
Army - ME
Navy - AS, OS, MC, CG
Air Force - 11

*U.S. GOVERNMENT PRINTING OFFICE: 1977—703-020/2736

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:08Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:08Z
Check the source to verify that this is the current version before use.