MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

© 1/ TYPE 1X2C

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Rectifier, miniature, half wave, vacuum

Outline	---	6-7(EIA)
Envelope	---	T6-1/2
Base	---	E9-1
© Cap	---	C1-2, C1-33, or C1-45 (skirted miniature)
Cathode	---	Coated filament

Base connections: See note 1

Pin No.	---	1	2	3	4	5	6	7	8	9	Cap
Element	---	-f, sd	+f	nc	-f, sd	+f	-f, sd	nc	-f	-f, sd	a

© ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	epx	Rf	Cf	Io	ib	x-radiation	Alt
Unit:	V	kv	Meg	pF	mAdc	ma	mr/hr	ft
Maximum:	1.45	22	---	---	1.6	15.0	0.5 (see note 3)	10,000 (see note 2)
Minimum:	1.05	---	---	---	---	---	---	---
TEST CONDITIONS:	1.25	20	7	4,000	1.5	11.0	---	---

© GENERAL:

Qualification - Not required

1/ Replaces tube type 1X2B

© denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:10Z
Check the source to verify that this is the current version before use.