MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 5784WB

This amendment forms a part of Military Specification Sheet MIL-E-1/1096D, dated 24 February 1981, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

Quality conformance inspection, part 3, Method 1501, Intermittent life, Notes column: Delete "7" and substitute "7,11". Also, Conditions column: Delete "TA = room" and "Group E".

NOTES, add the following note:

"11. The life-test sample shall consist of 20 tubes per lot and not more than 1 tube failure shall be permitted. In the event of rejection of the first sample, a second sample of 40 tubes shall be selected from the lot. Acceptance shall then be based on the combined first and second samples and shall not exceed a total of three tube failures."

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - MI
Air Force - 99
DLA - ES

User activities:
Army - AR, ME
Navy - AS, OS, MC, CG
Air Force - 11

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5960-3280-5)

★ U.S. GOVERNMENT PRINTING OFFICE: 1982—505-022/1050 2-1

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:08Z
Check the source to verify that this is the current version before use.