DDD-L-20b
November 22, 1961

SUPERSEDING
Int. Fed. Spec. DDD-L-0020a (ARMY-QMC)
November 10, 1959 and
Fed. Spec. DDD-L-20
September 25, 1957
(see 6.3)

FEDERAL SPECIFICATION

LABEL; FOR CLOTHING, EQUIPAGE, AND TENTAGE, (GENERAL USE)

This specification was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

1. SCOPE AND CLASSIFICATION

1.1 Scope. This specification covers the requirements of four types of labels, utilized in fabricated textile, plastic, and leather items.

1.2 Classification.

1.2.1 *Types and classes.*—The labels shall be of the following types and classes, as specified (see 6.2 and 6.5).

Type I.—Label, cloth, cotton, permanent coated, printed.

Type II.—Label, cloth, cotton, permanent coated, mildew resistant treated, printed.

Type III.—Marking, heat transfer (decalcomania).

Type IV.—Marking, direct printing, stamping or stenciling.

Class 1.—Identification label for garments.
Class 2.—Size label for garments.
Class 3.—Instruction labels for garments.
Class 4.—Combination identification and size label for headwear, neckwear and handwear.
Class 5.—Identification label for equipage.
Class 6.—Identification label for tentage.
Class 7.—Instruction label for tentage.
Class 8.—Identification label for paulins and covers.
Class 9.—Special markings.
Class 10.—Personal identification label.
Class 11.—Identification label for aerial delivery items.

2. APPLICABLE SPECIFICATIONS AND STANDARDS

2.1 The following specifications and standards, of the issues in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

Federal Specifications:

O-P-191—Perchloroethylene (Tetrachlorethylene); technical grade.
P-S-580—Soap, Laundry Chip.
P-S-661—Solvent, Dry-cleaning.
UU-T-111—Tape; Paper, Gummed (Sealing and Securing).
CCC-T-191—Textile Test Methods.
PPP-B-566—Boxes, Folding Paperboard.
PPP-B-636—Box, Fiberboard.
PPP-B-676—Boxes, Set-up, Paperboard.
PPP-T-60—Tape; Pressure Sensitive Adhesive Waterproof for Packaging and Sealing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:31Z
Check the source to verify that this is the current version before use.

Federal Standards:

Fed. Std. No. 102—Preservation, Packaging, and Packing Levels.
Fed. Std. No. 123—Marking for Domestic Shipment (Civilian Agencies).

(Activities outside the Federal Government may obtain copies of Federal Specifications, Standards, and Handbooks as outlined under General Information in the Index of Federal Specifications, Standards, and Handbooks and at the prices indicated in the Index. The Index, which includes cumulative monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U. S. Government Printing Office, Washington 25, D. C.

(Single copies of this specification and other product specifications required by activities outside the Federal Government for bidding purposes are available without charge at the General Services Administration Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C.

(Federal Government activities may obtain copies of Federal Specifications, Standards, and Handbooks and the Index of Federal Specifications, Standards, and Handbooks from established distribution points in their agencies.)

Military Specification:

MIL–L–10547—Liners, Case, Waterproof.

Military Standards:

MIL–STD–105—Sampling Procedures and Tables for Inspection by Attributes.
MIL–STD–129—Marking for Shipment and Storage.

(Copies of Military Specifications and Standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Standard sample. Unless otherwise specified, the labels and markings shall be equal to the standard sample in respect to legibility, quality of printing, fastness of printing, durability of finish and, where applicable, in the ability to accept writing (see 6.6).

3.2 Materials.

3.2.1 *Type I label, cloth, cotton, permanent coated, printed.*

3.2.1.1 *Fabric.* The basic fabric for the label shall be cloth, cotton, print, bleached white. The finished coated fabric shall have not less than 80 ends per inch in the warp and 72 picks per inch in the filling when tested as specified in 4.2.4.

3.2.1.2 *Coating.* The fabric shall be impregnated or surface coated with a synthetic resin or rubber, suitably compounded and pigmented, to conform to the performance requirements for the finished labels. The printed surface of the classes 3 and 7 instruction labels and class 11 identification label shall be impregnated or surface coated with the finishing compound after printing. The following materials shall not be used in the coating or impregnating formulations.

Thermoplastic polyvinyl butyral resin.
Proteins and their derivatives.
Starch.
Hydrophilic oils and resins.
Rosin.
Sulfur compounds.

The finished labels shall be free from objectionable odor and shall have a relatively smooth surface.

3.2.1.3 *Blocking.* The labels shall not block to an extent greater than represented by scale rating No. 2 when tested as specified in 4.2.4.

3.2.1.4 *Weight of fabric.* The weight of the coated finished fabric used for the labels shall be not less than 3.6 nor more than 4.8 ounces per square yard when tested as specified in 4.2.4. A ten percent plus tolerance over the maximum weight will be allowed for the type I or II, classes 3 and 11 labels, due to the additional coating or impregnating required after printing.

3.2.1.5 *Color.* The color of the finished labels shall be bleached white.

3.2.1.6 *Printing medium.* The labels shall be printed with a black marking medium. The initial printing shall be legible and shall not show off-setting, smearing, or bleeding.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:31Z
Check the source to verify that this is the current version before use.

3.2.2 *Type II label, cloth, cotton, permanent coated, mildew resistant, printed.* Type II labels shall conform to all the requirements specified for type I labels and, in addition, shall be mildew-resistant treated with 1.35 ± 0.25 percent 2, 2′ methylene bis (4-chlorophenol) by weight of the coated fabric applied either to the base cloth or to the coating or both. The mildew-inhibitor content shall be determined as specified in 4.2.4, and the finished cloth shall not support mildew growth when tested as specified in 4.2.4.

3.2.3 *Type III marking, heat transfer (decalcomania).* Heat transfer (decalcomania) markings shall be applied by a dry-heat transfer process. The initial print shall be well defined, clearly legible, and shall not show smearing, bleeding, or off-setting and shall not show objectionable strike-through of the fabric to which applied. Unless otherwise specified, the printing shall be black.

3.2.4 *Type IV marking, direct printing, stamping or stenciling.* Unless otherwise specified, type IV markings shall be applied to the fabric by a black marking medium. The initial print shall be well defined, clearly legible, and shall not show smearing, bleeding or off-setting and shall not show objectionable strike-through of the fabric to which applied.

3.3 Printing.

3.3.1 *Print type.* All classes of labels shall be printed with Gothic, sansserif type. Italic or script type shall not be used. All printing shall be in capitals except instruction labels as specified in 3.3.2.3.

3.3.2 Unless otherwise specified, all classes of labels shall be printed with the contents, and in the format and size of print specified below. Unless otherwise specified, the space between lines shall be not less than the following for the size specified (exclusive of space resulting from type shoulder):

6- through 16-point type sizes incl.—space 2 points

18- through 36-point type sizes incl.—space 4 points

For all type sizes larger than 36 points—space 6 points

The end item description to be utilized in the labels shall be as specified in the applicable end-item specification or procurement document.

3.3.2.1 *Class 1, identification label for clothing items.* The contents, size of characters of the inscription, and the format of class 1 labels shall be as follows (see 6.4):

Item description	Minimum 10 point	(Approx. ⅛ inch)
Contract number	Minimum 8 point	(Approx. 3/32 inch)
Wool and/or Fiber Products Act Information	Minimum 8 point	(Approx. 3/32 inch)

(*Note:* The Wool Products and Fiber Products Acts information shall not be included unless specified in the applicable procurement document.)

3.3.2.2 *Class 2, size label for clothing items.* The contents, size of characters of the inscription, and the format of class 2 labels shall be as follows when the size is expressed adjectively (see 6.4):

Size	Minimum 10 point	(Approx. ⅛ inch)
Stock number	Minimum 8 point	(Approx. 3/32 inch)

When the size is expressed numerically, the size shall be printed in characters a minimum of 18 point (approximately ¼ inch in height) with fractions of comparable size.

3.3.2.3 *Class 3, instruction labels for clothing items.* The contents, size of characters of the inscription and the format of class 3 labels shall be as follows (see 6.4):

Item description	Minimum 10 point	(Approx. ⅛ inch)
Body of instructions	Minimum 8 point	(Approx. 3/32 inch)
Warnings or special notations	Minimum 10 point	(Approx. ⅛ inch)

The content of the instruction labels shall be as specified in the applicable specification or procurement document. The item description and warning or special notations shall be printed in capitals. The body of the instructions shall be in capitals and lower-case characters as shown by the example in the applicable end-item specification or procurement document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:31Z
Check the source to verify that this is the current version before use.

3.3.2.4 *Class 4, combination identification and size label for headwear, neckwear and handwear.* The contents, size of characters of the inscription, and format of class 4 labels shall be as follows:

Item description Contract number Stock number Wool and/or Fiber Products Acts Information	Size

The item description and the size, when indicated adjectively, shall be in characters not less than 8 point (approximately $\frac{3}{32}$ inch) in height, and the contract number, stock number, and Wool and Fiber Products Acts information in characters not less than 6 point (approximately $\frac{1}{16}$ inch) in height. When the size is expressed numerically, the height of the numerals shall be a minimum of 18 point (approximately $\frac{1}{4}$ inch) in height with fractions of comparable size.

(*Note:* The Wool Products and Fiber Products Acts information shall not be included unless specified in the applicable procurement document.)

3.3.2.5 *Class 5, identification label for equipage.* The contents, size of characters of the inscription, and the format of class 5 labels shall be as follows:

Item description	Minimum of 18 point	(Approx. ¼ inch)
Contract number	Minimum of 18 point	(Approx. ¼ inch)
Stock number	Minimum of 18 point	(Approx. ¼ inch)
Size (when specified)	Minimum of 18 point	(Approx. ¼ inch)

3.3.2.6 *Class 6, identification label for tentage.* The contents, size of characters of the inscription and the format of class 6 labels shall be as specified for class 5 labels.

3.3.2.7 *Class 7, instruction labels for tentage.* The contents, size of characters, and the format of class 7 labels shall be as specified in the applicable procurement document or end-item specification.

3.3.2.8 *Class 8, labels for paulins and covers.* The contents and the format of class 8 labels shall be as specified for class 5 labels. The size of characters for the size and class (when applicable) shall be 1½ inches minimum height. The item identification, contract number, and stock number shall be in characters a minimum of ½ inch in height.

3.3.2.9 *Class 9, special labels and markings.* The contents, size of marking, and format of class 9 labels shall be as specified in the applicable procurement document or end-item specification.

3.3.2.10 *Class 10, personal identification label.* The contents, size of characters of the inscription, and the format of class 10 labels shall be as follows:

Name	Minimum 10 point	(Approx. ⅛ inch)
Service No.	Minimum 10 point	(Approx. ⅛ inch)

When specified, the class 10 labels shall be combined with the class 1 label. When the combination is specified, the information required by the class 10 label shall precede the information required of the class 1 label.

3.3.2.11 *Class 11, identification label for aerial delivery items.* The contents, size of characters of the inscription, and format of class 11 labels shall be as specified in the applicable procurement document or end-item specification.

3.4 Label size. The size of the labels shall be as specified in the applicable end-item specification or procurement document and shall be governed by the contents and size of characters of the inscription (see 6.2). A tolerance of plus or minus $\frac{1}{16}$ inch in length and width on the size specified will be permitted.

3.4.1 *Type I and type II labels.* Type I and type II labels shall be provided with a minimum $\frac{3}{16}$-inch blank margin on all four sides for sewing purposes.

3.5 Fastness of printing.

3.5.1 *Classes 1, 2, 3, and 4 labels.* For classes 1, 2, 3, and 4 labels, the intended use of the item,

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:31Z
Check the source to verify that this is the current version before use.

that is whether the item is to be laundered or drycleaned, shall be stated in the applicable end-item specification or procurement document. Unless otherwise specified, the following fastness requirements shall apply:

3.5.1.1 *Fastness to laundering (see 3.5.1.3).* When the item is stated to be laundered, the classes 1, 2, 3, and 4 labels shall show fastness to laundering transference and accelerated laundering equal to, or better than, the standard sample when tested as specified in 4.2.4. When no standard sample is available, the labels shall show good fastness to laundry transference, shall be clearly legible, and shall show fair fastness to accelerated laundering except the class 3 instruction labels for clothing which shall show good fastness to accelerated laundering when tested as specified in 4.2.4.

3.5.1.1.1 When type III or type IV, class 4 labels are specified for leather gloves, the fastness properties for the labels shall be as specified in the applicable end-item specification or procurement document.

3.5.1.2 *Fastness to drycleaning (see 3.5.1.3).* When the item is stated to be drycleaned, the classes 1, 2, 3, and 4 labels shall show fastness to accelerated drycleaning equal to, or better than, the standard sample when tested as specified in 4.2.4. When no standard sample is available, the labels shall be clearly legible and show fair fastness to accelerated drycleaning except the class 3 instruction labels for clothing which shall show good fastness to accelerated drycleaning when tested as specified in 4.2.4.

3.5.1.3 *Types III and IV, classes 1, 2, 3, and 4 labels.* Unless otherwise specified, the fastness requirements specified in 3.5.1.1 and 3.5.1.2 shall apply to types III and IV, classes 1, 2, 3, and 4 labels and the tests specified shall be performed on labels printed on samples of the same material of which the end item is fabricated during the course of production of the end item. In addition to those tests, the labels in the fabricated end items shall show fastness equal to, or better than, the standard sample when subjected to the transference test specified in 4.2.4. When no standard sample is available, the labels in the fabricated end items shall show good fastness when subjected to the transference test specified in 4.2.4.

3.5.2 *Classes 5 and 6 labels.* Classes 5 and 6 labels shall be clearly legible after subjection to the accelerated laundering procedure specified in 4.2.4.

3.5.3 *Class 7 labels.* Class 7 labels shall be clearly legible and shall show fastness to accelerated laundering equal to, or better than, the standard sample when tested as specified in 4.2.4. When no standard sample is available the class 7 labels shall be clearly legible and shall show good fastness after subjection to accelerated laundering when tested as specified in 4.2.4.

3.5.4 *Class 8 labels.* Class 8 labels shall be clearly legible after subjection to accelerated weathering when tested as specified in 4.2.4.

3.5.5 *Class 9 labels.* The fastness properties of the class 9 labels shall be as specified in the applicable end-item specification or procurement document. When requirements for any of the following characteristics are specified, conformance shall be determined as specified in 4.2.4:

Fastness to laundering transference.
Fastness to transference.
Fastness to accelerated laundering.
Fastness to accelerated drycleaning.
Fastness to weathering.
Fastness to laundering transference (wool method).

3.5.6 *Class 10 labels.* Class 10 labels shall show fastness properties as specified for class 1 labels and, in addition, shall be equal to, or better than, the standard sample when subjected to the writing test specified in 4.2.4. When a combination of class 1 and class 10 labels is specified (see 3.3.10) the fastness of the combined label shall be as specified for class 10 labels.

3.5.7 *Class 11 labels.* Class 11 labels shall be clearly legible after subjection to the accelerated laundering procedure specified in 4.2.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:31Z
Check the source to verify that this is the current version before use.

3.6 Workmanship. The finished labels shall be clean, free from objectionable odor and shall conform to the quality and grade of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality levels.

3.7 Materials purchased by a contractor. When the labels are purchased by a contractor as a component of an end item, they shall be delivered in accordance with the label supplier's normal practice.

3.8 Materials purchased directly by the Government. When the labels are purchased directly by the Government, they shall be prepared for delivery in accordance with the requirements of section 5.

4. SAMPLING, INSPECTION, AND TEST PROCEDURES

4.1 Contractor's inspection responsibility. The supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own or any other inspection facilities and services acceptable to the Government. Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order. The Government reserves the right to perform any of the inspections set forth in the specifications where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

4.2 Inspection for acceptance. Except when otherwise specified by civil government agencies, sampling and inspection shall be performed in accordance with Military Standard MIL–STD–105, except where otherwise indicated.

4.2.1 *Inspection of components.* Quality assurance provisions for components described shall be in accordance with subsidiary specifications and drawings referenced to the extent applicable except that this specification shall govern in the event of conflict.

4.2.2 *Visual examination of the end item.* Defects found during this examination shall be classified as listed in table I below. The required number of labels shall be inspected. The unit of product for this examination shall be one label. The acceptable quality level shall be 2.5 defects per hundred units. The sample size shall be in accordance with Inspection Level II of Military Standard MIL–STD–105. The lot size shall be expressed in units of one label each.

TABLE I.—*Classification of visual defects*

Labels	Defect
Labels (all types)	Misshaped or distorted.
	Objectionable odor.
	Any measurement of the label (width or length) not within the 1/16 inch plus or minus tolerance of the dimensions specified.
Labels, printing (all types)	Incorrect.
	Omitted.
	Illegible, smeared.
	Wrong color (label and printing).
	Misplaced.
	Not specified size.
	Spacing between lines—not as specified.
	Not type specified.
	Not all capitals (exception 3.3.2.3).
	Format not as specified.
Labels (types I and II only)	Coating not as specified.
	Coating blistered or missing.
	Hole, float, broken thread, slub, smash, slough-off, light or heavy place.
	Spot or stain clearly noticeable.[1]
	Margin for sewing purposes less than 2/16 inch or more than 4/16 inch.

[1] At normal inspection distance (approximately 3 feet).

4.2.3 *Examination of preparation for delivery requirements.* An examination shall be made to determine that packaging, packing, and marking requirements of Section 5 of this specification are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully packed, selected just prior to the closing operation. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of con-

Source: https://assist.dla.mil -- Downloaded: 20260-26T12:31Z
Check the source to verify that this is the current version before use.

tainers in the inspection lot. The inspection level shall be L–4 and the acceptable quality level shall be 4.0 defects per hundred units.

Examine	Defect
Markings	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Any component missing or damaged, affecting serviceability.
Workmanship	Inadequate application of components such as incomplete closure of case liners, container flaps, loose strapping, etc. Bulging or distortion of containers.
Bundles	Consisting of more than one type or class.
Net weight: Intermediate containers	Exceeds requirements of 10 pounds.
Net weight: Shipping container	Exceeds requirements of 65 pounds.

4.2.4 *Testing of the end item.* The methods of testing specified in Federal Specification CCC–T–191, wherever applicable, and as listed in table II shall be followed. The physical and chemical values specified in Section 3 apply to the average of the detereminations made on a unit of product for test purposes as specified in the applicable test method.

The unit of product shall be as follows for the specified type:

Type	Unit of product
I	300 square inches
II	340 square inches
III and IV	15 labels

The sample size shall be as indicated below:

Lot size (labels)	Sample size
800 or less	2
801 to 22,000	3
22,001 and over	5

The lot shall be unacceptable if a single unit fails to meet any requirement.

TABLE II.—*Tests*[1]

Characteristic	Requirement reference	Test method
Texture (types I and II only)	3.2.1.1	5050
Blocking (types I and II only)	3.2.1.3	5872[3]
Weight (oz/sq. yd) (types I and II only)	3.2.1.4	5041
Coating (types I and II only)	3.2.1.2	[2]
Writing test (types I and II only)	3.5.6	4.2.4.1
Mildew resistance (type II only)	3.2.2	5752
Inhibitor content (type II only)	3.2.2	2011 or 2012[4]
Fastness of printing	3.5	[5]
—Fastness to laundering transference	[6]	5610[7]
—Fastness to transference		5640[7] [8]
—Fastness to accelerated laundering		4.2.4.2
—Fastness to accelerated drycleaning		4.2.4.3
—Fastness to weathering		5671[9]
—Fastness to laundering transference (wool)		5614[7]

[1] Tests to determine compliance with specification requirements may be made under prevailing atmospheric conditions, except in settlement of dispute in which case the test shall be made upon material which has reached equilibrium under standard conditions as defined in Federal Specification CCC–T–191.

[3] Method 5872 shall be followed except as follows:

a. The test specimen shall consist of four finished labels plied together, face to face, back to back, and face to back.

b. If the dimensions of the finished labels are under the 4½- by 4½-inch size of the glass plates, they shall be placed approximately in the center of the glass plates.

c. If the dimensions of the finished labels are in excess of the 4½- by 4½-inch size of the glass plates, they shall be trimmed where required to the 4½- by 4½-inch dimensions.

[2] Accepted on the basis of Contractor's Certificate of Compliance thereto.

[4] Method 2011 may be used to determine the percentage of inhibitor present in the material. In cases of dispute, or when Method 2011 shows that the amount of inhibitor present is not within the specified tolerances, Method 2012 shall be used and the results obtained shall be final.

[5] In the tests for fastness of printing, when the label is specified to be fast to laundering (see 3.5.1.1 and 3.5.1.3), the laundry transference test (Method 5610) shall be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:31Z
Check the source to verify that this is the current version before use.

performed first. If the labels fail this test, no other tests shall be performed and the lot shall be unacceptable.

[6] Method 5610 shall be followed except that in evaluating the results of this test only the staining of the color transfer cloth shall be evaluated.

[7] When a white or yellow printing medium is specified, the transfer cloth utilized in the test shall conform to the colored crock cloth specified in Method 5651 of Federal Specification CCC–T–191.

[8] Method 5640 shall be followed except that the evaluation shall be conducted as follows:

a. When a standard sample has been established, the color transfer shall be evaluated as "satisfactory" or "unsatisfactory" by comparing the transfer produced by the standard sample with that produced by the specimen under examination.

b. When no standard sample has been established, the transfer onto the transfer press cloth shall be rated as follows:

Excellent—No transfer to the transfer cloth.

Good—No more than very slight transfer of marking to transfer cloth requiring close examination.

Fair—Appreciable but not objectionable transfer of the marking to the transfer cloth readily discernible upon examination.

Poor—Objectionable transfer of the marking to the transfer cloth.

[9] Unless otherwise specified, the apparatus shall be as specified in Method 5804, except that:

a. Delete from title "(National Weathering Unit)."

b. The filters shall be removed when testing.

c. Water-spray nozzles shall be mounted horizontally (the water spray assembly vertically) in the test chamber inside the specimen rack and so placed that the water shall strike the specimens evenly over their entire length in the form of a fine spray in sufficient volume to cover specimens immediately on impact. The apparatus shall be so operated that the specimens are exposed to successive cycles of 102 minutes of light without spray, and 18 minutes of light with spray.

d. The rack shall rotate about the arc at a uniform speed of one revolution per minute.

e. The pressure of the water entering the spray shall be 12-18 p.s.i. inclusive.

f. The black panel thermometer shall be mounted on the test panel rack and readings taken at a point where maximum heat is developed and where water spray is not striking the panel. The black panel temperature at the exposure plane of the specimen rack shall be 155° plus or minus 10° F., when the filters are in place and 175° plus or minus 10° F., when the filters are removed.

g. Note: Attention is called to manufacturers who own equipment which operates at one cycle in two hours. This equipment may continue to be used. However, the one cycle per minute shall be the standard procedure in the event of dispute.

4.2.4.1 *Writing test.* One test specimen subjected to the laundering transference procedure (method 5610) as specified in 4.2.4 and another in the state as received shall be printed, by pen, with a commercial-grade indelible black ink. The printing on the unlaundered and the laundered test specimens shall be compared with the printing on the standard sample under the same conditions of test and shall show no more skipping, smudging or blotting than the standard sample.

4.2.4.2 *Fastness to laundering.*

4.2.4.2.1 *Test specimen.*

4.2.4.2.1.1 The specimen shall consist of a number of rectangles of labels weighing a total of 3.5 ± 0.3 grams, each unit measuring approximately 2 inches by 3 inches. (Labels smaller than 2 inches by 3 inches shall be lap stitched together, with all printing in the same plane. Labels larger than 2 by 3 inches shall be cut to conform to the specified unit size.) Each unit of specimen shall be pinked along each edge. In addition, a thin ribbon of adhesive (see 6.8) shall be applied to the type III and type IV labels to each pinked edge.

4.2.4.2.2 *Apparatus.*

4.2.4.2.2.1 *Accelerotor (see 6.7).* The machine shall be capable of varying the speed of the rotor from 0 to 4,000 r.p.m. with a 4½-inch S rotor. The liner for the test chamber shall be rubber ribbed, having 2 ribs per inch, with the ribs approximately 1/16 inch in height.

4.2.4.2.2.2 *Soaking chamber.* Any convenient vessel with 100 ml. per gram of specimen capacity.

4.2.4.2.2.3 *Pressing equipment.*

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:31Z
Check the source to verify that this is the current version before use.

4.2.4.2.2.3.1 *Steam pressing.* Flat bed press at temperature of 135° to 149° C. (275° to 300° F.) hot head or polished metal top for flat fabrics; cloth top press for rough crepes.

4.2.4.2.2.3.2 *Hand pressing.* A hand iron weighing approximately 6 lbs. capable of maintaining temperatures between 135° to 149° C. (275° — 300° F.).

4.2.4.2.3 *Reagents.*

4.2.4.2.3.1 *Soap and alkali solution.* The soap and alkali solution shall contain the foling in soft water (not over 50 p.p.m. in hardness calculated as $CaCO_3$):

0.2 percent soap conforming to Federal Specification P–S–580.

0.2 percent Metasilicate, Technical ($Na_2 SiO_3 . 9 H_2O$).

0.2 percent Sodium Carbonate, Technical ($Na_2 CO_3 . 10 H_2O$).

4.2.4.2.3.2 *Adhesive.* Adhesive, preferably a latex acrylic adhesive, for sealing sample edges of types III and IV labels to prevent fraying of samples during test cycle (6.8).

4.2.4.2.4 *Procedure.*

4.2.4.2.4.1 The specimens shall be crumpled by hand to prevent their adhering to one another and then soaked for a period of approximately 30 ± 2 minutes at 150° ± 5° in the soap and alkali solution of 100 ml. per gram of material.

4.2.4.2.4.2 The specimens shall then be placed in the Accelerotor with 150 ml. of the soap and alkali solution at 80° ± 2°F. The speed control of the Accelerotor shall be set to approximately 50 on the control dial. The motor shall then be started and quickly adjusted to 2,000 r.p.m. (Average speed shall be used since the tachometer pointer will fluctuate.)

4.2.4.2.4.3 The machine shall be run for exactly 6 minutes (including that time to adjust initial speed) without further adjustment of speed.

4.2.4.2.4.4 The machine shall be shut down at the end of the six minute period and the liquid allowed to drain out. The specimens shall be removed, squeezed by hand and then rinsed free from soap with soft water at approximately 105° F. The exposed test specimens shall then be hydroextracted or passed between wringer rolls to remove excess moisture and then dried by pressing between press cloths with a hand iron or flat bed press.

4.2.4.2.5 *Evaluation.* Change in color or definition of print shall be considered in rating fastness to laundering.

4.2.4.2.5.1 The comparison shall be made with the test specimen and the standard or comparison sample which was tested in a similar manner. The comparison shall be made at normal reading distance under average north-sky daylight or equivalent light in the standard manner.

4.2.4.2.5.2 When a standard of comparison has been established the test specimen shall be compared with the specimen tested from the standard sample and rated as follows: Satisfactory—Equal or superior to the standard; Unsatisfactory—Inferior to the standard sample.

4.2.4.2.5.3 When no standard sample for comparison has been established, unless otherwise specified, the tested specimen shall be rated as to definition and legibility of print at a normal reading distance. Specimens shall be rated as follows: Excellent—Practically no change in legibility or definition of print; Good—Readily legible without difficulty; Fair—Legible without need for deciphering; Poor—Not readily legible, requiring deciphering.

4.2.4.3 *Fastness to dry cleaning.*

4.2.4.3.1 *Test specimen.*

4.2.4.3.1.1 The test specimen shall consist of a number of rectangles of labels weighing a total of 4.5 ± 0.5 grams, each unit measuring approximately 2 by 4 inches. (Labels smaller than 2 by 4 inches shall be lap stitched together

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:31Z
Check the source to verify that this is the current version before use.

each sample faced in the same plane. Labels larger than 2 by 4 inches shall be cut to conform to the specified unit size.)

4.2.4.3.2 *Apparatus.*

4.2.4.3.2.1 *Launderometer or similar machine as described in method 5610.* This machine shall have the required metal adapter to hold stainless-steel cylindrical containers 8 inches by 3½ inches in diameter, each equipped with a sealing device which has solvent resistant rings. ¼-inch diameter stainless-steel balls are also required.

4.2.4.3.2.2 *Pressing equipment.*

4.2.4.3.2.2.1 *Steam pressing.* Flat bed press at temperature of 135° to 149° C. (275° to 300° F.); hot head or polished metal top for flat fabrics; cloth top press for rough crepes.

4.2.4.3.2.2.2 *Hand pressing.* A hand iron weighing approximately 6 lbs. capable of maintaining temperatures between 135° to 140° C. (275° to 300° F.).

4.2.4.3.2.3 Covered frame or screen suitable for drying specimen in room.

4.2.4.3.3 *Reagents.*

4.2.4.3.3.1 *Stoddards solvent.* Solvent dry cleaning conforming to Federal Specification P–S–661.

4.2.4.3.3.2 *Perchloroethylene.* Perchloroethylene (tetrachlorethylene) technical grade conforming to Federal Specification O–P–191.

4.2.4.3.3.3 *Drycleaning soap.* Drycleaning soap made by dissolving 56 grams of caustic potash (KOH) in 100 ml. of water. This solution is poured slowly with constant stirring into a mixture of 340 grams of oleic acid, 400 ml. of Stoddard solvent, 100 ml. of tertiary butyl alcohol or an equal quantity of butyl cellosolve.

4.2.4.3.4 *Procedure.*

4.2.4.3.4.1 The specimen shall be placed in the stainless steel container with 150 ml. of perchloroethylene, 1 ml. of drycleaning soap and 100 stainless-steel balls. The jar shall be sealed, clamped in the launderometer, and run at 80° ± 2° F. for 10 minutes at which time the solvent is drained.

4.2.4.3.4.2 Replace the solvent with 150 ml. Stoddard solvent and 1 ml. of drycleaning soap and 100 stainless-steel balls and run 10 minutes at 80° ± 2° F. followed by draining.

4.2.4.3.4.3 Replace the solvent with 150 ml. of perchloroethylene without drycleaning soap and with 100 stainless-steel balls run for 10 minutes at 80° ± 2° F. Drain the solvent at the end of the ten minute cycle, remove specimen, blot thoroughly between paper towels or blotters, or extract centrifically to remove excess solvent and then air dry on covered frame or screen.

4.2.4.3.4.4 *Pressing.* When dry, the specimen shall be pressed as follows:

4.2.4.3.4.4.1 *Hand pressing.* Cover with a damp muslin cloth weighing 4 to 4½ ounces per square yard, previously saturated with water and wrung out to retain approximately 75 percent moisure by weight, and press with hand iron until cover cloth is dry.

4.2.4.3.4.4.2 *Steam pressing.* Lower the head of the machine and hold in contact with the fabric. During this period admit steam from the back of the press for a period of 5 to 10 seconds and maintain the head of the press down until specimen is dry.

4.2.4.3.5 *Evaluation.* Change in color, appearance and definition of print shall be considered in rating the durability.

4.2.4.3.5.1 The comparison shall be made with the test specimen and the standard or comparison sample which was tested in a similar manner. The comparison shall be made at normal reading distance under average north-sky daylight, or equivalent standard artificial light, in the standard manner.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:31Z
Check the source to verify that this is the current version before use.

4.2.4.3.5.2 When a standard of comparison has been established the test specimen shall be compared with the specimen tested from the standard sample and rated as follows: Satisfactory—Equal or superior to the standard; Unsatisfactory—Inferior to the standard sample.

4.2.4.3.5.3 When no standard sample for comparison has been established, unless otherwise specified, the test specimen shall be rated as to change in color, appearance and definition of print at a normal reading distance. Specimen shall be rated as follows: Excellent—practically no change in legibility or definition or print; Good—Readily legible without difficulty; Fair—Legible without need for deciphering; Poor—not readily legible, requiring deciphering.

5. PREPARATION FOR DELIVERY

(Federal Standard No. 102 shall be referred to for definitions and applications of the various levels of packaging and packing for civil agency procurement.)

5.1 Packaging. Packaging shall be level A or C as specified (see 6.2).

5.1.1 *Level A.*

5.1.1.1 *Types I and II.*

5.1.1.1.1 *Sizes up to and including nine square inches.* Five hundred labels, of one type and class only, shall be neatly stacked in a bundle and securely cross-tied with cotton tape or twine. A quantity of bundles of labels, of one type and class only, not exceeding a net weight of 10 pounds, shall be placed in an intermediate paperboard box as hereinafter specified.

5.1.1.1.2 *Sizes over nine square inches.* Two hundred labels, of one type and class only, shall be neatly stacked in a bundle and cross-tied with cotton tape or twine or held in place with an elastic band. A quantity of bundles of labels, of one type and class only, not exceeding a net weight of 10 pounds, shall be placed in an intermediate paperboard box as hereinafter specified.

5.1.1.1.3 *Intermediate box.* The intermediate box shall be a snug-fitting folding paperboard box conforming to style III, type B, class A of Federal Specification PPP–B–566; or set-up paperboard box conforming to type I, grade B, class A, style 3 or 4 or Federal Specification PPP–B–676. Thumb-hole requirements shall be optional. The box closure shall be secured with 2-inch minimum width gummed paper tape conforming to class 2 of Federal Specification UU–T–111 applied at the center of the length opening and extending along the bottom and up the sides.

5.1.1.2 *Types III and IV.* Packaging not acceptable.

5.1.2 *Level C.* The labels shall be packaged in accordance with the industry's practice.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 *Level A.*

5.2.1.1 *Types I and II.* Labels, of one type and class only, packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to class 2, V3c or V3s, style RSC of Federal Specification PPP–B–636. Each shipping container shall be provided with a type I or II, grade B or C, class 2 sealed case liner conforming to Military Specification MIL–L–10547. Alternatively, in lieu of the case liner, each shipping container shall have all seams, corners, and manufacturer's joint sealed by the application of a 3-inch minimum width olive drab color cloth tape conforming to type III, class 1 of Federal Specification PPP–T–60. Each container shall be closed and reinforced with flat steel strapping or tape banding in accordance with the appendix of the container specification. The net weight of the contents in each shipping container shall not exceed 65 pounds.

5.2.1.2 *Types III and IV.* Packing not applicable.

5.2.2 *Level B.*

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:31Z
Check the source to verify that this is the current version before use.

5.2.2.1 *Types I and II.* Labels, of one type and class only, packaged as specified in 5.1, shall be packed in a fiberboard shipping container conforming to type I or II, class 1, style RSC of Federal Specification PPP–B–636. The minimum bursting strength of the fiberboard shall be 275 p.s.i. All flaps of the shipping container shall be securely sealed with an adhesive commercially used for the specific product being packed by application throughout the entire area of contact between the flaps, or by a combination of metal stitching the bottom flaps and sealing the top flaps with adhesive. The net weight of the contents in each shipping container shall not exceed 65 pounds.

5.2.2.2 *Types III and IV.* Packing not applicable.

5.2.3 *Level C.* The labels, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination. Shipping containers shall be in accordance with rules and regulations of carriers applicable to the mode of transportation.

5.3 Marking.

5.3.1 *Civil agencies.* In addition to any special marking required by the contract or order, intermediate packages and shipping containers shall be marked in accordance with Federal Standard No. 123.

5.3.2 *Military requirements.* In addition to any special marking required by the contract or order, intermediate packages and shipping containers shall be marked in accordance with Military Standard MIL–STD–129.

6. NOTES

6.1 Intended use. The labels covered by this specification are intended for use in items of clothing, tentage, equipage and related items as specified for the applicable class (see 1.2 and 6.5).

6.2 Ordering data. Purchasers should exercise any desired options offered herein and procurement documents should specify the following:

(*a*) Title, number, and date of this specification.

(*b*) Type and class required (see 1.2).

(*c*) Size required (see 3.4).

(*d*) Availability of standard sample (see 6.6).

(*e*) Information and illustrations to be printed on labels (when required) (see 3.3).

(*f*)) Printing, color of printing, contents and fastness if other than specified (see 3.3.2, 3.3.2.9 and 3.5).

(*g*) Contents, printing and fastness of class 9 labels (see 3.3.2.9 and 3.5).

(*h*) Selection of applicable levels of packaging and packing (see 5.1 and 5.2).

(*i*) Types of labels and use (see 6.5).

(*j*) When the combination of class 1, 2 and 3 is allowed (see 6.4).

(*k*) Contents, size of characters and format of class 7 labels (see 3.3.2.7).

(*l*) Fastness properties of type III or IV class 4 labels when used for leather gloves (3.5.1.1.1).

6.3 Supersession data. This document incorporates the requirements of the following specifications:

(*a*) Federal Specification DDD–L–20, Label (Cotton, Woven, General Use), dated September 25, 1957.

(*b*) Interim Federal Specification DDD–L–0020a—Labels, Printed and Markings, General Use (For Clothing, Equipage and Tentage), dated November 10, 1959.

(*c*) Military Specification JAN–C–517, Cloth, Label, Cotton, Permanent Coated, dated 12 November 1947 and Amendment No. 3 thereto dated 30 December 1954.

(*d*) The requirements for type III labels of Military Specification MIL–L–15040C (S&A), Labels, Garment, dated 5 March 1953 and Amendment No. 1 thereto, dated 10 September 1956.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:31Z
Check the source to verify that this is the current version before use.

(*e*) Military Specification MIL–T–16338B, Tickets: Cap and Hat, dated 30 November 1956.

6.4 It is to be noted that the intent of this specification is to allow a suitable combination of classes 1, 2 and 3 labels when it is economically and structurally feasible. However, the end item specification or procurement document must state when a combining of these labels is allowed and the extent of the combination (see 6.2).

6.5 Types of labels and use—Department of Defense only. In order to keep the number of sizes of labels to a minimum and in the interest of standardization, it is Department of Defense policy to adhere as closely as possible to the following when procuring labels for specific use and when specifying the type of label to be utilized in an end item specification:

(*a*) All combat and utility clothing will utilize type I, classes 1, 2 and 3 labels with the exception of cotton shirts as noted in "d" below.

(*b*) Dress clothing will utilize type I, classes 1, 2 and 3 labels with the exception of cotton shirts as in "d" below. Woven labels conforming to Military Specification MIL–L–15040C may be utilized for size and instruction labels on dress items, but only where they are permanently visible and the use of another type label would adversely affect the appearance of the item.

(*c*) All trousers and shorts will utilize the type I, classes 1, 2 and 3 labels.

(*d*) Cotton shirts and miscellaneous items, will utilize the type III and IV labels (on shirts the size and stock number will be printed in the collar and the identification label shall be printed on the left side of the tail).

(*e*) All woolen items, synthetic, or blends of synthetics and knitted items shall utilize type I labels or woven labels as noted above for dress items.

(*f*) Gloves, hats and neckwear will utilize type I, class 4 labels when possible.

(*g*) Type IV labels shall be utilized for classes 5 and 8 labels.

(*h*) Type II shall be utilized for classes 6 and 7 labels.

(*i*) Special markings such as the "US" on tentage and equipage will normally utilize the type IV label (see 6.2).

6.6 Standard sample. For access to standard sample address the procuring office issuing the invitation to bid.

6.7 Accelerotor Model AB–7 has been found to meet the requirements of this test method. This model complete with accessories is available from Atlas Electric Devices Company, 4114 North Ravenswood Avenue, Chicago 13, Illinois.

6.8 Adhesive Bulcanol AL–100–58 available from Oleo Oil and Chemical Corporation, Trenton Avenue and Williams Street, Philadelphia 34, Pennsylvania, has ben found to adequately seal specimen edges. Materials giving the same degree of sealing of specimen without transfer are acceptable.

6.9 Level B packaging and packing should be used by ordering agencies only when shipment is known to be made to a holding supply depot or warehouse from which partial shipments will be made to ultimate consumers.

6.10 Transportation descriptions and minimum weights applicable to this commodity are:

Rail:

Labels, Cloth.

Carload minimum weight 24,000 pounds, subject to Rule 34, Uniform Freight Classification.

Motor:

Labels, Cloth.

Motor volume minimum weight 24,000 pounds.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:31Z
Check the source to verify that this is the current version before use.

thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

MILITARY INTERESTS:

Army—M Q
Navy—S MC
Air Force—WADD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:31Z
Check the source to verify that this is the current version before use.