DDD-R-00255 (GSA-FSS)
AMENDMENT-1
August 8, 1974

AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

RIBBON, ADDRESS PLATE MACHINE

This amendment was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information. The General Services Administration has authorized this amendment as a part of Interim Federal Specification DDD-R-00255 (GSA-FSS), dated June 11, 1971.

PAGE 4

Paragraph 4.1.1.2, delete "Note" paragraph and substitute:

"Note: Thickness of fabric determination shall be conducted in accordance with procedure 4.1.2 of method 5030, Fed. Test Method Std. 191, or equivalent approved textile test method with the following exceptions (the exceptions apply to method 5030, or equivalent method):

The gage presser foot shall not rest on treated or fused edges of fabric. The average thickness shall be reported to the nearest 0.0001 inch. Disputes shall be resolved in accordance with method 5030, procedure 4.1.2, except dial of the gage will be graduated to read directly to 0.0001 inch, and a 0.375 or 0.407 presser foot (with an appropriate dead weight) shall be used."

PAGE 5

Paragraph 4.4.2, delete 2nd subparagraph and substitute:

"The impression force of the capital letter "B" shall be adjusted through the use of aluminum foil having a thickness of 0.0031 ± 0.0002 inch (see 6.3). Thickness shall be determined with a dead-weight micrometer having two plane faces, the smaller of which is circular and 0.25 to 0.33 square inch in area. An average of five readings taken at widely separated points shall be used for the thickness dimension. The impression force of the "B" shall be adjusted to provide an increase in the foil's embossed thickness of 0.0017 to 0.0021 inch".

PAGE 6

Delete paragraph 5.3.3 and substitute the following:

5.3.3 Special Marking. In addition to the marking required by 5.3.1 or 5.3.2, the following special marking is required:

UNIT CONTAINER	INTERMEDIATE CONTAINER	SHIPPING CONTAINER
Composition (cotton)	Composition (cotton)	
Complete line of machines on which the ribbon may be used.	Complete line of machines on which the ribbon may be used.	
Contract No.		
Contractor's name.	Contractor's name.	
Date of manufacture.*	Date of manufacture.*	Date of manufacture.*

*Date of manufacture shall be expressed numerically (month and year), followed by the letter "P", e.g. - 12-75-P.

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:33Z
Check the source to verify that this is the current version before use.

Add new Paragraph 6.3, as follows:

"6.3 The aluminum foil specified in 4.4.2 is available from Alufoil Products Co., Inc., 1143 Conklin Street, Farmingdale, Long Island, New York 11735. Alufoil Catalog description: grade 1145-H-19 (0.003 hard) (average Mullen bursting strength - 96 P.S.I.)."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:33Z
Check the source to verify that this is the current version before use.