DDD-R-250E
AMENDMENT-6
April 5, 1976
SUPERSEDING
AMENDMENT-5
January 6, 1975

FEDERAL SPECIFICATION

RIBBON, ACCOUNTING MACHINE

This amendment, which forms a part of Federal Specification DDD-R-250E, dated January 2, 1964, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 1

Section 2: Delete and substitute "APPLICABLE DOCUMENTS".

Paragraph 2.1 Under Federal Specifications, delete "CCC-T-191", "PPP-B-676 - Boxes, Set-up, Paperboard" and substitute "PPP-B-676 - Box, Set-up". Delete "PPP-T-45 - Tape, Gummed, Paper Reinforced" and substitute "PPP-T-45 - Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing". Under Federal Standards, delete "Fed. Std. No. 102 - Preservation, Packaging, and Packing Levels", add "Fed. Test Method Std. 191 - Textile Test Methods".

PAGE 2

Paragraph 2.1 At the end of the second parenthetical paragraph, delete "and Auburn, Wash." and substitute "Los Angeles, and Seattle, WA". In the parenthetical paragraph under Military Standards, delete "supplies" and substitute "contractors".

Paragraph 3.2.2 Delete "as specified (see 6.2)" and substitute "at the option of the manufacturer".

Paragraph 3.4 Delete "4.4.1.1" and substitute "Table VI".

PAGE 3

Paragraph 3.7 Delete entire paragraph and substitute:

3.7 Color. Impressions made by ribbons shall be black in color.

PAGE 4

Section 4 Delete and substitute "QUALITY ASSURANCE PROVISIONS".

PAGE 5

Paragraph 4.2.2 Delete "CCC-T-191" and substitute "Fed. Test Method Standard No. 191".

Paragraph 4.3 Delete in its entirety and substitute the following:

"4.3 Testing of the end item. The methods of testing specified in Federal Test Method Standard No. 191 wherever applicable and as listed in table VI shall be followed. The physical and chemical values specified in section 3 apply to the average of the determinations made on a sample unit for test purposes as specified in the applicable test methods. The sample unit shall be 3 continuous yards of finished ribbon. The sample size shall be in accordance with MIL-STD-105 with an inspection level of S-2 and an acceptable quality level (AQL) of 2.5 percent defective."

FSC 7510

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:33Z
Check the source to verify that this is the current version before use.

PAGE 6

Paragraph 4.4.1.1 In the second and eleventh lines delete "CCC-T-191" and substitute "Federal Test Method Standard No. 191".

Paragraph 4.4.2 Delete "CCC-T-191" and substitute "Federal Test Method Standard No. 191".

PAGE 7

Paragraph 4.4.6 Delete "CCC-T-191" and substitute "Federal Test Method Standard No. 191".

Section 5 Delete entire paragraph under heading "Preparation for Delivery".

PAGE 8

Paragraph 5.1.1.1 Delete paragraph and substitute the following new paragraphs:

5.1.1.1 Unit packaging.

5.1.1.1.1 Ribbons on flanged spools. Each ribbon shall be enclosed in a sheet or bag of flexible packaging material. The packaging material used may be plastic film, aluminum foil, or laminated film. The wrap or bag used to enclose the ribbon shall be sealed. The method of sealing shall insure a water-resistant seal. Each enclosed ribbon shall be packaged in a metal, paperboard, fiberboard, or other suitable container.

5.1.1.1.2 Ribbons, core wound. Each ribbon shall be enclosed in a sheet or bag of flexible packaging material. The packaging material used may be plastic film, aluminum foil, or laminated film. Heat shrinking of film will not be permitted. The wrap or bag used to enclose the ribbon shall be sealed to insure a water-resistant seal. Each completely enclosed ribbon over 10 inches in width shall be supported by die-cut fiberboard or molded plastic supports or saddles positioned at each end of the core. The supports shall be outside of the sealed wrap, and shall be designed to prevent movement of the ribbon and to prevent contact between the ribbon and the inside facings of the container. Alternatively, the supports or saddles may be positioned inside the wrap prior to sealing. When fiberboard supports or saddles are positioned inside the wrap, strips of flexible packaging shall be inserted between the fiberboard and both edges of the ribbon to prevent contact between the inked fabric and the fiberboard. Each enclosed ribbon over 10 inches in width shall be packaged in a corrugated fiberboard box. Each enclosed ribbon 10 inches or less in width shall be packaged in a box conforming to PPP-B-566, style II, type A, class A.

Paragraph 5.1.1.2 Delete paragraph and substitute the following new paragraph:

5.1.1.2 Intermediate packaging. Twelve ribbons of one composition, class, width, and length, unit packaged as specified in 5.1.1.1, shall be intermediately packaged in a snug-fitting paperboard box conforming to PPP-B-566, PPP-B-676, or a snug-fitting fiberboard box conforming to type CF or SF, class domestic, of PPP-B-636. Intermediate packaging shall not be required when 12 unit packages exceed 30 pounds. Each box shall be securely closed in accordance with the appendix to the box specification.

Paragraph 5.2.1 Delete paragraph and substitute the following new paragraph:

5.2.1 Level A. Ribbons, packaged as specified in 5.1, shall be packed in a snug-fitting fiberboard shipping container conforming to V3c or V3s of PPP-B-636. Each shipping container shall be closed, waterproofed by means of tape, and reinforced with flat steel strapping or tape banding in accordance with the appendix of the container specification. The weight of contents of each shipping container shall not exceed 75 pounds.

Paragraph 5.2.2 Delete in its entirety and substitute the following:

5.2.2 Level B. Twenty-four intermediate packages (288 ribbons), or 12 unit packages (where 12 units exceed 30 pounds), shall be packed in a close-fitting box conforming to PPP-B-636, class domestic. When 288 ribbons exceed 70 pounds, a smaller quantity shall be packed so that the shipping container weight does not exceed 70 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:33Z
Check the source to verify that this is the current version before use.

PAGE 8 (cont.)

5.3.3 Delete in its entirety and substitute the following:

5.3.3 Special marking. In addition to the marking required by 5.3.1 or 5.3.2, the following special marking is required:

UNIT CONTAINER	INTERMEDIATE CONTAINER	SHIPPING CONTAINER
Composition (cotton, silk or nylon, as applicable).	Composition (cotton, silk, or nylon, as applicable).	
Complete line of machines on which the ribbon may be used.	Complete line of machines on which the ribbon may be used.	
Contract No.		
Contractor's name.	Contractor's name.	
Date of manufacture. *	Date of manufacture. *	Date of manufacture. *

*Date of manufacture shall be expressed numerically (month and year), followed by the letter "P"; e.g., 12-75-P.

PAGE 9

6.2 (d) Delete in its entirety.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:33Z
Check the source to verify that this is the current version before use.