FEDERAL SPECIFICATION

PIPE, CORRUGATED (IRON OR STEEL, ZINC COATED)

This amendment, which forms a part of Federal Specification WW-P-405B, dated June 14, 1974, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

PAGE 8

Paragraph 3.4.3: delete the last sentence and in its place substitute the following:

"Except for channel bands in accordance with 3.4.3.2, the bands with projections shall conform to table V."

Paragraph 3.4.3.2: delete and in its place substitute the following:

"3.4.3.2 Channel band. Channel bands couplers may be used in helical pipe with ends which have been reformed and flanged specifically to receive these bands. The channel band couplers shall:

a. be of two piece design,
b. be fabricated from galvanized steel stock conforming to 3.1.1,
c. be 0.079-inch thickness for pipe of 0.109-inch or lighter,
d. be 0.109-inch thickness for pipe of 0.138-inch or heavier,
e. be 3/4-inch wide for pipe of 0.109-inch or lighter,
f. be 1-inch wide for pipe of 0.138-inch or heavier,
g. have 2-inch x 2-inch x 3/16-inch angles securely fastened to the band ends to allow for proper tightening.

Two 1/2-inch diameter connection bolts shall be furnished with each band. These bolts shall conform to ASTM A 307, grade A and shall be electroplated in accordance with ASTM A 164, type RS. Other equally effective fastening bands or methods for connecting the pipe sections may be used when approved by the contracting officer (see 6.2).

MILITARY CUSTODIANS:

Army - ME
Navy - YD
Air Force - 82

Review activities

Army - ME
DSA - CS

Military Coordinating Activity:

Army - ME

Preparing activity:

DOT-FHW

Civil Agency Coordinating Activities:

GSA-FSS
HEW-FEC
INTERIOR-BPA
USDA-AFS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:22Z
Check the source to verify that this is the current version before use.