MILITARY SPECIFICATION

COUPLING ASSEMBLIES, QUICK-DISCONNECT, GENERAL PURPOSE, FOR SUBMINIATURE WAVEGUIDE FLANGES, GENERAL SPECIFICATION FOR

This specification has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1 1 This specification covers the general requirements for general purpose quick-disconnect coupling assemblies which are used to connect mechanically and electrically two subminiature waveguide flanges

2 APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL
- PPP-B-566 - Boxes, Folding, Paperboard
- PPP-B-636 - Box, Fiberboard
- PPP-B-676 - Boxes, Set-Up, Paperboard
- PPP-T-60 - Tape, Pressure-Sensitive Adhesive, Waterproof - For Packaging and Sealing.
- QQ-S-763 - Steel Bars, Shapes, and Forgings-Corrosion Resisting

MILITARY
- MIL-P-116 - Preservation, Methods of
- MIL-L-10547 - Liners, Case, Waterproof
- MIL-C-39004/1 - Coupling Assemblies, Quick-Disconnect, General Purpose, for Subminiature Waveguide Flanges.

STANDARDS

MILITARY
- MIL-STD-10 - Surface Roughness Waviness and Lay.
- MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
- MIL-STD-129 - Marking for Shipment and Storage.
- MIL-STD-130 - Identification Marking of U. S. Military Property.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2 2 Other publications - The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL BUREAU OF STANDARDS
- Handbook H28 - Screw-Thread Standards for Federal Services

FSC 5985

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:07Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D C 20402)

OFFICIAL CLASSIFICATION COMMITTEE
Uniform Freight Classification Rules

(Application for copies should be addressed to the Official Classification Committee, One Park Avenue at 33rd Street, New York, N. Y. 10016.)

3. REQUIREMENTS

3.1 Specification sheets - The individual part requirements shall be as specified herein and in accordance with the applicable specification sheets (see 6.2)

3 2 Material - The material for the quick-disconnect coupling assemblies and alignment pins described herein shall be corrosion-resisting steel conforming to class 302 or 304 of Specification QQ-S-763

3.3 Design and construction - Quick-disconnect coupling assemblies described herein shall be of the design, construction, and physical dimensions specified (see 3.1)

3.3 1 Condition.- When specified (see 6 2), quick-disconnect coupling assemblies shall be annealed before finish machining.

3 3.2 Threaded parts - All threaded parts shall be in accordance with Handbook H28 and shall be as specified in the applicable specification sheet(s) (see 3.1)

3 4 Surface roughness - When surface roughness is determined as specified in 4 6 2, all finished mating surfaces shall be 63 root mean square microinches which shall include surface defects

3.5 Marking - Quick-disconnect coupling assemblies shall be marked in accordance with Standard MIL-STD-130, with the part number and the manufacturer's code symbol The numbers shall be marked in depressed or raised characters in proportion to the size of the part and at least 1/16 of an inch high, in the place specified (see 3.1.) No periods shall be used either between the numbers or at the end of the code

3 6 Workmanship - Quick-disconnect coupling assemblies shall be processed in such a manner as to be uniform in quality and all surfaces shall be free from pits, cracks, burrs, die marks, chatter marks, scratches, dirt, grease, scale, splinters, and other defects that will affect life, serviceability, or appearance.

4 QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-

4 1.1 Supplier - Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements

4.1 1 1 Test equipment and inspection facilities.- Test equipment and inspection facilities shall be of sufficient accuracy, quality, and quantity to permit performance of the required inspection The supplier shall establish calibration of inspection equipment to the satisfaction of the Government

4 2 Classification of inspection - The examination and testing of quick-disconnect coupling assemblies shall be classified as follows.

(a) Materials inspection (see 4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:07Z
Check the source to verify that this is the current version before use.

(b) Quality conformance inspection (see 4.5).
(1) Inspection of product for delivery (see 4.5.1).
(2) Inspection of preparation for delivery (see 4.5.2).

4.3 Materials inspection.- Materials inspection shall consist of verification that the materials used in fabricating the quick-disconnect coupling assemblies are in accordance with the applicable referenced specifications or requirements prior to such fabrication.

4 4 Inspection conditions - Unless otherwise specified herein, all inspection shall be made at room ambient temperature, relative humidity, and pressure

4.5 Quality conformance inspection -

4 5.1 Inspection of product for delivery - ,Inspection of product for delivery shall consist of group A

4.5 1 1 Inspection lot - An inspection lot, as far as practicable, shall consist of all the quick-disconnect coupling assemblies of the same part number, produced under essentially the same conditions, and offered for inspection at one time

4.5.1.2 Rejected lots.- If an inspection lot is rejected, the supplier may withdraw the lot, rework it to correct the defects, or screen out the defective units, as applicable, and reinspect Such lots shall be kept separate from new lots and shall be clearly identified as reinspected lots. Rejected lots shall be inspected using tightened inspection

4.5 1 3 Group A inspection - Group A inspection shall consist of the examinations and test specified in table I, and shall be made on the same set of sample units, in the order shown

4 5 1 3 1 Sampling plan - Statistical sampling and inspection shall be in accordance with Standard MIL-STD-105 for general inspection The acceptable quality levels (AQL) shall be as specified in table I Major and minor defects shall be as defined in Standard MIL-STD-105

4.5.2 Inspection of preparation for delivery.- Sample items and packs shall be selected and inspected in accordance with Specification MIL-P-116 to verify conformance with requirements in section 5 of this specification

4 6 Methods of examination and test -

Table I. Group A inspection.

Examination or test	Requirement paragraph	Method paragraph	AQL (percent defective)	
			Major	Minor
Visual and mechanical examination:		4 6.1		
Design and construction . .	3 1, 3 2, and 3 3 to 3.3.2 incl	.	1.0	4.0
Marking.....	3.5	. .		
Workmanship..	3 6			
Surface roughness.....	3.4	4.6.2		

4 6.1 Visual and mechanical examination - Quick-disconnect coupling assemblies shall be examined to verify that the materials, design, construction, physical dimensions, marking, and workmanship are in accordance with the applicable requirements. (see 3.1, 3.2 to 3.3.2 inclusive, 3.5, and 3.6).

4 6.2 Surface roughness.- Surface roughness shall be determined in accordance with Standard MIL-STD-10 (see 3.4).

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging - Preservation and packaging shall be level A, B, or C as specified (see 6 2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:07Z
Check the source to verify that this is the current version before use.

5 1 1 Level A.-

5.1.1 1 Cleaning.- Quick-disconnect coupling assemblies shall be cleaned in accordance with Specification MIL-P-116, process C-1.

5.1.1.2 Drying.- Quick-disconnect coupling assemblies shall be dried by one or more of the procedures outlined in Specification MIL-P-116 The procedure(s) selected shall not be injurious to the item

5 1 1 3 Preservation application - None required.

5.1.1.4 Unit packaging - Each quick-disconnect assembly shall be preserved in accordance with method 1C-3 of Specification MIL-P-116 When an item weighs more than one pound, the package shall be placed in unit containers conforming to Specification PPP-B-566 or PPP-B-676.

5.1.2 Level C.- Cleaning, drying, preservation and packaging shall be in accordance with manufacturer's commercial practice

5 2 Packing.- Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A - Quick-disconnect coupling assemblies packaged as specified in 5 1 shall be packed in fiberboard boxes conforming to type I, class 2 of Specification PPP-B-636 As far as practical, exterior containers shall be of uniform shape and size and contain identical quantities The container shall be closed and strapped in accordance with the appendix to Specification PPP-B-636. The exterior containers shall have a case liner conforming to Specification MIL-L-10547, the case liners shall be closed and sealed in accordance with the appendix thereto A case liner is not required when the exterior container is sealed at all joints and seams, including manufacturer's joint, with tape conforming to type III, class 1 of Specification PPP-T-60.

5.2.2 Level B.- Quick-disconnect coupling assemblies preserved and packaged as specified in 5 1 shall be packed in fiberboard containers conforming to types I, class I of Specification PPP-B-636 Exterior containers shall be of minimum cube and tare consistent with the protection required As far as practical, exterior containers shall be uniform shape and size and contain identical quantities Containers shall be closed and strapped in accordance with the appendix to Specification PPP-B-636.

5.2.3 Level C.- Quick-disconnect coupling assemblies preserved and packaged as specified in 5 1 shall be packed in a manner to insure carrier acceptance and safe delivery at destination Containers shall be in accordance with Uniform Freight Classification Rules or regulations of other carriers applicable to the mode of transportation

5.3 Marking.- In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with the requirements of MIL-STD-129

6. NOTES

6.1 Intended use - The quick-disconnect coupling assemblies covered by this specification are intended for use with flanged subminiature waveguide assemblies which are to be coupled and uncoupled frequently Flanges and waveguides are described in the applicable specification sheet (see 3.1)

6.2 Ordering data.- Procurement documents should specify the following.

(a) Title, number, and date of this specification.
(b) Title, number, and date of the applicable specification sheet, and the complete part number (see 3.1).
(c) That the supplier shall not substitute for a specified material or fabricated part unless he obtains approval from the Government. Evidence to substantiate his claim that such a substitute is suitable shall be submitted with his request. Similar notification and substantiating evidence shall be submitted at any later time if substitution becomes necessary or desirable. At the discretion of the Government, test samples may be required to prove the suitability of the proposed substitute.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:07Z
Check the source to verify that this is the current version before use.

(d) Whether quick-disconnect coupling assemblies are to be annealed before finish machining (see 3.3.1).
(e) Levels of preservation and packaging, packing, and applicable marking (see 5.1 and 5.2)

Custodians:
Army - EL
Navy - Ships
Air Force - SEG

Preparing activity:
Navy - Ships
(Project 5985-0332)

Reviewers
Army - EL,MU,MI
Navy - Ships
Air Force - 11,17,85

Users
Army - MO
Navy - MC,WP

Note: Review/user information is current as of the date of this document For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:07Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY
BUREAU OF SHIPS
WASHINGTON , D.C. 20360

OFFICIAL BUSINESS

POSTAGE AND FEES PAID
NAVY DEPARTMENT

CHIEF, BUREAU OF SHIPS
SPECIFICATIONS AND STANDARDIZATION BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:07Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved Budget Bureau No 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor involved in the use of the specification in procurement of products for ultimate use by the Department of Defense This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost Comments and the return of this form will be appreciated Fold on lines on reverse side staple in corner, and send to preparing activity

SPECIFICATION		
ORGANIZATION		CITY AND STATE
CONTRACT NO	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT $

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1 HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2 COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3 IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF YES IN WHAT WAY?

4 REMARKS *(Attach any pertinent data which may be of use in improving this specification If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 68 1426 REPLACES NAVSHIPS FORM 4863 WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:07Z
Check the source to verify that this is the current version before use.