INCH-POUND
MIL-C-3003/lOA
Amendment 1
21 Nov 1994

MILITARY SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE), TANTALUM, (POLARIZED, SINTERED SLUG), ESTABLISHED RELIABILITY, STYLES CSS13 AND CSS33 (HIGH RELIABILITY APPLICATIONS)

This amendment forms a part of MIL-PRF-39003/10A, dated 17 February 1993, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Case Type: delete "Tubular, insulated." and substitute "Tubular, insulated or uninsulated.'

PAGES 3, 4, AND 5

TABLE I, failure rate level dash number column heading, delete "Part no. M39003/10A-" and substitute "PIN M39003/10-."

PAGE 4

TABLE I, Case size column, line 12, delete "A" and substitute "B."

PAGES 6 AND 7

TABLE II, failure rate level dash number column heading, delete "Part no. M39003/10A-" and substitute "PIN M39003/10-."

TABLE II, ESR column heading, delete "±25°C" and substitute "+25°C."

PAGE 6

TABLE II, ESR column line 43: delete ".20" and substitute "1.20."

PAGE 8

First paragraph heading, delete in its entirety: "QUALIFICATION INSPECTION," replace with "QUALIFICATION/QUALITY CONFORMANCE INSPECTION."

Second paragraph heading, delete in its entirety: "QUALITY CONFORMANCE INSPECTION."

TABLE Ill, sample size column, subgroup 2, delete "1.0 AQL" and substitute "13 pcs."

TABLE III, bottom of table, footnote 7, delete in its entirety and substitute:

AMSC N/A FSC 5910

DISTRIBUTION STATEMENT A. Approved for public release; distribution limited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:06Z
Check the source to verify that this is the current version before use.

"7/ MIL-C-39003 X-ray pictorials shall be used with the following details and exceptions:

a. Solder voids are acceptable if at least 50 percent of each side of the anode length is supported by solder and at least 50 percent of the anode diameter is covered on the bottom.

b. Excessive solder is acceptable if the top surface of the anode and the riser wire are not obscured.

c. Anodes may be cocked within the case, provided the pellet is not greater than 15 degrees from being parallel with the wall of the case.

d. Bent tantalum riser wire is rejectable."

CONCLUDING MATERIAL

Custodians:

Army- ER
Navy- EC
Air Force - 19

Review activities:
Navy - SH
Air Force - 17, 85, 99
DLA - ES

User activities: 0 S
Navy - MC, AS, OSF

Preparing activity:

Air Force - 19

Agent:
DLA- ES

(Project 5910-1871)

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:06Z
Check the source to verify that this is the current version before use.