NOTE: The document identifier and heading has been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.

INCH-POUND

MIL-PRF-39003/2E
AMENDMENT 1
10 November 1994

PERFORMANCE SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE), TANTALUM,
(POLARIZED, SINTERED SLUG), ESTABLISHED RELIABILITY,
STYLE CSR09

This amendment forms a part of MIL-C-39003/2E, dated 10 June 1993, and is approved for use by all Department and Agencies of the Department of Defense.

PAGE 3

Life: Delete "Cap.: In accordance with MIL-C-39003." and substitute "ΔCap.: Not greater than ±5 percent of initial measured value.".

Following "Life, At 125°C:, DCL: See table I" add the following:

"4,000, 6,000, 8,000, and 10,000 hours (exponential only):

At +25°C (as applicable):

DCL: 200 percent of initial limit.

ΔCap.: Not greater than ±10 percent of initial measured value.

DF: See table I.

At +85°C:

DCL: 200 percent of initial limit.

At +125°C:

DCL: 200 percent of initial limit."

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Navy - AS, MC, OS, SH
Air Force - 17, 19, 99

Preparing activity:
DLA - ES

(Project 5910-1912)

DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:03Z
Check the source to verify that this is the current version before use.