MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (SOLID ELECTROLYTE), TANTALUM,
(POLARIZED, SINTERED SLUG), ESTABLISHED RELIABILITY,
STYLE CSR33

This amendment forms a part of MIL-C-39003/6A, dated 2 February 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

* Following title, add:

"

FAILURE RATE LEVELS "M", "P" AND "R" ARE INACTIVE FOR NEW DESIGN AFTER 2 FEBRUARY 1984.
FAILURE RATE LEVEL "S" IS INACTIVE FOR NEW DESIGN AFTER 15 AUGUST 1994.

"

* Following acquisition note: Delete existing inactivation note.

FIGURE 1, dimension M max: Delete "M max" and substitute "J max".

PAGE 3

Measurements after completion of the surge current test: Delete "Cap. - Shall not change more than ±2 percent of initial measured value." and substitute "Cap. - Shall be as specified in table I."

PAGES 4 AND 5

TABLE I, heading for columns 10 through 16: Delete "M39003/03-" and substitute "M39003/06-".

NOTE: The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Navy - OS, SH
Air Force - 17, 99
DLA - ES

User activities:
Navy - AS, MC
Air Force - 11, 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5910-1525-3)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T16:05Z
Check the source to verify that this is the current version before use.