MIL-C-55669B
23 January 1978
Superseding
MIL-C-55669A
28 June 1972

MILITARY SPECIFICATION

CAMERA, STILL PICTURE 35MM, SINGLE LENS REFLEX

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for two types of high-quality, 35mm, single lens reflex, through-the-lens metering, still picture camera bodies, lenses and ancillary equipment.

1.2 Classification. Cameras covered by this specification shall be of the following types, classes, and styles, as specified (see 6.2).

1.2.1 Types. Cameras shall be classified as to mode of operation:

Type I - Manually operated
Type II - Motor operated

1.2.2 Classes. Cameras shall be classified as to type of exposure control:

Class A - Automatic exposure control
Class B - Semi-automatic exposure control

1.2.3 Styles. Cameras shall be classified as to the type of metering:

Style 1 - Averaging through-the-lens metering
Style 2 - Spot through-the-lens metering

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Electronics Command, ATTN: DRSEL-RD-TS-S, Ft. Monmouth, New Jersey 07703, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 6720

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents, of the issue in effect on the date of the invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

NN-P-71	Pallet, Materials-handling, Wood (General Construction Requirements)
QQ-S-781	Strapping, Steel, Flat and Seals
PPP-B-585	Box, Wood, Wirebound
PPP-B-601	Box, Wood, Cleated Plywood
PPP-B-621	Box, Wood, Nailed and Lock Corner
PPP-B-636	Box, Fiberboard
PPP-B-640	Box, Fiberboard, Corrugated, Triple-wall
PPP-F-320	Fiberboard, Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes
PPP-S-760	Strapping, Nonmetallic (And Connectors)
PPP-T-97	Tape, Pressure-sensitive Adhesive, Filament Reinforced

MILITARY

MIL-P-116	Preservation-packaging, Methods of
MIL-C-675	Coating of Glass Optical Elements (Anti-Reflection)
MIL-P-19644	Plastic Molding Material (Polystyrene Foam, Expanded Bead)
MIL-P-26514	Polyurethane Foam, Rigid or Plastic, for Packaging

STANDARDS

FEDERAL

FED STD No 356 Commercial Packaging of Supplies and Equipment

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-130	Identification Marking of US Military Property
MIL-STD-147	Palletized and Containerized Unit Loads 40 inch x 48 inch Pallets, Skids, Runners or Pallet Type Base
MIL-STD-150	Photographic Lenses
MIL-STD-461	Electromagnetic Interference Characteristics Requirements for Equipment
MIL-STD-462	Electromagnetic Interference Characteristics Measurement of
MIL-STD-810	Environmental Test Methods

(Copies of specifications and standards required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issue in effect on date of invitation for bids or request for proposal shall apply.

NATIONAL BUREAU OF STANDARDS

Handbook H-28	Screw-Threads Standards for Federal Services

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402.)

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

PH1.14-1965	35mm Film Magazine and Film for Still Picture Cameras, Dimensions for
PH2.15-1964	Automatic Exposure Control for Cameras
PH3.6-1952	Tripod Connections for American Cameras 1/4 inch-20 Thread
PH3.23-1950	Shutter Cable Release Tip and Socket with Tapered (European) Thread
PH3.24-1950	Shutter Cable Release Tip and Socket With Straight (American) Thread
PH3.32-1972	Exposure-Time Markings for Still Picture Cameras
PH3.39-1972	Picture Sizes for Roll Film, 35mm Film and 126 Film Still-Picture Cameras

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

PH3.48-1972 Shutter Tests for Still-Picture Cameras

(Application for copies should be addressed to American National Standards Institute, 1430 Broadway, New York, New York 10018.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Description.

3.1.1 Type I Camera. Type I camera shall consist of a manually operable, single-lens-reflex, through-the-lens metering as specified, focal plane shutter, 35mm camera body with body cap, and the lenses and ancillary equipment as specified by the procuring activity (see 6.2).

3.1.2 Type II Camera. Type II camera shall consist of an electric motor operable, single-lens-reflex, through-the-lens metering as specified, focal plane shutter, 35mm camera body with body cap and the lenses and ancillary equipment as specified by the procuring activity (see 6.2).

3.1.3 Lenses and ancillary equipment. Additional components, as specified by the procuring activity (see 6.2) shall include but not be limited to the following:

a. Lenses (see 3.6)

b. Right-angle viewer (see 3.8)

c. Repeating electronic flash equipment (see 3.9)

d. Cable releases (see 3.10)

e. Filters (see 3.7)

f. Lens extension tubes (see 3.6.4)

g. Carrying cases (see 3.13)

h. 250 exposure bulk film back and magazine (see 3.4.6.2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

3.2 First article. When specified (see 6.2) the contractor shall furnish first article units in accordance with 4.3.

3.3 Parts, materials and processes; general. Parts, materials and processes shall be such as to enable the equipment to meet the performance and other requirements as specified herein.

3.3.1 Fungus-inert materials. Materials which are not nutrients for fungus shall be used wherever possible. If it is necessary to use nutrient materials, the parts and materials shall be treated prior to their use in the equipment so that overall spraying of the equipment is not necessary. Certification by the contractor of type of material and treatment shall be acceptable in lieu of formal testing (see 6.2).

3.3.2 Screw threads. Screws, nuts, bolts and threaded parts shall be in accordance with the National Bureau of Standards Handbook H-28.

3.4 Camera body. The camera body shall be constructed of aluminum alloy or similar light-weight metal and shall be so constructed that all seams are light-tight and dust resistant. The body shall maintain all operating parts of the camera in proper functional alignment during the life of the camera. The camera body shall accept interchangeable lenses of various focal lengths as specified by the procuring activity The camera body shall accept lenses, bellows and adapters for acquisition of closeup photography.

3.4.1 Tripod socket. A tripod socket whose screw thread and depth shall be in accordance with ANSI Standard PH3.6-1952 shall be provided in the base of the camera body. The socket shall be firmly embedded and flush with the base.

3.4.2 Body cap. A body cap shall be provided to protect the camera interior when the lens is removed.

3.4.3 Camera back. The camera back shall permit film loading and unloading without necessitating camera removal from a tripod. The back shall be hinged but removable, completely light-tight, and provided with a positive locking device that resists accidental opening.

3.4.3.1 Pressure plate. The pressure plate shall assure flatness of the film during exposure and shall not damage the film during exposure or transport.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

3.4.4 Film transport. The camera shall be provided with a film advance lever for single-stroke film advance, shutter cocking, and exposure count. A built-in double exposure prevention means shall be provided. The film advance lever shall automatically return to its starting position upon completion of each stroke. Successive frames of film shall be positioned accurately with equal spacing between frames. Frame lines shall not fall at a sprocket hole. Means shall be provided for rewinding exposed film back into the film magazine. The film advance lever shall be capable of being operated when all accessories are attached and the operator is wearing military issue gloves with inserts.

3.4.5 Film plane. The film plane shall be perpendicular to the lens axis within seven minutes of arc.

3.4.6 Film loading. The camera shall be equipped with a fixed takeup spool. The spool shall be capable of properly engaging the film leader.

3.4.6.1 Film capacity. The camera shall be capable of accepting 20 and 36 exposure daylight loading magazines conforming to ANSI Standard PH1.14-1965.

3.4.6.2 Bulk film back. Upon removal of the hinged camera back, the camera body shall be capable of accepting a 250 exposure bulk film back and magazines. The bulk film back shall be capable of being used with the electric motor drive and also manually operated.

3.4.7 Image size. The size of the image recorded on the film shall be in accordance with ANSI Standard PH3.39-1972 as specified by the procuring activity (see 6.2). (See 4.15.1.)

3.4.8 Shutter. The camera body shall be provided with a focal plane shutter having a speed range of at least 1 second to 1/1000 second and bulb (B). The exposure time markings shall be in accordance with ANSI Standard PH3.32-1972. The shutter speeds shall be selected via a dial equipped with a click stop at each marked speed. When specified in the contract or purchase order (see 6.2) the set speed shall be displayed in the viewfinder. The shortest exposure time suitable for use with zero delay (X) flash synchronization shall be suitably marked on the shutter speed selector dial. Speed settings shall be capable of being changed before and after the shutter is cocked. The shutter speed selector dial shall not rotate during shutter operation. Shutter speed selection and shutter release shall be operable by a person wearing military gloves with inserts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

3.4.8.1 Shutter release pressure. The pressure required to operate the shutter release shall be between 225 and 550 grams.

3.4.8.2 Self-timer. A self-timer, capable of delaying the shutter action for eight seconds or more, shall be provided (see 4.15.2). The mechanism shall activate the shutter within ± one second of the selected time delay.

3.4.8.3 Shutter speed tolerances. Shutter speeds shall be within ±25 percent of the indicated setting at all shutter speeds between 1 second to 1/500 second inclusive and ±30 percent at 1/1000 second when tested as specified in 4.14, at ambient temperature of 73 ±18 degrees Fahrenheit (23 ±10 degrees centigrade).

3.4.8.4 Flash synchronization. The camera shall be synchronized for electronic flash equipment and flash bulbs. Electronic flash shall be synchronized at a speed range from one second to a minimum of 1/60 second. Proper indication for correct synchronization of flash exposure shall be marked on the shutter speed dial.

3.4.8.5 Cable release socket. The camera shall be capable of utilizing a cable release conforming to ANSI Standard PH3.23-1950 or PH3.24-1950.

3.4.9 Viewfinder. The viewfinder shall be an eyelevel, pentaprism type in which framing, focusing, depth-of-field check, luminance determination, aperture, and shutter speed selection if required, are viewed. The eyepiece shall be designed with sufficient eye relief so that an operator wearing glasses will be able to see the field of view. The viewfinder system shall incorporate a split prism rangefinder, micro-prism, or other aid suitable for critical focusing at short working distances, and in low ambient light levels. The viewfinder housing shall be interchangeable with other ancillary viewfinders used for action photography, image magnification, and other specialized purposes. The viewfinder system shall be compatible with all lens focal lengths as specified by the procuring activity (see 6.2). The viewfinder shall accommodate focusing screens as specified by the procuring activity (see 6.2).

3.4.9.1 Field of view. The viewfinder field of view shall be not less than 22mm by 33mm, or greater than actual film image size. The field of view shall be concentric with the lens axis.

3.4.9.2 Depth-of-field preview. A means shall be provided for viewing the effect of stopping down lenses incorporating automatic diaphragms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

3.4.10 Light measurement system. The camera shall be provided with a through-the-lens exposure meter.

3.4.10.1 Exposure meter. Light measurement shall be made by battery-powered photo resistor(s) with the output driving the meter needle. A reference indicator, which when in alignment with the meter needle determines the correct exposure, shall be part of the meter for Class B cameras.

3.4.10.1.1 Sensitivity. The meter shall respond to an object luminance range of at least 0.19 to 1500 (inclusive) candles-per-square foot at f/2.

3.4.10.1.2 Accuracy. The accuracy of the meter shall be within ±1/2 f/stop over the complete range.

3.4.10.1.3 Meter switch. Provision shall be made for the deactivation of the meter circuit.

3.4.10.2 Battery. The exposure meter shall utilize a battery that shall properly operate the electrical functions of the camera. Easily accessible means of holding and replacing the battery shall be provided.

3.4.10.3 Meter battery condition test facility. An integral means to test and indicate the condition of the battery shall be provided.

3.4.11 Exposure control.

3.4.11.1 Class A. Class A camera shall be provided with full automatic exposure control with manual override.

3.4.11.2 Class B. Class B camera shall be semi-automatic, with the indicator cross coupled to the shutter speed dial, the lens diaphragm adjustment control and the film speed (ASA) control. Proper exposure shall be established by alignment of the pointer of the exposure meter with a reference indicator or other positive means of indication.

3.4.11.3 Film speed setting range. The ASA film speed setting range shall be at least from 25 to 1600 inclusive.

3.4.12 Mirror. An "instant-return" mirror shall be provided. The mirror shall be capable of being locked in the up position. The action of the mirror shall not cause any vibration which deteriorates image sharpness.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

3.4.13 Exposure counter. A clearly visible exposure counting device shall be provided to indicate the number of exposed frames. The counter shall return to its starting position automatically when the camera back is opened. The counter shall arrive at zero after two frames have been transported.

3.5 Type II camera. In addition to the requirements specified in 3.4, the following requirements for the motor drive, power pack, and power pack charger shall apply for the Type II camera.

3.5.1 Motor drive. The motor drive shall permit selective operation of the camera in automatic or semi-automatic drive modes. The attached motor shall in no manner prevent or impair manual operation of the camera.

3.5.1.1 Automatic drive. In the automatic drive mode, the motor-driven camera shall be capable of at least 36 consecutive exposures at the rate of at least 3 exposures per second over the camera's range of shutter speeds of 1/30 second and faster. A facility for preprogrammed automatic cut-off of operation shall be provided.

3.5.1.2 Semi-automatic drive. The motor-driven camera shall be capable of semi-automatic operation over the camera's full range of shutter speeds of one second and faster.

3.5.1.3 Remote control. The motor unit shall be provided with a facility to permit its remote activation via a wire, radio, sound, light, or other type of transmittal signal as specified in the contract (see 6.2).

3.5.2 Power pack. The motor unit housing shall have provision for a self-contained, replaceable power pack consisting of a nominal 12 volt dc power supply. The power-pack shall be furnished with nickel cadmium (Ni Cad) batteries. When fully charged the power pack shall have sufficient capacity to activate motor-driven camera for 500 consecutive exposures in automatic and semi-automatic drive modes. The power pack shall be provided with either an integral or supplementary power pack (battery) test facility.

3.5.3 Power supply charger. An auxilliary power pack charger assembly, with requisite cable(s), shall be provided. The charger shall be capable of operation from dc sources of nominal 12 and 24 volts, and from ac sources of nominal 110 and 220 volts, 50-60 hertz (Hz). The charger shall incorporate a facility providing for automatic circuit cut-off when the batteries attain full charge. A silent visual signal device shall indicate that the automatic circuit cut-off has occurred.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

3.6 Lenses. Interchangeable, bayonet or threaded base type mounting, Type III lenses in accordance with MIL-STD-150 shall be provided as specified by the procuring activity (see 6.2).

3.6.1 Anti-reflection coating. All glass to air surfaces shall be coated in accordance with MIL-C-675.

3.6.2 Iris diaphragm. Each lens furnished shall have an automatic iris diaphragm. The iris diaphragm shall provide a continuously variable size opening over its entire range and shall be provided with an easily operated aperture control. The control shall work against a scale which shall be permanently marked in accordance with MIL-STD-150. In addition to the marked f/stops, the iris control ring shall be equipped with detent "click stops". Detent pressure shall be sufficient to preclude accidental changing of the set f/stop. The iris shall not close completely. The diaphragm shall be coupled to the shutter release which shall close the diaphragm to its predetermined value before the exposure is made and shall reopen the diaphragm to its widest opening after the exposure is complete.

3.6.3 Lens resolution. The minimum Area Weighted Average Resolution (AWAR) for each lens shall be as specified in the contract by the procuring activity.

3.6.4 Unit magnification. The camera shall be capable of close-up photography when utilizing the appropriate bellows or extension tubes and lenses. A continuous focusing capability shall be provided from the close-up range to infinity. Provision shall be made to retain the exposure meter operation as specified in 3.4.11.

3.7 Filters. Filters shall be provided as specified by the procuring activity (see 6.2).

3.8 Right-angle viewer. When specified by the procuring activity (see 6.2), a right-angle viewer, suitable for viewing the entire field of view, correct side up and properly left-right oriented as seen through the viewfinder eyepiece shall be provided. The right-angle viewer shall be capable of 360 degree rotation about the viewfinder eyepiece lens axis and shall be lockable in any position. The right-angle viewer eyepiece shall be provided with correction of not less than +2 to -2 diopters inclusive.

3.9 Repeating electronic flash. When specified by the procuring activity (see 6.2) a combination, automatic-and manual-operating electronic flash

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

shall be provided. The electronic flash shall have a self-contained rechargeable, Ni Cad or similar power supply, a self-contained battery recharging capability, one each removable, nominal 3-foot maximum extension coiled, PC-tipped, flash to camera connecting cable and a removable, nominal 10-foot (3.05m) long, combination AC operating and charging cable. Flash units shall be able to recharge and operate in a slave mode from commercial power of 110-220 volts, 50-60 Hertz.

3.9.1 Light output. The repeating electronic flash light output shall be capable of an exposure guide number of not less than 40 nor more than 60 with ASA 25 rated daylight color film when the flash is operated in the manual mode. When used in the automatic mode the flash shall provide for the cameraman's choice between at least two different f/stops.

3.9.2 Power supply charging. The power supply shall not require more than one hour of charging before first use.

3.9.3 Flash per charge. The electronic flash shall be capable of an average eight flashes after five minutes charging, ten flashes after fifteen minutes charging and 65, or over, after 60 minutes charging.

3.9.4 Angle of coverage. The full illumination angle of coverage shall not be less than 70 degrees horizontal or vertical.

3.10 Cable release. A cable release conforming to ANSI Standard PH3.24-1950, within the range of 200 to 300 millimeters (8 to 13 inches) overall length shall be provided. The cable release shall be provided with a locking device for locking the cable to prevent movement.

3.11 Accessory shoe. The camera body shall be provided with an accessory shoe. The shoe may be either permanently attached to the camera body or part of an accessory unit.

3.12 Neckstrap. A neckstrap, capable of being attached to the camera body, shall be provided. It shall be made of strong, long-lasting material; adjustable in length; and 13mm ±2mm (1/2 inch ±1/16 inch) in width.

3.13 Carrying cases. Carrying cases, of the following types, shall be provided as specified by the procuring activity (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

a. Eveready type (see 3.13.1)

b. Gadget bag type (see 3.13.2)

c. Camera set type (see 3.13.3)

3.13.1 Eveready camera case. The eveready type case shall be capable of containing the camera body equipped with the nominal 50mm lens and its lens-hood. The case shall be provided with a captive, camera-retaining screw to engage the camera's tripod socket.

3.13.2 Gadget bag. The collapsible, shoulder-carrying, gadget bag type case shall be capable of carrying the camera body equipped with the nominal 50mm lens, two additional lenses, lenshoods and filters, electronic flash unit, and not less than two rolls of film. When specified by the procuring activity (see 6.2), the bag shall be capable of being folded and stored in an allotted space within the camera set carrying case.

3.13.3 Camera set carrying case. The carrying case, with a comfortable handle, shall be capable of holding the camera in the eveready case, all ancillary equipment as specified by the procuring activity (see 6.2) and at least four film magazines conforming to ANSI Standard PH1.14-1965. The case shall be made of glass-fiber reinforced plastic, aluminum alloy, or similar lightweight, high-strength material. The case shall contain chemically inert shock-absorbing material with openings therein, shaped so that the camera and ancillary equipment will fit snugly. The cushioning material shall be of such quality that repeated insertions or removal of the camera and ancillary equipment will not damage it. The case and cushioning material shall be capable of meeting the service condition of 3.19 without functional impairment. The cushioning material shall be of sufficient thickness to protect the equipment when subjected to the test specified in 4.10. The case shall have positive means of closure. When a shoulder strap is specified by the procuring activity, provisions shall be made for attachment of it to the carrying case.

3.13.3.1 Shoulder strap. When specified by the procuring activity (see 6.2), a shoulder strap shall be provided. It shall be made of strong, long-lasting material, 25mm ±3mm (1 inch ±1/8 inch) wide, and shall be adjustable in length. The shoulder-bearing area shall be at least two times the width of the strap.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

3.14 Breakdown voltage, insulation. Electrical insulation shall have a minimum breakdown voltage as follows:

Circuit	Voltage
Electronic flash	1000 volts dc
Flash bulb	500 volts dc

After 10-second application of voltage, there shall be no visible or electrical deterioration of the equipment (see 4.16).

3.15 Cleaning. The camera and ancillary equipment shall be free of burrs, sharp and rough edges, and shall be cleaned in accordance with good commercial practice. Cleaning process shall have no deleterious effect. Corrosive material shall be removed completely.

3.16 Finish, protective. All finishes, including plating, shall be in accordance with the highest quality commercial practice and shall enable the equipment to meet the service conditions specified herein. The color of the camera, lens barrels, lenshoods, and right-angle viewer shall be professional black. The color and finish of the carrying cases and straps shall be in accordance with standard commercial practice.

3.17 Marking. The camera body and ancillary equipment shall be marked in accordance with MIL-STD-130.

3.17.1 Lens marking. Each of the Type III lenses shall have the name, focal length, and maximum aperture on the front of the lens cell. The lens serial number may be placed on the lens barrel if space limitations so require. The lens name and serial number shall be assigned by the manufacturer.

3.17.1.1 Aperture marking. Lenses shall be marked with maximum aperture followed by the standard series of full-stop openings in accordance with MIL-STD-150.

3.17.2 Visibility. Wherever practicable, identification markings shall be readily visible with minimum disassembly of the equipment.

3.17.3 Serial numbers. The camera body, motor unit and each lens shall have serial numbers assigned by the manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

3.18 Camera resolution. The system resolution of the lens-camera body combination shall be specified by the procuring activity (see 6.2).

3.19 Service conditions. Unless otherwise specified by the procuring activity (see 6.2) the camera and ancillary equipment shall meet the following service conditions:

3.19.1 Temperature.

3.19.1.1 Low. The degradation in the shutter speeds shall not exceed +30 percent when the equipment is operated at an ambient temperature of -18 degrees C (0 degrees F) (see 4.7).

3.19.1.2 High. The degradation in the shutter speed shall not exceed +30 percent when the equipment is operated at an ambient temperature of +49 degrees C (120 degrees F) (see 4.5).

3.19.2 Humidity (moisture resistance). After testing as specified in 4.8, the camera and ancillary equipment shall be operable without degradation in specified performance, and shall have sustained no physical damage.

3.19.3 Altitude. The equipment shall be operable without degradation in specified performance at altitudes up to 3 kilometers (10,000 feet) above sea level and shall withstand air transportation at altitudes up to 12 kilometers (40,000 feet) above sea level (see 4.6).

3.19.4 Dust. The camera and ancillary equipment, in its carrying case, (see 3.13.3) shall withstand exposure to fine dust particles with wind speeds of 17 knots (see 4.9).

3.19.5 Vibration. After testing as specified in 4.10, the camera and ancillary equipment shall be operable without degradation in specified performance and shall have sustained no physical damage.

3.19.6 Electromagnetic interference. The equipment's electrical components shall conform to the requirements of MIL-STD-461, class IIB.

3.20 Reliability. Reliability of the camera shall be at least 15,000 mean cycles between failures when operated under any of the environmental conditions specified herein with routine preventive maintenance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

3.20.1 Service life. The camera shall have a minimum service life of at least 150,000 cycles, when operated under any combination of environmental conditions specified herein with allowance for corrective maintenance with replacement of worn or damage parts.

3.21 Interchangeability. All lenses, magazines, and ancillary equipment shall be completely interchangeable on each body of the same model and manufacturer.

3.22 Technical literature. Technical literature including operating and maintenance instructions will be supplied with each unit.

3.23 Workmanship. The camera, including all parts and ancillary equipment, shall be constructed and finished in such a manner as to permit it to accomplish the task for which it was intended. Particular attention shall be given to neatness and thoroughness of soldering, wiring, marking of parts and assemblies, welding and brazing, painting, riveting, machine-screw assemblies, and freedom of parts from burrs and sharp edges.

3.23.1 Dimensions. Dimensions and tolerances not specified shall be as close as its consistent with the best shop practices. Where dimensions and tolerances may affect the interchangeability, operation or performance of the camera, they shall be held or limited accordingly.

3.23.2 Threaded parts. Screws, nuts, and bolts shall show no evidence of cross threading, mutilation, detrimental or hazardous burrs. All screw-type fasteners shall be tight. The word tight means the screw shall be firmly secured and that there shall be no relative movement possible between the attached parts.

3.23.3 Riveting. The riveting operation shall be carefully performed in order to assure that rivets are tight and satisfactorily headed with the rivet heads tightly seated against their bearing surface.

3.23.4 Gears. Gear assemblies shall be aligned and meshed and shall be operable without interference, tight spots, loose spots, or other irregularities that could cause unsatisfactory operation. Where required for accurate adjustments, gear assemblies shall be free from backlash.

3.23.5 Cleaning. The camera and ancillary equipment shall be thoroughly cleaned of loose, spattered or excess solder, metal chips and other foreign material, after final assembly. Burrs and sharp edges, as well as resin flash that may crumble, shall be removed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order the supplier may utilize his own facilities or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

c. Packaging inspection (see 4.23).

4.3 First article. Unless otherwise specified in the contract or purchase order, the first article inspection shall be performed by the contractor.

4.3.1 First article units. The contractor shall furnish two first article units of the camera and of the ancillary equipment specified by the procuring activity.

4.3.2 First article inspection. The first article inspection shall consist of the inspections specified for Group A, Group B and Group C (see Tables I, II and III respectively). The inspection shall be performed in the following order: Group A and Group B for all units and designated units for specific groups within Group C in accordance with 4.4.3.1. After completion of Group C environmental tests, conforming units shall be reinspected and shall pass all Group A inspections.

4.3.3 First article data. The first article test plan and test report(s) shall be as required in the contract or purchase order.

4.4 Quality conformance inspection. The contractor shall perform the inspections specified in 4.4.1 through 4.4.4. This does not relieve the

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

contractor of his responsibility for performing any additional inspection which is necessary to control the quality of the product and to assure compliance with all specification requirements.

4.4.1 Group A inspection. Each unit on contract or purchase order shall be inspected for conformance to the inspections specified in Table I. Discrete lots shall be formed from units that pass this inspection. Factors of lot composition not defined herein, or in the contract or purchase order, shall be in accordance with MIL-STD-105. Each lot shall be subject to sampling inspection, utilizing the procedures of MIL-STD-105, using the general inspection levels, and AQL's indicated in Table I.

Table I. Group A Inspection

Inspection	Req Para	Test Para	AQL	
			Major	Minor
Visual and Mechanical				
Camera, Still Picture Type I	3.23	4.22	1.0%	4.0%
Camera, Still Picture Type II	3.23	4.22	1.0%	4.0%
Ancillary Equipment	3.23	4.22	1.0%	4.0%
Resolution (Bench)	3.6.3	4.12.1	1.0%	*
Resolution, Camera	3.18	4.12.2	1.0%	*
Shutter, Release Pressure	3.4.8.1	4.20	1.0%	*
Operational	3.4.3 thru 3.4.13; 3.5.2	4.15	1.0%	*
Flash synchronization	3.4.8.4	4.19	1.0%	*

*All operational defects are considered major.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

4.4.1.1 Order of inspection within Group A. Group A inspection shall be performed in an order satisfactory to the Government.

4.4.2 Group B inspection. Group B inspection shall normally be performed on inspection lots that have passed Group A inspection and on samples selected from units that have been subjected to and met the Group A inspection. This inspection shall conform to Table II and to the special inspection levels of Table I of MIL-STD-105.

Table II. Group B Inspection

Inspection	Req Para	Test Para
Shutter Speed	3.4.8.3	4.14
Breakdown Voltage	3.14	4.16
Interchangeability	3.21	4.17
Exposure Control	3.4.10 & 3.4.11	4.18
Power Supply Charger	3.5.3	4.21

4.4.2.1 Group B sampling plan. The Group B AQL shall be 6.5 percent defective and the inspection level shall be S-4.

4.4.2.2 Order of inspection within Group B. Group B inspection shall be performed in an order satisfactory to the Government.

4.4.3 Group C inspection. Group C inspection shall be performed on units that have passed Group A and Group B inspection. This inspection shall consist of the inspections specified in Table III. Samples shall be selected in accordance with 4.4.3.1.

4.4.3.1 Sampling for inspection. One sample unit shall be selected at random for each group of inspections in Table III from every 100 units or fraction thereof produced. The first samples selected shall be at the start of the contract from the first quality conformance inspection production lot (see 4.4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

Table III. Group C Inspection

Inspection	Req Para	Test Para
Group I		
Reliability	3.20 & 3.20.1	4.13
Group II		
High Temperature	3.19.1.2	4.5
Altitude	3.19.3	4.6
Low Temperature	3.19.1.1	4.7
Humidity	3.19.2	4.8
Dust	3.19.4	4.9
Vibration	3.19.5	4.10
Electromagnetic Interference	3.19.6	4.11

4.4.3.2 Order of inspection within Group C. Group C inspection shall be performed in accordance with Table III.

4.4.3.3 Group C failures. Actions required relative to Group C failures shall be as specified in the contract or purchase order.

4.4.4 Reinspection of conforming Group B and Group C sample units. Unless otherwise specified, sample units which have been subjected to and passed both Group B and Group C inspection may be accepted on the contract provided all damage is repaired and the sample units are resubjected to and pass Group A inspection.

4.5 High temperature. The camera and ancillary equipment, in the camera set carrying case, shall be tested in accordance with Method 501.1, Procedure II of MIL-STD-810. The camera shall be subjected to the operational test specified in 4.15 at the end of the first 12-hour cycle at ambient room temperature. The remaining two 12-hour cycles shall be conducted with the camera and the attached nominal 50mm lens outside of the carrying case. The carrying case shall be open for these two cycles. The shutter speed test specified in 4.14 shall be performed at Step 8 of Procedure II. Steps 9 and 10 will be performed at the conclusion of the three 12-hour cycles. The operational test specified in 4.15 shall be repeated at the end of the test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

4.6 Altitude. The camera and ancillary equipment, in the camera set carrying case, shall be tested in accordance with Method 500.1, Procedure I of MIL-STD-810. After completion of the test, the camera shall be subjected to the operational test specified in 4.15.

4.7 Low temperature. The camera and ancillary equipment, in the camera set carrying case, shall be tested in accordance with Method 502.1, Procedure I of MIL-STD-810. The storage temperature shall be minus 54 degrees C (-65 degrees F) for 12 hours and the operating temperature shall be minus 18 degrees C (0 degrees F). After completion of the test, the camera shall be subjected to the operational test specified in 4.15.

4.8 Humidity. The camera and ancillary equipment, in the camera set carrying case, shall be tested in accordance with Method 507.1, Procedure I of MIL-STD-810 except step 5 shall be three cycles only. After completion of the three cycles, the camera shall be subjected to the operational test specified in 4.15.

4.9 Dust. The camera and ancillary equipment with the lenses protected, in the camera set carrying case, shall be tested in accordance with Method 510.1, Procedure I, of MIL-STD-810 except steps 2 and 3 shall be omitted. The operational test, specified in 4.15, shall be conducted at the completion of the test.

4.10 Vibration. The camera and ancillary equipment, in its carrying case shall be subjected to sinusoidal vibration in its three mutually perpendicular axes, consisting of logarithmic cycling from 5 to 200 to 5 Hz. The sweep rate shall be 5 to 200 to 5 Hz in 12 minutes. Vibrating inputs to the test item shall be one inch double amplitude constant displacement from 5 to 5.5 Hz, and 1.5 G's peak constant acceleration from 5.5 to 200 Hz. Total test time shall be 84 minutes per axis of vibration. After the final axis of vibration, the camera shall be subjected to the operational test of 4.15 herein.

4.11 Electromagnetic interference. The Type II camera's motor drive unit shall be tested over a frequency range of 150 KHz to 50 MHz in accordance with the applicable test procedures of MIL-STD-462. The drive unit shall meet the requirements specified in 3.19.6.

4.12 Resolution test.

4.12.1 Lenses (Bench). Each lens shall be tested in accordance with Method II of MIL-STD-150 (see 3.6.3). The film, developer, and processed gamma utilized shall be as specified by the procuring activity. (See 6.2.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

4.12.2 System. The camera body and lenses shall be tested in accordance with Method II of MIL-STD-150 to determine compliance with the resolution requirements as specified by the procuring activity (see 3.18). The film developer, and processed gamma shall be as specified by the procuring activity (see 6.2).

4.13 Reliability. The camera body, lenses, and ancillary equipment shall be tested to determine compliance with the requirements of 3.20 and 3.20.1.

4.14 Shutter speed test. The camera shall be tested in accordance with ANSI Standard PH3.48-1972 to determine compliance with 3.4.8.3.

4.15 Operational test. The camera shall be loaded utilizing film as specified by the procuring activity and, utilizing the nominal 50mm lens, three exposures (one each at the maximum, middle, and minimum lens aperture) shall be made at each shutter speed setting. The level of illumination shall be varied as the exposure (determined by the camera's meter system) requires. The subject shall consist of material the image of which shall be suitable for an empirical decision as to the acceptability of the image quality. The film shall be processed as specified by the procuring activity.

4.15.1 Image size. The frame dimensions of the processed film shall be measured to determine compliance with the requirement specified in 3.4.7.

4.15.2 Self-timer. The camera shall be operated using the self time to determine compliance with 3.4.8.2.

4.15.3 Power pack. The power pack utilized with Type II camera, shall be tested to determine compliance with the requirement specified in 3.5.2.

4.16 Breakdown voltage test. The camera's flash circuitry shall be tested for conformance to 3.14. During testing, disconnections shall be made where necessary to protect circuit elements.

4.17 Interchangeability. The camera body, lenses, and ancillary equipment shall be tested to determine compliance with the requirements as stated in 3.21.

4.18 Exposure control test. The camera shall be tested in accordance with any method of ANSI Standard PH2.15-1964, which is acceptable to the Government, to determine compliance with 3.4.10.1.1 and 3.4.10.1.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

4.19 Flash synchronization test. The camera shall be tested for synchronization with an electronic synchronization tester which is acceptable to the Government to determine compliance with 3.4.8.4.

4.20 Shutter release pressure test. The shutter release pressure shall be measured by any method acceptable to the Government to determine compliance with 3.4.8.1.

4.21 Power supply charger test. The charger shall be tested by using inputs of 12 Vdc ± 10 percent; 24 Vdc ± 10 percent; 110 Vac ± 5 percent, 50 Hz; 110 Vac ± 10 percent, 60 Hz; 220 Vac ± 5 percent, 50 Hz; and 220 Vac ± 5 percent, 60 Hz. The output shall be connected to a dummy load simulating the discharged batteries (both voltage and amperage).

4.22 Visual and mechanical inspection. The camera, lenses and ancillary equipment shall be examined for the defects listed in Table IV.

Table IV. Classification of Visual and Mechanical Defects

Classification	Defect
Major	a. Film position in film plane not as specified. b. Focusing screen mountings not within specified tolerance. c. Controls and parts missing, in operative or defective. d. Camera housing leaks light, general construction poor. e. Operating adjustments unsuitable, imperfections affecting operation. f. Interchangeable lenses do not fit camera. g. Lens hood and filter - wrong size, insufficient clearance. h. Viewfinder - Viewing range off and poor coverage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

Table IV. Classification of Visual and Mechanical Defects (Contd)

Classification	Defect
	i. Tripod fittings - mechanical imperfections, incorrect size. j. Carrying case - imperfections, poor fit of contents. k. Camera does not accept film holder or magazine. l. The film cannot be rewound into the magazine. m. The internal synchronization mechanism, does not energize the flash lamp. n. Excessive backlash in the film advance lever. o. Lens - scratches, cracks, looseness, poor fit of components. p. Markings - missing, illegible, or incorrect operational markings. q. Motor drive does not properly mate with and operate camera.
Minor	a. Finishes - scratches, cuts, poor application. b. Hardware - improperly assembled, imperfections not affecting operation. c. Foreign matter - causing temporary delay in adjustments.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

4.23 Packaging inspection. The contractor shall perform the inspection specified by 4.23.1 and 4.23.2. This does not relieve the contractor of his responsibility for performing any additional inspection which is necessary to control the quality of the product and compliance with all specification requirements.

4.23.1 Preservation and packaging. Preservation and packaging shall be inspected in accordance with MIL-P-116.

4.23.2 Packing and marking of exterior containers. Packing and marking of exterior containers shall be given visual inspection to determine conformance to Section 5 and requirements of the contract or purchase order. This inspection shall conform to the special inspection Levels of Table I of MIL-STD-105. The AQL shall be 4.0 percent defective for major defects and 10.0 percent defective for minor defects and the level shall be S-4.

4.23.2.1 Inspection lot. A lot for visual inspection of the pack shall be all completed packs which are identical and will be submitted for acceptance at one time.

4.24 Rough handling test (packaging). When rough handling test in accordance with MIL-P-116 is required by the contract or purchase order (see 6.2), the operational test specified in 4.15 shall be conducted to determine freedom from operational malfunction caused by the rough handling.

5. PACKAGING

5.1 Preservation-packaging. Preservation and packaging shall be Level A, B or Commercial, as specified (see 6.2q).

5.1.1 Level A, maximum military protection.

5.1.1.1 Cleaning. The camera and ancillary equipment shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. The camera and ancillary equipment shall be dried in accordance with the applicable procedures of MIL-P-116.

5.1.1.3 Preservation application. None required.

5.1.1.4 Unit packaging. Unit packaging shall be in accordance with the methods prescribed in MIL-P-116 as specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

5.1.1.4.1 Technical literature. Each technical literature shall be packaged Method IC-1.

5.1.1.4.2 Camera and ancillary equipment. The camera and ancillary equipment shall be packaged Method III as follows: Place the camera and ancillary equipment within the carrying case, close the case and secure fastenings. Cushion the case on all surfaces with cells or pads or both fabricated of fiberboard conforming to PPP-F-320, type CF, class weather-resistant, variety SW, grade W5c, designed and fabricated to protect all projections and absorb the shock of impact in handling and transit. As an alternate, cushioning material may be fabricated of plastic molding material conforming to MIL-P-19644 or polyurethane foam conforming to MIL-P-26514. Place the cushioned case within a close-fitting fiberboard box conforming to PPP-B-636, W5c. Place the technical literature, packaged as specified in 5.1.1.4.1, in the box directly under the lid of the box. Close the box in accordance with the appendix of the box specification.

5.1.2 Level B, minimum military protection. The camera and ancillary equipment shall be cleaned, dried, preserved and unit packaged as specified in 5.1.1.

5.1.3 Commercial packaging. Commercial packaging shall be in accordance with FED STD No. 356.

5.2 Packing. Packing shall be Level A, B or Commercial, as specified (see 6.2). Shipping containers for level A and B shall be capable of stacking and supporting superimposed loads during shipment and storage without damaging the container(s) or its contents.

5.2.1 Level A, maximum military protection. A quantity of items, (camera and ancillary equipment), packaged as specified in 5.1, shall be packed within a close-fitting box conforming to PPP-B-601, overseas type; PPP-B-621, style 4, class 2; or PPP-B-585, style 2 or 3; class 3. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, 3 x 4-inch skids, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto except that metal strapping shall conform to QQ-S-781, type I, finish A.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

5.2.1.1 Palletization. Palletization shall be required when: containers specified in 5.2.1 do not require skids; quantities per destination comprise a pallet load; and container size permits use of one of the pallet patterns of MIL-STD-147. A quantity of containers, packed as specified in 5.2.1, except that container strapping may be omitted, shall be placed on a pallet, load type 1, conforming to MIL-STD-147. The pallet shall be softwood conforming to NN-P-71, type IV, size 2. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I, finish A, or shrink film.

5.2.2 Level B, minimum military protection. A quantity of items (camera and ancillary equipment), packaged as specified in 5.1, shall be packed within a close-fitting fiberboard box conforming to PPP-B-640, class 2, style E, or PPP-B-636, type CF, class weather-resistant, variety SW. The gross weight of boxes conforming to PPP-B-640, shall not exceed 250 pounds. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, containers will be pallet-mounted on pallets conforming to NN-P-71, type IV. Closure shall be in accordance with the appendix of the applicable box specification. Reinforcing shall be by pressure-sensitive filament tape banding or nonmetallic strapping conforming to PPP-T-97 and PPP-S-760, respectively; selection of the material and application shall be in accordance with the appendix of the applicable box specification. When a single unit is shipped to a single destination no packing is required; the unit container shall serve as the shipping container. Reinforcing shall be as specified above.

5.2.2.1 Palletization. Palletization shall be required when quantities per destination comprise a pallet load. A quantity of items (camera and ancillary equipment), packaged as specified in 5.1, shall be placed on a pallet, load type 1, conforming to MIL-STD-147. The pallet shall be softwood conforming to NN-P-71, type IV, size 2. A fiberboard cap shall be employed over the load having two sides extending down the stacked load at least 12 inches to accommodate marking requirements. The cap shall be fabricated of fiberboard conforming to PPP-F-320, class weather-resistant, W5s or V3c. The load shall be "bonded" to the pallet by strapping conforming to QQ-S-781, type I, finish A or shrink film.

5.2.3 Commercial packing. Commercial packing shall be in accordance with Fed Std No. 356.

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The camera body, lenses and ancillary equipment covered by this specification are intended for use in the making of 35 millimeter black and white and color negatives and transparencies using 20, 36 and 250 exposure magazines of 35 millimeter roll film for world-wide military field, studio, and laboratory photography.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number and date of this specification and any amendment thereto.

b. When a first article is required for inspection and approval (see 3.2, 4.3 and 6.3).

c. Type, class and style of camera required. (See 1.2, 3.1, 3.4.11 and 3.4.10.)

d. Ancillary equipment required. (See 3.1.3.)

e. Address to which the certification of material and treatment should be sent. (See 3.3.1.)

f. Image size of film (see 3.4.7).

g. If shutter speed is required to be displayed in viewfinder (see 3.4.8).

h. Type of focusing screen required (see 3.4.9).

i. Type of remote control signal for motor drive, if required (see 3.5.1.3).

j. Type and focal length of lenses required (see 3.6).

k. Type or color of filters required (see 3.7).

l. The ancillary equipment to be housed in the camera set carrying case (see 3.13.3).

m. Shoulder strap if required (see 3.13.3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

n. Resolution of lens-camera body combination, if required (see 3.18).

o. If the service conditions are not applicable (see 3.19).

p. If rough handling test is required (see 4.24).

q. Level A, Level B or Commercial preservation and packing (see Section 5).

r. Technical literature required.

s. Group C failure action (see 4.4.3.3).

t. The type of film, developer and processed gamma to be utilized for testing (see 4.12.1, 4.12.2 and 4.15).

6.3 First article. When a first article is required, it shall be tested and approved under the appropriate provisions of 7-104.55 of the Armed Services Procurement Regulation. The first article should be a preproduction sample unless otherwise specified. The first article should consist of two units (see 4.3.1). The contracting officer should include specific instructions in all procurement instruments regarding arrangements for examinations, test and approval of the first article.

6.4 Environmental. Environmental pollution prevention measures are contained in the packaging material specifications referenced herein. Refer to material specifications or preparing activity for recommended disposability methods.

6.5 Group C inspection. Approval to ship may be withheld, at the discretion of the Government, pending the decision from the contracting officer on the adequacy of the corrective action (see 4.4.3.3).

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodians:

Army-EL
Navy-AS
Air Force - 99

User activities:

Army - AT, ME, SC

Preparing activity:

Army-EL

Project Number 6720-0268

☆U.S. GOVERNMENT PRINTING OFFICE: 1978 — 703-122/1058

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE MIL-C-55669B CAMERA, STILL PICTURE 35MM, SINGLE LENS REFLEX

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY
DOD – 314



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
US Army Electronics Command
ATTN: DRSEL-RD-TS-S
Fort Monmouth, NJ 07703

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:18Z
Check the source to verify that this is the current version before use.