MIL-C-60174(MU)
19 March 1965
SUPERSEDING
FA(FC)-PD-145
2 July 1961

MILITARY SPECIFICATION

CONNECTOR, ELECTRICAL, RECEPTACLE: 10526125

1. SCOPE

1.1 This specification covers one type of electrical receptacle connector for quick-connecting multi-contact circuit board assemblies with interconnection wiring used in the Gun Direction Computer: M18.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military

MIL-C-5015	Connectors, Electric, AN Type
MIL-C-8384	Connectors, Plug and Receptacle, Electrical: General Specification for
MIL-F-13926	Fire Control Materiel, General Specification Governing the Manufacture and Inspection of
MIL-P-14232	Parts, Equipment and Tools for Ordnance Materiel: Packaging of
MIL-I-45607	Inspection Equipment, Supply and Maintenance of
MIL-C-46357	Computer, Gun Direction: M18; Manufacturing Processes and Inspection of

STANDARDS

Military

MIL-STD-105	Sampling Procedure and Tables for Inspection by Attributes
MIL-STD-109	Quality Assurance Terms and Definitions
MIL-STD-202	Test Methods for Electronic and Electrical Component Parts

DRAWINGS

U.S. Army Munitions Command

F10526125	Connector

FSC 1220

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

PACKAGING DATA SHEET

MIL-P-14232/P10526125 Packaging of Connector, Receptacle, Electrical

(Copies of specifications, standards, drawings, and packaging data sheets, required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Fabrication.- The connector shall be manufactured in accordance with Drawing F10526125 and drawings pertaining thereto.

3.1.1 Insertion force.- The maximum insertion force required to insert a 0.071 inch gold plated printed circuit board, with a surface finish of 16 microinches (16), shall not exceed 40 lbs.

3.1.2 Contact float.- The contact in each cavity shall be free to float in two directions parallel to the inserted board. In the direction of direct pull on the contact terminal, the float shall not be more than 0.010 inch with a reversing load of 0.5 pound. In the direction of the long axis of the connector the float shall be not more than 0.005 inch and not less than .001 inch. A 10 pound direct pull on the contact terminal shall not distort the electrical contact surface of the contact.

3.2 Materials.- Materials shall be in accordance with drawings, material specifications, and general specifications forming a part of this specification.

3.2.1 Contact material.- The contact material shall be a type of beryllium copper which can be formed into the shape required by the Drawing 10526125, and also retain a spring-back characteristic such that the force required to remove from the connector a 0.061 to 0.063 inch thick goldplated board, will be in the range of 4 to 8 ounces per contact pair. The total force required to separate the 0.062 $\pm$ 0.001 inch thick goldplated board from the connector shall not exceed 32.5 pounds initially or after 500 insertions and removals of the board. The contact resistance of the contact material to a 0.054 to 0.056 inch thick goldplated board shall result in a voltage drop of 0.023 volt or less with a current of 3.0 amperes dc flowing through the contact initially and after 500 cycles of insertion and withdrawal of the board.

3.3 General specifications.- The connector shall meet the following requirements of MIL-F-13926 and MIL-C-46357.

3.3.1 MIL-F-13926

a. Order of precedence
b. Dimensions and tolerances
c. Inorganic protective surface finished
d. Workmanship

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

3.3.2 MIL-C-46357

a. Connector damage
b. Connector

3.4 Environmental service conditions.

3.4.1 Vibration.- The connector shall be subjected to a simple harmonic motion in accordance with MIL-STD-202, Method 204, Condition D. For this requirement the connector shall be mated with a circuit board, mounted by its normal mounting means, wired so that all contacts are in series, and connected to an electrical circuit such that 1.0 ampere dc is flowing through all of the contacts and a detection device which can detect an interruption or load break of one microsecond duration. The sweep rate during resonance search shall not exceed 100 cycles per minute. Care must be taken to exclude resonances occurring in the test jig or attachment to shake table. This motion shall be applied for a period of two hours in each of three mutually perpendicular directions (total of six hours). During the vibration period the total time of interruption or load break of the electrical current shall not exceed one microsecond. Subsequent to vibration, the connector shall not have been damaged or adversely affected and shall meet the requirements of 3.5.

3.4.2 Shock.- The connector shall be capable of withstanding 18 shock impulses, in accordance with MIL-STD-202, Method 202, of 50G while carrying a load of 1.0 ampere dc through all contacts without a load break exceeding one microsecond total time, while mated with a circuit board, and while mounted by its normal mounting means. Subsequent to shock the connector shall not have been damaged or adversely affected and shall meet the requirements of 3.5.

3.4.3 Temperatures.

3.4.3.1 Operating.- The connector shall meet the requirements of 3.5.2 while exposed to temperatures of -40° and +135°F.

3.4.3.2 Storage.- The connector shall meet the requirements of 3.5 at a temperature of between 60°F and 90°F after having been exposed to each temperature of -80°F and +160°F.

3.4.4 Salt spray.- Mated connectors shall be capable of withstanding Test Condition B of MIL-STD-202, Method 101 and the contact resistance requirements 3.5.3 causing less than 0.040 volt drop across each contact with 3.0 amperes dc flowing through the contact from an open circuit voltage source of 1.5 volts dc following insertion and withdrawal of a 0.054 inch to 0.056 inch thick gold-plated board subsequent to salt spray testing. Subsequent to such exposure, the connector shall not have been damaged or adversely affected, and shall meet the requirements of 3.5 after being washed and dried in accordance with MIL-C-5015.

3.4.5 Temperature cycling.- The connector shall be capable of withstanding Test Condition C of MIL-STD-202, Method 102, and the requirements of 3.5.2 with a minimum insulation resistance of 100,000 megohms following temperature cycling. The connector shall then meet all other requirements of 3.5 at the standard ambient temperature (60° to 90°F).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

3.4.6 Moisture resistance.- Mated and wired connectors, without sleeving over the terminals, shall be capable of recovering insulation resistance following exposure to MIL-STD-202, Method 106, and the requirements of this specification as follows:

Time After Moisture Resistance Test	Insulation Resistance
5 minutes	25 Megohms minimum
1 hour	500 Megohms minimum
24 hours	10,000 Megohms minimum

3.4.7 Sand and dust.- Mated connectors shall be capable of withstanding Test Condition A, Part I only, of MIL-STD-202, Method 110 and the requirements of 3.5.3 with a contact resistance for each contact causing less than 0.025 volt drop with 3.0 amperes flowing from an open circuit voltage source of 1.5 volts dc after sand and dust exposure at a velocity of 300 ± 200 feet per minute for six hours. The connector shall also meet all other requirements of 3.5.

3.4.8 Humidity.- The connector shall meet the requirements of 3.5.2 in an atmosphere with a relative humidity up to 97 percent, and after storage for a period not in excess of four hours in an atmosphere with a relative humidity of 100 percent including condensation, shall when thoroughly dried, meet the requirements of 3.5.

3.4.9 Fungus resistance.- The connector, electrical, receptacle shall show no evidence of damage and shall meet all the requirements of this specification after being inoculated with the composite spore suspension specified in MIL-F-13926 and incubated at an ambient temperature of between 77° and 84°F with a RH of 97 ± 2 percent.

3.5 Electrical.- Unless otherwise specified the connector shall meet the electrical requirements at ambient temperatures between 60° and 90°F; a barometric pressure of 28 to 32 inches of mercury; and a RH up to 90%.

3.5.1 Dielectric withstanding voltage.- The mated connector, mounted by its normal mounting means, and wired without sleeving, shall withstand a voltage of 1000 volts rms without flashover, sparkover, or breakdown in accordance with MIL-STD-202, Method 301.

3.5.2 Insulation resistance.- The connector shall have a minimum of 100,000 megohms insulation resistance between adjacent contacts or a metallic insert and any contact in accordance with MIL-STD-202, Method 302.

3.5.3 Contact resistance.- The connector, when mated with a 0.054 to 0.056 inch thick goldplated board, shall have a contact resistance which will cause a 0.023 volt maximum drop with 3 amperes dc flowing both before and after 500 cycles of insertion and withdrawal of the board at a rate not exceeding 600 cycles per hour in accordance with MIL-STD-202, Method 307.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 General provisions.- The component inspection requirements of MIL-F-13926 form a part of the Quality Assurance Provisions of this specification. Definitions of inspection terms shall be as listed in MIL-STD-109.

4.2 Inspection provisions.

4.2.1 Submission of Product.- Unless otherwise specified herein, or by the contracting officer, inspection lot size, lot formation and presentation of lots shall be in accordance with "Submission of Product" as specified in MIL-STD-105.

4.2.2 Examinations and tests.- Except where otherwise specified herein, components and sub-assemblies shall be inspected in accordance with the "Inspection provisions for components and sub-assemblies" and the Sampling Plan ables contained in MIL-F-13926. Examinations and tests related to Section 3 herein shall be performed in accordance with Tables I to IV incl. and the test methods and procedures in 4.5. Examinations and tests for packaging, packing and marking shall be in accordance with MIL-P-14232 and Section 5 herein.

4.2.3 Acceptance and rejection.- Rejected lots shall be screened for all defective characteristics. Removal or correction of defective units and resubmittance of rejected lots shall be in accordance with "Acceptance and Rejection" as specified in MIL-STD-105.

4.2.4 Functional tests.- The requirements and tests in Table I shall be inspected on a 100% basis. All examinations and tests shall be conducted at the standard ambient temperature (60° to 90°F).

TABLE I
(100 percent inspection)

Characteristics	Requirements	Test Procedures
101. Contact resistance	3.2.1, 3.5.3.	4.5.2.3
102. Insertion Force	3.1.1	4.5.3.2
103. Contact float	3.1.2	4.5.3.3

4.3 Standard sampling.

4.3.1 General.- One connector shall be selected at random by a Government representative as a standard sample from each 100 produced. The sample shall meet the requirements and tests in Table II.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:19Z
Check the source to verify that this is the currentversion before use.

TABLE II

Characteristics	Requirements	Test Procedures
301. Fabrication	3.1	Applicable drawings - visual
302. General specifications	3.3	MIL-F-13926 and MIL-C-46357 - visual

4.3.1.1 Material.- Compliance with 3.2 shall be determined by certification. To insure proper contact material, certification shall include test data and results for characteristics specified in 3.2.1. Certification will be required prior to performing final acceptance inspection and shall suffice for the remainder of the production quantities, provided the manufacturing processes and techniques used to produce the material for which certification was issued have not been changed or revised. Any and all changes will require a new certification from the contractor.

4.3.2 Environmental.

4.3.2.1 Vibration and shock.- Inspection shall be conducted in accordance with Special Inspection Level S-4 with Sampling Plan Table II-A of MIL-STD-105 to determine compliance with the requirements and tests of Table III.

TABLE III

Classification of Defects	Requirements	Test Procedures
CRITICAL: NONE		
MAJOR: AQL 1.0% Defective		
104. Vibration	3.4.1	4.5.1.1
105. Shock	3.4.2	4.5.1.2
MINOR: NONE		

4.3.2.2 Miscellaneous.- Three connectors shall be selected at random, by a Government representative as a standard sample from each 100 produced or from each month's production, whichever occurs first. The control samples shall have met the requirements and tests in Tables I and III and shall them meet the requirements and tests in Table IV.

TABLE IV

Characteristics	Requirements	Test Procedures
303. Operating temperature	3.4.3.1, 3.5.2	4.5.1.3, 4.5.2.2
304. Storage temperature	3.4.3.2	4.5.1.3, 4.5.2
305. Temperature cycling	3.4.5	4.5.1.5
306. Salt spray (corrosion)	3.4.4	4.5.1.4
307. Moisture resistance	3.4.6	4.5.1.6
308. Sand and dust	3.4.7	4.5.1.7
309. Humidity	3.4.8	4.5.1.8.1, 4.5.1.8.2
310. Insulation resistance	3.5.2	4.5.2.2
311. Dielectric strength	3.5.1	4.5.2.1
312. Contact material (separation force)	3.2.1	4.5.3.1

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.3.3 Failure of sample.- Should any one item of a standard sampling fail to meet the specified test requirements, acceptance of the represented inspection lot will be suspended by the Government until necessary corrections have been made by the contractor and the resubmitted samples have been approved (see 4.2.3).

4.4 Inspection equipment.- Except as otherwise provided for by the contract, the contractor shall supply equipment in accordance with the applicable requirements of MIL-I-45607. The Government reserves the right to use the test equipment for its own independent inspections to the extent that such use will not unduly interfere with the contractor's delivery schedule.

4.4.1 Contractor design.- The contractor shall provide inspection equipment compatible with the "Test Methods and Procedures" specified in 4.5 and with the "Component Inspection" and "Test Facilities" requirements of MIL-F-13926. Since tolerance of test equipment is normally considered to be within 10% of the product tolerance for which it is intended, this inherent error in the test equipment design must be considered as part of the prescribed product tolerance limit. Thus, concept, construction, materials, dimensions and tolerances used in the design of test equipment shall be so selected and controlled as to insure that the test equipment will reliably indicate acceptability of a product which does not exceed 90% of the prescribed tolerance limit, and permit positive rejection when non-conforming. Construction shall be such as to facilitate routine calibration of test equipment.

4.4.1.1 Test equipment.- In conjunction with 4.4.1, the following test equipment shall be utilized in the performance of the applicable tests as specified in 4.5:

Item Number		Description
1	Weight	0.5 pound, including device for attachment to one contact terminal.
2	Weight	32.5 pounds, including device for attachment to 0.062 ± 0.001 inch thick goldplated board.
3	Board	0.062 ± 0.001 inch thick, goldplated, finished size equal to circuit board outline with mating key for connector.
4	Board	0.055 ± 0.001 inch thick, goldplated, finished size equal to circuit board outline with mating key for connector and 130 mating contacts for connector wired in pairs so that all contacts can be series connected.
5	Board	0.055 ± 0.001 inch thick, plain insulating, to withstand 1000 volts rms across 0.050 inch and have 100,000 megohms insulation resistance across 0.050 inch.
6	Recording Device	Device for recording load break time in series with all contacts with 1.0 amp dc flowing. Open circuit voltage shall not exceed 1.5 volts dc per contact. A load break shall exist when the voltage across the contacts rises to 50 percent of the open circuit voltage. The device shall record a load break time of one microsecond or less. If the device record less than 0.5 microsecond load break, it shall also record the total number of load break times up to a total of one microsecond.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

Item Number		Description
7	Insertion device	Device for inserting and withdrawing boards into and out of connectors at a rate not exceeding 500 insertions and withdrawals per hour.
8	Board, goldplated	Outline equal to printed circuit boards. Maximum thickness of finished board shall not exceed 0.071 inch.
9	Force gage	Push type, 0-50 lb range, accuracy 2% on full scale.

4.5 Test methods and procedures.

4.5.1 Environmental.

4.5.1.1 Vibration.- The connector shall be mated, mounted by its normal mounting means, wired so that all contacts are in series, placed on the mounting apparatus, and tested in accordance with MIL-STD-202, Method 204, Condition D, and with the following conditions, to determine compliance with 3.4.1.

(a) Simple harmonic motion.- Frequency Range: 10 to 2000 cycles per second. Total Excursion: 0.06 inch maximum, but not more than 20g acceleration. A 1.0 amp electrical load, shall flow through all contacts in series, during and after the test.

(b) Load break time (open circuit).- 1.0 microsecond maximum, during four hours vibration in compliance with 3.4.1. Contact resistance after vibration shall be 0.023 volt maximum per contact with 3 amps flowing.

4.5.1.2 Shock.- The connector shall be mated, mounted by its normal mounting means, wired so that all contacts are in series, mounted on the shock testing device, and tested in accordance with MIL-STD-202, Method 202, with an acceleration of 50 G's under the following conditions to determine compliance with 3.4.2.

(a) Number of blows-18 (3 blows in opposite directions along 3 mutually perpendicular axes).

(b) Electrical load - 1.0 amp shall flow through all contacts in series during test.

(c) Measurements during shock - Load break time (open circuit) shall be 1.0 microsecond maximum, during blows to conform to 3.4.2.

4.5.1.3 Temperature (Operating and storage).- The connector shall be subjected to Test Procedure I specified in MIL-F-13926, except the temperatures specified in 3.4.3 shall apply. While at the operating temperatures of 3.4.3.1, the unit shall be tested in accordance with 4.5.2.2 to determine compliance with the requirement of 3.4.3.1. The temperature shall then be returned to standard temperature (60° to 90°F) and the unit shall be tested in accordance with 4.5.2 to determine compliance with 3.4.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.5.1.4 Salt spray (corrosion).- The mated connectors shall be placed in the chamber in such a way that they will not shield one another from the salt spray. If the connectors are hung on stringers, care must be exercised that they do not touch one another at any time during the test. The connectors shall be subjected to the Salt Spray Test of MIL-STD-202, Method 101. Condition B (48) to 50 hours) and under the following conditions and procedures to determine compliance with 3.4.4:

4.5.1.4.1 Measurements after exposure: Within five minutes after this test, the exterior surfaces of the connectors shall be washed with tap water and dried in accordance with MIL-C-5015. At the end of the drying cycle, the connectors shall be subjected to the contact resistance tests defined in 4.5.2.3 of this specification. The contact resistance shall cause 0.040 volt drop across the contact maximum with 3 amps flowing through the contacts after the salt spray test, as required by 3.4.4 and 3.5.3.

4.5.1.5 Temperature cycling.- The connector shall be tested in accordance with MIL-STD-202, Method 102, Test Condition C and the following conditions and procedures to determine compliance with 3.4.5.

4.5.1.5.1 Measurements after cycling.- Subject the connector to the insulation test of 4.5.2.2 while at the test condition above as required by 3.4.5. The connector shall then be subjected to the tests of 4.5.2.1 and 4.5.3.1 at the standard ambient temperature (60° to 90°F) in compliance with 3.4.5.

4.5.1.6 Moisture resistance.- Mated and wired connectors, without sleeving over the terminals, shall be placed in the test chamber and tested in accordance with MIL-STD-202, Method 106. Insulation resistance shall be as specified below to determine compliance with 3.4.6.

Time	Insulation Resistance Test
Within 5 minutes after completion of step 6 of the final cycle	25 Megohms minimum
One hour after	500 Megohms minimum
24 hours after	10,000 Megohms minimum

4.5.1.7 Sand and dust.- Mated connectors shall be placed in the test chamber and tested in accordance with MIL-STD-202, Method 110 (A, Part 1 only). Velocity shall be 300 ± 200 feet per minute. The mated connector shall then be subjected to the contact resistance test in 4.5.2.3 to determine compliance with 3.5.3 as required by 3.4.7.

4.5.1.8 Humidity.

4.5.1.8.1 Non-operating.- This test shall be conducted in accordance with the conditions in 3.4.8 and the humidity test defined in Procedure I of MIL-F-13926 except that the 4-1/2 hour period shall be reduced to 2 hours, the 6 hour period reduced to 2 hours, and the total test period shall not exceed 5.5 hours per cycle. The unit shall then be thoroughly dired and then subjected to the tests in 4.5.1.8.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.5.1.8.2 Operating.- This test shall be conducted in accordance with the operating conditions in 3.4.8 and the humidity test defined in Procedure III of MIL-F-13926 except that the humidity shall be maintained at 95 ± 5 percent for the 24 hour period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test the unit shall be operated in accordance with 4.5.2 to determine compliance with 3.4.8.

4.5.1.9 Fungus.- To determine compliance with 3.4.9, one of the first 5 units produced shall be submitted for testing in accordance with the fungus test defined in MIL-F-13926. After approval, subsequent acceptance for fungus requirements may be by certification.

4.5.2 Electrical.

4.5.2.1 Dielectric withstanding voltage.- The connector shall be mated, mounted, wired without sleeving, and tested in accordance with MIL-STD-202, Method 301. The test voltage shall be 1000V A.C. RMS and shall cause no flashovers, no sparkovers, and no breakdown as required in 3.5.1.

4.5.2.2 Insulation resistance.- The connector shall be tested in accordance with MIL-STD-202, Method 302, test condition "B". The points of measurement shall be between three pairs of adjacent contacts, and one metal insert to nearest contact. The insulation resistance under ambient conditions shall be greater than 100,000 megohms as specified in 3.5.2.

4.5.2.3 Contact resistance.- The connector shall be mated with a 0.054 to 0.056 inch thick goldplated board and tested in accordance with MIL-STD-202, Method 307. The method of connection at extreme ends of terminal shall be as specified in Figure 2 of MIL-C-8384. Test current shall be 3 amps and maximum open-circuit test voltage shall be 1.5 volts dc. The voltage drop requirement of 3.2.1 and 3.5.3 shall be determined during this test

4.5.2.3.1 The number of activations prior to measurements shall be 500 cycles of insertion and withdrawal at a rate not exceeding 600 cycles per hour.

4.5.3 Mechanical.

4.5.3.1 Contact material (separation force).- Separation force shall be conducted on at least 3 pairs of contacts selected at random except that the board shall span only one pair of contacts. The separation force of 4 ounces minimum and 8 ounces maximum per contact pair shall be determined to insure compliance with 3.2.1. The total force to separate the 0.062 ± .001 inch thick goldplated board from the connector shall not exceed the 32.5 pounds specified in 3.2.1, both prior to and after the 500 insertion and removals.

4.5.3.2 Insertion force.- Insert board (Item 8 of 4.4.1.1) into the keyed mating surface of the connector. The force required to insert the .312 inch board engagement area shall not exceed 40 lbs as specified in 3.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.

4.5.3.3 Contact float.- To determine compliance with 3.1.2 test the float of 5 contacts selected at random by attaching 0.5 pound weight to the terminal, rotating the connector, and observing the movement of the contact. In the direction of direct pull on the contact terminal the float shall not be more than .010 inches. In the direction of the long axis of the connector the float shall be not more than .005 inches and not less than .001 inches. Pull with 10 pounds force directly on the contact terminal of four contacts selected at random. Observe the contact surface which shall not distort, bend, or warp.

5. PREPARATION FOR DELIVERY

5.1 Packaging, packing and marking.- Packaging, packing and marking shall be in accordance with MIL-P-14232 and Packaging Data Sheet MIL-P-14232/P10526125. The level of protection shall be as specified in the procurement document.

6. NOTES

6.1 Intended use.- The connector described in this specification is intended as a multi-contact, molded body, electrical connector to be used as a receptacle for electronic circuit board assemblies. The terminals of the connector provide for the interconnection wiring between circuit board assemblies. (The Drawing C10526208 Key, Connector, Receptacle can be placed in the connector in accordance with Drawings F10526105-1 through F10526105-20 in order to allow only matching circuit board assemblies to be inserted in the connector.) A single polarizing barrier has been moulded into the connector to provide polarization for connectors without keying and to provide alignment between circuit board and connector which is independent of board edge cut tolerances and limits the effects of thermal expansion dissimilarities to one-half the long axis. The terminal numbers on the board receiving face of the connector have been placed below a flush surface which can mate with a gasket on the circuit board if environmental conditions become more stringent.

6.2 Ordering data.- Procurement documents should specify the following:

(a) Title, number and date of this specification
(b) Applicable stock number
(c) Selection of applicable level of preservation, packaging and packing (see 5.1)
(d) Applicable packaging data sheet
(e) Block of serial numbers to identify each connector

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1220-A196Y

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:19Z
Check the source to verify that this is the current version before use.