MIL-C-60317D(AR)
8 FEBRUARY 1988
SUPERSEDING
MIL-C-60317C(PA)
15 April 1974

MILITARY SPECIFICATION

CARTRIDGE, 60MM, SMOKE, WP, M302A1 ASSEMBLING, MARKING AND PACKING

This specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers quality assurance provisions for the requirements and assembling, marking and packing of the Cartridge, 60MM, Smoke, WP, M302A1.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (See 6.1), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the soliicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	- Ammunition, Standard Quality Assurance Provisions, General Specification For
MIL-P-60316	- Primer Percussion, M32, Loading, Assembling and Packing

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1167	- Data Card Format

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament,Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1310
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

PRODUCT AND PACKING DRAWINGS

9215575	-	Cartridge, 60MM, Smoke, WP, M302A1.
9215576	-	Container, Ammunition, Fiber, M567 for Cartridge, 60MM Smoke, WP, M302A1 in Jungle Wrap.
9215577	-	Box, Ammo, Packing, Wood, Nailed for Cartridge, 60MM Smoke, SP, M302A1 in Jungle Wrap.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions, should be obtained from the contracting activity or as directed by the contracting officer.

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

3.2 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.3 Loaded cartridges. The cartridge shall comply with all requirements specified on Drawing (dwg.) 9215575 and will all requirements specified in applicable specifications and standards.

3.4 Proving ground test. The cartridge shall comply with the following requirements when tested as specified in 4.5.2.

3.4.1 Failure to fire. The cartridge shall not fail to fire.

3.4.2 Safety. There shall be no premature functioning in the mortar tube or in flight before impact.

3.4.3 Impact functioning. There shall be visable evidence of functioning upon impact as indicated by presence of a flash or smoke cloud.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

3.4.4 Horizontal range.

3.4.4.1 No cartridge shall have a horizontal range less than 80 percent of the average horizontal range.

3.4.4.2 The standard deviation in the horizontal range shall be no greater then the maximum (max.) lot values indicated below.

Increment Charge Zone	Max. Lot Standard Deviation (Meters)
0	12
4	32

3.5 Data requirements. The contractor shall generate data in accordance with the requirements of the data item descriptions cited in 6.3.

3.6 Workmanship. All parts and assemblies shall be in the condition and of a quality as specified on the applicable drawings and specifications. They shall be free from other defects such as, but not limited to, blemishes, burrs, cavities, pitts, voids, corrosion, cracks, dents, distortion, warpages, gouges, scores, nicks, inclusions, laps, porosity, slivers, or obstructions. Cleaning shall be through to remove all dirt, chips, grease, oil, flux, chemical deposits, residues and other foreign matter. The cleaning method and agents used shall not be injurious to any part, not shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item.

a. First article inspection.

b. Quality conformance inspection.

c. Proving ground test.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

Part Description	Dwg. Number	Quantity
Cartridge, 60MM, Smoke WP, M302A1	9215575	80

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

MIL-C-60317D(AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cartridge, 60MM, Smoke, WP, M302A1	80	1	3.3	
	Examination for defects				
	Proving ground test	80	1	3.4	

NOTES:
1. The same units used for the examinationf or defects can be used in the proving ground test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots for the following shall comply with the following criteria:

a. Loaded ignition cartridges of one interfix number from one manufacturer.

b. Fin assemblies of one lot interfix number from one manufacturer.

c. Loaded primers of one interfix number from one manufacturer.

d. Propellant increments made from not more than one propellant lot from one manufacturer.

e. Loaded fuzes of one lot interfix number from one manufacturer.

f. Loaded projectile bursters from one lot interfix number from one manufacturer.

g. Fin extensions of one lot interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with Standard MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-60317D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Body Filling Assembly				9205339
					NEXT HIGHER ASSEMBLY 9215575
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	WP leakage		100%	3.3	Visual
Major	None defined				
Minor 201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:20Z
Check the source to verify that this is the currenversion before use.

QUALITY CONFORMANCE INSPECTION

MIL-C-60317D(AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Cartridge, Prior to Inserting Burster				9215575
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	Burster pad missing		100%	3.3	Visual
Major 101	Foreign matter in burster cavity		0.40%	3.3	Visual
Minor 201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Cartridge, Prior to Assembling Fuze		9215575
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Burster charge missing		0.40%	3.3	Visual
102	Foreign matter in fuze well		0.40%	3.3	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-60317D(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Cartridge, Prior to Assembling Primer				9215575
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Igniter cartridge missing or inverted		100%	3.3	Visual
Major					
101	Fin or fin extension loose		0.40%	3.3	Test (See 4.5.1)
102	Fuze loose		0.40%	3.3	Test (See 4.5.1)
103	Fin extension to fin and shell body sealing compound missing		0.40%	3.3	Visual
104	Sealing compound bead improperly located missing or not a full 360° in base of cartridge housing (prior to insertion of ignition cartridge)		0.40%	3.3	Visual
105	Sealing compound bead improperly located or not a full 360° on red end of ignition cartridge (prior to seating of primer into fin cavity)		0.40%	3.3	Visual
106	Excessive sealing compound on primer pellet closing disc		0.40%	3.3	Visual
Minor					
201	Foreign matter in cavity		0.65%	3.6	Visual

NOTES:

10

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Cartridge				9215575
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Primer head above flush with rear surface of fin		100%	3.3	Straight-edge
2	Fin damaged or distorted		100%	3.3	Profile & Alignment Gage
3	Fuze safety wire damaged or distorted		100%	3.3	Visual
Major					
101	Total length, max.		0.40%	3.3	Gage
102	Primer stake missing or inadequate		0.40%	3.3	Visual
103	Sealing compound does not cover a minimum of one-half the primer thread for 360°		0.40%	3.3	Visual
104	Component (other than fin damaged)		0.40%	3.3	Visual
105	Primer fails to withstand reapplication of min assembly torque		0.40%	3.3	Test (See 4.5.1)
Minor					
201	Protective coating with total damaged area of 1/4 square inch		0.65%	3.3	Visual
202	Marking misleading, missing, or unidentifiable including incorrect color code		0.65%	3.3	Visual
203	Fuze not fully seated		0.65%	3.3	Visual
204	Evidence of poor workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Unsealed Fiber Container				9215576
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Propellant increment missing		100%	3.3	Visual
Major					
101	Propellant increment cut or torn		0.40%	3.3	Visual
102	Ring support missing		0.40%	3.3	Visual
103	Filler assembly missing		0.40%	3.3	Visual
Minor					
201	Glue or asphalt on round		0.65%	3.32	Visual
202	Cartridge improperly assembled into container		0.65%	3.3	Visual
203	Round cannot be removed by hand		0.65%	3.3	Manual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Sealed Fiber Container				9215576
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Container cut or damaged		0.40%	3.3	Visual
102	Tape incomplete, wrinkled or missing		0.40%	3.3	Visual
103	Metal end loose or distorted		0.40%	3.3	Visual
Minor					
201	Sealing strip improperly applied		0.65%	3.3	Visual
202	Gap between cover and body exceeds 1/8 inch		0.65%	3.3	Gage
203	Contents loose		0.65%	3.3	Manual
204	Marking incorrect, incomplete or illegible		0.65%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Fiber Container Wrapped in Barrier Material Prior to Waxing (Jungle Wrap)				9215576
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Barrier material improperly assembled		0.40%	3.3	Visual
102	Barrier material ends improperly folded or taped		0.40%	3.3	Visual
Minor					
201	Marking missing or incomplete		0.65%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Fiber Container, After Waxing (Jungle Wrap				9215576
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Wax coating incomplete or damaged		0.40%	3.3	Visual
Minor					
201	Marking missing or unidentifiable		0.65%	3.3	Visual
202	Kraft paper improperly placed on container		0.65%	3.3	Visual
203	Tear tab not visible		0.65%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Sealed Wood Packing Box		9215577
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Contents exposed		0.40%	3.3	Visual
102	DOD symbol missing or incorrect		0.40%	3.3	Visual
103	Board broken or split		0.40%	3.3	Visual
104	Hardware or strapping missing, broken or loose		0.40%	3.3	Visual - Manual
Minor					
201	Hardware improperly engaged		0.65%	3.3	Visual
202	Car seal missing, unsealed or improperly positioned		0.65%	3.3	Visual
203	Contents loose		0.65%	3.3	Manual
204	Handle missing or insecure		0.65%	3.3	Visual - Manual
205	Marking missing, misleading or unidentifiable		0.65%	3.3	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Proving grounds (See 3.4). The cartridges shall be observed for the characteristics listed below:

	Defect Classification	Accept	Reject
a. Failure to fire	Major	1	2
b. Safety	Critical	0	1
c. Impact functioning	Major	3	4
d. Horizontal range less than 80 percent of average horizontal range but not less then 60 percent of horizontal range	Major	1	2
e. Horizontal range less than 60 percent of average horizontal range	Critical	0	1
f. Range Standard Deviation (See	Major		

4.4.3.1.1 Beginning with the first lot produced and continuing until three (3) consecutive lots have complied with the applicable acceptance criteria specified in a, b, c, d and e above, a sample of eighty (80) cartridges shall be selected from each lot for this test. In addition, for f above, if the standard deviation in horizontal range for the sample cartridges fired at charge Zone 0 or charge Zone 4 multiplied by the factor 0.79 exceeds the applicable maximum limit specified in 3.4.4.2 the lot shall be rejected. The test shall be performed as specified in 4.4.4.

4.4.3.1.2 After three (3) consecutive lots have met the criteria of 4.4.3.1, a sample of fifty (50) cartridges shall be selected from each lot for this test. Acceptance criteria shall be as specified in a, b, c, d and e of 4.4.3.1. In addition, for f, if the standard deviation in the horizontal range for the sample cartridges fired at charge Zone 0 or charge Zone 4 multiplied by the factor 0.75 exceed the applicable maximum limit specified in 3.4.4.2, the lot shall be rejected. The test shall be performed as specified in 4.4.4.

4.4.3.2 Check test for possible deterioration of primer, percussion, M32, if the total elaped time between original acceptance of the M32 primer lot and the assembly of that lot into the complete round cartridges exceeds two (2) years, or if the M32 primers have been subjected to adverse conditions, however brief, at any time since previous tests, the applicable lot shall be subjected

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

to, and must satisfactorily pass, the check test for deterioration specified in specification MIL-P-60316, before the M32 primer lot is assembled into the cartridge lot. The test shall be performed by the contractor on assemblies selected by the Government inspector at the facility assembling the complete cartridge (See 6.4).

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the table starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.2 herein.

4.5 Methods of inspections.

4.5.1 Torque test. The torque shall be applied to the applicable component while holding the adjacent mating component in such a manner as to avoid possible damage to any component of the assembly. Any assembly that shows evidence of movement when the specified torque is applied shall be classed defective.

4.5.2 Proving ground test. The test shall be performed at a Government proving ground specified by the Contracting Officer in accordance with approved acceptance test procedures. The cartridge shall be fired from a 60MM Mortar for which the round is standard. One-half the sample cartridges shall be fired with an ignition cartridge (Charge Zone 0) and one-half of the sample cartridges shall be fired with an ignition cartridge and four (4) propellant increments (Charge Zone 4). The individual velocities, maximum pressures and impact ranges shall be obtained and recorded. The standard deviation and the arithmetic averages of the impact ranges shall be calculated and recorded.

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level A. The cartridges shall be preserved and packaged in accordance with Dwg. 9215576.

5.2 Packing.

5.2.1 Level A. The cartridges in fiber containers shall be packed in accordance with Dwg. 9215577.

5.3 Marking. Marking of the wood box shall be in accordance with Dwg. 9215577. The fiber container shall be marked in accordance with Dwg. 9215576.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

5.4 Ammunition data cards. Data card information shall be as specified in standard MIL-STD-1167.

5.5 Ammunition lot number. See MIL-A-48078.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Submission of designs for approval. See 6.2.3 of MIL-A-48078. Submit equipment designs, as required to: Commander, US Army Armament, Munitions and Chemical Command, ATTN: DRSMC-QAT-I (D), Dover, NJ 07801.

6.3 Data requirements. Deliverable data required by this specification in the following paragraphs:

Paragraph	Data Requirement	Applicable DID
4.4.2	Quality Defect Inspection Report	DI-R-1721

(Copies of the data item descriptions required by the contractor in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer).

6.4 Cost of check test. The contracting officer shall arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test. The test shall be conducted at Government expense without cost to the contractor who loaded the primers or to the contractor assembling the cartridges and shall not constitute a basis of rejecting against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-A335)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-60317D	CARTRIDGE, 60MM, SMOKE, WP, M302A1 ASSEMBLING, MARKING AND PACKIN

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil – Downloaded: 2026-03-26T04:20Z
Check the source to verify that this is the current version before use.