M 7

MIL-C-60368 (MU)
24 March 1966

MILITARY SPECIFICATION

CARTRIDGE, 57MM, TP, M306
LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of target practice cartridge designated as Cartridge, 57MM, TP, M306A1 for use in 57MM rifles.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons, General Specification for
MIL-I-45607 - Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

FSC: 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

M 7

DRAWINGS

ARMY

9215633 - Cartridge, TP, M306A1, W/F PD, M503A2 for 57MM Rifle M18 and M18A1
9215018 - Ammunition Container, Fiber, 57MM, M167A2 Assembly, Details, Packing and Marking
8796471 - Box, Packing, Ammunition for 57MM Rifle, Ammunition in Fiber Container M167A2, Assembly, Details and Packing

PUBLICATIONS

ARMY

ET-9215633 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Cartridge.-The cartridge shall comply with all requirements specified on Drawing (dwg.) 9215633 and with all requirements specified in applicable specifications.

3.3 Propellant weight.-The weight of the propellant shall not differ by more than plus or minus 0.02 ounce from that designated by the loading authorization for the particular lot of propellant used.

3.4 Cartridge case crimp

3.4.1 Torque.-The projectile shall withstand a torque of 100 inch-pounds, minimum (min.), without rotating in the cartridge case, when tested as specified in 4.3.1.1.

3.4.2 Bullet pull.-The cartridge case shall separate from the projectile at a load between 1000 pounds, min., and 2500 pounds, maximum (max.), when tested as specified in 4.3.1.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

3.5 Proving ground.-The cartridge shall comply with the following requirements when tested as specified in 4.3.2.

3.5.1 Muzzle velocity.-The corrected muzzle velocity of the projectile at ambient temperature shall be not more than 1236 feet per second (fps) nor less than 1164 fps and the standard deviation of the lot shall not exceed 13 fps.

3.5.2 Projectile functioning.-There shall be visible evidence of functioning upon impact as evidenced by presence of a smoke cloud.

3.5.3 Premature burst and security of parts.-There shall be no premature burst or indication of metal parts failure in the gun bore or in flight before impact.

3.5.4 Safety.-There shall be no premature burst or indication of metal parts failure in the gun bore or in flight when fired with propellant adjusted to give 112 percent of the rated maximum pressure of the cartridge.

3.6 Workmanship

3.6.1 Cartridge.-All manufacturing, processing and assembly operations of the cartridge shall be correctly performed in a thoroughly workmanlike manner. Parts shall be free of burrs, chips, dirt, cracks, grease, rust and other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents. The cartridge or components shall not be damaged in any manner during the loading operation.

3.6.1.1 Painting and marking.-The painting and marking shall be restored by the loading and assembling contractor on any component furnished him when such painting or marking has been marred or obliterated.

3.6.1.2 Cartridge case.-The cartridge case shall be free of any roughness, scratches, rust or dents which will adversely affect serviceability.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define the terms used herein. The provisions of Specification MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all quality assurance provisions specified within this specification.

b. Number of units of product inspected.

c. Results obtained, by defect code, for all inspections performed.

d. Drawing, specification number and date, together with an identification and date of changes.

e. Certificates of conformance on all material purchased by the contractor when such material is controlled by Government or commercial specifications referenced in any of the contractual documents.

f. Number of items in the lot.

g. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.2 Government verification.-Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be performed to the extent necessary to assure

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 Inspection provisions

4.2.1 Lot formation.-A lot shall consist of cartridges produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification and process changes not affecting safety, performance or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The examinations and tests listed herein shall be performed on inspection lots submitted in accordance with Standard MIL-STD-105, MIL-STD-1235 or MIL-STD-414, as applicable. The criteria and procedures for the assignment of lot numbers shall be in accordance with Standard MIL-STD-1168. Each lot shall contain:

a. Projectile metal parts of one lot interfix number from one manufacturer.

b. Propellant charge from not more than one lot.

c. Loaded primers from one lot interfix number from one manufacturer.

d. Cartridge cases from one manufacturer with one lot interfix number.

e. Loaded fuzes from one lot interfix number from one manufacturer.

f. Black powder pellets from one manufacturer produced in accordance with the same drawing, same drawing revision, same specification and same specification revision.

g. Inert charge from not more than one lot.

4.2.2 Examination.-Inspection for Critical defects (and Major defects, when so specified,) shall be 100 percent. Sampling plans and procedures for Major and Minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with Standard MIL-STD-1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to individual characteristics listed using an AQL of 0.65 percent for each Minor defect and an AQL of 0.40 percent for each Major defect except where 100 percent inspection is specified. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.2.2.1 Primer, prior to assembly to cartridge case (see dwg. 8839466 covering a detail of dwg. 9215633)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	One or more flash holes missing	Visual	01001
Major:	None defined.		
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6).....	Visual	01002

4.2.2.2 Cartridge case prior to assembling propelling charge (see dwg. 10535911 covering a detail of dwg. 9215633)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Primer obviously loose	Manual	02001
Major:	AQL 0.40 percent		
101.	Primer damaged	Visual	02002
Minor:	AQL 1.5 percent		
201.	Foreign matter on interior of liner.....	Visual	02003
202.	Foreign matter in charge	Visual	02004
203.	Evidence of poor workmanship (see 3.6.1.2).....	Visual	02005

4.2.2.3 Cartridge case with propelling charge, prior to assembling to projectile (see dwg. 10535911 covering a detail of dwg. 9215633)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.40 percent		
101.	Propellant charge missing.....	Visual	03001
102.	Liner improperly closed.....	Visual	03002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6).....	Visual	03003

4.2.2.4 Projectile, with inert charge (see dwg. 9215634 covering a detail of dwg. 9215633)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Assembly weight.....	Balance	04001
102.	Depth of fuze well from forward face, max.....	Gage	04002
103.	Distance from forward face to inert charge, max.....	Gage	04003
104.	Foreign matter in fuze well...	Visual	04004
Minor:	AQL 1.5 percent		
201.	Diameter of fuze well, max....	Gage	04005
202.	Marking missing, misleading or unidentifiable including incorrect color.....	Visual	04006
203.	Evidence of poor workmanship (see 3.6).....	Visual	04007

4.2.2.5 Pellet (see dwg. 9215635 covering a detail of dwg. 9215633)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined.		
Major:	AQL 0.65 percent		
101.	Weight of pellet.....	Balance	05001
102.	Diameter of pellet.....	Gage	05002
103.	Length of pellet.....	Gage	05003

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6).....	Visual	05004

4.2.2.6 Cartridge assembly, prior to assembly of fuze (see dwg. 9215633)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Pellet missing.....	Visual	06001
102.	Washer missing.....	Visual	06002
103.	Foreign matter in fuze well.....	Visual	06003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.6).....	Visual	06004

4.2.2.7 Cartridge assembly with fuze (see dwg. 9215633)

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Primer above flush.....	Gage	07001
2.	Liner damaged to extent that propellant can escape.....	Visual	07002
Major:	AQL 1.0 percent		
101.	Torque test failure of fuze.....	Test	07003
102.	Total length.....	Gage	07004
103.	Primer percussion element below flush, max.	Gage	07005
104.	Fuze not staked.....	Visual	07006
105.	Fuze not fully seated.....	Visual	07007
106.	Rotating band damaged.....	Visual	07008
Minor:	AQL 1.0 percent		
201.	Marking missing, misleading or unidentifiable, including incorrect color.....	Visual	07009
202.	Evidence of poor workmanship (see 3.6).....	Visual	07010

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.2.2.8 Unsealed fiber container (see dwg. 9215018)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Packing component missing	Visual	08001
Minor:	AQL 1.0 percent		
201.	Round excessively tight in container	Manual	08002
202.	Evidence of poor workmanship (see 3.6)	Visual	08003

4.2.2.9 Sealed fiber container (see dwg. 9215018)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Container cut or damaged through all impregnated asphalt layers	Visual	09001
102.	Tape incomplete or badly wrinkled	Visual	09002
103.	Metal end loose or distorted	Visual	09003
Minor:	AQL 2.5 percent		
201.	Tear tab missing or improper	Visual	09004
202.	Gap between cover and body of container	Visual	09005
203.	Color of tape incorrect	Visual	09006
204.	Marking missing, misleading or unidentifiable	Visual	09007
205.	Contents loose	Manual	09008

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.2.2.10 Sealed wood packing box (see dwg. 8796471)

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Box damaged	Visual	10001
102.	Hardware or strapping missing, broken or loose	Visual	10002
103.	Boards loose or nails protruding	Visual	10003
Minor:	AQL 2.5 percent		
201.	Hardware improperly engaged	Visual-Manual	10004
202.	Strapping improperly assembled	Visual-Manual	10005
203.	Car seal missing, unsealed or improperly positioned	Visual-Manual	10006
204.	Contents loose	Manual	10007
205.	Handle missing or insecure	Visual	10008
206.	Marking missing, misleading or unidentifiable	Visual	10009

4.2.3 Testing

4.2.3.1 Check test for possible deterioration of the primer.- Major defect - Code No. 01003. If the total elapsed time between original acceptance of any primer lot and the assembly of that lot into complete round cartridges exceeds two years, or if the primers have been subjected to adverse conditions, however brief, at any time since previous tests, the applicable lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in the applicable primer loading specification immediately before the primer lot is assembled into the cartridges. The test shall be performed by the contractor on primers selected by the government inspector at the facility assembling the primers into the cartridges (see 6.4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

M

4.2.3.2 Profile and alignment (see dwg. 9215633) Major defect - Code No. 07011. The · cartridges, including those which have had the bourrelet repainted (see 3.6.1.1), shall be gaged 100 percent for profile and alignment. Any cartridge which fails to comply with the applicable requirement shall be classed defective and removed from the lot. Equipment shall be in accordance with 4.2.4.

4.2.3.3 Propellant weight (see 3.3) Critical defect - Code No. 02006.-The propellant shall be weighed and check-weighed 100 percent. The check-weighing shall be accomplished independently of the original weighing and, if performed manually, shall be performed by another operator. Any charge which fails to comply with the applicable requirement shall be classed defective and removed.

4.2.3.4 Cartridge case crimp

4.2.3.4.1 Torque (see 3.4.1) Major defect - Code No. 07012.-The sampling plan for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code letter F and AQL 1.5 percent. The test shall be performed as specified in 4.3.1.1. Equipment shall be in accordance with 4.2.4.

4.2.3.4.2 Bullet pull (see 3.4.2) Major defect - Code No. 07013.-The sampling plan for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code letter F and AQL 1.5 percent. The test shall be performed as specified in 4.3.1.2. Equipment shall be in accordance with 4.2.4.

4.2.3.5 Proving ground.-The proving ground tests shall be performed as specified in 4.3.2.

4.2.3.5.1 Muzzle velocity (see 3.5.1) Major defect - Code No. 07014.

4.2.3.5.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code letter I and AQL 1.0 percent. In addition, if the standard deviation of the projectile sample multiplied by the factor 0.75 exceeds the applicable lot requirement, the lot shall be rejected.

4.2.3.5.1.2 After three consecutive lots have met the criteria of 4.2.3.5.1.1, the sampling plan and procedure for this test shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

M

be in accordance with Standard MIL-STD-414, Section B, Table B-3, Code letter F, and AQL 1.0 percent. In addition if the standard deviation of the projectile sample multiplied by the factor 0.65 exceeds the applicable lot requirement, the lot shall be rejected.

4.2.3.5.2 Projectile functioning (see 3.5.2) - Major defect - Code No. 07015.

4.2.3.5.2.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sample cartridges used in the muzzle velocity test (see 4.2.3.5.1.1) shall be observed for projectile functioning. If three or more projectiles fail to comply with the applicable requirement, the lot shall be rejected.

4.2.3.5.2.2 After three consecutive lots have met the criteria of 4.2.3.5.2.1, the sample cartridges in the muzzle velocity test (see 4.2.3.5.1.2) shall be observed for projectile functioning. If two or more projectiles fail to comply with the applicable requirement, the lot shall be rejected.

4.2.3.5.3 Safety (see 3 5.4) - Critical defect - Code No. 07016.

4.2.3.5.3.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, fifteen sample cartridges shall be selected at random from each lot for this test. If any cartridge fails to comply with the safety requirements, the lot shall be rejected.

4.2.3.5.3.2 After three consecutive lots have met the criteria of 4.2.3.5.3.1, five sample cartridges shall be selected at random from each lot for this test. If any cartridge fails to comply with the safety requirements, the lot shall be rejected.

4.2.3.5.4 Premature burst and security of parts (see 3.5.3) - Critical defect - Code No. 07017.-If any of the sample cartridges used in any of the proving ground tests fail to comply with the applicable requirements for premature burst and security of parts, the applicable lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:20Z
Check the source to verify that this is the current version before use.

4.2.4 Inspection Equipment.-Equipment Tabulation Number ET-9215633 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment inaccordance with the instructions in paragraph 6.3.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed in the ET shall be in accordance with Specification MIL-I-45607.

4.2.4.3 Government use of contractor's inspection and test equipment.-The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

4.3 Test methods and procedures

4.3.1 Cartridge case crimp

4.3.1.1 Torque.-The security of the crimp of the cartridge case to the projectile shall be determined by applying a torque load at a rate of travel not to exceed 10 degrees per minute. Observation shall be made for compliance with the applicable requirement.

4.3.1.2 Bullet pull.-The security of the crimp of the cartridge case to the projectile shall be determined by applying a load in the axial direction at the rate of 0.125 inch per minute. Observation shall be made for compliance with the applicable requirement.

4.3.2 Proving ground tests.-These tests shall be conducted at a Government proving ground in accordance with the applicable Acceptance Test Procedure. The sample cartridges shall be fired from a rifle for which the cartridge is standard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

4.3.2.1 Muzzle velocity.-The sample cartridges shall be fired as specified in 4.3.2.2 and the muzzle velocity shall be measured.

4.3.2.2 Projectile functioning.-Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, fifteen sample cartridges shall be fired for impact against a 1-inch wood bursting screen placed not less than 400 feet from the muzzle of the rifle and ten sample cartridges shall be fired for impact on firm ground with the rifle elevated at not less than 320 mils. After three consecutive lots have met the criteria of 4.2.3.5.1.1, five sample cartridges shall be fired for impact against a 1-inch wood bursting screen placed not less than 400 feet from the muzzle of the rifle and five sample cartridges shall be fired for impact on firm ground with the rifle elevated at not less than 320 mils.

4.3.2.3 Safety.-The sample cartridges shall be fired with propelling charges adjusted to give 112 percent of the rated maximum pressure for the cartridge. In addition for the first three production lots from each manufacturer (loading facility), a smear camera shall be used to observe the projectile in flight, in order to record any possible malfunctioning.

5.1 Preservation and packaging

5.1.1 Level A.-The cartridges shall be preserved and packaged in accordance with dwg. 9215018.

5.2 Packing

5.2.1 Level A.-The containers shall be packed in accordance with dwg. 8796471.

5.3 Marking.-Marking of the wood box shall be in accordance with dwg. 8796471. The fiber container shall be marked in accordance with dwg. 9215018.

6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government.

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the referenced inspection Equipment Lists (EL) in accordance with the instructions of paragraphs 6.3.1 through 6.3.7.

6.3.1 Inspection equipment lists.-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (SMUPA Form 1010) the numbers of drawings of existing equipment designs or codes as indicated in paragraph 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in paragraphs 6.3.3 and 6.3.4. Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5. The contractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5 and 6.3.6 will be designated in the EL by the following codes:

CDAF - Contractor's design responsibility on Army format in accordance with MIL-D-45608.
CDCF - Contractor's design responsibility on contractor format.
AD - Army design.
ADMU - Army design, mandatory for use.
CE - Commercial equipment.
SCD - Specification control drawing.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications, mandatory and non-mandatory. When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The

Source: https://assist.dla.mil -- Downloaded: 202610-26T04:20Z
Check the source to verify that this is the current version before use.

contractor may, however, in connection with non-mandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs (see 6.3.6) or commercial equipment selections (see 6.3.5) must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 Specification control drawing.-Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagramatic or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings must be described in sufficient detail to permit identification and evaluation by the Government (see 6.3.5). Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 Commercial equipment.-Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and Government. Contractors normally are not required to furnish drawings of commercial inspection equipment, but a list of such equipment must be approved by the Government. When commercial inspection equipment requires the use of special fixturing, the design of this fixturing shall be considered as part of the total design, and 6.3.6 shall apply. In the latter case, only those portions of the commercial equipment need be detailed in the designs as are necessary to completely fabricate, calibrate, and operate the total item of inspection equipment. Lists and fixturing designs shall be submitted for approval as specified in 6.3.7.

6.3.6 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection quipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.

required. Contractor designs identified as CDCF may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDAF shall comply with the format and requirements of MIL-D-45608, and in addition, contain the detail and information specified above. Final approved contractor designs identified as CDCF shall be suitable for microfilming. They must be non-reproducible diazo or electrostatic prints of top quality full size with black lines on white background and shall provide a legible print produced via the 35mm microfilm process. Contractors shall submit one copy of the final design as a rolled set or flat set. Designs shall be submitted for approval as specified in 6.3.7.

6.3.7 Submission of contractor designs.-Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the Contracting Officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

6.4 Cost of check test.-The contracting officer shall arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test. The test shall be conducted at Government expense without cost to the contractor who loaded the primers or to the contractor assembling the cartridge and shall not constitute a basis for rejection against either contractor except when deterioration has occurred as a direct result of carelessness in handling, storage, etc. permitted while the primer lot was under the jurisdiction of either contractor.

6.5 Submission of test data and ammunition data cards.- In addition to the normal distribution of records, for loaded items procured by the Department of the Army, one copy of all ballistic test data and ammunition data cards shall be forwarded to the following:

Commanding Officer
Picatinny Arsenal
ATTN: SMUPA-ND
Dover, New Jersey 07801

Custodian:
Army-MU

Preparing activity:
Army-MU

Project No. 1310-A031

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:20Z
Check the source to verify that this is the current version before use.