MIL-C-60586 (MU)
14 October 1966

SUPERSEDING
FA-PD-MI-2466, Rev 1
19 April 1962
FA-PD-MI-2461, Rev 1
15 Nov 1962

MILITARY SPECIFICATION
CARTRIDGE, POWDER ACTUATED CUTTER, M129, ASSEMBLY

1. SCOPE

1.1 This specification covers Cartridge, Powder Actuated Cutter, M129, for use with Cutter, Cartridge Actuated, Reefing Line, M9.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

Military

MIL-P-223	- Powder, Black
MIL-B-550	—Barium Chromate
MIL-A-2550	- Ammunition and Special Weapons, General Specification For
MIL-E-5272	- Environmental Testing, Aeronautical and Associated Equipment, General Specification For
MIL-W-5625	- Webbing, Textile, Nylon, Tubular
MIL-C-60539	- Coating, Anodic, Conventional for Aluminum and Aluminum Alloys

Picatinny Arsenal

PA-PD-451	- Boron

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-413	- Visual Inspection Guide for Rubber O-rings
MIL-STD-639	- Surface Roughness Values Preferred for Army Ordnance Material
MIL-STD-1167	- Ammunition Data Card

Federal

FED-STD-151	- Metals, Test Methods

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

DRAWINGS

Munitions Command

D10520297	- Cartridge, Powder Actuated Cutter, M129, Assembly
C8864166	- Carton, Inner, Packing, Ammunition for Cartridge, Powder Actuated Cutter, M129
C8864167	- Carton, Outer, Packing, Ammunition for Cartridge, Powder Actuated Cutter, M129
IEL-10520297	- Index to Inspection Equipment List for Cartridge, Powder Actuated Cutter, M129 Assembly

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 General.- Materials, parts and assemblies shall conform to the requirements specified on the applicable drawings and referenced specifications.

3.2 First article sample.- Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.3 Cutter extraction.- The force required to extract the cutter from the cartridge case shall not be less than 100 pounds, and the extraction rate of travel shall not be less than six inches nor more than 10 inches per minute.

3.4 Vibration.- The assembled cartridge shall withstand vibration as prescribed in MIL-E-5272, Procedure XII, without evidence of any disintegration of the primer, delay charge or propellant, or derangement of any component.

3.5 Primer sensitivity.

3.5.1 The M42 Primer, when primed into a cartridge case, shall fire when drop tested at an energy level of 26.0 inch ounces.

3.5.2 The M42 Primer, when primed into a cartridge case, shall not fire when drop tested at an energy level of 4.0 inch ounces.

3.6 Shock.- The assembled cartridge, when assembled into an acceptable M9 Cutter, temperature conditioned as specified in table I, subjected to a shock load of 750g in either direction along the major axis, and fired, shall not fail to comply with the delay times specified in table I.

3.7 Hardness.- The requirements for hardness shall be as specified on the applicable drawings and shall be uniform throughout the part within specified tolerances. Requirements for alloy steel parts shall be achieved by quenching and tempering.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

3.8 Protective finish.- Protective finish shall be in accordance with MIL-C-60539.

3.9 Functional.

3.9.1 The cartridge shall not fail to fire.

3.9.2 The cartridge shall function without mechanical failure (see 6.1).

3.9.3 Ballistics.- The cartridge, when assembled into an acceptable M9 Reefing Line Cutter, temperature conditioned as specified in table I, and fired, shall generate sufficient force to completely sever two lines of 1/2-inch, 1000 pound tubular nylon webbing, fabricated in accordance with MIL-W-5625. Delay Time shall be as specified in table I (see 6.4).

Table I

Temperature	Delay Times, Seconds Min	Max
-65° to -70° F	---	2.4
70° to 75° F	1.8	2.2
160° to 165° F	1.6	---

3.10 Workmanship.- Workmanship shall be in accordance with the requirements of the applicable drawings, referenced specifications, and the following:

3.10.1 Metal defects.- The metal parts shall be free from cracks, splits, cold shuts, inclusions, porosity or other metal defects.

3.10.2 Burr.- The part or assembly shall not have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.10.3 Foreign matter.- The part or assembly shall not contain chips, dirt, grease, oil, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

4.1.2 Inspection.- Inspection shall be in accordance with MIL-A-2550.

4.2 First article sample.

4.2.1 Initial production sample.- At the beginning of regular production, a sample shall be submitted in accordance with contract requirements and shall consist of 53 assembled cutter cartridges, 50 cartridge cases for the hardness test, 10 sets of unassembled components (including explosive components) for visual and dimensional examination, and 100 primed cartridge cases to be tested as indicated in table II herein.

Table II

Paragraph Req	Paragraph Test	Test to be Performed	Sample Size		Nature of Test Destr	Nature of Test Nondestr
3.3	4.4.1	Cutter Extraction	23	Assembled Cartridges	x	-
3.4	4.4.2	Vibration	12	From Ballistic Sample	-	x
3.5	4.4.3	Primer Sensitivity	100	Primed Cases	x	-
3.6	4.4.4	Shock	30	From Ballistic Sample	x	-
3.7	4.4.5	Hardness	50	Cartridge Cases	x	-
Dwg	4.4.6	Airtightness		Each Cartridge	-	x
3.9.3	4.4.8.1	Ballistics	30	Assembled Cartridges	x	-

The sample shall be manufactured using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply.

4.2.1.1 Examination and test.- After inspection and provisional acceptance at source, the sample shall be inspected for all requirements of the drawings and specifications at a Government laboratory or such other facility specified in the contract.

4.2.1.2 Ballistics.- The sample for ballistic tests shall be temperature conditioned and produce the delay times indicated in table I. The sample for firing shall consist of the following:

Table III

Temperature	Not Vibrated	Vibrated
-65°to -70°F	6	4
65°to 75°F	6	4
160°to 165°F	6	4

4.2.1.3 Initial production sample failure.- Failure of the sample to comply with requirements of the drawings and specifications shall result in sample disapproval.

4.3 Inspection provisions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

4.3.1 Lot.

4.3.1.1 Submission of product. - The product shall be submitted in accordance with MIL-STD-105.

4.3.1.2 Size of lot. - Unless otherwise specified by the procuring agency, a lot shall consist of 5,000 cartridges, maximum, exclusive of test samples, and shall consist of:

a. Components produced by a homogeneous process.
b. Propellant from not more than one lot.
c. Primers from not more than one lot.
d. Delay Elements from not more than one lot.

4.3.2 Examination. - One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects contained herein, using the sampling plan and associated criteria in tables IV and V. For an individual defect (single characteristic) the criteria in table IV shall be used. For total defects within a major or minor class, the criteria in table V shall be used. All nonconforming material shall be rejected. Inspection for rubber O-rings shall be in accordance with MIL-STD-413. The ordnance standard finish blocks prescribed in MIL-STD-639 shall be used as a basis of comparison for surface roughness determination. Four power (4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

Table IV

Lot Size	Sample Size	Major		Minor	
		Accept	Reject	Accept	Reject
1 - 300	100% examination	-	-	-	-
301 - 1,300	110	1	2	2	3
1,301 - 3,200	150	2	3	3	4
3,201 - 8,000	225	3	4	4	5
8,001 - 22,000	300	4	5	5	6

Table V

Total Allowable Defects per Sample Size

Sample Size for Major Defects	110	150	225	300
Number of Defects in Class				
2 - 3	1	2	3	4
4 - 7	2	3	4	5
8 - 19	3	4	5	7
20 - 43	4	5	8	10
Over - 43	6	8	11	14

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

Sample Size for Minor Defects	110	150	225	300
Number of Defects in Class				
2 - 3	2	3	4	5
4 - 7	3	4	5	7
8 - 16	4	5	8	10
17 - 48	6	8	11	14
Over - 48	8	11	17	20

4.3.2.1 Primer, Percussion, M42, Dwg C8799925 covering a detail of Dwg D10520297.

Defect	Method of Inspection
CRITICAL	
1. Improper assembly	X-ray 1/ and Visual
2. Any part missing	X-ray 1/ and Visual
3. Primer pellet broken, cracked or dislodged	X-ray 1/ and Visual
4. Metal defective	X-ray 1/ and Visual
5. Primer foil discolored	Visual
6. Mixed primers	Visual
MAJOR	
101. Burr	Visual
102. Foreign matter	Visual
MINOR	
None defined.	

1/ Prior to assembly into a cartridge, the primer shall be x-rayed with the sides of the cup perpendicular to the rays. The x-ray negatives, properly identified, shall be forwarded to the procuring activity.

4.3.2.2 Cartridge Case, Dwg C10520298 covering a detail of Dwg D10520297.

CRITICAL	
1. Depth of primer pocket, min	Gage
2. Metal defective	Visual
MAJOR	
101. Concentricity of primer pocket with body	Gage
102. Concentricity of primer flash hole with primer pocket	Gage
103. Concentricity of cavity with body	Gage
104. Diameter of head, min	Gage
105. Diameter of primer pocket	Gage
106. Diameter of cavity	Gage
107. Diameter of flash hole	Gage
108. Depth of primer pocket, max	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

	Defect	Method of Inspection
109.	Thickness of web	Gage
110.	Protective finish inadequate or defective	Visual
111.	Surface finish of primer pocket improper	Visual
112.	Burr or sharp corner	Visual
113.	Foreign matter	Visual

MINOR

201.	Diameter of head, max	Gage
202.	Diameter of body	Gage
203.	Total length	Gage
204.	Thickness of head	Gage
205.	Radius or chamfer missing or incorrect	Visual
206.	Surface finish improper, except as otherwise classified	Visual

4.3.2.3 Body, Delay, Dwg B10520299, a detail of Dwg D10520317, which in turn, is a component of Dwg D10520297.

CRITICAL

None defined.

MAJOR

101.	Concentricity of flash hole with body	Gage
102.	Concentricity of cavity with body	Gage
103.	Diameter of body	Gage
104.	Diameter of cavity	Gage
105.	Diameter of flash hole	Gage
106.	Total length, max	Gage
107.	Thickness of web	Gage
108.	Metal defective	Visual
109.	Protective finish inadequate or defective	Visual
110.	Burr	Visual
111.	Foreign matter	Visual

MINOR

201.	Total length, min	Gage
202.	Radius missing or incorrect	Visual
203.	Surface finish improper	Visual

4.3.2.4 Cutter, Dwg C10520300 covering a detail of Dwg D10520297.

CRITICAL

1.	Metal defective	Visual

MAJOR

101.	Concentricity of body, small end with large end	Gage
102.	Concentricity of O-ring groove with body, large end	Gage
103.	Concentricity of radial diameter with body, large end	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

Defect	Method of Inspection
104. Perpendicularity of cutting edge with body, large end	Gage
105. Diameter of body, large end	Gage
106. Diameter of small cavity	Gage
107. Depth of crimping groove	Gage
108. Location of crimping groove	Gage
109. Cutting edge not sharp	Visual
110. Protective finish inadequate or defective	Visual
111. Surface finish of cutter blade and O-ring groove improper	Visual
112. Burr	Visual
113. Foreign matter	Visual
MINOR	
201. Diameter of O-ring groove	Gage
202. Diameter of cavity, large end	Gage
203. Diameter of body, small end	Gage
204. Diameter at radial	Gage
205. Depth to drill point, large cavity	Gage
206. Depth of large cavity	Gage
207. Depth of drill point, small cavity	Gage
208. Depth of small cavity	Gage
209. Total length	Gage
210. Length of crimp groove	Gage
211. Width of O-ring groove	Gage
212. Location of O-ring groove	Gage
213. Location of radial diameter	Gage
214. Profile of O-ring groove	Gage
215. Radius or chamfer missing or incorrect	Visual
216. Surface finish improper, except as otherwise classified	Visual

4.3.2.5 Delay Element, Cartridge, M29, Assembly, Dwg D10520317 covering a detail of Dwg D10520297.

CRITICAL	
1. Improper assembly	Visual
2. Mixed delay elements	Visual
3. Flash hole missing or obstructed	Visual
4. Marking or stamping missing, incorrect or illegible	Visual
5. Metal defective	Visual
6. Protective finish inadequate or defective	Visual
7. Delay charge missing	Visual
MAJOR	
101. Foreign matter	Visual
MINOR	
None defined.	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

4.3.2.6 Cutter Guard, Dwg B10520417 covering a detail of Dwg D10520297.

Defect	Method of Inspection
CRITICAL	
None defined.	
MAJOR	
101. Diameter of small cavity, max	Gage
102. Diameter of small cavity at base, max	Gage
103. Diameter of venthole	Gage
104. Material defective	Visual
105. Flash	Visual
106. Foreign matter	Visual
MINOR	
201. Diameter of body	Gage
202. Diameter of large cavity	Gage
203. Diameter of small cavity, min	Gage
204. Diameter of small cavity at base, min	Gage
205. Depth of small cavity	Gage
206. Depth to base of small cavity	Gage
207. Total length	Gage
208. Radius missing or incorrect	Visual

4.3.2.7 Cartridge, Powder Actuated Cutter, M129, Assembly, Dwg D10520297.

CRITICAL	
1. Primer not properly seated	Gage
2. Any part missing	X-ray 1/ and Visual
3. Improper assembly	X-ray 1/ and Visual
4. Marking missing, incorrect or illegible	Visual
MAJOR	
101. Cutter guard cut, torn,or otherwise defective	Visual
102. O-ring cut, split, torn or broken	Visual
103. Crimping missing	Visual
104. Foreign matter	Visual
MINOR	
201. Diameter of body, max	Gage
202. Total length, max	Gage
203. Varnish over marking missing, or inadequate	Visual

1/ The cartridge shall be x-rayed with the sides of the case perpendicular to the rays. The x-ray negatives, properly identified, shall be forwarded to the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

4.3.2.8 Carton, Inner, Packing, Ammunition for Cartridge, M129, Dwg C8864166.

Defect	Method of Inspection
CRITICAL	
None defined.	
MAJOR	
None defined.	
MINOR	
201. Contents loose	Manual and Visual
202. Quantity of contents incorrect	Visual
203. Separator or filler missing	Visual
204. Heat sealing incomplete, loose or distorted	Visual
205. Cut or damaged through impregnated carton	Visual
206. Marking missing, incorrect, or illegible	Visual
207. Carton sealing defective, improper or missing	Visual

4.3.2.9 Carton, Outer, Packing, Ammunition for Cartridge, Powder Actuated, Cutter, M129, Dwg C8864167.

CRITICAL	
None defined.	
MAJOR	
None defined.	
MINOR	
201. Contents loose	Manual and Visual
202. Quantity of contents incorrect	Visual
203. Contents of carton exposed	Visual
204. Filler or separator missing	Visual
205. Carton damaged	Visual
206. Sealing improper, missing or insecure	Visual
207. Marking missing, incorrect or illegible	Visual

4.3.3 Inspection testing.- The following tests shall be performed in accordance with the provisions of 4.4:

4.3.3.1 Cutter extraction.- Twenty-three assembled cartridges shall be selected at random from each lot and subjected to the cutter extraction test. Failure of any cartridge to comply with the requirement of 3.3 shall be cause for rejection of the lot of cartridges.

4.3.3.2 Vibration.- Twelve of the 30 assembled cartridges of the initial production sample shall be subjected to vibration. After vibration, the 12 cartridges shall be x-rayed in accordance with 1/ of 4.3.2.7 and ballistically tested. If any change is made in the lot

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

of primers, propellant, delay element, or method of charging in any subsequent production lot, an additional sample of 12 cartridges shall be selected and vibrated as above. Failure of any cartridge to comply with the requirement of 3.4 shall be cause for rejection of the lot.

4.3.3.3 Primer sensitivity.

4.3.3.3.1 All fire.- Fifty cartridges, less propellant and pyrotechnic charges, shall be tested at the 13.0-inch height in accordance with 3.5.1. Any cartridge failing to comply with 3.5.1 shall be cause for rejection of the lot.

4.3.3.3.2 No fire.- Fifty cartridges, less propellant and pyrotechnic charges, shall be tested at the 2.0-inch height in accordance with 3.5.2. Any cartridge failing to comply with 3.5.2 shall be cause for rejection of the lot.

4.3.3.4 Shock.- Thirty cartridges of the initial production sample shall be subjected to this test. Failure of any cartridge to comply with the requirement of 3.6 shall be cause for rejection of the lot of cartridges.

4.3.3.5 Hardness.- Fifty cartridge cases from each heat-treated lot shall be tested. Failure of any unit to comply with the requirements of the drawing shall be cause for rejection of the lot.

4.3.3.6 Airtightness.- Each cartridge assembly shall be subjected to the specified pressure differential. Failure to comply with the requirements of the drawing shall be cause for rejection of the lot of cartridges.

4.3.3.7 Protective finish.- Twenty-three units of each anodized component shall be selected for the protective finish tests. Failure of any component to comply with the requirement of 3.8 shall be cause for rejection of the lot.

4.3.3.8 Functional.- The following tests shall be performed by the Government:

4.3.3.8.1 Ballistics.- Thirty cartridges from each lot shall be temperature conditioned as prescribed in table VI and 4.4.8.1.1. Failure of any cartridge to comply with 3.9 shall be cause for rejection of the lot of cartridges.

Table VI

Temperature	Sample Size
-65° to -70° F	10
65° to 75° F	10
160° to 165° F	10

4.3.4 Inspection equipment.- The examination and tests shall be made using equipment listed on IEL-10520297.

4.4 Test methods and procedures.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

4.4.1 Cartridge extraction.- The cutter shall be extracted from the cartridge case by the use of an extraction machine approved by the Government.

4.4.2 Vibration.- The method and procedure for performing the vibration test shall be in accordance with MIL-E-5272, Procedure XII.

4.4.3 Primer sensitivity.- The primer sensitivity test shall be made with primed cartridge cases from which the propellant and pyrotechnic charges have been removed. The test shall be made utilizing the test equipment listed on the designated inspection equipment list, using a 15/16-inch diameter ball weighing 1.94 ± 0.02 ounces at each of the two heights. The machine shall have a firing pin protrusion of .039 + .002 inch. This shall be measured by seating the firing pin fully against the shoulder stop in the firing pin retainers and measuring the resulting protrusion of the point of the firing pin from the face of the firing pin retainer. The contour on the end of the firing pin shall simulate the actual firing pin, including the shoulder diameter next to the spherical end. The headspace shall be zero. All height measurements shall be made between the head of the firing pin and the bottom of the suspended ball. The primer sensitivity machine shall be checked to be sure the drop ball is impacting the center of the firing machine. All firing pin indent centers shall be within 0.02 inch of the center of the primer.

4.4.4 Shock.- The 30 cartridges shall be assembled into acceptable M9 Cutters. The assembly shall then be mounted in the specified fixture and fired. Five cartridges shall be fired in each direction at the three temperatures specified in table I. At the time of the firing of each cartridge, the cartridge shall be shocked at 750g in accordance with 3.6. This shock test shall be performed on the initial production sample only, and need not be repeated on subsequent production lots, except when a new initial production sample is required.

4.4.5 Hardness.- Prior to the application of protective finish, a hardness testing machine shall be used to determine compliance with the hardness requirements specified on the applicable drawing.

4.4.6 Airtightness.- The test and procedure for determining airtightness shall be by use of equipment approved by the Government.

4.4.7 Protective finish.- Test procedures for protective finish shall be in accordance with FED-STD-151. The cartridge case, delay body and cutter shall be sectioned longitudinally to better expose the significant surfaces to the salt spray.

4.4.8 Functional.

4.4.8.1 Ballistics.- The test sample shall be rigidly supported in the fixture designated by the appropriate inspection equipment list. The sample shall be tested within five minutes after removal from the conditioning chamber. When this time limit is exceeded, the sample shall be re-conditioned in accordance with 4.4.8.1.1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

4.4.8.1.1 Temperature conditioning.- A standard M9 Cutter, loaded with a dummy M129 Cartridge containing a temperature sensitive element, shall be placed in the conditioning chamber at the same time as the samples. The conditioning time shall be a minimum of 1 hour longer than the time necessary to bring the element contained in the dummy cartridge to the required temperature.

5. PREPARATION FOR DELIVERY

5.1 Packing and marking - Level A.- Packing and marking shall be in accordance with Dwgs C8864166 and C8864167.

5.2 Data cards.- Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 A mechanical failure is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

6.2 Advisory delay charge.- Composition (formulation) approximately 30 grains of composition, comprising 4.5% Boron and 95.5% Barium Chromate, as specified in MIL-B-550 and PA-PD-451.

6.3 Advisory propellant charge.- Black Powder - Class 5, 5.4 minus 0.1 grains, as specified in MIL-P-223.

6.4 Delay Time is defined as the time lapse between the impact of the firing pin on the primer and the complete severance of two lines of 1/2-inch, 1000 pound tubular nylon webbing of the type specified in MIL-W-5625.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1377-A096

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.

To detach this form, cut along this line

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity.

SPECIFICATION

ORGANIZATION	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 OCT 64 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T04:21Z
Check the source to verify that this is the current version before use.